

METHODS 3: MULTILEVEL STATISTICAL MODELLING AND MACHINE LEARNING



BACHELOR OF COGNITIVE SCIENCE

AARHUS UNIVERSITY

1 SEPTEMBER 2021

EMIL TRENCKNER JESSEN

METHODS 3: MULTILEVEL STATISTICAL MODELING AND MACHINE
LEARNING



COURSE OVERVIEW (FIRST HALF)

W1: Introduction

Setting up R and Python and recollection of the general linear model

W2: Linear Mixed Effects Models

Modelling random effects – and how do they differ from fixed effects?

W3: Generalized Linear Mixed Effects Models

What to do when the response variable is not continuous?

W4: Explanation and prediction

Why are good explanations sometimes bad?

W5: Evaluating and comparing models

How do we assess how models compare to one another?

Fall break:

Machine Learning and Python programming follows



COURSE OVERVIEW (FIRST HALF)

W1: Introduction

Setting up R and Python and recollection of the general linear model

W2: Linear Mixed Effects Models

Modelling random effects – and how do they differ from fixed effects?

W3: Generalized Linear Mixed Effects Models

What to do when the response variable is not continuous?

W4: Explanation and prediction

Why are good explanations sometimes bad?

W5: Evaluating and comparing models

How do we assess how models compare to one another?

Fall break:

Machine Learning and Python programming follows



TODAYS PLAN

- Catch-up
- Output – logistic regression
- QQ-plots
- *(Model selection criteria*
 - *R-squared (revisited)*
 - *AIC/BIC*
 - *Out-of-sample-error)*
- Assignment tips
- Assignment work



TODAYS PLAN

- **Catch-up**
- Output – logistic regression
- QQ-plots
- *(Model selection criteria*
 - *R-squared (revisited)*
 - *AIC/BIC*
 - *Out-of-sample-error)*
- Assignment tips
- Assignment work



CATCH-UP



BACHELOR OF COGNITIVE SCIENCE

AARHUS UNIVERSITY

1 SEPTEMBER 2021

EMIL TRENCKNER JESSEN

METHODS 3: MULTILEVEL STATISTICAL MODELING AND MACHINE
LEARNING



CATCH-UP

- How are you hanging in? Last assignment? Git/GitHub?
- Extra readings
- Where would you want new messages?
- Bigger visualizations this time around
- Disclaimer



TODAYS PLAN

- Catch-up
- **Output – logistic regression**
- QQ-plots
- *(Model selection criteria*
 - *R-squared (revisited)*
 - *AIC/BIC*
 - *Out-of-sample-error)*
- Assignment tips
- Assignment work



OUTPUT – LOGISTIC REGRESSION



BACHELOR OF COGNITIVE SCIENCE

AARHUS UNIVERSITY

1 SEPTEMBER 2021

EMIL TRENCKNER JESSEN

METHODS 3: MULTILEVEL STATISTICAL MODELING AND MACHINE
LEARNING



OUTPUT – LOGISTIC REGRESSION

```
logistic_model <- glm(formula = am ~ wt,  
                        data = mtcars,  
                        family = "binomial")
```



OUTPUT – LOGISTIC REGRESSION

```
logistic_model <- glm(formula = am ~ wt,  
                        data = mtcars,  
                        family = "binomial")
```

- am = automatic transmission (1 or 0)
- wt = weight (continuous)

OUTPUT – LOGISTIC REGRESSION

```
logistic_model <- glm(formula = am ~ wt,  
                        data = mtcars,  
                        family = "binomial")
```

- am = automatic transmission (1 or 0)
- wt = weight (continuous)



Uses link function

->

**To log-odds, to have linear
scale**

OUTPUT – LOGISTIC REGRESSION

am ~ wt



OUTPUT – LOGISTIC REGRESSION

```
am ~ wt
```

```
> summary(logistic_model)
```

Coefficients:

	Estimate	Std.
(Intercept)	12.040	
wt	-4.024	



OUTPUT – LOGISTIC REGRESSION

```
am ~ wt
```

```
> summary(logistic_model)
```

- Output in log-odds to have linear relationship between wt and am

Coefficients:

	Estimate	Std.
(Intercept)	12.040	
wt	-4.024	


OUTPUT – LOGISTIC REGRESSION

Coefficients:

	Estimate	Std.
(Intercept)	12.040	
wt	-4.024	



OUTPUT – LOGISTIC REGRESSION



Coefficients:

	Estimate	std.
(Intercept)	12.040	
wt	-4.024	



OUTPUT – LOGISTIC REGRESSION

$$y = 12.04 + -4.024 * x$$

Coefficients:

	Estimate	Std.
(Intercept)	12.040	
wt	-4.024	



OUTPUT – LOGISTIC REGRESSION

- Going through example of a Mazda

$$y = 12.04 + -4.024 * x$$

Coefficients:

	Estimate	Std.
(Intercept)	12.040	
wt	-4.024	



OUTPUT – LOGISTIC REGRESSION

- Going through example of a Mazda

```
> head(mazda)
```

```
      mpg  cyl  disp  hp drat   wt  qsec vs  am  gear  carb  
Mazda RX4  21    6  160 110  3.9 2.62 16.46  0   1     4     4
```

```
> y_log_odds = 12.04 + -4.024 * 2.62
```



OUTPUT – LOGISTIC REGRESSION

- Going through example of a Mazda

```
> head(mazda)
```

```
      mpg  cyl disp  hp drat   wt  qsec vs am gear carb  
Mazda RX4  21   6  160 110  3.9 2.62 16.46  0  1    4    4
```

```
> y_log_odds = 12.04 + -4.024 * 2.62
```

```
> y_log_odds
```


```
[1] 1.49712
```



OUTPUT – LOGISTIC REGRESSION

- Going through example of a Mazda

```
> head(mazda)
      mpg cyl  disp  hp drat   wt  qsec
Mazda RX4  21   6  160 110  3.9 2.62 16.46
> y_log_odds = 12.04 + -4.024 * 2.62
> y_log_odds
[1] 1.49712
```



OUTPUT – LOGISTIC REGRESSION

- Going through example of a Mazda

```
> head(mazda)
```

```
      mpg  cyl  disp  hp drat   wt  qsec vs  am  gear  carb  
Mazda RX4  21    6  160 110  3.9 2.62 16.46  0   1    4     4
```

```
> y_log_odds = 12.04 + -4.024 * 2.62
```

```
> y_log_odds
```

```
[1] 1.49712
```

```
> y_odds = exp(y_log_odds)
```



OUTPUT – LOGISTIC REGRESSION

- Going through example of a Mazda

```
> head(mazda)
      mpg cyl  disp  hp drat   wt  qsec vs am gear carb
Mazda RX4  21   6  160 110  3.9 2.62 16.46  0  1    4    4
> y_log_odds = 12.04 + -4.024 * 2.62
> y_log_odds
[1] 1.49712
> y_odds = exp(y_log_odds)
> y_odds
[1] 4.4688
```



OUTPUT – LOGISTIC REGRESSION

- Going through example of a Mazda

```
> head(mazda)
      mpg cyl  disp  hp drat   wt  qsec vs am gear carb
Mazda RX4  21   6  160 110  3.9 2.62 16.46  0  1    4    4
> y_log_odds = 12.04 + -4.024 * 2.62
> y_log_odds
[1] 1.49712
> y_odds = exp(y_log_odds)
> y_odds
[1] 4.4688
> y_probability = y_odds / (1+y_odds)
```

OUTPUT – LOGISTIC REGRESSION

- Going through example of a Mazda


```
> head(mazda)
      mpg cyl  disp  hp drat   wt  qsec vs am gear carb
Mazda RX4  21   6  160 110  3.9 2.62 16.46  0  1    4    4
> y_log_odds = 12.04 + -4.024 * 2.62
> y_log_odds
[1] 1.49712
> y_odds = exp(y_log_odds)
> y_odds
[1] 4.4688
> y_probability = y_odds / (1+y_odds)
> y_probability
[1] 0.8171445
```



OUTPUT – LOGISTIC REGRESSION

- Going through example of a Mazda

```
> head(mazda)
      mpg cyl  disp  hp drat   wt  q:
Mazda RX4  21   6  160 110  3.9 2.62 16
> y_log_odds = 12.04 + -4.024 * 2.62
> y_log_odds
[1] 1.49712
> y_odds = exp(y_log_odds)
> y_odds
[1] 4.4688
> y_probability = y_odds / (1+y_odds)
> y_probability
[1] 0.8171445
```



OUTPUT – LOGISTIC REGRESSION

- Going through example of a Mazda

```
> y_log_odds
```

```
[1] 1.49712
```

```
> y_probability
```

```
[1] 0.8171445
```



OUTPUT – LOGISTIC REGRESSION

- Going through example of a Mazda

```
> y_log_odds
```

```
[1] 1.49712
```

```
> y_probability
```

```
[1] 0.8171445
```

“Inverse-link function”



```
inv.logit <- function(x) exp(x) / (1 + exp(x))
```

OUTPUT – LOGISTIC REGRESSION

- Going through example of a Mazda

```
> y_log_odds
```

```
[1] 1.49712
```

```
> y_probability
```

```
[1] 0.8171445
```

```
inv.logit <- function(x) exp(x) / (1 + exp(x))
```

```
> inv.logit(1.49712)
```

```
[1] 0.8171445
```



OUTPUT – LOGISTIC REGRESSION

- Going through example of a Mazda
- `logistic_model$fitted.values` takes the inv-logit automatically





OUTPUT – LOGISTIC REGRESSION

- Going through example of a Mazda
- `logistic_model$fitted.values` takes the inv-logit automatically

```
> logistic_model$fitted.values  
      Mazda RX4      Mazda RX4 Wag  
8.172115e-01      6.157283e-01
```



OUTPUT – LOGISTIC REGRESSION



TODAYS PLAN

- Catch-up
- Output – logistic regression
- **QQ-plots**
- *(Model selection criteria*
 - *R-squared (revisited)*
 - *AIC/BIC*
 - *Out-of-sample-error)*
- Assignment tips
- Assignment work



QQ-PLOTS



BACHELOR OF COGNITIVE SCIENCE

AARHUS UNIVERSITY


1 SEPTEMBER 2021

EMIL TRENCKNER JESSEN



METHODS 3: MULTILEVEL STATISTICAL MODELING AND MACHINE
LEARNING




QQ-PLOTS





QQ-PLOTS



QQ-PLOTS



QQ-PLOTS



QQ-PLOTS

- Quantiles-quantile plots



QQ-PLOTS

- Quantiles-quantile plots
- What is a quantile?




QQ-PLOTS

- Quantiles-quantile plots
- What is a quantile?
- Generalization of median, quartile, percentile, etc.




QQ-PLOTS

- Quantiles-quantile plots
- What is a quantile?
- Generalization of median, quartile, percentile, etc.



QQ-PLOTS

- Quantiles-quantile plots
- What is a quantile?
- Generalization of median, quartile, percentile, etc.



QQ-PLOTS

- Quantiles

1, 1, 3, 5, 7, 8, 10, 11, 11,



QQ-PLOTS

- Quantiles



QQ-PLOTS

- Quantiles



QQ-PLOTS

- Quantiles



TODAYS PLAN

- Catch-up
- Output – logistic regression
- QQ-plots
- *(Model selection criteria*
 - *R-squared (revisited)*
 - *AIC/BIC*
 - *Out-of-sample-error)*
- **Assignment tips**
- Assignment work



ASSIGNMENT TIPS



BACHELOR OF COGNITIVE SCIENCE

AARHUS UNIVERSITY

1 SEPTEMBER 2021

EMIL TRENCKNER JESSEN

METHODS 3: MULTILEVEL STATISTICAL MODELING AND MACHINE
LEARNING




ASSIGNMENT TIPS

- Understanding assignment data
 - Experiment paradigm




ASSIGNMENT TIPS

- Understanding the paradigm



ASSIGNMENT TIPS

- Understanding the paradigm
 - Task (8, quadrant, pairs)
 - PAS (how clearly was target seen?)
 - rt.obj (Reaction time -> Even/Odd)
 - rt.sub (Reaction time -> PAS)




ASSIGNMENT TIPS

- `ggplot(mtcars, aes(mpg, disp)) +
 geom_point()`




ASSIGNMENT TIPS

- `ggplot(mtcars, aes(mpg, disp)) +
 geom_point()`



ASSIGNMENT TIPS


- `ggplot(mtcars, aes(mpg, disp)) +
 geom_point()`




- `ggplot(mtcars, aes(mpg, disp)) +
 geom_point() +
 facet_wrap(~ cyl)`

ASSIGNMENT TIPS

- `ggplot(mtcars, aes(mpg, disp)) +
 geom_point()`



- `ggplot(mtcars, aes(mpg, disp)) +
 geom_point() +
 facet_wrap(~ cyl)`



ASSIGNMENT TIPS

- Loading in the files
 - `pwd` in R = `getwd()`
 - `ls` in R = `list.files()`



ASSIGNMENT TIPS

- Loading in the files
 - pwd in R = getwd()
 - ls in R = list.files()

```
> getwd()
```

```
[1] "C:/Users/Lenovo/Desktop/Diverse dokumenter/Con-  
ference/github_methods_3/week_03/non_student"
```

```
list.files("/experiment_2/")
```

```
[1] "001.csv" "002.csv" "003.csv" "004.csv" "005.csv"  
[6] "006.csv" "007.csv" "008.csv" "009.csv" "010.csv"  
11] "011.csv" "012.csv" "013.csv" "014.csv" "015.csv"  
16] "016.csv" "017.csv" "018.csv" "019.csv" "020.csv"  
21] "021.csv" "022.csv" "023.csv" "024.csv" "025.csv"  
26] "026.csv" "027.csv" "028.csv" "029.csv"
```



BREAK TIME

THIS IS GIT. IT TRACKS COLLABORATIVE WORK ON PROJECTS THROUGH A BEAUTIFUL DISTRIBUTED GRAPH THEORY TREE MODEL.

COOL. HOW DO WE USE IT?

NO IDEA. JUST MEMORIZE THESE SHELL COMMANDS AND TYPE THEM TO SYNC UP. IF YOU GET ERRORS, SAVE YOUR WORK ELSEWHERE, DELETE THE PROJECT, AND DOWNLOAD A FRESH COPY.



TODAYS PLAN

- Catch-up
- Output – logistic regression
- QQ-plots
- *(Model selection criteria*
 - *R-squared (revisited)*
 - *AIC/BIC*
 - *Out-of-sample-error)*
- Assignment tips
- **Assignment work**



ASSIGNMENT



BACHELOR OF COGNITIVE SCIENCE

AARHUS UNIVERSITY

1 SEPTEMBER 2021


EMIL TRENCKNER JESSEN

METHODS 3: MULTILEVEL STATISTICAL MODELING AND MACHINE
LEARNING



ASSIGNMENT

1. *Pull new assignment from upstream*
2. Download files from BrightSpace, put into new folder “github_methods_3/week_03/”
3. Create copy of “practical_exercise_3.Rmd”, give unique filename ending
4. Work on new copied version of assignment



- list.files()
- getwd()
- + facet_wrap(~ subject)





AARHUS
UNIVERSITY

MODEL SELECTION CRITERIA



BACHELOR OF COGNITIVE SCIENCE

AARHUS UNIVERSITY

1 SEPTEMBER 2021

EMIL TRENCKNER JESSEN

METHODS 3: MULTILEVEL STATISTICAL MODELING AND MACHINE
LEARNING



MODEL SELECTION CRITERIA



SCHOOL OF COMMUNICATION AND CULTURE

AARHUS UNIVERSITY

1 SEPTEMBER 2021

EMIL TRENCKNER JESSEN

METHODS 3: MULTILEVEL STATISTICAL MODELING AND MACHINE
LEARNING



MODEL SELECTION CRITERIA

- Why are we modeling?
- What constitutes a good model?




MODEL SELECTION CRITERIA

- Why are we modeling?
 - *To be able to understand the world*
 - *Why understand? To be able to predict/manipulate*
- What constitutes a good model?
 - *A model is good if it accurately models the world*
 - *... is good if it generalizes to new data*
 - *... is good if we accurately have estimated the underlying parameters of the population distribution*




MODEL SELECTION CRITERIA



MODEL SELECTION CRITERIA

- R-squared
- AIC, BIC
- Out-of-sample performance



R SQUARED

$$R^2 = 1 - \frac{\sum_i (y_i - \hat{y}_i)^2}{\sum_i (y_i - \mu)^2}$$




R SQUARED

$$R^2 = 1 - \frac{\sum_i (y_i - \hat{y}_i)^2}{\sum_i (y_i - \mu)^2}$$




R SQUARED

$$R^2 = 1 - \frac{\sum_i (y_i - \hat{y}_i)^2}{\sum_i (y_i - \mu)^2}$$




R SQUARED

$$R^2 = 1 - \frac{\sum_i (y_i - \hat{y}_i)^2}{\sum_i (y_i - \mu)^2}$$




R SQUARED

$$R^2 = 1 - \frac{\sum_i (y_i - \hat{y}_i)^2}{\sum_i (y_i - \mu)^2}$$




R SQUARED

$$R^2 = 1 - \frac{\sum_i (y_i - \hat{y}_i)^2}{\sum_i (y_i - \mu)^2}$$




^




R SQUARED


$$R^2 = 1 - \frac{\sum_i (y_i - \hat{y}_i)^2}{\sum_i (y_i - \mu)^2}$$



^







^



R SQUARED

$$R^2 = 1 - \frac{\sum_i (y_i - \hat{y}_i)^2}{\sum_i (y_i - \mu)^2}$$



R SQUARED

- Can we use a criteria that accounts for overfitting?



AIC



SCHOOL OF COMMUNICATION AND CULTURE

AARHUS UNIVERSITY

1 SEPTEMBER 2021

EMIL TRENCKNER JESSEN

METHODS 3: MULTILEVEL STATISTICAL MODELING AND MACHINE
LEARNING



AIC

$$AIC = -2 \ln(L) + 2k$$



AIC

$$\begin{aligned} AIC &= -2 \ln(L) + 2k \\ &= \\ AIC &= 2k - 2 \ln(\hat{L}) \end{aligned}$$



AIC

$$AIC = -2 \ln(L) + 2k$$



AIC - BIC

$$AIC = -2 \ln(L) + 2k$$

$$BIC = k \ln(n) - 2 \ln(\hat{L})$$



AIC - BIC

$$AIC = -2 \ln(L) + 2k$$


$$BIC = k \ln(n) - 2 \ln(\hat{L})$$




AIC - BIC

—


R-squared model rating:



^




^




AIC - BIC

—


R-squared model rating:



^




^




AIC - BIC

—


AIC / BIC model rating:




^



>



AIC - BIC



OUT-OF-SAMPLE ERROR



SCHOOL OF COMMUNICATION AND CULTURE

AARHUS UNIVERSITY


1 SEPTEMBER 2021

EMIL TRENCKNER JESSEN

METHODS 3: MULTILEVEL STATISTICAL MODELING AND MACHINE
LEARNING



OUT-OF-SAMPLE ERROR



SCHOOL OF COMMUNICATION AND CULTURE



AARHUS UNIVERSITY

1 SEPTEMBER 2021


EMIL TRENCKNER JESSEN
METHODS 3: MULTILEVEL STATISTICAL MODELING AND MACHINE
LEARNING



OUT-OF-SAMPLE ERROR



OUT-OF-SAMPLE ERROR





AARHUS
UNIVERSITY