

# Contribution Title

Joris LIMONIER<sup>1</sup>[0000-0002-0393-2247]

Université Côte d'Azur, Biot, France [joris.limonier@etu.unice.fr](mailto:joris.limonier@etu.unice.fr)

**Abstract.** The abstract should briefly summarize the contents of the paper in 15–250 words.

**Keywords:** Computer Vision · Human Pose Estimation · 3D Human Pose Estimation

## 1 State of the Art

### 1.1 Introduction

The Deep Learning revolution, coupled with increasing computing power and the improved use of GPU opened new opportunities in Computer Vision. New architectures arose and new techniques suggested parameters in numbers that were unseen before, some of them reaching hundreds of millions of parameters [4]: up to 94.9M for Faster R-CNN [5], 127.3M for Cascade R-CNN [6], 51.0M for FCOS [7], 210.1M for CenterNet [8], 135.2M for Cascade Mask R-CNN [6], 138.2M for Hybrid Task Cascade [9] and 63.4M for Mask R-CNN [5].

## References

1. C. Zheng et al., “Deep Learning-Based Human Pose Estimation: A Survey,” arXiv:2012.13392 [cs], Jan. 2021, Accessed: Jan. 12, 2022. [Online]. Available: <http://arxiv.org/abs/2012.13392>
2. H.-Y. Wu, L. Nguyen, Y. Tabei, and L. Sassatelli, “Evaluation of deep pose detectors for automatic analysis of film style,” in EUROGRAPHICS Workshop on Intelligent Cinematography and Editing, Reims, France, 2022, p. 9.
3. W. Li, H. Liu, H. Tang, P. Wang, and L. V. Gool, “MHFormer: Multi-Hypothesis Transformer for 3D Human Pose Estimation,” in 2022 IEEE/CVF International Conference on Computer Vision (ICCV), Montreal, QC, Canada, Jun. 2022.
4. Wang J, Sun K, Cheng T, Jiang B, Deng C, Zhao Y, Liu D, Mu Y, Tan M, Wang X, Liu W. Deep high-resolution representation learning for visual recognition. IEEE transactions on pattern analysis and machine intelligence. 2020 Apr 1;43(10):3349-64.
5. He, K., Zhang, X., Ren, S. and Sun, J., 2016. Deep residual learning for image recognition. In Proceedings of the IEEE conference on computer vision and pattern recognition (pp. 770-778).
6. Cai, Z. and Vasconcelos, N., 2019. Cascade R-CNN: high quality object detection and instance segmentation. IEEE transactions on pattern analysis and machine intelligence, 43(5), pp.1483-1498.

7. Tian, Z., Shen, C., Chen, H. and He, T., 2019. Fcos: Fully convolutional one-stage object detection. In Proceedings of the IEEE/CVF international conference on computer vision (pp. 9627-9636).
8. Duan, K., Bai, S., Xie, L., Qi, H., Huang, Q. and Tian, Q., 2019. Centernet: Key-point triplets for object detection. In Proceedings of the IEEE/CVF international conference on computer vision (pp. 6569-6578).
9. Chen, K., Pang, J., Wang, J., Xiong, Y., Li, X., Sun, S., Feng, W., Liu, Z., Shi, J., Ouyang, W. and Loy, C.C., 2019. Hybrid task cascade for instance segmentation. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (pp. 4974-4983).