




US 20100007717A1

(19) **United States**(12) **Patent Application Publication**
Spektor et al.(10) **Pub. No.: US 2010/0007717 A1**(43) **Pub. Date: Jan. 14, 2010**(54) **INTEGRATED PROCESSOR FOR 3D
MAPPING****Related U.S. Application Data**

(60) Provisional application No. 61/079,254, filed on Jul. 9, 2008.

(75) Inventors: **Evgeny Spektor**, Petach Tikva (IL);
Zafrir Mor, Ein Habsor (IL);
Dmitri Rais, Ramat Gan (IL)**Publication Classification**(51) **Int. Cl.**
H04N 13/00 (2006.01)
G06T 15/00 (2006.01)(52) **U.S. Cl.** **348/43; 345/427; 348/E15.001**(57) **ABSTRACT**

A device for processing data includes a first input port for receiving color image data from a first image sensor and a second input port for receiving depth-related image data from a second image sensor. Processing circuitry generates a depth map using the depth-related image data. At least one output port conveys the depth map and the color image data to a host computer.

Correspondence Address:
D. Kligler I.P. Services LTD
P.O. Box 25
Zippori 17910 (IL)(73) Assignee: **PRIME SENSE LTD**, Tel Aviv (IL)(21) Appl. No.: **12/397,362**(22) Filed: **Mar. 4, 2009**




FIG. 1




FIG. 2





FIG. 3B






FIG. 4





FIG. 5







FIG. 6B

FIG. 7



INTEGRATED PROCESSOR FOR 3D MAPPING

CROSS-REFERENCE TO RELATED APPLICATION

[0001] This application claims the benefit of U.S. Provisional Patent Application 61/079,254, filed Jul. 9, 2008, which is incorporated herein by reference.

FIELD OF THE INVENTION

[0002] The present invention relates generally to methods and systems for three-dimensional (3D) mapping, and specifically to processing devices for generation and processing of 3D mapping data.

BACKGROUND OF THE INVENTION

[0003] Various methods are known in the art for optical 3D mapping, i.e., generating a 3D profile of the surface of an object by processing an optical image of the object. This sort of 3D profile is also referred to as a depth map or depth image, and 3D mapping is also referred to as depth mapping.

[0004] Some methods are based on projecting a laser speckle pattern onto the object, and then analyzing an image of the pattern on the object. For example, PCT International Publication WO 2007/043036, whose disclosure is incorporated herein by reference, describes a system and method for object reconstruction in which a coherent light source and a generator of a random speckle pattern project onto the object a coherent random speckle pattern. An imaging unit detects the light response of the illuminated region and generates image data. Shifts of the pattern in the image of the object relative to a reference image of the pattern are used in real-time reconstruction of a 3D map of the object. Further methods for 3D mapping using speckle patterns are described, for example, in PCT International Publication WO 2007/105205, whose disclosure is incorporated herein by reference.

[0005] Other methods of optical 3D mapping project different sorts of patterns onto the object to be mapped. For example, PCT International Publication WO 2008/120217, whose disclosure is incorporated herein by reference, describes an illumination assembly for 3D mapping that includes a single transparency containing a fixed pattern of spots. A light source transilluminates the transparency with optical radiation so as to project the pattern onto an object. An image capture assembly captures an image of the pattern on the object, and the image is processed so as to reconstruct a 3D map of the object.

[0006] As a further example, PCT International Publication WO 93/03579 describes a 3D vision system in which one or two projectors establish structured light comprising two sets of parallel stripes having different periodicities and angles. As another example, U.S. Pat. No. 6,751,344 describes a method for optically scanning a subject in which the subject is illuminated with a matrix of discrete two-dimensional image objects, such as a grid of dots. Other methods involve projection of a grating pattern, as described, for example, in U.S. Pat. No. 4,802,759. The disclosures of the above-mentioned patents and publications are incorporated herein by reference.

SUMMARY OF THE INVENTION

[0007] Embodiments of the present invention that are described hereinbelow provide devices and methods for processing of image data for 3D mapping.

[0008] In accordance with an embodiment of the present invention, a device for processing data includes a first input port for receiving color image data from a first image sensor and a second input port for receiving depth-related image data from a second image sensor. Processing circuitry generates a depth map using the depth-related image data, and at least one output port conveys the depth map and the color image data to a host computer.

[0009] In a disclosed embodiment, the first and second input ports, the processing circuitry and the at least one output port are integrated circuit components, which are fabricated on a single semiconductor substrate.

[0010] In some embodiments, the at least one output port includes a single port and is coupled to convey the depth map and the color image data to the host computer as a single data stream in a multiplexed format. Typically, the processing circuitry is configured to synchronize the depth map with the color image data in the single data stream. Optionally, the device includes a third input port for receiving audio information, wherein the processing circuitry is configured to incorporate the audio information together with the depth map and the color image data into the single data stream for conveyance to the host computer via the single port. In one embodiment, the single port includes a Universal Serial Bus (USB) port.

[0011] In disclosed embodiments, the processing circuitry is configured to register the depth map with the color image data. The depth map includes an array of pixels with respective depth values, and the processing circuitry is typically configured to compute respective shifts for the pixels responsively to the depth values, and to apply the respective shifts to the pixels in the depth map in order to register the depth map with the color image data. In one embodiment, the processing circuitry is configured to compute the respective shifts incrementally, using an incremental fitting process, such that the shifts of the pixels within a line of the depth map are computed as a function of a preceding pixel shift. Typically, the processing circuitry is configured to compute the respective shifts for the pixels on the fly, while receiving the depth values, without storing the entire depth map in the device.

[0012] In some embodiments, the processing circuitry is configured to compress the depth map and the color image data for transmission to the host via the at least one output port. In one embodiment, the processing circuitry is configured to apply a process of lossless compression to the depth map and the color image data.

[0013] In a disclosed embodiment, the depth-related image data include an image of a pattern that is projected onto an object, and the processing circuitry is configured to generate the depth map by measuring shifts in the pattern relative to a reference image.

[0014] There is also provided, in accordance with an embodiment of the present invention, apparatus for imaging, including a first image sensor, which is configured to capture and output a color image of an object, and a second image sensor, which is configured to capture and output depth-related image data with respect to the object. A processing device includes a first input port for receiving the color image data from the first image sensor and a second input port for receiving the depth-related image data from the second image sensor, as well as processing circuitry, for generating a depth map using the depth-related image data, and at least one output port for conveying the depth map and the color image data to a host computer.

[0015] Optionally, the apparatus includes an audio sensor, wherein the processing device includes a third input port for receiving audio information from the audio sensor, and wherein the processing circuitry is configured to convey the audio information together with the depth map and the color image data to the host computer via the at least one output port.

[0016] In a disclosed embodiment, the apparatus includes an illumination subassembly, which is configured to project a pattern onto the object, wherein the depth-related image data include an image of the pattern on the object, and the processing circuitry is configured to generate the depth map by measuring shifts in the pattern relative to a reference image.

[0017] There is additionally provided, in accordance with an embodiment of the present invention, a method for processing data, including receiving color image data from a first image sensor via a first input port and receiving depth-related image data from a second image sensor via a second input port. A depth map is generated using the depth-related image data, and the depth map and the color image data are conveyed via an output port to a host computer.

[0018] The present invention will be more fully understood from the following detailed description of the embodiments thereof, taken together with the drawings in which:

BRIEF DESCRIPTION OF THE DRAWINGS

[0019] FIG. 1 is a schematic, pictorial illustration of a system for 3D mapping, in accordance with an embodiment of the present invention;

[0020] FIG. 2 is a schematic top view of an imaging assembly, in accordance with an embodiment of the present invention;

[0021] FIGS. 3A and 3B are block diagrams of a processing device, in accordance with an embodiment of the present invention;

[0022] FIG. 4 is a block diagram that schematically shows elements of a depth processor, in accordance with an embodiment of the present invention;

[0023] FIG. 5 is a block diagram that schematically shows details of a registration engine, in accordance with an embodiment of the present invention;

[0024] FIGS. 6A and 6B are block diagrams that schematically show details of a coordinate calculation circuit, in accordance with an embodiment of the present invention; and

[0025] FIG. 7 is a block diagram that schematically illustrates a compression circuit, in accordance with an embodiment of the present invention.

DETAILED DESCRIPTION OF EMBODIMENTS

System Overview

[0026] FIG. 1 is a schematic, pictorial illustration of a system 20 for 3D mapping and imaging, in accordance with an embodiment of the present invention. In this example, an imaging assembly 24 is configured to capture and process 3D maps and images of a user 22. This information may be used by a host computer 26 as part of a 3D user interface, which enables the user to interact with games and other applications running on the computer. (This sort of functionality is described, for example, in U.S. patent application Ser. No. 12/352,622, filed Jan. 13, 2009, whose disclosure is incorporated herein by reference.) This particular application of system 20 is shown here only by way of example, however, and the mapping and imaging capabilities of system 20 may be

used for other purposes, as well, and applied to substantially any suitable type of 3D object.

[0027] In the example shown in FIG. 1, imaging assembly 24 projects a pattern of optical radiation onto the body (or at least parts of the body) of user 22, and captures an image of the pattern that appears on the body surface. The optical radiation that is used for this purpose is typically in the infrared (IR) range. A processing device in assembly 24, which is described in detail hereinbelow, processes the image of the pattern in order to generate a depth map of the body, i.e., an array of 3D coordinates, comprising a depth (Z) coordinate value of the body surface at each point (X, Y) within a pre-defined area. (In the context of an array of image-related data, these (X, Y) points are also referred to as pixels.) In the embodiments that are described hereinbelow, the processing device computes the 3D coordinates of points on the surface of the user's body by triangulation, based on transverse shifts of the spots in the pattern, as described in the above-mentioned PCT publications WO 2007/043036, WO 2007/105205 and WO 2008/120217. Alternatively, system 20 may implement other methods of 3D mapping, using single or multiple cameras or other types of sensors, as are known in the art.

[0028] In addition, imaging assembly 24 captures color (2D) images of the user and may also receive audio input. The imaging assembly registers and synchronizes the depth maps with the color images, and generates a data stream that includes the depth maps and image data (and possibly the audio data, as well) for output to computer 26. In some embodiments, as described hereinbelow, the depth maps, color images, and possibly the audio data are integrated into a single data stream, which is output to the computer via a single port, for example, a Universal Serial Bus (USB) port.

[0029] Computer 26 processes the data generated by assembly 24 in order to extract 3D image information. For example, the computer may segment the depth map in order to identify the parts of the body of user 22 and find their 3D locations. Computer 26 may use this information in driving an output device, such as a display 28, typically to present 3D image information and/or user interface elements that may be controlled by movements of parts of the user's body. Generally, computer 26 comprises a general-purpose computer processor, which is programmed in software to carry out these functions. The software may be downloaded to the processor in electronic form, over a network, for example, or it may alternatively be provided on tangible media, such as optical, magnetic, or electronic memory media.

[0030] As another alternative, the processing functions that are associated here with computer 26 may be carried out by a suitable processor that is integrated with display 28 (in a television set, for example) or with any other suitable sort of computerized device, such as a game console or media player.

[0031] FIG. 2 is a schematic top view of imaging assembly 24, in accordance with an embodiment of the present invention. Here the X-axis is taken to be the horizontal direction along the front of assembly 24, the Y-axis is the vertical direction (into the page in this view), and the Z-axis extends away from assembly 24 in the general direction of the object being imaged by the assembly.

[0032] For 3D mapping, an illumination subassembly 30 illuminates the object with an appropriate pattern, such as a speckle pattern. For this purpose, subassembly 30 typically comprises a suitable radiation source 32, such as a diode laser, LED or other light source, and optics, such as a diffuser 34 or

a diffractive optical element, for creating the pattern, as described in the above-mentioned PCT publications. A depth image capture subassembly 36 captures an image of the pattern on the object surface. Subassembly 36 typically comprises objective optics 38, which image the object surface onto a detector 40, such as a CMOS image sensor.

[0033] As noted above, radiation source 32 typically emits IR radiation, although other radiation bands, in the visible or ultraviolet range, for example, may also be used. Detector 40 may comprise a monochrome image sensor, without an IR-cutoff filter, in order to detect the image of the projected pattern with high sensitivity. To enhance the contrast of the image captured by detector 40, optics 38 or the detector itself may comprise a bandpass filter, which passes the wavelength of radiation source 32 while blocking ambient radiation in other bands.

[0034] A color image capture subassembly 42 captures color images of the object. Subassembly 42 typically comprises objective optics 44, which image the object surface onto a detector 46, such as a CMOS color mosaic image sensor. Optics 44 or detector 46 may comprise a filter, such as an IR-cutoff filter, so that the pattern projected by illumination subassembly 30 does not appear in the color images captured by detector 46.

[0035] Optionally, a microphone 48 captures audio input, such as voice commands uttered by user 22.

[0036] A processing device 50 receives and processes image and audio inputs from subassemblies 36 and 42 and from microphone 48. Details of these processing functions are presented hereinbelow with reference to the figures that follow. Briefly put, processing device 50 compares the image provided by subassembly 36 to a reference image of the pattern projected by subassembly 30 onto a plane 54, at a known distance D_{src} from assembly 24. (The reference image may be captured as part of a calibration procedure and stored in a memory 52, such as a flash memory, for example.) The processing device matches the local patterns in the captured image to those in the reference image and thus finds the transverse shift for each pixel 56, or group of pixels, within plane 54. Based on these transverse shifts and on the known distance D_{cc} between the optical axes of subassemblies 30 and 36, the processing device computes a depth (Z) coordinate for each pixel.

[0037] Processing device 50 synchronizes and registers the depth coordinates in each such 3D map with appropriate pixels in the color images captured by subassembly 42. The registration typically involves a shift of the coordinates associated with each depth value in the 3D map. The shift includes a static component, based on the known distance D_{cc} between the optical axes of subassemblies 36 and 42 and any misalignment between the detectors, as well as a dynamic component that is dependent on the depth coordinates themselves. The registration process is described in detail hereinbelow.

[0038] After registering the depth maps and color images, processing device 50 outputs the depth and color data via a port, such as a USB port, to host computer 26. The output data may be compressed, as described hereinbelow, in order to conserve bandwidth. As noted above, the audio information provided by microphone 28 may also be synchronized and output together with the depth and color data to computer 26.

Processing Device Architecture

[0039] FIG. 3 (consisting of FIGS. 3A and 3B) is a block diagram that schematically shows functional elements of pro-

cessing device 50, in accordance with an embodiment of the present invention. Device 50 may be fabricated as a dedicated integrated circuit, on a single semiconductor substrate, with interfaces to the other components of assembly 24 and a USB port to computer 26 as described above. This sort of implementation is useful in minimizing the cost, size and power consumption of assembly 24. Alternatively, device 50 may be implemented using a number of separate circuit components. Device 50 may include other interfaces, as well, including data and control interfaces to a "thin" host 60, such as a special-purpose multimedia application processor.

[0040] The components of device 50 are described hereinbelow in detail as an example of a possible implementation of the principles of the present invention. Further details of this implementation are presented in the above-mentioned provisional patent application. Alternative implementations will be apparent to those skilled in the art on the basis of the present description and are considered to be within the scope of the present invention. For instance, although the embodiment described hereinbelow uses dedicated hardware processing components, some or all of the processing functions in question may be performed in software by a general-purpose programmable processor with suitable interfaces. The software for this purpose may be downloaded to the processor in electronic form, over a network, for example. Alternatively or additionally, the software may be stored on tangible computer-readable media, such as optical, magnetic, or electronic memory.

[0041] In the present example, device 50 comprises the following components:

[0042] A depth processor 62 processes the information captured by depth image capture subassembly 36 in order to generate a depth map. Processor 62 uses dedicated memory space in a memory 130. This memory can also be accessed by a controller 104, which is described hereinbelow, but typically not by host computer 26. Rather, processor 62 may be programmed by the host computer via an application program interface (API).

[0043] Depth processor 62 receives input video data from detector 40 via a depth CMOS sensor interface 64. The depth processor processes the video data in order to generate successive depth maps, i.e., frames of depth data, as is described in detail hereinbelow with reference to the figures that follow. The depth processor loads these data into a depth first-in-first-out (FIFO) memory 66 in a USB FIFO unit 68.

[0044] In parallel with the depth input and processing, a color processing block 72 receives input color video data from detector 46 via a color CMOS sensor interface 70. Block 72 converts the raw input data into output frames of RGB video data, and loads these data into a RGB FIFO memory 74 in unit 68. Alternatively, block 72 may output the video data in other formats, such as YUV or Bayer mosaic format.

[0045] In addition, audio signals from microphone 48 are digitized by an analog/digital converter (ADC) 76. The resulting digital audio samples are then conveyed by an audio interface 78 to an audio FIFO memory 80 in unit 68. In the example shown in FIG. 3A, interface 78 comprises an Integrated Interchip Sound (I2S) bus receiver.

[0046] USB FIFO unit 68 acts as a buffer level between the various data suppliers and a USB controller 86. Unit 68 packs and formats the various data types according to different classes (such as a USB video class and a USB audio class), and also serves to prevent data loss due to USB bandwidth

glitches. It arranges the data into USB packets according to the USB protocol and format prior to transferring them to the USB controller.

[0047] A high-bandwidth bus, such as an Advanced High-performance Bus (AHB) matrix **82**, is used to carry data between the components of device **50**, and specifically for conveying data from USB FIFO unit **68** to USB controller **86** for transfer to host computer **26**. (AHB is a bus protocol promulgated by ARM Ltd., of Cambridge, England.) When there are packets ready in FIFO unit **68** and space available in the internal memory of USB controller **86**, the USB controller uses direct memory access (DMA) to read data from FIFO memories **66**, **74** and **80** via an AHB slave module **84** and AHB matrix **82**. The USB controller multiplexes the color, depth and audio data into a single data stream for output via USB interface to host computer **26**.

[0048] For the purpose of USB communications, device **50** comprises a USB physical layer interface (PHY) **88**, which may be operated by USB controller **86** to communicate via a suitable USB cable with a USB port of host computer **26**. The timing of USB PHY **88** is controlled by a crystal oscillator **92** and a phase-locked loop (PLL) **94**, as is known in the art. Alternatively, USB controller **86** may optionally communicate with the host computer via a USB 2.0 Transceiver Macrocircuit Interface (UTMI) and an external PHY **90**.

[0049] By the same token, an external ADC **96** may optionally be used to digitize the audio signals generated by microphone **48**. A 2:1 switch **98** selects the source of digital audio data to be input to I2S receiver **78**.

[0050] The I2S receiver may also output audio data directly to thin host **60** via an audio output interface **100**, in case the thin host is not configured (in distinction to host computer **26**) to receive the audio data together with the color and depth image data via a single serial bus. In this case, the RGB and depth (RGBD) data are output to the thin host via a separate RGBD interface **102**. Alternatively, for some applications, interface **102** may output only the depth data to thin host **60**.

[0051] Controller **104** is responsible for managing the functions of device **50**, including boot-up and self-test, configuration, power and interface management, and parameter adjustment. The controller comprises a digital signal processor (DSP) core **106** and an AHB master **108** for controlling data movement on AHB matrix **82**. Typically, controller **104** boots from a boot read-only memory (ROM) **110**, and then loads program code from flash memory **52** via a flash interface **132** into an instruction random-access memory (RAM) **112**. The controller also has its own data memory **114**. Controller **104** may, in addition, have a test interface **116**, such as a Joint Test Action Group (JTAG) interface, for purposes of debugging by an external computer **118**.

[0052] Controller **104** distributes configuration data and parameters to other components of device **50** via a register configuration interface, such as an Advanced Peripheral Bus (APB) **120**, to which the controller is connected through AHB matrix **82** and an APB bridge **122**. Various control interfaces are available for controlling these other components, including a Serial Synchronous Interface (SSI) and Serial Peripheral Interface (SPI) master unit **124** and slave unit **128**, as well as an Inter-Integrated Circuit (I2C) master unit **122** and slave unit **126**. A power management interface **133** provides power and reset signals to the peripheral devices. These particular interfaces are shown here by way of example, and other interface configurations may alternatively be used for similar purposes.

[0053] FIG. 4 is a block diagram that schematically shows details of depth processor **62**, in accordance with an embodiment of the present invention. The figure also shows certain functions of the parallel color processing block **72**.

[0054] To reduce on-chip storage and memory requirements, processor **62** typically uses a sliding window approach, in which only part of each processed image is stored in device **50** at any given time, and not the entire image. The window typically contains only a small number of lines of pixels, as required by the algorithms described hereinbelow. Newly-arrived data continually replaces old, processed data in the processor memory. The depth values are reconstructed by processor **62** on the fly, based on the input image data, and are output on the fly via FIFO buffer **66** to host computer **26**.

[0055] An input data preprocessing block **140** in processor **62** accepts depth-related pixel values from detector **40** via interface **64** and performs filtering operations to reduce noise and possibly to classify the pixels into different groups. The preprocessed data within the current processing window are stored in a picture memory **142**. The picture memory may comprise a number of memories or banks to allow simultaneous read of multiple data blocks.

[0056] For purposes of depth computation, a reference read engine **146** reads the reference image from memory **52** via interface **132** into a reference memory **148**. The reference data are read from memory **52** synchronously with the arrival of the corresponding parts of the current image into memory **142** from preprocessing block **140**. Like the picture memory, the reference memory stores only the part of the reference image that falls within the current processing window for the purpose of depth reconstruction, and may comprise a number of memories or banks. Reference read engine **146** may also be controlled to store the reference image initially in memory **52** during the calibration procedure.

[0057] A match engine **144** matches groups of input pixels from memory **142** with corresponding groups of reference pixels from memory **148** in order to find the relative offset of the input pixels. The match engine translates this offset into a depth value, as explained above, and writes the depth value to an output memory **150**. Again, at any given time, the output memory stores only a small sliding window out of the overall depth map, and may comprise a number of memories or banks.

[0058] A registration engine **152** registers the depth values generated by match engine **144** with color image data obtained from detector **46**. This registration process is described in detail hereinbelow. Registration engine **152** shifts the locations of the depth values in the depth map to coincide with the appropriate color pixels in the color image. Alternatively, it would be possible to shift the color pixel values to coincide with the corresponding depth map pixels. Following registration, a depth post-processing block **154** applies filtering and possibly other mathematical operations to the depth data.

[0059] A compression block **156** compresses the depth data prior to passing the data to USB FIFO unit **68**, in order to reduce the required bandwidth on the USB output link. Details of the compression function are described hereinbelow with reference to FIG. 7.

[0060] In parallel with the depth processing operations described above, a color image processor **158** in color processing block **72** converts input pixel values received from interface **70** into image data in accordance with an appropri-

ate video standard, such as RGB or YUV, for example. A compression block **160**, of similar design to block **156**, compresses the color image data, as well.

Registration of Depth with Color Image Data

[0061] FIG. 5 is a block diagram that schematically shows details of registration engine **152**, in accordance with an embodiment of the present invention. The registration engine is connected to receive depth pixel values via a pixel bus **170**. The pixels have the form (x_0, y_0, dX_0) , wherein X_0 and Y_0 are the raw horizontal and vertical coordinates, before registration, and dX_0 is the pixel shift value measured by match engine **144** between this pixel and the corresponding pixel in the reference image. (Because illumination subassembly **30** and depth image capture subassembly **36** are arranged along the X axis, only X-direction shift is significant in triangulation of the depth.)

[0062] A registered coordinate calculation block **172** counts columns and lines of incoming pixels and uses a parabolic fitting process to calculate registered coordinates (x_r, y_r) for each dX_0 pixel shift value. This calculation is described in detail hereinbelow. Input streaming write logic **174** writes the incoming pixel shift values into the appropriate registered locations in an N-line buffer **176**, according to the registered coordinates. Logic **174** also manages buffer line allocation as the pixels advance.

[0063] A vertical range calculator **178** calculates the minimum registered line number (Y_r) that will no longer be affected by the current input line. This number indicates the next line that may be read out of buffer **176**. Calculator **178** likewise uses a parabolic fitting equation for this calculation. Output streaming logic **180** uses the minimum registered line number value in choosing lines of registered pixel values to read out of buffer **176** to pixel bus **170**. As a result of the registration process, this stream of pixel depth values is registered with the corresponding color values in block **72**.

[0064] Operation of registered coordinate calculation block **172** will now be presented in detail. The calculation performed by block **172** uses the following parameters, some of which are shown in FIG. 2:

[0065] D_{cl} —distance between the optical axes of the illumination and depth image capture subassemblies **30** and **36**.

[0066] dX —calculated pattern shift at a point between reference and current depth images.

[0067] D_{srs} —distance between depth image capture subassembly **36** and reference plane **54**.

[0068] D_{srr} —distance between subassembly **36** and a registration reference plane.

[0069] d —depth value (which may be positive or negative) of a point on the object surface relative to reference plane **54**.

[0070] D_{cc} —distance between the depth and color image capture subassemblies **38** and **44**.

[0071] The depth d can be calculated from the shift dX as follows:

$$d = \frac{dX * D_{srs}}{D_{cl} - dX} \quad (1)$$

Due to geometrical factors, the depth d at a given point causes a shift Δ between the color and depth images at that point:

$$\Delta = \Delta_0 + \frac{D_{cc} * d}{D_{srr} + d} \quad (2)$$

In the above formula, Δ_0 is an initial set of point-wise shifts between the color and depth images at a reference plane at the distance D_{srr} from assembly **24**, due to the offset and possibly misalignment between the cameras. The formula theoretically applies to both X and Y shifts, but in the configuration shown in FIG. 2, the Y shift is essentially constant throughout any given region of interest: $\Delta^y = \Delta_0^y$, and the above formula applies only to the X shift Δ^x .

[0072] The registered coordinates for each input pattern shift value dX at point (x_0, y_0) in the unregistered image are then given by:

$$\begin{aligned} x_r &= x_0 + \Delta^x = x_0 + \Delta_0^x + \frac{D_{cc} * d}{D_{srr} + d} \\ y_r &= y_0 + \Delta^y = y_0 + \Delta_0^y \end{aligned} \quad (3)$$

The initial set of point-wise shifts could be stored in a lookup table, but to reduce on-chip storage, block **172** may use a parabolic fitting calculation instead:

$$\begin{aligned} \Delta_0^x(x, y) &= a_x x^2 + b_x y^2 + c_x xy + d_x x + e_x y + f_x \\ \Delta_0^y(x, y) &= a_y x^2 + b_y y^2 + c_y xy + d_y x + e_y y + f_y \end{aligned} \quad (4)$$

The twelve fitting coefficients in the above equation are calculated in advance, typically based on a calibration procedure, and are then loaded into the appropriate registers in processor **50**. Alternatively, other types of fitting functions may be used.

[0073] Now combining the above formulas, and assuming $D_{srs} = D_{srr}$, the registered coordinates are given by:

$$\begin{aligned} x_r &= x_0 + a_x x_0^2 + b_x y_0^2 + c_x x_0 y_0 + d_x x_0 + e_x y_0 + \beta dX_0 \\ y_r &= y_0 + a_y x_0^2 + b_y y_0^2 + c_y x_0 y_0 + d_y x_0 + e_y y_0 + f_y \end{aligned} \quad (5)$$

wherein

$$\beta = \frac{D_{cc}}{D_{cl}}$$

To simplify the above calculation, the values of Δ_0^x and Δ_0^y in the formula may be calculated incrementally for each pixel, based on values calculated previously for neighboring pixels

$$\begin{aligned} \Delta_0^x(x_0+1, y_0) &= \Delta_0^x(x_0, y_0) + \Delta_x \Delta_0^x(x_0, y_0)_x \\ \Delta_0^y(x_0+1, y_0) &= \Delta_0^y(x_0, y_0) + \Delta_y \Delta_0^y(x_0, y_0) \\ \Delta_0^x(x_0, y_0+1) &= \Delta_0^x(x_0, y_0) + \Delta_x \Delta_0^x(x_0, y_0) \\ \Delta_0^y(x_0, y_0+1) &= \Delta_0^y(x_0, y_0) + \Delta_y \Delta_0^y(x_0, y_0) \end{aligned} \quad (6)$$

The values $\Delta_0^x(0, -1)$ and $\Delta_0^y(0, -1)$ at the upper left corner of the picture, are pre-calculated as the start point for the above incremental calculation.

[0074] FIG. 6 (consisting of FIGS. 6A and 6B) is a block diagram that schematically shows details of registered coordinate calculation block **172**, in accordance with an embodiment of the present invention. FIG. 6A shows an X-coordinate calculation sub-block **186**, while FIG. 6B shows a Y-coordinate calculation sub-block **188**. These sub-blocks implement the calculation outlined above in equations (5) and (6). More specific details of the digital logic design of these

sub-blocks are presented in the above-mentioned provisional patent application, but some of these details are omitted here for the sake of simplicity.

[0075] Sub-blocks **186** and **188** are built around incremental parabolic fitting circuits **190** and **192**, which perform the calculations of equation (6). For each successive pixel, circuits **190** and **192** receive as inputs the registered coordinate values calculated for the previous pixel (x_{prev} , y_{prev}), as well as the parabolic fitting parameters a , b , c , d , e for X and Y . (Capital and small letters are used interchangeably in the text and figures for convenience.) Multiplexers **196** select the “0” input during horizontal advance along each line of the image (incrementing X) and the “1” input during vertical advance from line to line (incrementing Y).

[0076] The output of circuits **190** and **192** are the Δ_o^x and Δ_o^y shift values for the current pixel. During horizontal advance, these values are stored in column shift accumulators **198** and **206**, which then output the accumulated results for input as the previous X and Y shift values to the fitting calculation of circuits **190** and **192** for the next pixel. The shift values are also stored, via multiplexers **202** and **210**, in line shift accumulators **200** and **208**. During vertical advance, multiplexers **204** and **212** select the contents of accumulators **200** and **208** for input to circuits **190** and **192**. As above, the multiplexers select the “0” input during horizontal advance and the “1” input during vertical advance.

[0077] For the X -direction, sub-block **186** receives the depth-related pattern shift values dX_o and dX_c from matching engine **144** and takes the difference between these values in a subtractor **214** to give the incremental shift for the current pixel dX . (When no input value is available for dX_o or dX_c , the value 0 may be used instead.) A multiplier **216** multiplies this shift by the pre-calibrated parameter β . An adder **222** sums the result with the parabolic shift value calculated by circuit **190**. The result, finally, is summed with the current X -coordinate x_o by an adder **226** to give the registered coordinate x_r , as defined by equation (5). The registered Y -coordinate is similarly calculated by an adder **230**, but without any depth-related pattern shift component, as explained above.

[0078] Returning now to FIG. 5, since the registration shift that is calculated for each pixel varies over the area of the image, the stream of registered coordinates generated in registration engine will generally be unsynchronized with the input pixel stream. Buffer **176** and read logic **180** compensate for the variable delay between input and output. The number of lines in buffer **176** is given by the value of

$$\max_{any\ x_o, y_o} (\max \Delta^y - \min \Delta^y).$$

For any input line y_o , the greatest registered line y_r in buffer **176** that can receive pixels from input line y_o is $y_r = y_o + \min \Delta^y(y_o)$. This value is calculated by vertical range calculator **178** and fed to logic **180**. On this basis, logic **180** can read out from buffer **176** all lines above line y_r .

[0079] Depending on the values of the coefficients f_x and f_y in equation (5), there may be several columns and/or rows at the edges of the depth map produced by depth processor **62** that do not overlap with the color image produced by color processing block **72**. As a result, read logic **180** may need to discard lines of depth values at the edge of the depth map that “spill over” the edge of the color image, and add one or more lines of null or dummy depth values to extend the depth map so that it covers the entire color image. Such dummy values may be created synthetically by post-processing block **154**.

Lossless Compression of Depth and Color Images

[0080] FIG. 7 is a block diagram that schematically shows details of lossless compression blocks **156** and **160**, in accordance with an embodiment of the present invention. The block design shown in the figure is capable of compressing from one to three image components simultaneously. For depth maps, only one component is typically used. For color images, two or three components may be used, depending on the type of color encoding. The compression block uses difference and run-length encoding to compress the input stream efficiently without data loss. This compression makes it possible to transmit both the depth and color image data (as well as audio data) over the limited bandwidth afforded by the single USB serial link to host computer **26**. Alternatively, the compression blocks may be bypassed when sufficient output bandwidth is available.

[0081] A pixel distributor **240** divides the stream of input pixel values into components. For each component, a subtractor **244** calculates the difference between the current component value and the previous value, as provided by a component delay line **242**. The difference values are input to a pixel merger circuit **246**, which merges the differences back into a single difference stream. Circuit **246** also receives and merges the component values themselves, which are used instead of the difference values for the first pixel in each line and whenever the difference between successive pixels exceeds a certain threshold.

[0082] A symbol generator **248** encodes the difference and/or original pixel values. Typically, the symbol generator uses run-length encoding to represent the number of repetitions of the same value, and thus reduce the data volume still further. The symbol generator may also add synchronization signals on line and frame boundaries, to assist in subsequent decoding and reduce the impact of any possible data loss downstream. A bit stream packer **250** converts the encoded symbols into a continuous bit stream for USB transmission. The bit stream packer may add stuff bits so that the beginning of each new line and frame will be properly byte-aligned in a USB packet.

[0083] Although the embodiments above use specific device architectures, protocols, and configurations, the principles of the present invention may similarly be applied using architectures, protocols, and configurations of other types. It will thus be appreciated that the embodiments described above are cited by way of example, and that the present invention is not limited to what has been particularly shown and described hereinabove. Rather, the scope of the present invention includes both combinations and subcombinations of the various features described hereinabove, as well as variations and modifications thereof which would occur to persons skilled in the art upon reading the foregoing description and which are not disclosed in the prior art.

1. A device for processing data, comprising:

- a first input port for receiving color image data from a first image sensor;
- a second input port for receiving depth-related image data from a second image sensor;
- processing circuitry, for generating a depth map using the depth-related image data; and
- at least one output port for conveying the depth map and the color image data to a host computer.

2. The device according to claim 1, wherein the first and second input ports, the processing circuitry and the at least

one output port are integrated circuit components, which are fabricated on a single semiconductor substrate.

3. The device according to claim 1, wherein the at least one output port comprises a single port and is coupled to convey the depth map and the color image data to the host computer as a single data stream in a multiplexed format.

4. The device according to claim 3, wherein the processing circuitry is configured to synchronize the depth map with the color image data in the single data stream.

5. The device according to claim 3, and comprising a third input port for receiving audio information, wherein the processing circuitry is configured to incorporate the audio information together with the depth map and the color image data into the single data stream for conveyance to the host computer via the single port.

6. The device according to claim 3, wherein the single port comprises a Universal Serial Bus (USB) port.

7. The device according to claim 1, wherein the processing circuitry is configured to register the depth map with the color image data.

8. The device according to claim 7, wherein the depth map comprises an array of pixels with respective depth values, and wherein the processing circuitry is configured to compute respective shifts for the pixels responsively to the depth values, and to apply the respective shifts to the pixels in the depth map in order to register the depth map with the color image data.

9. The device according to claim 8, wherein the processing circuitry is configured to compute the respective shifts incrementally, such that the shifts of the pixels within a line of the depth map are computed as a function of a preceding pixel shift.

10. The device according to claim 9, wherein the processing circuitry is configured to compute the respective shifts using an incremental fitting process.

11. The device according to claim 8, wherein the processing circuitry is configured to compute the respective shifts for the pixels on the fly, while receiving the depth values, without storing the entire depth map in the device.

12. The device according to claim 1, wherein the processing circuitry is configured to compress the depth map and the color image data for transmission to the host via the at least one output port.

13. The device according to claim 12, wherein the processing circuitry is configured to apply a process of lossless compression to the depth map and the color image data.

14. The device according to claim 1, wherein the depth-related image data comprise an image of a pattern that is projected onto an object, and wherein the processing circuitry is configured to generate the depth map by measuring shifts in the pattern relative to a reference image.

15. Apparatus for imaging, comprising:

a first image sensor, which is configured to capture and output a color image of an object;

a second image sensor, which is configured to capture and output depth-related image data with respect to the object; and

a processing device, which comprises:

a first input port for receiving the color image data from the first image sensor;

a second input port for receiving the depth-related image data from the second image sensor;

processing circuitry, for generating a depth map using the depth-related image data; and

at least one output port for conveying the depth map and the color image data to a host computer.

16. The apparatus according to claim 15, and comprising an audio sensor, wherein the processing device comprises a third input port for receiving audio information from the audio sensor, and wherein the processing circuitry is configured to convey the audio information together with the depth map and the color image data to the host computer via the at least one output port.

17. The apparatus according to claim 15, wherein the at least one output port comprises a single port and is coupled to convey the depth map and the color image data to the host computer as a single data stream in a multiplexed format.

18. The apparatus according to claim 15, and comprising an illumination subassembly, which is configured to project a pattern onto the object, wherein the depth-related image data comprise an image of the pattern on the object, and wherein the processing circuitry is configured to generate the depth map by measuring shifts in the pattern relative to a reference image.

19. A method for processing data, comprising:

receiving color image data from a first image sensor via a first input port;

receiving depth-related image data from a second image sensor via a second input port;

generating a depth map using the depth-related image data; and

conveying the depth map and the color image data via an output port to a host computer.

20. The method according to claim 19, wherein the depth map is generated by processing circuitry, and wherein the first and second input ports, the processing circuitry and the at least one output port are integrated circuit components, which are fabricated on a single semiconductor substrate.

21. The method according to claim 19, wherein the at least one output port comprises a single port and is coupled to convey the depth map and the color image data to the host computer as a single data stream in a multiplexed format.

22. The method according to claim 21, wherein conveying the depth map comprises synchronizing the depth map with the color image data in the single data stream.

23. The method according to claim 21, and comprising receiving audio information, and incorporating the audio information together with the depth map and the color image data into the single data stream for conveyance to the host computer via the single port.

24. The method according to claim 21, wherein the single port comprises a Universal Serial Bus (USB) port.

25. The method according to claim 19, wherein generating the depth map comprises registering the depth map with the color image data.

26. The method according to claim 25, wherein the depth map comprises an array of pixels with respective depth values, and wherein registering the depth map comprises computing respective shifts for the pixels responsively to the depth values, and applying the respective shifts to the pixels in the depth map.

27. The method according to claim 26, wherein computing the respective shifts comprises processing the respective shifts incrementally, such that the shifts of the pixels within a line of the depth map are computed as a function of a preceding pixel shift.

28. The method according to claim **27**, wherein processing the respective shifts comprises computing the respective shifts using an incremental fitting process.

29. The method according to claim **26**, wherein computing the respective shifts comprises calculating the respective shifts for the pixels on the fly, while receiving the depth values, without storing the entire depth map while calculating the respective shifts.

30. The method according to claim **19**, wherein conveying the depth map and the color image data comprises compressing the depth map and the color image data for transmission to the host via the at least one output port.

31. The method according to claim **30**, wherein compressing the depth map and the color image data comprises applying a process of lossless compression to the depth map and the color image data.

32. The method according to claim **19**, wherein the depth-related image data comprise an image of a pattern that is projected onto an object, and wherein generating the depth map comprises measuring shifts in the pattern relative to a reference image.

* * * * *