

# Project Report

## Concepts of Program Design

Joris ten Tusscher, Joris Burgers, Ivo Gabe de Wolff, Cas van der Rest, Orestis Melkonian

## 1 Problem

### 1.1 Experiment

### 1.2 Janus - Reversible Computation

## 2 Methodology

### 2.1 Expected outcome

### 2.2 Planning

## 3 Results

### 3.1 Achievements

#### 3.1.1 Semantics of operators

In Hanus, a user is able to define their own types and operators. These operators can be defined for their own types or for types that are already defined in Haskell. In Hanus, there are already a number of operators and types defined that users can use.

##### 3.1.1.1 Definition of arbitrary types

In a reversible language, any variable should have a default value with which a variable is initialised before the *main* procedure is run. The original *Janus* specification only allowed for integers. For integers the default value of 0 is chosen. In Hanus, for any number of the *Haskell Num* class, the default is also 0. There are also a number of other types predefined in Hanus. Their defaults are implemented as follows:

- Bool: *False*
- $[\alpha]$  : *[]*
- Map  $\alpha$   $\beta$ : *Data.Map.empty*
- Maybe  $\alpha$ : *Nothing*

Any user that wants to define their own type, has to implement an instance of *DefaultValue* type class for the type they want to use as a *Hanus* variable. It is possible to implement a *DefaultValue* for a type without implementing any operators for that type. A variable of this type can not be changed in this case, except if the type also implements the type class of another type. An example of this would be the class *Real*. Because any *Real* in Haskell has to be also a *Num*, all operators defined on *Num* could also be used on a *Real*.

### 3.1.1.2 Definition of operators

In *Hanus*, operators can be defined to manipulate variables. These operators always come in pairs, one operator for the forward manipulation and one operator for the reverse manipulation. There is no restriction that these operators should be different. For example, the reverse of the negation operator is the negation operator. However, in most circumstances, there operator are two different manipulations. In the original *Janus*, there were 4 manipulation operators defined. There are the operators  $+=$ ,  $-=$ ,  $\hat{=}$  and  $\Leftrightarrow$ . All of these operators only work on integers, as the original *Janus* does not support any other types. The semantics are as follows:

- $x+=e$  adds any arbitrary expression  $e$  to the variable  $x$ . The reverse of this statement is  $x-=e$ . As long as the variable on the right hand side of the operator is not used in the expression  $e$ ,  $e$  can be any computation that results in an integer. The expression  $x+=x$  is therefore not allowed, because this statement does not have a reverse. The constraint that the variable on the left can not occur on the right applies for all operators.
- $x-=e$  subtract the arbitrary expression  $e$  from the variable  $x$ . The reverse is the statement  $x+=e$ .
- $x \hat{=} e$  does a bitwise *xor* with the expression  $e$ . This operator is its own reverse.
- $x \Leftrightarrow y$  is the swap manipulator. This operator takes two variables and swaps their values. This operator is its own reverse.

For a user to implement their own operator in *Hanus*, they have to define their operator to be of the type *Operator*. The type *Operator* is defined in *Haskell* as *Operator*  $\alpha \beta = \text{Operator } (\alpha \rightarrow \beta \rightarrow \alpha) (\alpha \rightarrow \beta \rightarrow \alpha)$ . The first variable is the operator to be used in forward operation, the second variable is the reverse of the first operator. The definition of  $+=$  in *Hanus* is  $(+=) = \text{Operator } (+) (-)$ . A user can use the function `inverse` to inverse an *Operator*. The definition of  $-=$  would become  $(-=) = \text{inverse } (+=)$ . Other operators that are defined for the users convenience include  $\hat{=}$ , swap, push and pop on a stack. All these operators are defined in *Haskell*. Any user wanting to implement their own operators have to define these in *Haskell*, as there is no way to define these in *Hanus*.

### 3.1.1.3 Guarantee of reversibility

The *Operator* type does not guarantee reversibility. This means that there is no check that if a user specifies two manipulations  $m_1$  and  $m_2$  that  $(x \ m_1 \ e) \ m_2 \ e = x$  holds

for every variable  $x$  and every expression  $e$ . It is possible that the user defines `(*) = Operator (*) (+)`. It should be clear that this operator is incorrect, because the reverse of multiplication is not addition. However, *Hanus* will not detect such a mistake and will run a program containing this code without problem. Therefore, a user that defines their own operator, should be careful to make sure that every operator they define is indeed reversible in every situation.

### 3.1.2 Indexers

Indexer are functions that are used to access specific fields in a data structure. These data structures are implemented in *Haskell* using the *DefaultValue* type.

#### 3.1.2.1 Field indexer

A field index is an indexer used to point to a specified field of a data type. One example, implemented in *Hanus*, is the type *BinaryTree*. This *BinaryTree* is either a *Node* with a value and two sub trees or a *Leaf*. The *DefaultValue* of a *BinaryTree* is a *Leaf*. This *BinaryTree* is not very useful unless there would be an option to access the values or children of the tree. This is where *FieldIndexer* is used. To define a *FieldIndexer*, a user should specify both a *get* and a *set* function. The *get* function is used to retrieve the value from the data structure and the *set* function is used insert the value in the data structure, possibly removing the data that was there before. This is not a problem for reversibility, because this *set* and *get* are never directly called by the program at runtime. They are used by the operators, retrieving the value, updating it and returning the updated value using the *set* function. A few examples of the usage of a *Field Indexer* include *x.nodeValue* and *x.leftChild*. Each of these fields can then be used as a variable with any operator that support the type of the field. The details of the implementation of *BinaryTree* can be found in the code repository in the module *StdLib.BinaryTree*.

#### 3.1.2.2 Array indexer

Array indexer have the same purpose as Field Indexer in that they are used to access specific parts of the data structure. The difference between the two indexers is that an *ArrayIndexer* has one more variable. This variable is used to access a specific part of the data structure that is not necessary known at compile time. The most notable example is the default way access items in an array:  $x[i]$  where  $x$  is an array and  $i$  is the key that points to a position in array  $x$ . In some languages, there is a restriction that the key has to be an integer. This restriction does not exists in *Hanus*. A user is free to use any type as a key. For the definition, the *ArrayIndexer* also requires two functions, one *get* function and one *set* function. The *get* function requires the variable that needs to be accessed and a key that points to an item in the data structure. The *set* function requires a function that receives the data structure, the key of the variable in the data structure and the new value that needs to be inserted in the data structure. In *Hanus*, *ArrayIndexer* is used to implement arrays. This indexer can also be used for structures like maps, lists and similar structures.

## 3.2 Examples of *Hanus*

### DIVISION

---

```
1  {-# LANGUAGE TemplateHaskell, ScopedTypeVariables, QuasiQuotes, FlexibleContexts #-}
2
3  module Divide where
4
5  import QQ
6  import StdLib.Operator
7  import StdLib.DefaultValue
8
9  [hanusT|
10 procedure divide(x :: Int, y :: Int, z :: Int){
11     from x >= y && z == 0 loop
12         z += 1;
13         x -= y;
14     until x < y;
15 }
16
17 procedure main(x :: Int, y :: Int, z :: Int){
18     call divide x y z;
19     uncall divide x y z;
20 }|]
```

---

The division example is a simple example of what *Hanus* is capable of. This function computes the division and the remainder. When the variable is called in reverse, it can be used to compute the multiplication. Because the *main* procedure calls *divide* and then *uncalls* *divide* with the same arguments, *main* acts as the identity function for most parameters. With this program, it is possible to explain the loop in *Hanus*. The loop has a precondition and a postcondition and a body. The precondition has to be *True* only the first iteration and the postcondition has to be *True* only the last iteration. When the loop is reversed, precondition and postcondition change places.

### FIBONACCI

---

```

1  {-# LANGUAGE TemplateHaskell, ScopedTypeVariables, QuasiQuotes, FlexibleContexts #-}
2
3  module Fibonacci where
4
5  import QQ
6  import StdLib.Operator
7  import StdLib.DefaultValue
8
9  [hanusT|
10 procedure fib(x1 :: Int, x2 :: Int, n :: Int){
11     if n == 0 then
12         x1 += 1;
13         x2 += 1;
14     else
15         n -= 1;
16         call fib x1 x2 n;
17         x1 += x2;
18         swap x1 x2;
19     fi x1 == x2;
20 }
21
22 procedure main(x1 :: Int, x2 :: Int, n :: Int){
23     call fib x1 x2 n;
24 }
25 |]

```

---

The Fibonacci example has three parameters. The first two are two sequential Fibonacci numbers, the third parameter  $n$  represents the  $n$ th parameter. This function can normally be used to calculate the  $n$ th Fibonacci number. The reverse of this program is, given two sequential Fibonacci numbers, what is the position of the first Fibonacci number when all Fibonacci numbers are listed. For example,  $x_1 = 5$  and  $x_2 = 8$  return  $n = 4$  because 5 is the fourth Fibonacci number, starting on a list with 0. This example also includes an if-statement. This if-statement differs from regular if-statements with the addition of the postcondition. This postcondition must be *True* if the if-branch was executed and has to be *False* if the else-branch was executed. The reverse of the if-statement is the reverse of both bodies and the reversal of the precondition and the postcondition.

#### RUN LENGTH ENCODING

---

```

1  {-# LANGUAGE TemplateHaskell, ScopedTypeVariables, QuasiQuotes, FlexibleContexts #-}
2
3  module RLE where
4
5  import QQ
6  import StdLib.Operator
7  import StdLib.DefaultValue
8
9  [hanusT|
10 procedure encode(text :: [Int], arc :: [Int]){
11     from (text /= []) && arc == [] do
12         local val :: Int = 0;
13         local n :: Int = 0;
14         val += head text;
15         from n == 0 do
16             local tmp :: Int = 0;
17             pop text tmp;
18             delocal val;
19             n += 1;
20             until text == [] || ((head text) /= val);
21             push arc val;
22             push arc n;
23             delocal 0;
24             delocal 0;
25         until text == [];
26 }
27
28 procedure main(text :: [Int], arc :: [Int]){
29     call encode text arc;
30 }
31 |]
```

---

The run length encoding example shows the usage of a more complicated program that uses two nested loops and a stack to store the data. The program compresses the data using run-length encoding. An example is the array [12, 12, 12, 13, 13], which gets converted to the array [2, 13, 3, 12]. This is an example with a very useful reverse. A user has only to provide the encoder for such a compression and by uncalls the encode procedure, providing the compressed data, the original data is returned.

### 3.3 Goal/planning adjustments

## 4 Reflection

### 4.1 Good/bad surprises

### 4.2 Problems along the way

## 5 Appendix

### 5.1 Repo link

### 5.2 Code navigation