Concepts of programming languages Janus

Joris ten Tusscher, Joris Burgers, Ivo Gabe de Wolff, Cas van der Rest, Orestis Melkonian

fib: calculates (n+1)-th and (n+2)-th Fibonacci number.

```
procedure fib
  if n = 0 then
     x1 += 1     ; -- 1st Fib nr is 1.
     x2 += 1     ; -- 2nd Fib nr is 1.
else
     n -= 1
     call fib
     x1 += x2
     x1 <=> x2
fi x1 = x2
```

fib: calculates (n+1)-th and (n+2)-th Fibonacci number.

```
procedure fib
  if n = 0 then
     x1 += 1    ; -- 1st Fib nr is 1.
     x2 += 1    ; -- 2nd Fib nr is 1.
  else
     n -= 1
     call fib
     x1 += x2
     x1 <=> x2
  fi x1 = x2    ; -- Why do we need this?
```

fib: calculates (n+1)-th and (n+2)-th Fibonacci number.

```
procedure fib
  if n = 0 then
     x1 += 1    ; -- 1st Fib nr is 1.
     x2 += 1    ; -- 2nd Fib nr is 1.
  else
     n -= 1
     call fib
     x1 += x2
     x1 <=> x2
  fi x1 = x2    ; -- Why do we need this?
```

Q: How do we calculate the inverse?

fib: calculates (n+1)-th and (n+2)-th Fibonacci number.

```
procedure fib
   if n = 0 then
        x1 += 1     ; -- 1st Fib nr is 1.
        x2 += 1     ; -- 2nd Fib nr is 1.
   else
        n -= 1
        call fib
        x1 += x2
        x1 <=> x2
   fi x1 = x2     ; -- Used for inverting the if-statement.
```

Q: How do we calculate the inverse?

```
\mathcal{I}[\![\!] if e_1 then s_1 else s_2 fi e_2]\!] =  if e_2 then \mathcal{I}[\![\![s_1]\!]\!] else \mathcal{I}[\![\![s_2]\!]\!] fi e_1

[Faculty of Science Universiteit Utrecht Information and Computing Sciences]
```

fib: calculates (n+1)-th and (n+2)-th Fibonacci number.

fib: calculates (n+1)-th and (n+2)-th Fibonacci number.

Q: What does the inverse of fib do?