



SysAdminHCP

Client Portal — Complete User Manual

A step-by-step guide to managing your domains, email, databases, SSL certificates, files, backups and support tickets from your SysAdminHCP hosting account.

Document version 1.2

Covers the Client Portal (not the Admin Portal)

In memory of Kloxo CP

Table of Contents

Getting Started

- Logging in
- Portal layout & navigation
- Feature permissions & hidden menu items
- Appearance: themes, font size & density

Dashboard & Resource Usage

Domains

- Adding a domain
- Editing a domain
- Advanced: VHost, SSL VHost & Webmail VHost editors
- Viewing visitor statistics
- Deleting a domain

Subdomains

DNS Records

Email

- Mail accounts
- Mail domains
- Forwards
- Recent mail
- Spam whitelist
- Spam blacklist

Webmail

FTP Accounts

Databases

- Creating a database
- Database users & access

phpMyAdmin

SSL Certificates

Let's Encrypt (Free SSL)

File Manager

Backups

PHP Version

Bandwidth

AI Spam Filter & Email Log

Email Log — Recent Entries

Per-Account Filtering

Support Tickets **PRO**

Notifications **PRO**

App Installer **PRO**

Email Migration **PRO**

My Account

Profile

Changing your password

Two-Factor Authentication (2FA)

API Access

Web Config

Redirects

Custom Error Pages

Directory Password Protection

Custom MIME Types

Calendar & Contacts **PRO**

PHP Settings **PRO**

Troubleshooting & FAQ

Getting Help

1. Getting Started

1.1 Logging in

Your hosting provider gives you a Client Portal URL (usually `https://yourserver:7777/display` or a custom address they provide), along with a username and password. Open the URL in your browser and sign in with those credentials.

If your provider has enabled Two-Factor Authentication (2FA) on your account, you'll be asked for a 6-digit code from your authenticator app after entering your password. See Section 22.3 to set this up yourself if it isn't already enabled.

1.2 Portal layout & navigation

The left sidebar is your main menu, grouped into sections:

Group	Contains
Overview	Dashboard
Hosting	Domains, Subdomains, DNS Records, Email, Webmail, FTP, Databases, phpMyAdmin
Security	SSL, Let's Encrypt
Tools	File Manager, Backups, PHP Version, Bandwidth, App Installer PRO , Email Migration PRO
Analytics	AI Spam Filter (only visible if enabled for you)
Support	Support Tickets PRO
Account	My Account, About

The header bar at the top shows the current page title, a notification bell (Pro accounts), your username, and a **Logout** button. On mobile devices, tap the hamburger icon (≡) to open the sidebar.

Tip — Quick Links

The Dashboard has a grid of Quick Link tiles (Domains, Email, DNS, FTP, Databases, phpMyAdmin, SSL, Files, Backups) that jump straight to each section — handy shortcuts once you're logged in.

1.3 Feature permissions & hidden menu items

Not every account can use every feature. Your administrator controls, per account, which actions you're allowed to perform (adding domains, adding mailboxes, deleting FTP accounts, managing DNS, etc.), as well as numeric limits (maximum number of domains, mailboxes, FTP accounts, databases, disk space and bandwidth).

If a button doesn't work

If you click a "Create" or "Delete" button and get a permission error, or a menu item you expect to see is missing entirely, your administrator has most likely restricted that feature on your account, or you've hit a resource limit. Contact your administrator to review your account's permissions and limits.

Similarly, some sidebar items only appear when applicable:

- **AI Spam Filter** — only shows if your administrator has turned on AI-based spam filtering for at least one of your domains.
- **Support Tickets, Notifications bell, App Installer, Email Migration** — these are Pro features. They only appear if your hosting account is on a Pro license.

1.4 Appearance: themes, font size & density

Under [My Account](#) you'll find an Appearance/Theme section where you can personalize how the portal looks — purely visual, saved to your browser, and doesn't affect your hosting in any way:

- **Theme:** Cosmic (default), Classic, Dark, Ocean, Sunset, Forest
- **Font Size:** Small, Medium, Large
- **Density:** Compact, Cozy, Comfortable

2. Dashboard & Resource Usage

The Dashboard is your home page after logging in. It shows:

- A **Quick Links** grid for jumping directly to any major feature.
- A **Resource Usage** card with a usage bar for each of the following, showing how much you've used against your account's limit:
 - **Disk Space** — calculated from your home directory and mailbox storage
 - **Bandwidth** — calculated for your current billing cycle
 - **Domains, Mail Accounts, FTP Accounts, Databases** — counts against your account limits

Each usage bar changes color as you approach your limit: **green** under 70%, **orange** between 70–90%, and **red** above 90%. If a limit shows as ∞, that resource is unlimited on your account.

No "plan" picker

Unlike some hosting panels, there is no self-service plan-upgrade page in the Client Portal — your resource limits are individual settings on your account configured by your administrator. If you need more space, domains, or mailboxes, contact your administrator (or open a support ticket, if enabled — see Section 18).

3. Domains

The Domains page lists every domain on your account with its Type, Status, PHP version, and whether SSL is active (✓/X).

3.1 Adding a domain

- 1 Click **+ Add Domain** in the top-right toolbar.
- 2 Enter the **Domain Name** (e.g. `example.com`).
- 3 Choose a **Type**: *Virtual* (a normal, independent website), *Addon*, or *Forward* (redirects to another URL).
- 4 Click **Create**.

Domain limit reached?

If you see "Domain limit reached", your account has hit its maximum number of domains. Contact your administrator to raise the limit.

3.2 Editing a domain

Click **Edit** on any domain row to open its settings, organized into four groups:

Group	Settings
General	Document Root (default <code>/home/{you}/{domain}</code>), Index File (default <code>index.html</code>)
Forward (<i>Forward-type domains only</i>)	Forward URL, Forward Type (301 Permanent / 302 Temporary)
Web	SSL Enabled, PHP Version (5.6 – 8.4), PHP Mode (PHP-FPM, mod_php, suPHP, FCGId, CGI, LSAPI), Force HTTPS
Mail	Catchall Enabled/Disabled, Catchall Email address
DNS	DNS Managed (Yes/No)

Make your changes and click **Save**.

3.3 Advanced: VHost, SSL VHost & Webmail VHost editors

Each domain row also has three advanced buttons that open the raw web-server configuration for that domain:

- **VHost** — the plain HTTP (port 80) Apache/Nginx virtual host configuration.
- **SSL VHost** — the HTTPS (port 443) virtual host. Includes a [Generate Template](#) button that fills in a working boilerplate block for you.
- **Webmail VHost** — the configuration for `webmail.{domain}`.

Advanced users only

These editors let you directly edit the live server configuration text for your domain. An invalid configuration can take your site offline. Only use these if you understand Apache/Nginx configuration syntax, or if your administrator has instructed you to make a specific change here.

3.4 Viewing visitor statistics

Click [Stats](#) on a domain row to open its traffic report in a new tab. If no report has been generated yet, you'll see a "No stats report available yet" message.

3.5 Deleting a domain

Click [Delete](#) on a domain row and confirm. This permanently removes the domain and **all** associated data (files, mail, databases tied to it, DNS records) — this action cannot be undone, so make sure you have a backup first (see Section 14).

4. Subdomains

Subdomains (like `shop.example.com` or `blog.example.com`) are managed on their own page.

- 1 Click `+ Add Subdomain`.
- 2 Enter the **Subdomain Name** (just the prefix, e.g. `shop`).
- 3 Choose the **Parent Domain** from the dropdown.
- 4 Click `Create`. Your new subdomain will be `shop.example.com`.

To remove one, click `Delete` on its row and confirm.

5. DNS Records

If you only have one domain, the DNS Records page opens straight into that domain's record list. With multiple domains, you'll first see a list of DNS zones — click [Manage Records](#) on the one you want to edit.

Adding a record

- 1 Click [+ Add Record](#).
- 2 Enter the **Hostname** (use [@](#) for the root domain, or a prefix like [www](#)).
- 3 Choose the **Type**: A, AAAA, CNAME, MX, TXT, or NS.
- 4 Enter the **Content** (an IP address for A/AAAA, or a hostname for CNAME/MX/NS).
- 5 Set the **TTL** in seconds (default [3600](#)).
- 6 If Type is **MX**, also set a **Priority** (default [10](#) — lower numbers are tried first).
- 7 Click [Add](#).

Editing or deleting a record

Click [Edit](#) on any record row to change its Type, Host, Value, TTL, Priority, or Weight (the edit form additionally supports SRV and CAA record types). Click [Delete](#) and confirm to remove a record.

Bulk-updating all A records ("Change IP")

If your server's IP address changes and you need to update every A record in a zone at once:

- 1 Click [Change IP](#) at the top of the zone view.
- 2 Enter the **New IP Address**.
- 3 Click [Update All A Records](#) — every A record in that zone is updated in one step.

6. Email

The Email page has six tabs: **Mail Accounts**, **Mail Domains**, **Forwards**, **Recent Mail**, **Spam Whitelist**, and **Spam Blacklist**.

6.1 Mail Accounts

This tab lists every mailbox on your account with its domain, quota, and status.

Creating a mailbox

- 1 Click [+ Add Account](#).
- 2 Enter the **Email Address** (just the part before the @).
- 3 Choose the **Domain**.
- 4 Set a **Password**.
- 5 Set a **Quota in MB** (enter [0](#) for unlimited).
- 6 Click [Create](#).

Click [Manage](#) on any row to open that mailbox's management panel — this is where you change its password, storage quota, and enable/suspend status, and find the manual email client (IMAP/SMTP) settings, all in one place. You can also click [Webmail](#) to jump straight into that domain's webmail login, or [Delete](#) to remove the mailbox entirely (including its stored mail).

The Manage panel

- **Status** — shows whether the mailbox is Active or Suspended, with a button to toggle it. Suspending disables IMAP/POP3/webmail login immediately, but new mail keeps arriving and will be waiting for you once you re-enable access — it is never rejected or bounced while suspended.
- **Storage** — shows current usage against your quota (with a color bar once a quota is set), and a field to change the quota (in MB; [0](#) means unlimited).
- **Password** — set a new password for this mailbox.
- **Email Client Setup** — the exact Incoming (IMAP) and Outgoing (SMTP) server, port, and security settings for configuring this mailbox in Apple Mail, Outlook, Thunderbird, or the Gmail app ("Add account → Other"). Each value has a small copy button next to it. Desktop clients usually auto-detect these settings once you enter your email and password — manual entry is normally only needed on phones and tablets.

6.2 Mail Domains

A read-only list of which of your domains have mail enabled, and their catchall address status.

6.3 Forwards

A forward automatically redirects incoming mail for one address to another address, without creating a real mailbox.

- 1 Click [+ Add Forward](#).
- 2 Enter the **Source Address** (e.g. [sales@example.com](#)).
- 3 Enter the **Destination** (e.g. [me@gmail.com](#)).
- 4 Choose whether to **Keep Copy** — Yes delivers to a local mailbox as well as forwarding; No forwards only.
- 5 Click [Create](#).

Click [Delete](#) on a forward's row to remove it.

6.4 Recent Mail

A live log of what actually happened to your mail — proof that a message arrived or went out, and when. It reads directly from the mail server's own delivery log, so it covers every message regardless of whether the AI Spam Filter is enabled for that mailbox.

- 1 If you have more than one mail domain, pick one from the dropdown, or leave it on *All my domains*.
- 2 Click [Load Incoming](#) to see mail delivered to your mailbox(es), or [Load Outgoing](#) to see mail sent from them.

Each row shows the time, sender, recipient, subject, and size. **Subject** is only available for mail sent or received after this feature was turned on for your server — older messages show a dash instead of a blank, so you can tell the difference between "no subject" and "not tracked yet."

6.5 Spam Whitelist

Senders on your whitelist always bypass the AI spam filter for your mailboxes.

- 1 Choose a **Scope**: *My Domain* (applies to every mailbox on a domain) or *My Mailbox* (applies to one address only).
 - 2 Choose an **Entry Type**: *Email address* or *Domain (all @)*.
-

- 3 Fill in the **Target** (which domain or mailbox this rule applies to) and the **Value** (the sender email or sender domain to whitelist).
- 4 Click [+ Add](#).

The table shows who added each entry — **Admin**, **You**, or **One-click link** (added via a quarantine notification email link). Click [Remove](#) to delete an entry.

6.6 Spam Blacklist

Senders on your blacklist are instantly marked as spam without being analyzed — this also saves AI processing cost. Works identically to the whitelist above (same Scope / Entry Type / Target / Value fields).

Ownership is always checked

You can only add whitelist/blacklist entries and forwards for domains and mailboxes you actually own — the portal will reject entries for domains that aren't on your account.

7. Webmail

This page lists a webmail login link for each of your domains (`https://webmail.{domain}/`) — click any link to open that domain's webmail in a new tab and log in with a mailbox address and password.

If your server has both Roundcube and RainLoop installed, a **Client** dropdown appears next to each domain so you can choose which webmail application serves that domain.

8. FTP Accounts

- 1 Click [+ Add FTP Account](#).
- 2 Enter a **Username** and **Password**.
- 3 Optionally choose a **Domain** to associate the account with.
- 4 Set the **Home Directory** (pre-filled to your home folder — you can point it at a specific subfolder to restrict what this FTP account can see).
- 5 Click [Create](#).

Use the [Password](#) button on any row to reset that account's password, or [Delete](#) to remove it.

9. Databases

This page has two cards: **Databases** and **Database Users**.

9.1 Creating a database

- 1 Click [+ Add Database](#).
- 2 Enter a **Database Name**.
- 3 Optionally, enter a **DB User Name** and **DB User Password** to create a dedicated user for it in the same step.
- 4 Click [Create](#).

Important — your databases are automatically prefixed

To keep every client's databases separate on a shared server, SysAdminHCP automatically prefixes anything you create with your account username. If your username is `acme` and you create a database called `shop`, the real database name on the server is `acme_shop` — and a database user `webuser` becomes `acme_webuser`. Use these **full, prefixed** names in your website's/application's database connection settings.

Click [phpMyAdmin](#) on any database row to open it directly in phpMyAdmin (see Section 10), or [Delete](#) to permanently remove the database and all its data.

9.2 Database users & access

Creating a standalone database user

- 1 Click [+ Add DB User](#).
- 2 Enter a **Username** and **Password**.
- 3 Click [Create](#).

Granting a user access to a database

- 1 On the user's row, click [Assign DB](#).
 - 2 Choose the **Database**.
-

3

Choose the **Privileges** level:

- *ALL PRIVILEGES* — full access
- *SELECT* — read-only
- *Read/Write* — can read and modify data, but not change the database schema

4

Click **Grant Access**.

Each granted database appears as a badge on the user's row with its own **Revoke** button. Use the row's **Password** button to reset a user's password, or **Delete** to remove the user entirely (this revokes all their access).

10. phpMyAdmin

Click  to log in automatically — no separate phpMyAdmin password to remember. You'll be signed in with the credentials of your own database user, and can see every database owned by your account.

How the automatic login works

If you haven't created a dedicated database user yet, the portal quietly creates one for you the first time you open phpMyAdmin. The single-click login link is valid for 60 seconds and can only be used once.

"Cannot connect to MySQL" error

If phpMyAdmin login fails with a message like *"Cannot connect to MySQL as '...': The database user may not exist or the password is incorrect."* — go to Section 9.2 and verify your database user exists and has a valid password.

If this page instead shows *"phpMyAdmin is not installed on this server"* or *"Your account does not have access to phpMyAdmin"*, contact your administrator.

11. SSL Certificates

The SSL page lists every certificate installed on your domains — Domain, Type, Valid From, Expires, Auto Renew, and Status.

Requesting a free certificate

This page is view-only. To actually request and install a certificate yourself, use **Let's Encrypt** (Section 12). There is currently no self-service option to upload your own purchased/custom SSL certificate — if you have one you need installed, contact your administrator.

12. Let's Encrypt (Free SSL)

Let's Encrypt certificates are free, automatically trusted by all browsers, and renew themselves — no ongoing action needed from you once issued.

Requesting a certificate

- 1 Go to [Let's Encrypt](#) in the sidebar.
- 2 Under **Request New Certificate**, select the **Domain** you want to secure.
- 3 Optionally enter a **notification Email** (if left blank, an address at your domain is used automatically).
- 4 Click [Request Certificate](#). You'll see "Requesting certificate... this may take a minute" while it's issued.
- 5 Once complete, you'll see "Certificate installed successfully!" and the domain now shows SSL as active everywhere in the portal.

Before requesting

Your domain's DNS must already be pointing at this server, and the domain must be reachable over plain HTTP, for Let's Encrypt's ownership verification to succeed. If DNS was only just changed, wait for it to propagate first.

The Issued Certificates table on this page shows status badges: **Expired**, **Expiring Soon** (within 30 days), or **Active**. Auto-renewal is always on for Let's Encrypt certificates — there is nothing further you need to do.

13. File Manager

File Manager gives you full access to your own home directory (`/home/{you}`) and everything inside it — you cannot browse outside this folder.

Navigating

Use the breadcrumb trail at the top, or type a path directly into the path box and click `Go`. Click `Show hidden` to reveal dotfiles (like `.htaccess`).

Uploading, creating & organizing files

- **Upload:** click `↑ Upload` and choose one or more files, or drag files directly onto the file listing (up to 200MB per file).
- **New Folder / New File:** use the respective toolbar buttons and enter a name.
- **Select multiple files** via the checkboxes to reveal a bulk toolbar: `Copy`, `Cut`, `Download` (bundles selected files into a zip), `Compress`, and `Delete`.
- After a Copy or Cut, navigate to the destination folder and click `📋 Paste`.

Per-file actions

Action	What it does
↓ Download	Downloads the file to your computer
Edit	Opens recognized text files (HTML, CSS, JS, PHP, config files, etc.) in a built-in editor
Extract	Unpacks a <code>.zip</code> , <code>.tar</code> , <code>.gz</code> , <code>.tgz</code> or <code>.tar.gz</code> archive into a folder you choose
Rename	Renames the file or folder
Chmod	Changes Unix permissions (e.g. <code>755</code>) — for folders, you can apply this recursively
Delete	Permanently deletes the file or folder

To compress files, select them and click `Compress`, name the archive, and choose **ZIP** or **TAR.GZ**.

14. Backups

You can create, download, restore, and delete your own account backups at any time — no need to wait for your administrator.

Creating a backup

- 1 Click [+ Create Backup](#).
- 2 By default, **Full Backup (all components)** is checked — this backs up everything. Uncheck it to pick specific components instead:
 -  Home Files — all files in your home directory
 -  Account Settings — domains, DNS zones, mail accounts, FTP users, database records
 -  Email Data — mailbox contents for all your domains
 -  SSL Certificates — certificate and key files
 -  Databases — MySQL/MariaDB dumps
 -  FTP Users — FTP account configuration
 -  DNS Zone Files
 -  Apache Config — virtual host files
 -  Webmail Config
- 3 Click [Create Backup](#). A progress bar tracks the job (this runs in the background, so you can navigate elsewhere and come back).

Downloading, restoring & deleting

Each backup in the list shows its contents, size, and creation date, with three actions:

- **Download** — saves the backup archive ([.tgz](#)) to your computer.
- **Restore** — opens a confirmation showing what's in the backup. Check **Skip existing records** if you only want to restore what's missing without overwriting current data, then click [Restore Now](#).
- **Delete** — permanently removes the backup file from the server.

Restoring overwrites data

Unless you check "Skip existing records", restoring a backup will overwrite your current domains, mail accounts, and other settings with what's in the backup, and databases are recreated from the backup's

SQL dumps. Only restore when you're sure this is what you want.

15. PHP Version

This page lists each of your domains with its current PHP version and a dropdown to change it.

- 1 Find the domain you want to change.
- 2 Choose a version from the **Change To** dropdown (only versions your administrator has enabled on the server are shown).
- 3 Click .

The change takes effect within a few seconds as the PHP process for your domain restarts automatically.

16. Bandwidth

This page shows your data-transfer usage for the current billing cycle, broken down per domain, plus a 12-month history chart (hover any bar to see the exact figure for that month).

Quota warnings

If you're nearing your bandwidth limit, an amber banner appears at 90% usage. If you go over 100%, a red banner warns that hosting services may be suspended until your next billing cycle or until your administrator raises your limit.

17. AI Spam Filter & Email Log

This menu item only appears if your administrator has enabled AI-based spam filtering on at least one of your domains. It shows, for the last 30 days: Emails Analyzed, Spam Blocked, Ham (legitimate mail) Delivered, and your Spam Rate percentage — plus a breakdown of AI token usage by day, month, and year.

17.1 Email Log — Recent Entries

Below the stats tiles is an **Email Log** card — a record of every individual email that reached your domain(s), showing exactly who it was from, who it was addressed to, its subject, and whether it was delivered to the inbox or quarantined as spam.

Proof an email actually arrived

This is the place to check whenever you (or one of your own clients) believe an expected email "never arrived." Search the log for the sender or subject — if it's there, you'll see immediately whether it was delivered normally or caught by the spam filter, instead of just taking "I never got it" at face value.

- 1 Go to **AI Spam Filter** in the sidebar.
- 2 If you have more than one domain with the filter enabled, choose which one to view from the **domain dropdown** (or leave it on "All my domains").
- 3 Click **Load Recent Entries**.
- 4 Use the **search box** to filter the list by sender, recipient, or subject — handy when you're looking for one specific email rather than scrolling the whole list.

Each row shows:

Column	Meaning
Date	When the email was received and processed
From	The sender's email address
To	The mailbox on your domain it was delivered to
Subject	The email's subject line

Status	✓ Delivered — reached the inbox normally, or 🚫 Quarantined — held as spam (hover the badge to see why, e.g. "phishing", "marketing")
Confidence	How confident the AI filter was in that verdict

Only covers domains with AI filtering enabled

The Email Log only has data for domains where your administrator has turned on AI spam filtering — it isn't a general record of every email your server has ever handled. If a domain doesn't appear in the dropdown, or the whole AI Spam Filter menu item is missing, filtering isn't enabled for it; ask your administrator if you'd like this turned on.

17.2 Per-Account Filtering

Below the Email Log is a **Per-Account Filtering** card, letting you override the AI Spam Filter for one specific mailbox — the same control your administrator has, scoped to mailboxes you own.

- 1 If you have more than one domain with filtering enabled, pick one from the dropdown, or leave it on *All my domains*.
- 2 Click [↻ Load Accounts](#).
- 3 For any mailbox, use the **Set Mode** dropdown to choose *Inherit* (use the domain's default setting), *Force ON* (always filter this mailbox, even if the domain default is off), or *Exempt* (never filter this mailbox, even if the domain default is on).

The **Effective** column shows what actually happens right now for each mailbox, after taking any override into account — this is the one to check if you're unsure whether a specific mailbox is currently protected.

18. Support Tickets PRO

If your hosting account is on a Pro license, you can open and track support tickets directly from the portal.

Opening a ticket

- 1 Click [+ New Ticket](#).
- 2 Enter a **Subject**.
- 3 Choose a **Department**.
- 4 Choose a **Priority**: Low, Medium (default), High, or Urgent.
- 5 Optionally select a **Related Domain**.
- 6 Write your **Message** describing the issue.
- 7 Click [Submit Ticket](#).

Replying to a ticket

Click any ticket in your list to open it. Support staff replies appear on a light-blue background labeled "Support Staff"; your own replies appear in gray. If the ticket is still open, type your reply in the box at the bottom and click [Send Reply](#). Closed tickets show "This ticket is closed" instead of a reply box — open a new ticket if you need further help on the same topic.

19. Notifications PRO

The bell icon () in the header shows important account notifications from your administrator or the system, color-coded by severity: **info** (blue), **warning** (orange), **critical** (red). Unread notifications are marked with a dot and shown in bold; click one to mark it read, or use "mark all read" to clear the badge.

20. App Installer PRO

Install common web applications onto a domain without manual setup.

- 1 Click [New Install](#) (or similarly-labeled button).
- 2 Choose the **Application** to install.
- 3 Choose the **Domain** (subdomains aren't listed here — install onto the main domain).
- 4 Optionally set an **Install Path** to install into a subfolder rather than the domain root.
- 5 Submit — the install list auto-refreshes every 5 seconds while your install is in progress (status moves from *pending* → *installing* → *completed/failed*).

Click a completed install to see its site URL and any post-install instructions. Use [Delete](#) to remove an install — note this removes the installed files from your hosting account.

21. Email Migration PRO

Bring your mailbox over from your old email host. SysAdminHCP connects to your old provider over IMAP and copies your messages straight into a mailbox here — your old account is never modified.

- 1 Click [New Import](#).
- 2 Under **Your Old Mailbox (IMAP)**, enter the old provider's IMAP Host, Port (default 993), whether to use TLS (default Yes), and your old Email/Username and Password.
- 3 Under **Your New Mailbox**, choose the destination Domain and Email. You can set a New Mailbox Password, or leave it blank to auto-generate one (only used if the mailbox doesn't already exist).
- 4 Submit the import.

Your old password is never stored

Your old mailbox's password is used only once, for this import, and is not saved anywhere afterward.

The import list shows live progress (`migrated/total` messages, current folder) and auto-refreshes every few seconds while running. Deleting an import from the list does not remove any mail already copied over.

22. My Account

22.1 Profile

Update your Real Name, Email, Phone, Language (English/Español/Português), Address, City, State and Country, then click [Save Changes](#). Your Username and Login Type are fixed and cannot be changed here.

22.2 Changing your password

- 1 Enter your **Current Password**.
- 2 Enter a **New Password**.
- 3 Click [Change Password](#).

22.3 Two-Factor Authentication (2FA)

2FA adds a second security step (a rotating 6-digit code from an app like Google Authenticator or Authy) on top of your password.

Enabling 2FA

- 1 Click [Enable 2FA](#).
- 2 Scan the QR code shown with your authenticator app (or type in the manual-entry code if you can't scan).
- 3 Enter the current 6-digit code from the app and click [Verify & Enable](#).
- 4 You'll be shown a set of one-time-use **backup codes** — save these somewhere safe now, as they will not be shown again. Use a backup code to log in if you ever lose access to your authenticator app.

Disabling 2FA

Click [Disable 2FA](#) and confirm with your current password.

22.4 API Access

Generate an API key to call the SysAdminHCP API from your own scripts or tools, without exposing your account password.

- 1 Click `Generate New Key`.
- 2 Enter a **Label** to remember what it's for, and optionally an expiry in **Days**.
- 3 Click `Generate` — the raw key is shown **once**. Copy it immediately; it cannot be retrieved again later.

To use the key, exchange it for a temporary access token by calling `POST /api/auth/api-login` with `{"apiKey":"..."}` — the key itself cannot be used to log into the portal directly. Revoke a key at any time from its row; this never affects your account password.

23. Web Config

Four small tools for controlling exactly how your web server handles requests to your domain, all generated directly into your vhost configuration — not written as `.htaccess` files that could be lost or tampered with.

23.1 Redirects

Send visitors from one URL to another automatically.

- 1 Go to `Redirects` in the sidebar.
- 2 Click `+ Add Redirect`.
- 3 Enter the **Source Path** (e.g. `/old-page`) and the **Destination URL** it should send visitors to.
- 4 Choose **301 (Permanent)** if the old page is gone for good, or **302 (Temporary)** if you'll restore it later — search engines treat these differently.
- 5 Click `Create`.

23.2 Custom Error Pages

Replace the default "404 Not Found" or "500 Server Error" page shown to visitors with your own branded page.

- 1 Go to `Error Pages` in the sidebar.
- 2 Pick the error code you want to customize (404, 403, 500, etc.).
- 3 Enter the path to your own HTML file (upload it via File Manager first), or paste HTML directly if the editor supports it.
- 4 Click `Save`.

23.3 Directory Password Protection

Password-protect any folder under your domain with HTTP Basic Auth — a browser login prompt appears before anyone can view that folder's contents.

- 1 Go to `Directory Protection` in the sidebar.
-

- 2 Click `+ Protect Directory` and choose the folder (e.g. `/private`).
- 3 Add one or more users, each with their own username and password — these are separate from your portal login.
- 4 Click `Save`.

Multiple users per directory

You can add several users to the same protected directory — useful for sharing access with a client or contractor without giving out your own portal credentials.

23.4 Custom MIME Types

Tell the web server how to serve a file extension it doesn't recognize by default (for example, serving `.webmanifest` files with the correct content type for a progressive web app).

- 1 Go to `MIME Types` in the sidebar.
- 2 Click `+ Add Mapping`.
- 3 Enter the file **Extension** (e.g. `webmanifest`) and the **MIME Type** it should be served as (e.g. `application/manifest+json`).
- 4 Click `Save`.

24. Calendar & Contacts PRO

If your administrator has enabled it for your domain, every mailbox gets its own CalDAV/CardDAV calendar and address book — sync-able with Apple Calendar/Contacts, iOS, Thunderbird, DAVx⁵, and Outlook. There may also be a **domain-shared** calendar and address book that everyone on the domain can see.

Connecting a device

- 1 Go to **Calendar & Contacts** in the sidebar to find your DAV address — it looks like `https://dav.yourdomain.com/you@yourdomain.com/`.
- 2 In your calendar/contacts app, add a new CalDAV or CardDAV account using that address.
- 3 Sign in with your normal mailbox email address and password — there's no separate DAV password to remember.

Works even if webmail is down

Calendar & Contacts authenticates directly against your mail account, not through webmail — so it keeps working even during a webmail outage.

Domain-shared calendar & contacts

If your administrator turned this on, a shared calendar and/or shared address book is visible to everyone on the domain, and may also be shared read-only outside the domain via a public link — check the Calendar & Contacts page for that link if one has been generated.

Not seeing this menu item?

Calendar & Contacts requires a Pro license and must be enabled per domain by your administrator — if it's missing entirely, ask them to turn it on for your domain.

25. PHP Settings PRO

Tune your own domain's PHP-FPM process pool directly, without waiting on your administrator — separate from PHP Version, which controls which PHP version runs, not how its processes are configured.

- 1 Go to **PHP Settings** in the sidebar and pick the domain to configure, if you have more than one.
- 2 Adjust **Memory Limit** if your application reports running out of memory.
- 3 Adjust **Max Children** (how many simultaneous PHP requests the pool can handle) if your site gets slow or unresponsive under traffic — higher values use more server RAM.
- 4 Adjust **Request Timeout** if a legitimately slow operation (a large import, a report) is being cut off before it finishes.
- 5 Click **Save** — the change applies within a few seconds.

Higher isn't always better

Raising Max Children or Memory Limit too far can exhaust your account's overall resource limit and affect other sites on a shared plan. Start with small increases and check whether the problem is actually resolved before raising further.

26. Troubleshooting & FAQ

"I don't have permission" / a button doesn't do anything

Your administrator can restrict individual actions (adding domains, deleting mailboxes, managing DNS, etc.) per account. This is expected behavior, not a bug — contact your administrator to review your permissions.

A menu item I expect to see is missing

Some sections only appear when relevant: **AI Spam Filter** requires it to be enabled on at least one domain; **Support Tickets**, the **notification bell**, **App Installer**, and **Email Migration** all require a Pro license.

My database isn't named what I typed

Databases and database users you create are automatically prefixed with your account username (`{username}_{name}`) — see Section 9.1. Use the full prefixed name in your application's connection settings.

phpMyAdmin says it can't connect to MySQL

Check that your database user exists and has a working password under Databases → Database Users.

I hit a limit (domains, mailboxes, disk space, bandwidth...)

These are individual account limits set by your administrator, visible as usage bars on the Dashboard. There's no self-service upgrade — contact your administrator or open a support ticket to request a higher limit.

I can't find a way to upload my own SSL certificate

Self-service SSL is currently limited to free Let's Encrypt certificates (Section 12). If you need a purchased/custom certificate installed, ask your administrator.

File Manager won't let me go outside my home folder

This is intentional — client accounts are confined to their own home directory (`/home/{username}`) for security.

A client (or I) says an email was never received

Check the Email Log under AI Spam Filter — search for the sender or subject and see whether it actually arrived and was delivered, or was caught and quarantined as spam. If the domain doesn't have AI spam filtering enabled, there's no log to check yet; ask your administrator to enable it.

27. Getting Help

If this manual doesn't answer your question:

- If your account has **Support Tickets** enabled, open a ticket from the Support Tickets page — this is the fastest way to reach your hosting provider directly.
- Otherwise, contact your hosting provider/administrator using whatever contact details they gave you when your account was set up.
- The [About](#) page in the sidebar shows information about the SysAdminHCP software itself.

SysAdminHCP Client Portal User Manual — generated for your hosting account. Screens and available features may vary slightly depending on your account's permissions and your provider's configuration.