Intelligent Robotics

SLAM

Luís Paulo Reis (University of Porto)

Armando Sousa (University of Porto)

U.PORTO

FEUP FACULDADE DE ENGENHARIA
UNIVERSIDADE DO PORTO

Background

- **Localization** – Where am I?
- **Mapping** – My (dynamic?) surroundings
- **Navigation** – How do I get where I want to go?
- TREND: **SLAM –**
  – Simultaneous Localization and Mapping

SLAM

- **SLAM =**
  Simultaneous Localization and Mapping

- **=> Cycle through both!**



Exploration with Active Loop-Closing for FastSLAM

Cyrill Stachniss Dirk Hähnel Wolfram Burgard

University of Freiburg

Taxonomy of the SLAM Problem

Known vs. unknown correspondence



Uncertainty…

- The **mapping between observations and the map is unknown**
- Picking **wrong** data associations can have **catastrophic** consequences (divergence)



(Cyrill Stachniss – Uni Freiburg)

SLAM

Given

- The robot's controls

$$u_{1:T} = \{u_1, u_2, u_3 \ldots, u_T\}$$

- Observations

$$z_{1:T} = \{z_1, z_2, z_3 \ldots, z_T\}$$

Wanted

- Map of the environment

$$m$$

- Path of the robot

$$x_{0:T} = \{x_0, x_1, x_2 \ldots, x_T\}$$

(Cyrill Stachniss – Uni Freiburg)

SLAM

In Probabilistic Terms

Estimate the robot's path and the map

$$p(x_{0:T}, m \mid z_{1:T}, u_{1:T})$$

distribution path map given observations controls

(Cyrill Stachniss – Uni Freiburg)

SLAM



$$p(x_{0:T}, m \mid z_{1:T}, u_{1:T})$$

(Cyrill Stachniss – Uni Freiburg)

Motion (=System) Model + Observation (=Sensor) Model



MOTION MODEL

- The motion model describes the relative motion of the robot

$$p(x_t \mid x_{t-1}, u_t)$$

distribution new pose given old pose control

MOTION MODEL example

- Gaussian model



- Non-Gaussian model

(Cyrill Stachniss – Uni Freiburg)

Observation Model

- The observation or sensor model relates measurements with the robot's pose

$$p(z_t \mid x_t)$$

Observation Model example

- Gaussian model

- Non-Gaussian model



(Cyrill Stachniss – Uni Freiburg)

Loop Closure



https://youtu.be/BaqSRf5pAZ0



https://youtu.be/WXeWFIUFTC4

The blue arrow is the 'odometric' robot position (where the robot 'thinks' it is).
The red arrow is the 'corrected' robot position.
The ellipses represent the uncertainties of the positions of the landmarks. The smaller the ellipse, the more certain the robot is about the position of the landmark.

SLAM simulation by Sjoerd de Jong under supervision of Gert Kootstra. Department of Artificial Intelligence University of Groningen

Loop Closure





https://youtu.be/O5Zu19-tjY8?t=45

Probabilistic Robotics

- Authors:
  - Sebastian Thrun
  - Wolfram Burgard
  - Dieter Fox
- Publisher:
  - MIT Press, 2005.



Sources

- **Video Class -** https://www.youtube.com/watch?v=wVsfCnyt5jA

- **Extra**
  - https://youtu.be/O5Zu19-tjY8?t=22
  - https://youtu.be/Qrtz0a7HaQ4