Trek Agent Cheatsheet

@trek/coding-agent

November 10, 2026

Overview

The `@trek/coding-agent` is a terminal-based coding agent that extends Pi with custom tools, skills, and extensions. This cheatsheet summarizes the most useful commands, keybindings, and features.

1 Quick Start

- Install: `npm install -g --ignore-scripts @trek/coding-agent`
- Authenticate: `export ANTHROPIC_API_KEY=sk-ant-...` then `pi`
- Or login via subscription: `/login`
- Run with initial prompt: `pi "List all .ts files in src/"`
- Non-interactive print mode: `pi -p "Summarize this codebase"`

2 Interactive Commands

Type `/` in the editor to trigger commands.

Command	Description
`/login`, `/logout`	OAuth authentication
`/model`	Switch models
`/scoped-models`	Enable/disable models for Ctrl+P cycling
`/settings`	Thinking level, theme, message delivery, transport
`/thinking briefly|deep|off`	Pin short-think, restore deep thinking, or turn thinking off
`/hierarchy`	Layering, mode, suite, and one role
`/resume`	Pick from previous sessions
`/new`	Start a new session
`/name <name>`	Set session display name
`/session`	Show session info (file, ID, messages, tokens, cost)
`/tree`	Jump to any point in the session and continue from there
`/fork`	Create a new session from a previous user message
`/clone`	Duplicate the current active branch into a new session
`/compact [prompt]`	Manually compact context, optional custom instructions
`/copy`	Copy last assistant message to clipboard
`/export [file]`	Export session to HTML file
`/share`	Upload as private GitHub gist with shareable HTML link
`/reload`	Reload keybindings, extensions, skills, prompts, and context files
`/hotkeys`	Show all keyboard shortcuts

3 Keyboard Shortcuts

Editor

Key	Action
Ctrl+C	Clear editor (twice to quit)
Escape	Cancel / abort
Escape twice	Open `/tree`
Ctrl+L	Open model selector
Ctrl+P / Shift+Ctrl+P	Cycle scoped models forward/backward
Shift+Tab	Cycle thinking level
Ctrl+O	Collapse/expand tool output
Ctrl+T	Collapse/expand thinking blocks
Shift+Enter	Insert new line (multi-line)
Ctrl+V	Paste image from clipboard (Alt+V on Windows)
`!command`	Run bash command, send output to LLM
`!!command`	Run bash command without sending output
@file	Fuzzy-search project files

Sessions & Models

Key	Action
Ctrl+L	Open model selector
Ctrl+P	Cycle to next model
Alt+P	Cycle to previous model
Shift+Tab	Cycle thinking level
Ctrl+T	Collapse/expand thinking blocks
Ctrl+O	Expand/collapse tool/thinking cards
Alt+Enter	Queue follow-up message
Alt+Up	Restore queued messages to editor

4 Built-in Tools

Tool	Description
`read`	Read file contents
`write`	Create or overwrite files
`edit`	Precise text replacement in files
`bash`	Execute shell commands
`grep`	Search for patterns in files
`find`	Find files by name or pattern
`ls`	List directory contents

5 Session Management

CLI Flag	Description
`pi -c`	Continue most recent session
`pi -r`	Browse and select from past sessions
`pi --no-session`	Ephemeral mode (don't save)
`pi --name "task"`	Set session display name at startup
`pi --session <path|id>`	Use specific session file or ID
`pi --fork <path|id>`	Fork session into a new session

6 Settings

Use `/settings` to modify common options, or edit JSON files directly:
- Global: `/.trek/agent/settings.json`
- Project: `.trek/settings.json` (overrides global)

Environment Variables

Variable	Description
`PI_OFFLINE`	Disable startup network operations
`PI_SKIP_VERSION_CHECK`	Skip version update check at startup
`PI_TELEMETRY`	Override install/update telemetry (0/1)
`PI_CACHE_RETENTION`	Set to `long` for extended prompt cache
`VISUAL`, `EDITOR`	External editor for Ctrl+G

7 Customization

Prompt Templates

Reusable prompts as Markdown files. Type `/name` to expand.
- Place in `/.trek/agent/prompts/`, `.pi/prompts/`, or a pi package
- Example: `Review this code for bugs. Focus on: { {focus} }`

Skills

On-demand capability packages. Invoke via `/skill:name`.
- Place in `/.trek/agent/skills/`, `.pi/skills/`, or a pi package
- See `docs/skills.md`

Extensions

TypeScript modules that extend pi with custom tools, commands, keyboard shortcuts, event handlers, and UI components.
- Place in `/.trek/agent/extensions/`, `.pi/extensions/`, or a pi package
- See `docs/extensions.md`

Themes

Built-in: `dark`, `light`. Themes hot-reload automatically.

- Place in `/.trek/agent/themes/`, `.pi/themes/`, or a pi package
- See `docs/themes.md`

Pi Packages

Bundle and share extensions, skills, prompts, and themes via npm or git.

- `pi install npm:@foo/pi-tools`
- `pi install git:github.com/user/repo@v1`
- `pi list  pi update  pi remove <source>`

8 CLI Reference

Flag	Description
`-p`, `--print`	Print response and exit
`--mode json`	Output all events as JSON lines
`--mode rpc`	RPC mode for process integration
`--export <in> [out]`	Export session to HTML
`--provider <name>`	Provider (anthropic, openai, google, etc.)
`--model <pattern>`	Model pattern or ID
`--api-key <key>`	API key (overrides env vars)
`--thinking <level>`	`off`, `minimal`, `low`, `medium`, `high`, `xhigh`
`--models <patterns>`	Comma-separated patterns for Ctrl+P cycling
`--list-models [search]`	List available models
`-t`, `--tools <list>`	Allowlist specific tool names
`-xt`, `--exclude-tools <list>`	Disable specific tool names
`-nbt`, `--no-builtin-tools`	Disable built-in tools by default
`-nt`, `--no-tools`	Disable all tools by default
`-e`, `--extension <source>`	Load extension from path, npm, or git
`--no-extensions`	Disable extension discovery
`--skill <path>`	Load skill (repeatable)
`--no-skills`	Disable skill discovery
`--prompt-template <path>`	Load prompt template (repeatable)
`--no-prompt-templates`	Disable prompt template discovery
`--theme <path>`	Load theme (repeatable)
`--no-themes`	Disable theme discovery
`-nc`, `--no-context-files`	Disable AGENTS.md and CLAUDE.md discovery
`--system-prompt <text>`	Replace default prompt
`--append-system-prompt <text>`	Append to system prompt
`--verbose`	Force verbose startup
`-h`, `--help`	Show help
`-v`, `--version`	Show version

9 File Arguments

Prefix files with `@` to include in the message:

- `pi @prompt.md "Answer this"`
- `pi -p @screenshot.png "What's in this image?"`
- `pi @code.ts @test.ts "Review these files"`

10 Philosophy

- **No MCP.** Build CLI tools with READMEs, or build an extension that adds MCP support.
- **No sub-agents.** Spawn pi instances via tmux, or build your own with extensions.
- **No permission popups.** Run in a container, or build your own confirmation flow with extensions.
- **No plan mode.** Write plans to files, or build it with extensions.
- **No built-in to-dos.** Use a TODO.md file, or build your own with extensions.