

# **Statistics and Machine Learning**

**Week 2**

**01/25 – 01/29**


**Introduction to Machine Learning**

# Contents for week 2

- Supervised learning
- Example: digit classification
- Elements of supervised learning
- Why statistics
- Unsupervised learning
- Clustering, principal component analysis, SVM
- Recommender system, natural language processing
- Lab: basic python

# Artificial neuron does the job

Google the keyword “pytorch”, “Keras”, “tensor flow” to learn more




A horse with 99% confidence

# Hand-written digit images




[https://scikit-learn.org/stable/auto\\_examples/classification/plot\\_digits\\_classification.html](https://scikit-learn.org/stable/auto_examples/classification/plot_digits_classification.html)


# Hand-written digit images




# Hand-written digit images




# Hand-written digit images




# Hand-written digit images



# Hand-written digit images



# Hand-written digit images



# Clarification on datum versus data

## Singular versus plural

### datum noun



Save Word

da·tum | \ 'dā-təm (听), 'da- (听), 'dä- \

#### Definition of *datum*

- 1 *plural data* \ 'dā-tə (听), 'da- (听) *also* 'dä- (听) \ : something given or admitted especially as a basis for reasoning or inference


// an important historical *datum*

// This enormous expense—and considerable risk—to pick up a *datum* or two about geriatrics?

— Charles Krauthammer

# Model, data set, and loss function

## Elements in machine learning



```
digits.images[0]
```

```
array([[ 0.,  0.,  5., 13.,  9.,  1.,  0.,  0.],
       [ 0.,  0., 13., 15., 10., 15.,  5.,  0.],
       [ 0.,  3., 15.,  2.,  0., 11.,  8.,  0.],
       [ 0.,  4., 12.,  0.,  0.,  8.,  8.,  0.],
       [ 0.,  5.,  8.,  0.,  0.,  9.,  8.,  0.],
       [ 0.,  4., 11.,  0.,  1., 12.,  7.,  0.],
       [ 0.,  2., 14.,  5., 10., 12.,  0.,  0.],
       [ 0.,  0.,  6., 13., 10.,  0.,  0.,  0.]])
```

```
# target_names store the label for the digit image
```


```
digits.target_names[0]
```

```
0
```

See the code in MNIST\_basic.ipynb

# Model, data set, and loss function

## Elements in machine learning



The whole thing in the left is a datum. The information contained:

1. Image (8x8, 64 numbers)
2. Label 'o'


```
digits.images[0]  
  
array([[ 0.,  0.,  5., 13.,  9.,  1.,  0.,  0.],  
       [ 0.,  0., 13., 15., 10., 15.,  5.,  0.],  
       [ 0.,  3., 15.,  2.,  0., 11.,  8.,  0.],  
       [ 0.,  4., 12.,  0.,  0.,  8.,  8.,  0.],  
       [ 0.,  5.,  8.,  0.,  0.,  9.,  8.,  0.],  
       [ 0.,  4., 11.,  0.,  1., 12.,  7.,  0.],  
       [ 0.,  2., 14.,  5., 10., 12.,  0.,  0.],  
       [ 0.,  0.,  6., 13., 10.,  0.,  0.,  0.]])
```

```
# target_names store the label for the digit image  
  
digits.target_names[0]  
  
0
```

See the code in MNIST\_basic.ipynb

# Model, data set, and loss function

## Elements in machine learning



```
digits.images[0]
```

```
array([[ 0.,  0.,  5., 13.,  9.,  1.,  0.,  0.],
       [ 0.,  0., 13., 15., 10., 15.,  5.,  0.],
       [ 0.,  3., 15.,  2.,  0., 11.,  8.,  0.],
       [ 0.,  4., 12.,  0.,  0.,  8.,  8.,  0.],
       [ 0.,  5.,  8.,  0.,  0.,  9.,  8.,  0.],
       [ 0.,  4., 11.,  0.,  1., 12.,  7.,  0.],
       [ 0.,  2., 14.,  5., 10., 12.,  0.,  0.],
       [ 0.,  0.,  6., 13., 10.,  0.,  0.,  0.]])
```

```
# target_names store the label for the digit image
```

```
digits.target_names[0]
```

```
0
```

The whole thing in the left is a datum. The information contained:

1. Image (8x8, 64 numbers)
2. Label 'o'


For convenience, we usually do

1. Reshape the image into a 64x1 vector,  
call it x
2. Call y = o

See the code in MNIST\_basic.ipynb

# Model, data set, and loss function

## Elements in machine learning



```
digits.images[0]
```

```
array([[ 0.,  0.,  5., 13.,  9.,  1.,  0.,  0.],  
       [ 0.,  0., 13., 15., 10., 15.,  5.,  0.],  
       [ 0.,  3., 15.,  2.,  0., 11.,  8.,  0.],  
       [ 0.,  4., 12.,  0.,  0.,  8.,  8.,  0.],  
       [ 0.,  5.,  8.,  0.,  0.,  9.,  8.,  0.],  
       [ 0.,  4., 11.,  0.,  1., 12.,  7.,  0.],  
       [ 0.,  2., 14.,  5., 10., 12.,  0.,  0.],  
       [ 0.,  0.,  6., 13., 10.,  0.,  0.,  0.]])
```

<— x

The whole thing in the left is a datum. The information contained:

1. Image (8x8, 64 numbers)
2. Label 'o'

```
# target_names store the label for the digit image
```

```
digits.target_names[0]
```

```
0
```


For convenience, we usually do

1. Reshape the image into a  $64 \times 1$  vector,  
call it x
2. Call  $y = o$

See the code in MNIST\_basic.ipynb

# Model, data set, and loss function

## Elements in machine learning



The whole thing in the left is a datum. The information contained:

1. Image (8x8, 64 numbers)
2. Label 'o'

```
digits.images[0]  
array([[ 0.,  0.,  5., 13.,  9.,  1.,  0.,  0.],  
       [ 0.,  0., 13., 15., 10., 15.,  5.,  0.],  
       [ 0.,  3., 15.,  2.,  0., 11.,  8.,  0.],  
       [ 0.,  4., 12.,  0.,  0.,  8.,  8.,  0.],  
       [ 0.,  5.,  8.,  0.,  0.,  9.,  8.,  0.],  
       [ 0.,  4., 11.,  0.,  1., 12.,  7.,  0.],  
       [ 0.,  2., 14.,  5., 10., 12.,  0.,  0.],  
       [ 0.,  0.,  6., 13., 10.,  0.,  0.,  0.]])
```

<— x

For convenience, we usually do

1. Reshape the image into a  $64 \times 1$  vector,  
call it x
2. Call  $y = o$


```
# target_names store the label for the digit image  
digits.target_names[0]  
0
```

<— y

See the code in MNIST\_basic.ipynb

# Model, data set, and loss function

## Elements in machine learning



```
digits.images[0]
```

```
array([[ 0.,  0.,  5., 13.,  9.,  1.,  0.,  0.],
       [ 0.,  0., 13., 15., 10., 15.,  5.,  0.],
       [ 0.,  3., 15.,  2.,  0., 11.,  8.,  0.],
       [ 0.,  4., 12.,  0.,  0.,  8.,  8.,  0.],
       [ 0.,  5.,  8.,  0.,  0.,  9.,  8.,  0.],
       [ 0.,  4., 11.,  0.,  1., 12.,  7.,  0.],
       [ 0.,  2., 14.,  5., 10., 12.,  0.,  0.],
       [ 0.,  0.,  6., 13., 10.,  0.,  0.,  0.]])
```

$\leftarrow \text{x}$

```
# target_names store the label for the digit image
```


```
digits.target_names[0]
```

```
0
```

$\leftarrow \text{y}$

The whole thing in the left is a datum. The information contained:

1. Image (8x8, 64 numbers)
2. Label 'o'




For convenience, we usually do

1. Reshape the image into a  $64 \times 1$  vector,  
call it x
2. Call y = o

See the code in MNIST\_basic.ipynb

# Model, data set, and loss function

## Elements in machine learning



```
digits.images[0]
```

```
array([[ 0.,  0.,  5., 13.,  9.,  1.,  0.,  0.],
       [ 0.,  0., 13., 15., 10., 15.,  5.,  0.],
       [ 0.,  0., 13., 15., 10., 15.,  5.,  0.],
       [ 0.,  3., 15.,  2.,  0., 11.,  8.,  0.],
       [ 0.,  4., 12.,  0.,  0.,  8.,  8.,  0.],
       [ 0.,  5.,  8.,  0.,  0.,  9.,  8.,  0.],
       [ 0.,  4., 11.,  0.,  1., 12.,  7.,  0.],
       [ 0.,  2., 14.,  5., 10., 12.,  0.,  0.],
       [ 0.,  0.,  6., 13., 10.,  0.,  0.,  0.]])
```

$\leftarrow \text{x}$

```
# target_names store the label for the digit image
```


```
digits.target_names[0]
```

```
0
```

$\leftarrow \text{y}$

The whole thing in the left is a datum. The information contained:

1. Image (8x8, 64 numbers)
2. Label 'o'



```
digits.images[1]
```

```
array([[ 0.,  0.,  0., 12., 13.,  5.,  0.,  0.],
       [ 0.,  0.,  0., 11., 16.,  9.,  0.,  0.],
       [ 0.,  0.,  3., 15., 16.,  6.,  0.,  0.],
       [ 0.,  7., 15., 16., 16.,  2.,  0.,  0.],
       [ 0.,  0.,  1., 16., 16.,  3.,  0.,  0.],
       [ 0.,  0.,  1., 16., 16.,  6.,  0.,  0.],
       [ 0.,  0.,  1., 16., 16.,  6.,  0.,  0.],
       [ 0.,  0.,  0., 11., 16., 10.,  0.,  0.]])
```


For convenience, we usually do

1. Reshape the image into a  $64 \times 1$  vector, call it x
2. Call  $y = o$

See the code in MNIST\_basic.ipynb

# Model, data set, and loss function

## Elements in machine learning




```
digits.images[0]
array([[ 0.,  0.,  5., 13.,  9.,  1.,  0.,  0.],
       [ 0.,  0., 13., 15., 10., 15.,  5.,  0.],
       [ 0.,  0., 13., 15., 10., 15.,  5.,  0.],
       [ 0.,  3., 15.,  2.,  0., 11.,  8.,  0.],
       [ 0.,  4., 12.,  0.,  0.,  8.,  8.,  0.],
       [ 0.,  5.,  8.,  0.,  0.,  9.,  8.,  0.],
       [ 0.,  4., 11.,  0.,  1., 12.,  7.,  0.],
       [ 0.,  2., 14.,  5., 10., 12.,  0.,  0.],
       [ 0.,  0.,  6., 13., 10.,  0.,  0.,  0.]])
```

<— x

The whole thing in the left is a datum. The information contained:

1. Image (8x8, 64 numbers)
2. Label 'o'



```
digits.images[1]
array([[ 0.,  0.,  0., 12., 13.,  5.,  0.,  0.],
       [ 0.,  0.,  0., 11., 16.,  9.,  0.,  0.],
       [ 0.,  0.,  3., 15., 16.,  6.,  0.,  0.],
       [ 0.,  7., 15., 16., 16.,  2.,  0.,  0.],
       [ 0.,  0.,  1., 16., 16.,  3.,  0.,  0.],
       [ 0.,  0.,  1., 16., 16.,  6.,  0.,  0.],
       [ 0.,  0.,  1., 16., 16.,  6.,  0.,  0.],
       [ 0.,  0.,  0., 11., 16., 10.,  0.,  0.]])
```

```
digits.target_names[1]
```

1

For convenience, we usually do

1. Reshape the image into a  $64 \times 1$  vector, call it x
2. Call  $y = o$

```
# target_names store the label for the digit image
digits.target_names[0]
0
```

<— y

See the code in MNIST\_basic.ipynb

# Mathematical notation for data set

$$x_i = \begin{pmatrix} x_{i1} \\ x_{i2} \\ \vdots \\ x_{ip} \end{pmatrix}. \quad (1.1)$$

# Mathematical notation for data set

$$x_i = \begin{pmatrix} x_{i1} \\ x_{i2} \\ \vdots \\ x_{ip} \end{pmatrix}. \quad (1.1)$$

$$\mathbf{X} = \begin{pmatrix} x_{11} & x_{12} & \dots & x_{1p} \\ x_{21} & x_{22} & \dots & x_{2p} \\ \vdots & \vdots & \ddots & \vdots \\ x_{n1} & x_{n2} & \dots & x_{np} \end{pmatrix}$$

# Mathematical notation for data set

$$x_i = \begin{pmatrix} x_{i1} \\ x_{i2} \\ \vdots \\ x_{ip} \end{pmatrix}. \quad (1.1)$$

$$\mathbf{X} = \left( \begin{array}{cccc} x_{11} & x_{12} & \dots & x_{1p} \\ x_{21} & x_{22} & \dots & x_{2p} \\ \hline \vdots & \vdots & \ddots & \vdots \\ x_{n1} & x_{n2} & \dots & x_{np} \end{array} \right)$$

# Mathematical notation for data set

$$x_i = \begin{pmatrix} x_{i1} \\ x_{i2} \\ \vdots \\ x_{ip} \end{pmatrix}. \quad (1.1)$$

$$\mathbf{X} = \left( \begin{array}{cccc} x_{11} & x_{12} & \dots & x_{1p} \\ x_{21} & x_{22} & \dots & x_{2p} \\ \hline \vdots & \vdots & \ddots & \vdots \\ x_{n1} & x_{n2} & \dots & x_{np} \end{array} \right)$$

$$\mathbf{y} = \begin{pmatrix} y_1 \\ y_2 \\ \vdots \\ y_n \end{pmatrix}.$$

# Mathematical notation for data set

$$x_i = \begin{pmatrix} x_{i1} \\ x_{i2} \\ \vdots \\ x_{ip} \end{pmatrix}. \quad (1.1)$$

$$\mathbf{X} = \begin{pmatrix} x_{11} & x_{12} & \dots & x_{1p} \\ x_{21} & x_{22} & \dots & x_{2p} \\ \vdots & \vdots & \ddots & \vdots \\ x_{n1} & x_{n2} & \dots & x_{np} \end{pmatrix}$$

$$\mathbf{y} = \begin{pmatrix} y_1 \\ y_2 \\ \vdots \\ y_n \end{pmatrix}.$$

Interpretation: there are  $n$  data, each datum contains  $p$  features (pixels in MNIST)

# Mathematical notation for data set

$$x_i = \begin{pmatrix} x_{i1} \\ x_{i2} \\ \vdots \\ x_{ip} \end{pmatrix}. \quad (1.1)$$



$$\mathbf{X} = \begin{pmatrix} x_{11} & x_{12} & \dots & x_{1p} \\ x_{21} & x_{22} & \dots & x_{2p} \\ \vdots & \vdots & \ddots & \vdots \\ x_{n1} & x_{n2} & \dots & x_{np} \end{pmatrix}$$

Interpretation: there are  $n$  data, each datum contains  $p$  features (pixels in MNIST)

$$\mathbf{y} = \begin{pmatrix} y_1 \\ y_2 \\ \vdots \\ y_n \end{pmatrix}.$$

The collection  $\{\mathbf{X}, \mathbf{y}\}$  is a data set.

# Model: a mathematical form for $y = f(\mathbf{x} \mid w, b)$





<https://tex.stackexchange.com/questions/132444/diagram-of-an-artificial-neural-network>


$$h(\mathbf{x}) = b + \sum_i w_i x_i$$

$$f(h) = \frac{1}{1 + e^{-h}}$$


# (Qualitative) loss function




# (Qualitative) loss function




# (Qualitative) loss function




# (Qualitative) loss function




# (Qualitative) loss function




# (Qualitative) loss function




# (Qualitative) loss function




# (Qualitative) loss function




# (Qualitative) loss function



# (Qualitative) loss function




# (Qualitative) loss function




# So what is machine learning?

**What we want? a capable model, and an unbiased estimate of error rate.**




# So what is machine learning?

**What we want? a capable model, and an unbiased estimate of error rate.**




# So what is machine learning?

**What we want? a capable model, and an unbiased estimate of error rate.**




# So what is machine learning?

**What we want? a capable model, and an unbiased estimate of error rate.**




# So what is machine learning?

**What we want? a capable model, and an unbiased estimate of error rate.**




# So what is machine learning?

**What we want? a capable model, and an unbiased estimate of error rate.**




# So what is machine learning?

**What we want? a capable model, and an unbiased estimate of error rate.**




# So what is machine learning?

**What we want? a capable model, and an unbiased estimate of error rate.**




# So what is machine learning?

**What we want? a capable model, and an unbiased estimate of error rate.**




# So what is machine learning?

**What we want? a capable model, and an unbiased estimate of error rate.**



# So what is machine learning?

**What we want? a capable model, and an unbiased estimate of error rate.**



# **Important notes for supervised learning**

**Must review this slide before midterm**

# Important notes for supervised learning

**Must review this slide before midterm**

Model is a mathematic function  $\hat{y} = f(x | w, b)$  which takes input  $x$  of a datum and output a prediction  $\hat{y}$

# Important notes for supervised learning

**Must review this slide before midterm**

Model is a mathematic function  $\hat{y} = f(x | w, b)$  which takes input  $x$  of a datum and output a prediction  $\hat{y}$

Lose function measures the deviation between the truth  $y$  and the prediction  $\hat{y}$

# Important notes for supervised learning

## Must review this slide before midterm

Model is a mathematic function  $\hat{y} = f(x | w, b)$  which takes input  $x$  of a datum and output a prediction  $\hat{y}$

Lose function measures the deviation between the truth  $y$  and the prediction  $\hat{y}$

Training error means the average lose function values associated with the training data, i.e. measure of average difference between  $y_{train}$  and  $\hat{y}_{train} = f(x_{train} | w, b)$

# Important notes for supervised learning

**Must review this slide before midterm**

Model is a mathematic function  $\hat{y} = f(x | w, b)$  which takes input  $x$  of a datum and output a prediction  $\hat{y}$

Lose function measures the deviation between the truth  $y$  and the prediction  $\hat{y}$

Training error means the average lose function values associated with the training data, i.e. measure of average difference between  $y_{train}$  and  $\hat{y}_{train} = f(x_{train} | w, b)$

Machine learning use some algorithm based on training error to correct the model parameters  $w$  and  $b$ .

# Important notes for supervised learning

**Must review this slide before midterm**

Model is a mathematic function  $\hat{y} = f(x | w, b)$  which takes input  $x$  of a datum and output a prediction  $\hat{y}$

Lose function measures the deviation between the truth  $y$  and the prediction  $\hat{y}$

Training error means the average lose function values associated with the training data, i.e. measure of average difference between  $y_{train}$  and  $\hat{y}_{train} = f(x_{train} | w, b)$

Machine learning use some algorithm based on training error to correct the model parameters  $w$  and  $b$ .

So during the training, the training error changes with time, and should be on the decreasing tracking.

# Important notes for supervised learning

**Must review this slide before midterm**

Model is a mathematic function  $\hat{y} = f(x | w, b)$  which takes input  $x$  of a datum and output a prediction  $\hat{y}$

Lose function measures the deviation between the truth  $y$  and the prediction  $\hat{y}$

Training error means the average lose function values associated with the training data, i.e. measure of average difference between  $y_{train}$  and  $\hat{y}_{train} = f(x_{train} | w, b)$

Machine learning use some algorithm based on training error to correct the model parameters  $w$  and  $b$ .

So during the training, the training error changes with time, and should be on the decreasing tracking.

So during the training, the model parameters  $w$  and  $b$  are varying too.

# Important notes for supervised learning

**Must review this slide before midterm**

Model is a mathematic function  $\hat{y} = f(x | w, b)$  which takes input  $x$  of a datum and output a prediction  $\hat{y}$

Lose function measures the deviation between the truth  $y$  and the prediction  $\hat{y}$

Training error means the average lose function values associated with the training data, i.e. measure of average difference between  $y_{train}$  and  $\hat{y}_{train} = f(x_{train} | w, b)$

Machine learning use some algorithm based on training error to correct the model parameters  $w$  and  $b$ .

So during the training, the training error changes with time, and should be on the decreasing tracking.

So during the training, the model parameters  $w$  and  $b$  are varying too.

Once the optimal  $\bar{w}$  and  $\bar{b}$  are reached, the training is complete.

# Important notes for supervised learning

**Must review this slide before midterm**

Model is a mathematic function  $\hat{y} = f(x | w, b)$  which takes input  $x$  of a datum and output a prediction  $\hat{y}$

Lose function measures the deviation between the truth  $y$  and the prediction  $\hat{y}$

Training error means the average lose function values associated with the training data, i.e. measure of average difference between  $y_{train}$  and  $\hat{y}_{train} = f(x_{train} | w, b)$

Machine learning use some algorithm based on training error to correct the model parameters  $w$  and  $b$ .

So during the training, the training error changes with time, and should be on the decreasing tracking.

So during the training, the model parameters  $w$  and  $b$  are varying too.

Once the optimal  $\bar{w}$  and  $\bar{b}$  are reached, the training is complete.

Now we feed the test data into the trained model, we calculate the test error be comparing  $y_{test}$  against  $\hat{y}_{test} = f(x_{test} | \bar{w}, \bar{b})$

# Important notes for supervised learning

## Must review this slide before midterm

Model is a mathematic function  $\hat{y} = f(x | w, b)$  which takes input  $x$  of a datum and output a prediction  $\hat{y}$

Lose function measures the deviation between the truth  $y$  and the prediction  $\hat{y}$

Training error means the average lose function values associated with the training data, i.e. measure of average difference between  $y_{train}$  and  $\hat{y}_{train} = f(x_{train} | w, b)$

Machine learning use some algorithm based on training error to correct the model parameters  $w$  and  $b$ .

So during the training, the training error changes with time, and should be on the decreasing tracking.

So during the training, the model parameters  $w$  and  $b$  are varying too.

Once the optimal  $\bar{w}$  and  $\bar{b}$  are reached, the training is complete.

Now we feed the test data into the trained model, we calculate the test error be comparing  $y_{test}$  against  $\hat{y}_{test} = f(x_{test} | \bar{w}, \bar{b})$

What you should deliver to the customer: model  $f(x | w, b)$ , optimal parameter  $\bar{w}$  and  $\bar{b}$ , and the test error.

# Important notes for supervised learning

## Must review this slide before midterm

Model is a mathematic function  $\hat{y} = f(x | w, b)$  which takes input  $x$  of a datum and output a prediction  $\hat{y}$

Lose function measures the deviation between the truth  $y$  and the prediction  $\hat{y}$

Training error means the average lose function values associated with the training data, i.e. measure of average difference between  $y_{train}$  and  $\hat{y}_{train} = f(x_{train} | w, b)$

Machine learning use some algorithm based on training error to correct the model parameters  $w$  and  $b$ .

So during the training, the training error changes with time, and should be on the decreasing tracking.

So during the training, the model parameters  $w$  and  $b$  are varying too.

Once the optimal  $\bar{w}$  and  $\bar{b}$  are reached, the training is complete.

Now we feed the test data into the trained model, we calculate the test error be comparing  $y_{test}$  against  $\hat{y}_{test} = f(x_{test} | \bar{w}, \bar{b})$

What you should deliver to the customer: model  $f(x | w, b)$ , optimal parameter  $\bar{w}$  and  $\bar{b}$ , and the test error.

# Supervised learning versus unsupervised learning

**It is subtle, but an easy answer will be ...**

Supervised learning:  
e.g. Image classification  
Data set:  $\{X, y\}$

# Supervised learning versus unsupervised learning

**It is subtle, but an easy answer will be ...**

Supervised learning:  
e.g. Image classification  
Data set:  $\{X, y\}$

unsupervised learning:  
e.g. Movie recommender, text auto-completion  
Data set:  $\{X\}$

# Supervised learning versus unsupervised learning

**It is subtle, but an easy answer will be ...**

Supervised learning:  
e.g. Image classification  
Data set:  $\{X, y\}$

unsupervised learning:  
e.g. Movie recommender, text auto-completion  
Data set:  $\{X\}$

Learning is driven by loss function.

Metaphor: physical penalty

# Supervised learning versus unsupervised learning

**It is subtle, but an easy answer will be ...**

Supervised learning:  
e.g. Image classification  
Data set:  $\{X, y\}$


unsupervised learning:  
e.g. Movie recommender, text auto-completion  
Data set:  $\{X\}$

Learning is driven by loss function.  
Metaphor: physical penalty

Learning is driven by likelihood.  
Metaphor: education with love

## clustering


**Task: given height-weight of a group of students, to separate data into two subgroups**




(a)

## clustering

**Task: given height-weight of a group of students, to separate data into two subgroups**




(a)




(b)

## clustering

**Task: given height-weight of a group of students, to separate data into two subgroups**



(a)



(b)

**Note: both height and weight are input of a datum, so we don't have a label  $y$  for each datum.**


# high-dimensional space of face images



each image is a point in  $64 \times 64 = 4096$  dimensional space

# principle-component analysis (PCA)

A face image can be thought of as a vector in high dimensional space. The important features are the projected component onto the principal direction vectors.



## **missing pixels completion**



(a)




(b)

**pixels reconstruction from  
statistics of test images**


**read 1.3.4.1**

## recommender system, collaborative filtering



think about how YouTube generates  
the recommending videos to you.

## recommender system, collaborative filtering



think about how YouTube generates  
the recommending videos to you.

# Natural language processing

**Why the free services from FB, google, twitter is actually profitable for them ...**

Data set: e-mails from all google users, wikipedia articles, twitter comments, Ig photos, etc...



Huge neural  
network

When I \_\_\_\_\_ my \_\_\_\_\_, \_\_\_\_\_,

# Natural language processing

**Why the free services from FB, google, twitter is actually profitable for them ...**

Data set: e-mails from all google users, wikipedia articles, twitter comments, Ig photos, etc...



Huge neural  
network

When I **visit** my \_\_\_\_\_, \_\_\_\_\_

# Natural language processing

**Why the free services from FB, google, twitter is actually profitable for them ...**

Data set: e-mails from all google users, wikipedia articles, twitter comments, Ig photos, etc...



Huge neural  
network

When I visit my grandma in nursing house, \_\_\_\_\_,

# Natural language processing

**Why the free services from FB, google, twitter is actually profitable for them ...**

Data set: e-mails from all google users, wikipedia articles, twitter comments, Ig photos, etc...



Huge neural  
network

When I visit my grandma in nursing house,

I would like to buy a flower for her

# Natural language processing

**Why the free services from FB, google, twitter is actually profitable for them ...**

Data set: e-mails from all google users, wikipedia articles, twitter comments, Ig photos, etc...



Huge neural  
network

When I visit my grandma in nursing house,  
call

I would like to buy a flower for her

# Natural language processing

**Why the free services from FB, google, twitter is actually profitable for them ...**

Data set: e-mails from all google users, wikipedia articles, twitter comments, Ig photos, etc...



Huge neural  
network

When I visit my grandma in nursing house,  
call my brother in Army

I would like to buy a flower for her

# Natural language processing

**Why the free services from FB, google, twitter is actually profitable for them ...**

Data set: e-mails from all google users, wikipedia articles, twitter comments, Ig photos, etc...




Huge neural  
network

When I visit my grandma in nursing house,  
call my brother in Army

I would like to buy a flower for her  
I want to tell him the flight fare is good for next two weeks.

# Breaking down neural networks


Regression (week 3 & 4) and logistic regression (week 5 &6)



<https://tex.stackexchange.com/questions/132444/diagram-of-an-artificial-neural-network>

# Breaking down neural networks

Regression (week 3 & 4) and logistic regression (week 5 &6)




Regression:  
 $\mathbf{x} \in \mathbb{R}^d$  and  $y \in \mathbb{R}$

<https://tex.stackexchange.com/questions/132444/diagram-of-an-artificial-neural-network>

# Breaking down neural networks

Regression (week 3 & 4) and logistic regression (week 5 &6)




Regression:  
 $\mathbf{x} \in \mathbb{R}^d$  and  $y \in \mathbb{R}$

<https://tex.stackexchange.com/questions/132444/diagram-of-an-artificial-neural-network>

# Breaking down neural networks

Regression (week 3 & 4) and logistic regression (week 5 &6)




Regression:  
 $\mathbf{x} \in \mathbb{R}^d$  and  $y \in \mathbb{R}$

<https://tex.stackexchange.com/questions/132444/diagram-of-an-artificial-neural-network>

# Breaking down neural networks

Regression (week 3 & 4) and logistic regression (week 5 &6)




Regression:  
 $\mathbf{x} \in \mathbb{R}^d$  and  $y \in \mathbb{R}$

<https://tex.stackexchange.com/questions/132444/diagram-of-an-artificial-neural-network>

# Breaking down neural networks

Regression (week 3 & 4) and logistic regression (week 5 & 6)




Regression:  
 $\mathbf{x} \in \mathbb{R}^d$  and  $y \in \mathbb{R}$

Logistic Regression:  
 $\mathbf{x} \in \mathbb{R}^d$  and  $y \in \{0,1\}$

<https://tex.stackexchange.com/questions/132444/diagram-of-an-artificial-neural-network>

# Breaking down neural networks

Regression (week 3 & 4) and logistic regression (week 5 &6)




Regression:  
 $\mathbf{x} \in \mathbb{R}^d$  and  $y \in \mathbb{R}$

Logistic Regression:  
 $\mathbf{x} \in \mathbb{R}^d$  and  $y \in \{0,1\}$

<https://tex.stackexchange.com/questions/132444/diagram-of-an-artificial-neural-network>

# Breaking down neural networks

Regression (week 3 & 4) and logistic regression (week 5 &6)



Regression:  
 $\mathbf{x} \in \mathbb{R}^d$  and  $y \in \mathbb{R}$

Logistic Regression:  
 $\mathbf{x} \in \mathbb{R}^d$  and  $y \in \{0,1\}$

<https://tex.stackexchange.com/questions/132444/diagram-of-an-artificial-neural-network>