

Statistics and Machine Learning



**Tree-based algorithm: Improvements
Bagging, Random Forest, Boosting**

Contents



Week 12

- Decision trees are simple, but not good enough; bigger trees better but overfit
- 1st improvement: from one tree to one forest — bagging
- 2nd improvement: inserting randomness into tree branching — random forest
- 3rd improvement: make next tree greater than previous tree — boosting
- Ada-boosting and gradient-boosting
- Homework

Simple trees (stump) usually under-fit



Deeper trees often over-fit



A forest of stumps is better than a big tree

Power of AVERAGE


Think about playing the following game: find 10 people and let each one can generate a random number from `Numpy.random.normal(0,1)`. The person whose number is closest to zero wins the contest. But who will win is unpredictable because everyone has an equal chance. However, if 5 participants decide to group together and average their random numbers, then the group has much bigger chance of winning over the rest individuals. Why?

Assume $E[X_1] = E[X_2] = \dots E[X_{10}] = 0$ And $E[X_1^2] = E[X_2^2] = \dots E[X_{10}^2] = 1$

$$\longrightarrow E\left[\frac{X_1 + \dots + X_5}{5}\right] = 0 \quad E\left[\left(\frac{X_1 + \dots + X_5}{5}\right)^2\right] = \frac{1}{5}$$


How to grow different trees with only one data set?

Bootstrapping data set is to generate copies of different versions of one data set




How to grow different trees with only one data set?

Bootstrapping data set is to generate copies of different versions of one data set




How to grow different trees with only one data set?

Bootstrapping data set is to generate copies of different versions of one data set




How to grow different trees with only one data set?

Bootstrapping data set is to generate copies of different versions of one data set




How to grow different trees with only one data set?

Bootstrapping data set is to generate copies of different versions of one data set




How to grow different trees with only one data set?


Bootstrapping data set is to generate copies of different versions of one data set



How to grow different trees with only one data set?

Bootstrapping data set is to generate copies of different versions of one data set





<— Using all data at once.

<— Using bootstrapped dataset #1

<— Using bootstrapped dataset #2

In the end, we average all the prediction.

$$\hat{y} = \frac{1}{B} \sum_{i=1}^B \hat{f}(x)$$

Random Forest

The point: randomly select features when branching

```
AtBat
Hits
HmRun
Runs
RBI
Walks
Years
CAtBat
CHits
CHmRun
CRuns
CRBI
CWalks
League
Division
PutOuts
Assists
Errors
```

Random Forest

The point: randomly select features when branching

AtBat
Hits
HmRun
Runs
RBI
Walks
Years
CAtBat
CHits
CHmRun
CRuns
CRBI
CWalks
League
Division
PutOuts
Assists
Errors

- Step 1: generate N bootstrapped data sets

Random Forest

The point: randomly select features when branching

AtBat
Hits
HmRun
Runs
RBI
Walks
Years
CAtBat
CHits
CHmRun
CRuns
CRBI
CWalks
League
Division
PutOuts
Assists
Errors

- Step 1: generate N bootstrapped data sets
- Step 2: Observe there are M features in the data set

Random Forest

The point: randomly select features when branching

AtBat
Hits
HmRun
Runs
RBI
Walks
Years
CAtBat
CHits
CHmRun
CRuns
CRBI
CWalks
League
Division
PutOuts
Assists
Errors

- Step 1: generate N bootstrapped data sets
- Step 2: Observe there are M features in the data set
- Step 3: Parameter $p \approx \sqrt{M}$ is determined

Random Forest

The point: randomly select features when branching

AtBat
Hits
HmRun
Runs
RBI
Walks
Years
CAtBat
CHits
CHmRun
CRuns
CRBI
CWalks
League
Division
PutOuts
Assists
Errors

- Step 1: generate N bootstrapped data sets
- Step 2: Observe there are M features in the data set
- Step 3: Parameter $p \approx \sqrt{M}$ is determined
- Step 4: For data set i , randomly select p features.

Random Forest

The point: randomly select features when branching

AtBat
Hits
HmRun
Runs
RBI
Walks
Years
CAtBat
CHits
CHmRun
CRuns
CRBI
CWalks
League
Division
PutOuts
Assists
Errors

- Step 1: generate N bootstrapped data sets
- Step 2: Observe there are M features in the data set
- Step 3: Parameter $p \approx \sqrt{M}$ is determined
- Step 4: For data set i , randomly select p features.
- Step 5: Grow a tree and can only use the p features to branch

Random Forest

The point: randomly select features when branching

AtBat
Hits
HmRun
Runs
RBI
Walks
Years
CAtBat
CHits
CHmRun
CRuns
CRBI
CWalks
League
Division
PutOuts
Assists
Errors

- Step 1: generate N bootstrapped data sets
- Step 2: Observe there are M features in the data set
- Step 3: Parameter $p \approx \sqrt{M}$ is determined
- Step 4: For data set i , randomly select p features.
- Step 5: Grow a tree and can only use the p features to branch
- Step 6: Back to Step 4 until B trees are built.

Random Forest


The point: randomly select features when branching

AtBat
Hits
HmRun
Runs
RBI
Walks
Years
CAtBat
CHits
CHmRun
CRuns
CRBI
CWalks
League
Division
PutOuts
Assists
Errors


- Step 1: generate N bootstrapped data sets
- Step 2: Observe there are M features in the data set
- Step 3: Parameter $p \approx \sqrt{M}$ is determined
- Step 4: For data set i , randomly select p features.
- Step 5: Grow a tree and can only use the p features to branch
- Step 6: Back to Step 4 until B trees are built.
- Step 7: For test sample x, the prediction is the average of B trees.

Built two simple trees as example with the baseball player data set

Tree #1



Tree #2




Suppose we have the following player’s data, we can predict their salary based on the two trees.

| Player Name | year | hits | salary |
|-------------|------|------|--------------------|
| A | 2 | 20 | $(1+2)/2 = 1.5$ |
| B | 4 | 120 | $(1+15)/2 = 8$ |
| C | 6 | 10 | $(10+2)/2 = 6$ |
| D | 7 | 150 | $(10+15)/2 = 12.5$ |


Boosting: A sequence of trees

Collection of weak learners become a strong learner



Classification

Tree 1




Tree 2

Tree 3

Final vote

Classification

Tree 1



of incorrect: 3


Tree 2

Tree 3

Final vote


Classification

Tree 1



of incorrect: 3

Tree 2




Final vote

Tree 3


Classification

Tree 1



of incorrect: 3

Tree 2




of incorrect: 3


Tree 3

Final vote

Classification




Classification




Classification

Tree 1




of incorrect: 3

Tree 2




of incorrect: 3

Tree 3




of incorrect: 3

Final vote




Classification

Tree 1




of incorrect: 3

Tree 2




of incorrect: 3

Tree 3




of incorrect: 3

Final vote




Classification

Tree 1




of incorrect: 3

Tree 2




of incorrect: 3

Tree 3




of incorrect: 3

Final vote




Classification

Tree 1




of incorrect: 3

Tree 2



of incorrect: 3

Tree 3




of incorrect: 3

Final vote




Classification

Tree 1




of incorrect: 3

Tree 2




of incorrect: 3

Tree 3





of incorrect: 3

Final vote






Regression







<https://towardsdatascience.com/boosting-in-machine-learning-and-the-implementation-of-xgboost-in-python-fb5365e9f2ao>

Regression







<https://towardsdatascience.com/boosting-in-machine-learning-and-the-implementation-of-xgboost-in-python-fb5365e9f2a0>

Regression







<https://towardsdatascience.com/boosting-in-machine-learning-and-the-implementation-of-xgboost-in-python-fb5365e9f2ao>

Regression







<https://towardsdatascience.com/boosting-in-machine-learning-and-the-implementation-of-xgboost-in-python-fb5365e9f2ao>

Regression







<https://towardsdatascience.com/boosting-in-machine-learning-and-the-implementation-of-xgboost-in-python-fb5365e9f2a0>

Regression



<https://towardsdatascience.com/boosting-in-machine-learning-and-the-implementation-of-xgboost-in-python-fb5365e9f2a0>

Regression



<https://towardsdatascience.com/boosting-in-machine-learning-and-the-implementation-of-xgboost-in-python-fb5365e9f2ao>

Homework

Boosting in sklearn

Complete Exercise 11 in page 335 of textbook

Data set Caravan.csv is available in Blackboard

Boosting method in R is different than in python. Find out what are the corresponding parameters (number of trees, shrinkage value) in python sklearn library.

There are ada-boosting and gradient-boosting methods. You just need to choose one to perform the homework.