


| | | | |
|--|--|--|---|
| <div>CeWL 5.4.8 Cheatsheet (ingenieriainformatica.uniovi.es)</div> <div>Custom wordlist generation tool</div> <div>https://digi.ninja/projects/cewl.php</div> | |  | <pre>operario@kali:~\$ cewl -c -m 5 www.di.uniovi.es -w di.txt CeWL 5.4.8 (Inclusion) Robin Wood (robin@digi.ninja) (https://digi.ninja/) Departamento, 417 Oviedo, 360 Informática, 356 Universidad, 307 uniovi, 206 García, 174 Ingeniería, 148 González, 130 Personal, 120 Gijón, 99 Dirección, 97 María, 96 Alonso, 96 conocimiento, 94</pre> |
| GENERAL USAGE | | | |
| cewl [OPTIONS] ... <url> | | | |
| NOTES | | | |
| <url> is the site to spider looking for words. | | | |
| OPTIONS | | | |
| -a, --meta: include meta data. | | -u, --ua <agent>: User agent to send. | |
| --allowed: A regex pattern that path must match to be followed | | -v, --verbose: Verbose. | |
| -c, --count: Show the count for each word found. | | -w, --write: Write the output to the file. | |
| --convert-umlauts: Convert common ISO-8859-1 (Latin-1) umlauts (ä-ae, ö-oe, ü-ue, ß-ss) | | --with-numbers: Accept words with numbers in as well as just letters | |
| -d <x>,--depth <x>: Depth to spider to, default 2. | | AUTHENTICATION | |
| --debug: Extra debug information. | | --auth_pass: Authentication password. | |
| -e, --email: Include email addresses. | | --auth_type: Digest or basic. | |
| --email_file <file>: Output file for email addresses. | | --auth_user: Authentication username. | |
| --exclude: A file containing A list of paths to exclude | | PROXY SUPPORT | |
| -h, --help: Show help. | | --proxy_host: Proxy host. | |
| -k, --keep: Keep the downloaded file. | | --proxy_password: Password for proxy, if required. | |
| --lowercase: lowercase all parsed words | | --proxy_port: Proxy port, default 8080. | |
| -m, --min_word_length: Minimum word length, default 3. | | --proxy_username: Username for proxy, if required. | |
| --meta_file file: Output file for meta data. | | HEADERS | |
| --meta-temp-dir <dir>: The temporary directory used by exiftool when parsing files, default /tmp. | | --header, -H: In format name:value - can pass multiple. | |
| -n, --no-words: Don't output the wordlist. | | EXAMPLES | |
| -o, --offsite: Let the spider visit other sites. | | <pre>cewl -c -m 5 www.uniovi.es cewl -e www.uniovi.es</pre> | |

by José Manuel Redondo López