Jobber → Google Calendar Sync — Requirements

What this builds: a Cloudflare Worker that copies every *scheduled Jobber Job Visit* into the assigned estimator's Google Calendar within seconds. Routemize reads those calendars as availability, and a job stop can be created from each event.

Scope: Job Visits only. Requests, Quotes/Estimates, Assessments, Tasks and Invoices never create calendar events.

---

1. Accounts and access

#	Account	Who needs it	What it's used for	Notes
1	**GitHub**	Implementer	Hosts the code; pushes trigger deploys	Private repo. The Claude GitHub app must be installed on the repo if an agent pushes code
2	**Cloudflare**	Implementer	Worker, D1 database, Queues, secrets, logs	The free plan works: Queues include 10,000 ops/day and logs 200K events/day
3	**Cloudflare ↔ GitHub link**	Implementer	Workers Builds auto-deploys from the repo	The Cloudflare account must be linked to the **same** GitHub account that owns the repo
4	**Jobber Developer Center** (developer.getjobber.com)	Implementer	Creates the Jobber app: client ID/secret, scopes, webhooks	A **separate login** from the normal Jobber app
5	**Jobber account** (the customer's)	Jobber **admin** user	Approves the app once ("Allow Access")	A trial account works for testing
6	**Google Cloud** (console.cloud.google.com)	Implementer	Project, Calendar API, service account and JSON key	No billing needed for the Calendar API at this volume
7	**Google Calendar** for each estimator	Each estimator, or their Workspace admin	Shares their calendar with the service account	Only the calendar owner or a Workspace admin can share it
8	**Routemize**	Estimators / admin	Connects each estimator's Google Calendar	Uses the same calendar that receives the Jobber events

2. Tools

- **Browser access** to all of the above. An agent can do almost everything through Claude in Chrome. Exceptions: sign-ins, pasting secrets, approving OAuth screens, and downloading the Google key file are done by the human.
- **Node.js 20+ and npm**, only to run the tests or deploy from a terminal. The normal path deploys from GitHub with no local terminal.
- **Optional:** the Cloudflare MCP connector (D1 queries, creating databases). The repo `jose24xhr-sys/jobber-gcal-sync` holds the complete, tested code: 65 tests.

3. Cloudflare resources

Resource	Name	Binding	Created by
Worker	`jobber-gcal-sync`	—	Workers Builds (import repo)
D1 database	`jobber_gcal_sync`	`DB`	Dashboard or `wrangler d1 create`; then run `migrations/0001_init.sql`
Queue	`jobber-visit-sync`	`SYNC_QUEUE` (producer + consumer)	Dashboard → Queues
Queue (dead letter)	`jobber-visit-sync-dlq`	—	Dashboard → Queues
Cron	daily `17 4 * * *`	—	`wrangler.toml` (prunes old logs)

4. Configuration values

Plain variables (in `wrangler.toml`, safe to commit)

Name	Example	Purpose
`JOBBER_API_VERSION`	`2026-09-25`	Required `X-JOBBER-GRAPHQL-VERSION` header
`JOBBER_REDIRECT_URI`	`https://jobber-gcal-sync.<subdomain>.workers.dev/oauth/jobber/callback`	Must match the Jobber app's Callback URL exactly
`GOOGLE_AUTH_MODE`	`service_account`	Or `oauth` (not recommended)
`DEFAULT_TIMEZONE`	`America/New_York`	Used only for all-day visits
`ALLOWED_TOPICS`	`VISIT_CREATE,VISIT_UPDATE,VISIT_COMPLETE,VISIT_DESTROY,JOB_CREATE,JOB_UPDATE,JOB_DESTROY,APP_DISCONNECT`	Webhook topics acted on
`EVENT_TITLE_PREFIX`	*(empty)* or `[Jobber]`	Optional prefix on event titles

Name	Example	Purpose
`JOBBER_CLIENT_ID`	from the Jobber app	Public identifier
`GOOGLE_SA_CLIENT_EMAIL`	`jobber-sync@<project>.iam.gserviceaccount.com`	Service account identity
`keep_vars = true`	top of `wrangler.toml`	Stops Git deploys from deleting variables added in the dashboard

Secrets (Cloudflare → Worker → Settings → Variables and Secrets → type Secret)

Name	Where it comes from	Format
`JOBBER_CLIENT_SECRET`	Jobber app → Authorization section	As shown. It also verifies webhook signatures
`GOOGLE_SA_PRIVATE_KEY`	The service-account JSON key file	Paste the **one-line** `"private_key": "-----BEGIN…\n…-----END PRIVATE KEY-----\n"` text from the JSON. **Do not paste the multi-line PEM**: the dashboard field keeps only the first line
`TOKEN_ENCRYPTION_KEY`	You generate it	Ideally `openssl rand -base64 32`; any long passphrase also works
`ADMIN_API_TOKEN`	You generate it	Long random string; it protects `/admin` and `/oauth/jobber/start`

Never commit secrets, put them in URLs, or paste them into chat.

5. Jobber app settings

Setting	Value
App name / developer	e.g. "Routemize Calendar Sync" / "Routemize"
Callback URL	`https://jobber-gcal-sync.<subdomain>.workers.dev/oauth/jobber/callback`
Short description	Required to save
Scopes (read only)	**Clients**, **Jobs**, **Scheduled Items**, **Users** — no Write boxes
Webhooks (all → `https://jobber-gcal-sync.<subdomain>.workers.dev/webhooks/jobber`)	`VISIT_CREATE`, `VISIT_UPDATE`, `VISIT_COMPLETE`, `VISIT_DESTROY`, `JOB_CREATE`, `JOB_UPDATE`, `JOB_DESTROY`, `APP_DISCONNECT`
Refresh token rotation	**ON** (default)

6. Google settings

Item	Value
Project	e.g. `jobber-gcal-sync`
API enabled	Google Calendar API (`calendar-json.googleapis.com`)
Service account	e.g. `jobber-sync` — **no project roles**
Key	JSON (Keys → Add key → Create new key → JSON)
OAuth scope used	`https://www.googleapis.com/auth/calendar.events` only
Per-estimator calendar sharing	Share with the service account email → **"Make changes (see private events as free/busy)"**

7. Information to collect from the business

- ☐ List of estimators/techs who should get Jobber visits on a calendar
- ☐ For each: **Jobber user** (name) → **Google Calendar ID**, usually their email; it's under Calendar settings → Integrate calendar
- ☐ Confirmation that each estimator has shared their calendar with the service account
- ☐ Business timezone (for all-day visits)
- ☐ Which Jobber admin will click "Allow Access"

8. Hosting model and cost

Two ways to offer it to other businesses

Model	How it works	Limits
Hosted (one Worker, many businesses)	Each business's Jobber admin opens `/oauth/jobber/start` and clicks Allow Access. Their estimators share calendars with your service account. The code is already multi-account	A custom Jobber app can connect to **5 paying Jobber accounts** at most; beyond that it must be published in the Jobber App Marketplace (review, logo, Terms of Service and Privacy Policy URLs). You hold customers' tokens and client data, so have a privacy policy
Self-hosted (one copy per business)	The business follows this guide with its own Cloudflare, Google and Jobber app	No 5-account limit; costs and data stay with the business

Running cost (prices checked Oct 2026)

Service	Cost	Notes
Cloudflare	**$0** on the free plan	Free plan: 100,000 Worker requests/day, 10,000 Queue operations/day, D1 100,000 rows written/day + 5 GB. One visit change ≈ 2 webhooks ≈ 2 requests + ~6 queue ops, so about 1,500 visit changes/day fit free. Paid: **$5/month** (10M requests + 1M queue ops/month included)

Service	Cost	Notes
Google Calendar API	**$0**	No per-call charge; daily quotas are far above this volume. No billing account required
Claude	**$0 to run**	The Worker never calls Claude; Claude was only used to build it
Jobber	**$0** for API use	The business needs its normal Jobber subscription