

# Lung Cancer

Jose Tamez

2023-04-28

## Contents

<b>1 Detailed Survival analysis of the Survival lung data.</b>	<b>1</b>
1.1 Exploring Raw Features with RRPlot . . . . .	2
1.2 Reporting the Metrics . . . . .	8
1.3 Modeling . . . . .	10
1.4 Cox Model Performance . . . . .	10
1.5 Cross-Validation . . . . .	26

## 1 Detailed Survival analysis of the Survival lung data.

```
library(survival)
library(FRESA.CAD)

## Loading required package: Rcpp
## Loading required package: stringr
## Loading required package: miscTools
## Loading required package: Hmisc
##
## Attaching package: 'Hmisc'
## The following objects are masked from 'package:base':
##
##     format.pval, units
## Loading required package: pROC
## Type 'citation("pROC")' for a citation.
##
## Attaching package: 'pROC'
## The following objects are masked from 'package:stats':
##
##     cov, smooth, var
op <- par(no.readonly = TRUE)
pander::panderOptions('digits', 3)
pander::panderOptions('keep.trailing.zeros', TRUE)

data(lung)

## Warning in data(lung): data set 'lung' not found
```

```
lung$inst <- NULL
lung$status <- lung$status - 1
lung <- lung[complete.cases(lung),]

pander::pander(table(lung$status))
```

0	1
47	121

```
pander::pander(summary(lung$time))
```

Min.	1st Qu.	Median	Mean	3rd Qu.	Max.
5	175	268	310	416	1022


## 1.1 Exploring Raw Features with RRPlot


```
convar <- colnames(lung)[lapply(apply(lung,2,unique),length) > 10]
convar <- convar[convar != "time"]
topvar <- univariate_BinEnsemble(lung[,c("status",convar)],"status")
pander::pander(topvar)
```

age	wt.loss
0.106	0.106


```
topv <- min(5,length(topvar))
topFive <- names(topvar)[1:topv]
RRanalysis <- list();
idx <- 1
for (topf in topFive)
{
  RRanalysis[[idx]] <- RRPlot(cbind(lung$status,lung[,topf]),
                             atProb=c(0.90),
                             timetoEvent=lung$time,
                             title=topf,
                             plotRR=FALSE
  )
  idx <- idx + 1
}
```

# Relative Risk: age







# Kaplan–Meier: age




# Relative Risk: wt.loss





## Kaplan–Meier: wt.loss



Low	157	83	27	8	1
At Risk > 31.200	11	6	3	0	0

```
names(RRanalysis) <- topFive
```

## 1.2 Reporting the Metrics

```
ROCAUC <- NULL
CstatCI <- NULL
RRratios <- NULL
LogRangp <- NULL
Sensitivity <- NULL
Specificity <- NULL

for (topf in topFive)
{
  CstatCI <- rbind(CstatCI, RRanalysis[[topf]]$c.index$cstatCI)
  RRratios <- rbind(RRratios, RRanalysis[[topf]]$RR_atP)
  LogRangp <- rbind(LogRangp, RRanalysis[[topf]]$surdif$pvalue)
  Sensitivity <- rbind(Sensitivity, RRanalysis[[topf]]$ROCAanalysis$sensitivity)
  Specificity <- rbind(Specificity, RRanalysis[[topf]]$ROCAanalysis$specificity)
  ROCAUC <- rbind(ROCAUC, RRanalysis[[topf]]$ROCAanalysis$aucs)
}

rownames(CstatCI) <- topFive
rownames(RRratios) <- topFive
rownames(LogRangp) <- topFive
rownames(Sensitivity) <- topFive
rownames(Specificity) <- topFive
```



```
rownames(ROCAUC) <- topFive
```

```
pander::pander(ROCAUC)
```

	est	lower	upper
<b>age</b>	0.589	0.491	0.686
<b>wt.loss</b>	0.559	0.460	0.658

```
pander::pander(CstatCI)
```

	mean.C Index	median	lower	upper
<b>age</b>	0.558	0.557	0.494	0.618
<b>wt.loss</b>	0.513	0.513	0.449	0.570

```
pander::pander(RRatios)
```

	est	lower	upper
<b>age</b>	1.005	0.744	1.36
<b>wt.loss</b>	0.785	0.462	1.33

```
pander::pander(LogRangp)
```

<b>age</b>	0.859
<b>wt.loss</b>	0.358

```
pander::pander(Sensitivity)
```

	est	lower	upper
<b>age</b>	0.1074	0.0585	0.177
<b>wt.loss</b>	0.0496	0.0184	0.105

```
pander::pander(Specificity)
```

	est	lower	upper
<b>age</b>	0.894	0.769	0.965
<b>wt.loss</b>	0.894	0.769	0.965

```
meanMatrix <- cbind(ROCAUC[,1],CstatCI[,1],Sensitivity[,1],Specificity[,1],RRatios[,1])
colnames(meanMatrix) <- c("ROCAUC","C-Stat","Sen","Spe","RR")
pander::pander(meanMatrix)
```

	ROCAUC	C-Stat	Sen	Spe	RR
<b>age</b>	0.589	0.558	0.1074	0.894	1.005

	ROCAUC	C-Stat	Sen	Spe	RR
<b>wt.loss</b>	0.559	0.513	0.0496	0.894	0.785

### 1.3 Modeling

```
ml <- BSWiMS.model(Surv(time,status)~1,data=lung,NumberOfRepeats = 10)
```

```
[++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++]..
```

```
sm <- summary(ml)
pander::pander(sm$coefficients)
```

Table 11: Table continues below

	Estimate	lower	HR	upper	u.Accuracy	r.Accuracy
<b>ph.ecog</b>	4.32e-01	1.194	1.541	1.988	0.679	0.649
<b>sex</b>	-4.59e-01	0.456	0.632	0.876	0.649	0.679
<b>pat.karno</b>	-1.77e-03	0.997	0.998	1.000	0.506	0.720
<b>ph.karno</b>	-4.64e-07	1.000	1.000	1.000	0.577	0.720
<b>age</b>	4.57e-08	1.000	1.000	1.000	0.565	0.720

Table 12: Table continues below

	full.Accuracy	u.AUC	r.AUC	full.AUC	IDI	NRI
<b>ph.ecog</b>	0.601	0.601	0.620	0.600	0.0449	0.405
<b>sex</b>	0.601	0.620	0.601	0.600	0.0285	0.478
<b>pat.karno</b>	0.506	0.585	0.500	0.585	0.0292	0.342
<b>ph.karno</b>	0.577	0.570	0.500	0.570	0.0143	0.280
<b>age</b>	0.565	0.549	0.500	0.549	0.0162	0.195

	z.IDI	z.NRI	Delta.AUC	Frequency
<b>ph.ecog</b>	3.33	2.48	-0.02005	1.0
<b>sex</b>	2.76	2.85	-0.00167	1.0
<b>pat.karno</b>	2.44	2.24	0.08546	1.0
<b>ph.karno</b>	2.22	1.64	0.06998	0.8
<b>age</b>	1.97	1.14	0.04871	0.1

### 1.4 Cox Model Performance

Here we evaluate the model using the `RRPlot()` function.

#### 1.4.1 The evaluation of the raw Cox model with `RRPlot()`

Here we will use the predicted event probability assuming a baseline hazard for events withing 5 years

```
timeinterval <- 2*mean(subset(lung,status==1)$time)

h0 <- sum(lung$status & lung$time <= timeinterval)
h0 <- h0/sum((lung$time > timeinterval) | (lung$status==1))
pander::pander(t(c(h0=h0,timeinterval=timeinterval)),caption="Initial Parameters")
```

Table 14: Initial Parameters


h0	timeinterval
0.85	578

```
index <- predict(ml, lung)


rdata <- cbind(lung$status, ppoisGzero(index, h0))

rrAnalysisTrain <- RRPlot(rdata, atProb=c(0.90),
  timetoEvent=lung$time,
  title="Raw Train: Lung Cancer",
  ysurvlim=c(0.00, 1.0),
  riskTimeInterval=timeinterval)
```


### Cumulative vs. Observed: Raw Train: Lung Cancer




## Decision Curve Analysis: Raw Train: Lung Cancer




# Relative Risk: Raw Train: Lung Cancer






**Time vs. Events: Raw Train: Lung Cancer**



## Kaplan–Meier: Raw Train: Lung Cancer



### Number at risk

Low	130	77	25	7	1
At Risk > 0.649	38	12	5	1	0

As we can see the Observed probability as well as the Time vs. Events are not calibrated.

### 1.4.2 Uncalibrated Performance Report

```
pander::pander(t(rrAnalysisTrain$OERatio),caption="O/E Ratio")
```

Table 15: O/E Ratio

est	lower	upper
1.65	1.37	1.97

```
pander::pander(t(rrAnalysisTrain$OE95ci),caption="O/E Ratio")
```

Table 16: O/E Ratio

mean	50%	2.5%	97.5%
1.21	1.21	1.16	1.25

```
pander::pander(t(rrAnalysisTrain$OAcum95ci),caption="O/Acum Ratio")
```



Table 17: O/Acum Ratio

mean	50%	2.5%	97.5%
1.2	1.2	1.19	1.21

```
pander::pander(rrAnalysisTrain$c.index$cstatCI,caption="C. Index")
```

mean.C Index	median	lower	upper
0.651	0.651	0.586	0.714

```
pander::pander(t(rrAnalysisTrain$ROCAalysis$aucs),caption="ROC AUC")
```

Table 19: ROC AUC

est	lower	upper
0.691	0.598	0.784

```
pander::pander((rrAnalysisTrain$ROCAalysis$sensitivity),caption="Sensitivity")
```

Table 20: Sensitivity

est	lower	upper
0.273	0.196	0.361

```
pander::pander((rrAnalysisTrain$ROCAalysis$specificity),caption="Specificity")
```

Table 21: Specificity

est	lower	upper
0.894	0.769	0.965

```
pander::pander(t(rrAnalysisTrain$thr_atP),caption="Probability Thresholds")
```

Table 22: Probability Thresholds

90%
0.649

```
pander::pander(t(rrAnalysisTrain$RR_atP),caption="Risk Ratio")
```

Table 23: Risk Ratio

est	lower	upper
1.31	1.11	1.54

```
pander::pander(rrAnalysisTrain$surdif, caption="Logrank test")
```

Table 24: Logrank test Chisq = 10.879375 on 1 degrees of freedom,  
p = 0.000972

	N	Observed	Expected	(O-E)^2/E	(O-E)^2/V
<b>class=0</b>	130	88	101.3	1.76	10.9
<b>class=1</b>	38	33	19.7	9.05	10.9

### 1.4.3 Cox Calibration

```
op <- par(no.readonly = TRUE)

calprob <- CoxRiskCalibration(ml, lung, "status", "time")

pander::pander(c(h0=calprob$h0,
  Gain=calprob$hazardGain,
  DeltaTime=calprob$timeInterval),
  caption="Cox Calibration Parameters")
```

h0	Gain	DeltaTime
1.29	1.52	749


### 1.4.4 The RRplot() of the calibrated model

```
h0 <- calprob$h0
timeinterval <- calprob$timeInterval;


rdata <- cbind(lung$status, calprob$prob)

rrAnalysisTrain <- RRPlot(rdata, atProb=c(0.90),
  timetoEvent=lung$time,
  title="Train: Lung",
  ysurvlim=c(0.00, 1.0),
  riskTimeInterval=timeinterval)
```


**Cumulative vs. Observed: Train: Lung**




Decision Curve Analysis: Train: Lung




# Relative Risk: Train: Lung






Time vs. Events: Train: Lung



## Kaplan–Meier: Train: Lung



### Number at risk

Low	130	77	25	7	1
At Risk > 0.796	38	12	5	1	0

### 1.4.5 Calibrated Train Performance

```
pander::pander(t(rrAnalysisTrain$OERatio),caption="O/E Ratio")
```

Table 26: O/E Ratio

est	lower	upper
1.45	1.2	1.73

```
pander::pander(t(rrAnalysisTrain$OE95ci),caption="O/E Ratio")
```

Table 27: O/E Ratio

mean	50%	2.5%	97.5%
1.04	1.04	0.996	1.08

```
pander::pander(t(rrAnalysisTrain$OAcum95ci),caption="O/Acum Ratio")
```



Table 28: O/Acum Ratio

mean	50%	2.5%	97.5%
1.01	1.01	0.999	1.01

```
pander::pander(rrAnalysisTrain$c.index$cstatCI,caption="C. Index")
```

mean.C Index	median	lower	upper
0.651	0.65	0.591	0.71

```
pander::pander(t(rrAnalysisTrain$ROCAalysis$aucs),caption="ROC AUC")
```

Table 30: ROC AUC

est	lower	upper
0.691	0.598	0.784

```
pander::pander((rrAnalysisTrain$ROCAalysis$sensitivity),caption="Sensitivity")
```

Table 31: Sensitivity

est	lower	upper
0.273	0.196	0.361

```
pander::pander((rrAnalysisTrain$ROCAalysis$specificity),caption="Specificity")
```

Table 32: Specificity

est	lower	upper
0.894	0.769	0.965

```
pander::pander(t(rrAnalysisTrain$thr_atP),caption="Probability Thresholds")
```

Table 33: Probability Thresholds

90%
0.796

```
pander::pander(t(rrAnalysisTrain$RR_atP),caption="Risk Ratio")
```

Table 34: Risk Ratio

est	lower	upper
1.31	1.11	1.54

```
pander::pander(rrAnalysisTrain$surdif, caption="Logrank test")
```

Table 35: Logrank test Chisq = 10.879375 on 1 degrees of freedom, p = 0.000972

	N	Observed	Expected	(O-E)^2/E	(O-E)^2/V
<b>class=0</b>	130	88	101.3	1.76	10.9
<b>class=1</b>	38	33	19.7	9.05	10.9

## 1.5 Cross-Validation

```
rcv <- randomCV(theData=lung,
  theOutcome = Surv(time,status)~1,
  fittingFunction=BSWiMS.model,
  trainFraction = 0.95,
  repetitions=200,
  classSamplingType = "Pro"
)
```

.[++++].[++++].[++-].[++++].[++].[+].[++].[++].[++++].[++++]10 Tested: 69 Avg. Selected: 3.3 Min Tests: 1  
Max Tests: 3 Mean Tests: 1.449275 . MAD: 0.4822321 .[++++].[++].[+].[++].[++].[++++].[++++].[++++].[++++].[++]+20  
Tested: 117 Avg. Selected: 3.35 Min Tests: 1 Max Tests: 5 Mean Tests: 1.709402 . MAD: 0.4774963  
.[++++].[++++].[++].[++++].[++].[++-].[++++].[++].[++-].[++]+30 Tested: 141 Avg. Selected: 3.333333 Min  
Tests: 1 Max Tests: 6 Mean Tests: 2.12766 . MAD: 0.4761588 .[++++].[++].[++++].[++++].[++].[++++].[++++].[++++].[++++].[++]+40  
Tested: 152 Avg. Selected: 3.4 Min Tests: 1 Max Tests: 7 Mean Tests: 2.631579 . MAD: 0.4739485  
.[++++].[++++].[++++].[++++].[++++].[+].[++++].[++].[++++].[++]+50 Tested: 161 Avg. Selected: 3.44 Min  
Tests: 1 Max Tests: 8 Mean Tests: 3.10559 . MAD: 0.476395 .[++++].[++].[++].[++].[++].[++++].[++].[++++].[++++].[++]+60  
Tested: 164 Avg. Selected: 3.416667 Min Tests: 1 Max Tests: 10 Mean Tests: 3.658537 .  
MAD: 0.475574 .[++++].[++++].[++++].[++++].[++++].[++].[++++].[++].[++++].[++++]+70 Tested: 166  
Avg. Selected: 3.471429 Min Tests: 1 Max Tests: 10 Mean Tests: 4.216867 . MAD: 0.4761199  
.[++++].[++++].[++++].[++++].[++++].[++++].[+].[++].[++]+80 Tested: 166 Avg. Selected: 3.4875 Min  
Tests: 1 Max Tests: 10 Mean Tests: 4.819277 . MAD: 0.4762632 .[++++].[++].[++++].[+].[++++].[++++].[++]+90  
Tested: 167 Avg. Selected: 3.444444 Min Tests: 1 Max Tests: 10 Mean Tests: 5.389222 . MAD: 0.4751278 .[++++].[++].[++++].[++++].[++++].[++++].[++++].[++++].[++++].[++++]+100  
Tested: 167 Avg. Selected: 3.51 Min Tests: 1 Max Tests: 12 Mean Tests: 5.988024 . MAD:  
0.4752975 .[++++].[+].[++++].[++++].[++++].[++++].[++++].[++++].[++++].[++++]+110 Tested: 167  
Avg. Selected: 3.536364 Min Tests: 1 Max Tests: 15 Mean Tests: 6.586826 . MAD: 0.4749925  
.[++++].[++++].[++].[++++].[++].[++++].[++++].[++++].[++++].[++]+120 Tested: 168 Avg. Selected: 3.558333  
Min Tests: 1 Max Tests: 17 Mean Tests: 7.142857 . MAD: 0.4756236 .[++++].[++++].[++].[++++].[++].[++++].[++].[++++].[++].[++]+130  
Tested: 168 Avg. Selected: 3.546154 Min Tests: 1 Max Tests: 17 Mean Tests: 7.738095 . MAD: 0.4752674  
.[++++].[++++].[+].[++++].[++++].[++].[++].[++++].[++].[+]+140 Tested: 168 Avg. Selected: 3.535714 Min  
Tests: 1 Max Tests: 17 Mean Tests: 8.333333 . MAD: 0.4750797 .[++++].[++].[++-].[++++].[++++].[++-]  
.[++++].[++].[++-].[++++]+150 Tested: 168 Avg. Selected: 3.526667 Min Tests: 1 Max Tests: 19 Mean  
Tests: 8.928571 . MAD: 0.4752041 .[++++].[++++].[++].[++].[++++].[++++].[++].[++++].[++++].[++]+160  
Tested: 168 Avg. Selected: 3.54375 Min Tests: 1 Max Tests: 20 Mean Tests: 9.52381 . MAD: 0.474961  
.[+].[++++].[++++].[++].[++++].[++].[++++].[+].[++].[++++]+170 Tested: 168 Avg. Selected: 3.529412 Min  
Tests: 1 Max Tests: 21 Mean Tests: 10.11905 . MAD: 0.4754508 .[++++].[++++].[++++].[++++].[++++].[++++].[++++].[+].[+]

Tested: 168 Avg. Selected: 3.544444 Min Tests: 1 Max Tests: 21 Mean Tests: 10.71429 . MAD: 0.4753713  
 .[+++].[++++].[++++].[++++].[+].[++].[++].[+].[++++].[++].190 Tested: 168 Avg. Selected: 3.526316 Min Tests:  
 2 Max Tests: 21 Mean Tests: 11.30952 . MAD: 0.475501 .[++++].[++].[++++].[++++].[++++].[++++].[++++].[++++].[++++].[++++].  
 Tested: 168 Avg. Selected: 3.56 Min Tests: 2 Max Tests: 22 Mean Tests: 11.90476 . MAD: 0.4755006


```
stp <- rcv$urvTestPredictions
stp <- stp[!is.na(stp[,4]),]

bbx <- boxplot(unlist(stp[,1])~rownames(stp),plot=FALSE)
times <- bbx$stats[3,]
status <- boxplot(unlist(stp[,2])~rownames(stp),plot=FALSE)$stats[3,]
prob <- ppoisGzero(boxplot(unlist(stp[,4])~rownames(stp),plot=FALSE)$stats[3,],h0)


rdatacv <- cbind(status,prob)
rownames(rdatacv) <- bbx$names
names(times) <- bbx$names

rrAnalysisTest <- RRPlot(rdatacv,atProb=c(0.90),
  timetoEvent=times,
  title="Test: Lung Cancer",
  ysurvlim=c(0.00,1.0),
  riskTimeInterval=timeinterval)
```


## Cumulative vs. Observed: Test: Lung Cancer




## Decision Curve Analysis: Test: Lung Cancer




# Relative Risk: Test: Lung Cancer






**Time vs. Events: Test: Lung Cancer**



## Kaplan–Meier: Test: Lung Cancer



### Number at risk

Low	140	79	24	6	0
At Risk > 0.810	28	10	6	2	1

### 1.5.1 Cross-Validation Test Performance

```
pander::pander(t(rrAnalysisTest$OERatio),caption="O/E Ratio")
```

Table 36: O/E Ratio

est	lower	upper
1.45	1.2	1.73

```
pander::pander(t(rrAnalysisTest$OE95ci),caption="O/E Ratio")
```

Table 37: O/E Ratio

mean	50%	2.5%	97.5%
1.03	1.03	0.996	1.07

```
pander::pander(t(rrAnalysisTest$OAcum95ci),caption="O/Acum Ratio")
```



Table 38: O/Acum Ratio

mean	50%	2.5%	97.5%
0.961	0.962	0.95	0.972

```
pander::pander(rrAnalysisTest$c.index$cstatCI,caption="C. Index")
```

mean.C Index	median	lower	upper
0.601	0.601	0.536	0.66

```
pander::pander(t(rrAnalysisTest$ROCAAnalysis$aucs),caption="ROC AUC")
```

Table 40: ROC AUC

est	lower	upper
0.615	0.515	0.715

```
pander::pander((rrAnalysisTest$ROCAAnalysis$sensitivity),caption="Sensitivity")
```

Table 41: Sensitivity

est	lower	upper
0.19	0.124	0.271

```
pander::pander((rrAnalysisTest$ROCAAnalysis$specificity),caption="Specificity")
```

Table 42: Specificity

est	lower	upper
0.894	0.769	0.965

```
pander::pander(t(rrAnalysisTest$thr_atP),caption="Probability Thresholds")
```

Table 43: Probability Thresholds

90%
0.81

```
pander::pander(t(rrAnalysisTest$RR_atP),caption="Risk Ratio")
```

Table 44: Risk Ratio

est	lower	upper
1.26	1.05	1.51

```
pander::pander(rrAnalysisTest$surdif, caption="Logrank test")
```

Table 45: Logrank test Chisq = 2.346444 on 1 degrees of freedom,  
p = 0.125569

	N	Observed	Expected	(O-E)^2/E	(O-E)^2/V
<b>class=0</b>	140	98	103.8	0.328	2.35
<b>class=1</b>	28	23	17.2	1.981	2.35

### 1.5.2 Calibrating the test results

```
rdatacv <- cbind(status,prob,times)
calprob <- CalibrationProbPoissonRisk(rdatacv)

pander::pander(c(h0=calprob$h0,
  Gain=calprob$hazardGain,
  DeltaTime=calprob$timeInterval),
  caption="Cox Calibration Parameters")
```


h0	Gain	DeltaTime
0.85	1	752

```
timeinterval <- calprob$timeInterval;


rdata <- cbind(status,calprob$prob)

rrAnalysisTest <- RRPlot(rdata,atProb=c(0.90),
  timetoEvent=times,
  title="Calibrated Test: Lung",
  ysurvlim=c(0.00,1.0),
  riskTimeInterval=timeinterval)
```


### Cumulative vs. Observed: Calibrated Test: Lung




### Decision Curve Analysis: Calibrated Test: Lung




# Relative Risk: Calibrated Test: Lung






**Time vs. Events: Calibrated Test: Lung**



## Kaplan–Meier: Calibrated Test: Lung



### Number at risk

Low	140	79	24	6	0
At Risk > 0.810	28	10	6	2	1

### 1.5.3 Calibrated Test Performance

```
pander::pander(t(rrAnalysisTest$OERatio),caption="O/E Ratio")
```

Table 47: O/E Ratio

est	lower	upper
1.45	1.2	1.73

```
pander::pander(t(rrAnalysisTest$OE95ci),caption="O/E Ratio")
```

Table 48: O/E Ratio

mean	50%	2.5%	97.5%
1.04	1.04	0.998	1.08

```
pander::pander(t(rrAnalysisTest$OAcum95ci),caption="O/Acum Ratio")
```



Table 49: O/Acum Ratio

mean	50%	2.5%	97.5%
0.961	0.961	0.951	0.972

```
pander::pander(rrAnalysisTest$c.index$cstatCI,caption="C. Index")
```

mean.C Index	median	lower	upper
0.601	0.602	0.536	0.664

```
pander::pander(t(rrAnalysisTest$ROCAAnalysis$aucs),caption="ROC AUC")
```

Table 51: ROC AUC

est	lower	upper
0.615	0.515	0.715

```
pander::pander((rrAnalysisTest$ROCAAnalysis$sensitivity),caption="Sensitivity")
```

Table 52: Sensitivity

est	lower	upper
0.19	0.124	0.271

```
pander::pander((rrAnalysisTest$ROCAAnalysis$specificity),caption="Specificity")
```

Table 53: Specificity

est	lower	upper
0.894	0.769	0.965

```
pander::pander(t(rrAnalysisTest$thr_atP),caption="Probability Thresholds")
```

Table 54: Probability Thresholds

90%
0.81

```
pander::pander(t(rrAnalysisTest$RR_atP),caption="Risk Ratio")
```

Table 55: Risk Ratio

est	lower	upper
1.26	1.05	1.51

```
pander::pander(rrAnalysisTest$surdif, caption="Logrank test")
```

Table 56: Logrank test Chisq = 2.346444 on 1 degrees of freedom,  
p = 0.125569

	N	Observed	Expected	(O-E)^2/E	(O-E)^2/V
<b>class=0</b>	140	98	103.8	0.328	2.35
<b>class=1</b>	28	23	17.2	1.981	2.35