

8 Types

Artículo • 06/04/2023

8.1 General

The types of the C# language are divided into two main categories: **reference types** and **value types**. Both value types and reference types may be **generic types**, which take one or more **type parameters**. Type parameters can designate both value types and reference types.

ANTLR

```
type
    : reference_type
    | value_type
    | type_parameter
    | pointer_type      // unsafe code support
    ;
```

pointer_type (§23.3) is available only in unsafe code (§23).

Value types differ from reference types in that variables of the value types directly contain their data, whereas variables of the reference types store **references** to their data, the latter being known as **objects**. With reference types, it is possible for two variables to reference the same object, and thus possible for operations on one variable to affect the object referenced by the other variable. With value types, the variables each have their own copy of the data, and it is not possible for operations on one to affect the other.

Note: When a variable is a ref or out parameter, it does not have its own storage but references the storage of another variable. In this case, the ref or out variable is effectively an alias for another variable and not a distinct variable. *end note*

C#'s type system is unified such that *a value of any type can be treated as an object*. Every type in C# directly or indirectly derives from the class type, and is the ultimate base class of all types. Values of reference types are treated as objects simply by viewing the values as type . Values of value types are treated as objects by performing boxing and unboxing operations (§8.3.13). object object object

For convenience, throughout this specification, some library type names are written without using their full name qualification. Refer to [§C.5](#) for more information.

8.2 Reference types

8.2.1 General

A reference type is a class type, an interface type, an array type, a delegate type, or the `type.dynamic`

ANTLR

```
reference_type
    : class_type
    | interface_type
    | array_type
    | delegate_type
    | 'dynamic'
    ;

class_type
    : type_name
    | 'object'
    | 'string'
    ;

interface_type
    : type_name
    ;

array_type
    : non_array_type rank_specifier+
    ;

non_array_type
    : value_type
    | class_type
    | interface_type
    | delegate_type
    | 'dynamic'
    | type_parameter
    | pointer_type           // unsafe code support
    ;

rank_specifier
    : '[' ',' '*' ']'
```

```
    ;

    delegate_type
    : type_name
    ;
```

pointer_type is available only in unsafe code ([§23.3](#)).

A reference type value is a reference to an *instance* of the type, the latter known as an object. The special value is compatible with all reference types and indicates the absence of an instance. `null`

8.2.2 Class types

A class type defines a data structure that contains *data members* (constants and fields), *function members* (methods, properties, events, indexers, operators, instance constructors, finalizers, and static constructors), and nested types. Class types support inheritance, a mechanism whereby derived classes can extend and specialize base classes. Instances of class types are created using *object_creation_expressions* ([§12.8.16.2](#)).

Class types are described in [§15](#).

Certain predefined class types have special meaning in the C# language, as described in the table below.

 Expandir tabla

Class type	Description
<code>System.Object</code>	The ultimate base class of all other types. See §8.2.3 .
<code>System.String</code>	The string type of the C# language. See §8.2.5 .
<code>System.ValueType</code>	The base class of all value types. See §8.3.2 .
<code>System.Enum</code>	The base class of all types. See §19.5 . <code>enum</code>
<code>System.Array</code>	The base class of all array types. See §17.2.2 .
<code>System.Delegate</code>	The base class of all types. See §20.1 . <code>delegate</code>
<code>System.Exception</code>	The base class of all exception types. See §21.3 .

8.2.3 The object type

The class type is the ultimate base class of all other types. Every type in C# directly or indirectly derives from the class type. `object` `object`

The keyword is simply an alias for the predefined class `.object` `System.Object`

8.2.4 The dynamic type

The type, like `,` can reference any object. When operations are applied to expressions of type `,` their resolution is deferred until the program is run. Thus, if the operation cannot legitimately be applied to the referenced object, no error is given during compilation. Instead, an exception will be thrown when resolution of the operation fails at run-time. `dynamic` `object` `dynamic`

The type is further described in [§8.7](#), and dynamic binding in [§12.3.1](#). `dynamic`

8.2.5 The string type

The type is a sealed class type that inherits directly from `.` Instances of the class represent Unicode character strings. `string` `object` `string`

Values of the type can be written as string literals ([§6.4.5.6](#)). `string`

The keyword is simply an alias for the predefined class `.string` `System.String`

8.2.6 Interface types

An interface defines a contract. A class or struct that implements an interface shall adhere to its contract. An interface may inherit from multiple base interfaces, and a class or struct may implement multiple interfaces.

Interface types are described in [§18](#).

8.2.7 Array types

An array is a data structure that contains zero or more variables, which are accessed through computed indices. The variables contained in an array, also called the elements of the array, are all of the same type, and this type is called the element type of the array.

Array types are described in [§17](#).

8.2.8 Delegate types

A delegate is a data structure that refers to one or more methods. For instance methods, it also refers to their corresponding object instances.

Note: The closest equivalent of a delegate in C or C++ is a function pointer, but whereas a function pointer can only reference static functions, a delegate can reference both static and instance methods. In the latter case, the delegate stores not only a reference to the method's entry point, but also a reference to the object instance on which to invoke the method. *end note*

Delegate types are described in [§20](#).

8.3 Value types

8.3.1 General

A value type is either a struct type or an enumeration type. C# provides a set of predefined struct types called the ***simple types***. The simple types are identified through keywords.

ANTLR

```
value_type
    : non_nullable_value_type
    | nullable_value_type
    ;

non_nullable_value_type
    : struct_type
    | enum_type
    ;

struct_type
    : type_name
    | simple_type
    | tuple_type
    ;

simple_type
    : numeric_type
```

```

    | 'bool'
    ;

numeric_type
    : integral_type
    | floating_point_type
    | 'decimal'
    ;

integral_type
    : 'sbyte'
    | 'byte'
    | 'short'
    | 'ushort'
    | 'int'
    | 'uint'
    | 'long'
    | 'ulong'
    | 'char'
    ;

floating_point_type
    : 'float'
    | 'double'
    ;

tuple_type
    : '(' tuple_type_element (',' tuple_type_element)+ ')'
    ;

tuple_type_element
    : type identifier?
    ;

enum_type
    : type_name
    ;

nullable_value_type
    : non_nullable_value_type '?'
    ;

```

Unlike a variable of a reference type, a variable of a value type can contain the value only if the value type is a nullable value type (§8.3.12). For every non-nullable value type there is a corresponding nullable value type denoting the same set of values plus the value `.null`.

Assignment to a variable of a value type creates a *copy* of the value being assigned. This differs from assignment to a variable of a reference type, which copies the reference but not the object identified by the reference.

8.3.2 The System.ValueType type

All value types implicitly inherit from the `System.ValueType`, which, in turn, inherits from class `System.Object`. It is not possible for any type to derive from a value type, and value types are thus implicitly sealed (§15.2.2.3). `class System.ValueType object`

Note that `System.ValueType` is not itself a *value_type*. Rather, it is a *class_type* from which all *value_types* are automatically derived.

8.3.3 Default constructors

All value types implicitly declare a public parameterless instance constructor called the **default constructor**. The default constructor returns a zero-initialized instance known as the **default value** for the value type:

- For all *simple_types*, the default value is the value produced by a bit pattern of all zeros:
 - For `sbyte`, `byte`, `short`, `ushort`, `int`, `uint`, `long`, and `ulong`, the default value is `0`.
 - For `char`, the default value is `'\x0000'`.
 - For `float`, the default value is `0.0f`.
 - For `double`, the default value is `0.0d`.
 - For `decimal`, the default value is (that is, value zero with scale 0) `0m`.
 - For `bool`, the default value is `false`.
 - For an *enum_type*, the default value is `0`, converted to the type `E`.
- For a *struct_type*, the default value is the value produced by setting all value type fields to their default value and all reference type fields to `null`.
- For a *nullable_value_type* the default value is an instance for which the property `HasValue` is false. The default value is also known as the **null value** of the nullable value type. Attempting to read the property of such a value causes an exception of type `InvalidOperationException` to be thrown (§8.3.12).

Like any other instance constructor, the default constructor of a value type is invoked using the operator `new`.

Note: For efficiency reasons, this requirement is not intended to actually have the implementation generate a constructor call. For value types, the default value expression (§12.8.20) produces the same result as using the default constructor. *end note*

Example: In the code below, variables `i`, `j`, and `k` are all initialized to zero.

C#

```
class A
{
    void F()
    {
        int i = 0;
        int j = new int();
        int k = default(int);
    }
}
```

end example

Because every value type implicitly has a public parameterless instance constructor, it is not possible for a struct type to contain an explicit declaration of a parameterless constructor. A struct type is however permitted to declare parameterized instance constructors (§16.4.9).

8.3.4 Struct types

A struct type is a value type that can declare constants, fields, methods, properties, events, indexers, operators, instance constructors, static constructors, and nested types. The declaration of struct types is described in §16.

8.3.5 Simple types

C# provides a set of predefined types called the simple types. The simple types are identified through keywords, but these keywords are simply aliases for predefined types in the namespace, as described in the table below.

 Expandir tabla

Keyword	Aliased type
sbyte	System.SByte
byte	System.Byte
short	System.Int16
ushort	System.UInt16
int	System.Int32
uint	System.UInt32
long	System.Int64
ulong	System.UInt64
char	System.Char
float	System.Single
double	System.Double
bool	System.Boolean
decimal	System.Decimal

Because a simple type aliases a struct type, every simple type has members.

Example: has the members declared in and the members inherited from , and the following statements are permitted: `int System.Int32` `System.Object`

C#

```
int i = int.MaxValue;    // System.Int32.MaxValue constant
string s = i.ToString(); // System.Int32.ToString() instance method
string t = 123.ToString(); // System.Int32.ToString() instance method
```

end example

Note: The simple types differ from other struct types in that they permit certain additional operations:

- Most simple types permit values to be created by writing *literals* (§6.4.5), although C# makes no provision for literals of struct types in general. *Example:* is a literal of type and is a literal of type . *end example* 123 int 'a' char
- When the operands of an expression are all simple type constants, it is possible for the compiler to evaluate the expression at compile-time. Such an expression is known as a *constant_expression* (§12.23). Expressions involving operators defined by other struct types are not considered to be constant expressions
- Through declarations, it is possible to declare constants of the simple types (§15.4). It is not possible to have constants of other struct types, but a similar effect is provided by static readonly fields. const
- Conversions involving simple types can participate in evaluation of conversion operators defined by other struct types, but a user-defined conversion operator can never participate in evaluation of another user-defined conversion operator (§10.5.3).

end note.

8.3.6 Integral types

C# supports nine integral types: , , , , , , , and . The integral types have the following sizes and ranges of values: sbyte byte short ushort int uint long ulong char

- The type represents signed 8-bit integers with values from to , inclusive. sbyte - 128 127
- The type represents unsigned 8-bit integers with values from to , inclusive. byte 0 255
- The type represents signed 16-bit integers with values from to , inclusive. short - 32768 32767
- The type represents unsigned 16-bit integers with values from to , inclusive. ushort 0 65535
- The type represents signed 32-bit integers with values from to , inclusive. int - 2147483648 2147483647
- The type represents unsigned 32-bit integers with values from to , inclusive. uint 0 4294967295
- The type represents signed 64-bit integers with values from to , inclusive. long - 9223372036854775808 9223372036854775807
- The type represents unsigned 64-bit integers with values from to , inclusive. ulong 0 18446744073709551615

- The type represents unsigned 16-bit integers with values from 0 to 65535, inclusive. The set of possible values for the type corresponds to the Unicode character set.

`char 0 65535 char`

Note: Although `char` has the same representation as `ushort`, not all operations permitted on one type are permitted on the other. *end note*

All signed integral types are represented using two's complement format.

The *integral_type* unary and binary operators always operate with signed 32-bit precision, unsigned 32-bit precision, signed 64-bit precision, or unsigned 64-bit precision, as detailed in §12.4.7.

The type is classified as an integral type, but it differs from the other integral types in two ways:

- There are no predefined implicit conversions from other types to the type. In particular, even though the `byte` and `ushort` types have ranges of values that are fully representable using the type, implicit conversions from `sbyte`, `byte`, or `ushort` to `char` do not exist.
- Constants of the type shall be written as *character_literals* or as *integer_literals* in combination with a cast to type `char`.

Example: `(char)10 '\x000A'` is the same as `char 10`.

The `checked` and `unchecked` operators and statements are used to control overflow checking for integral-type arithmetic operations and conversions (§12.8.19). In a `checked` context, an overflow produces a compile-time error or causes a `System.OverflowException` to be thrown. In an `unchecked` context, overflows are ignored and any high-order bits that do not fit in the destination type are discarded.

8.3.7 Floating-point types

C# supports two floating-point types: `float` and `double`. The `float` type is represented using the 32-bit single-precision IEC 60559 format, which provides the following sets of values:

- Positive zero and negative zero. In most situations, positive zero and negative zero behave identically as the simple value zero, but certain operations distinguish

between the two (§12.10.3).

- Positive infinity and negative infinity. Infinities are produced by such operations as dividing a non-zero number by zero.

Example: yields positive infinity, and yields negative infinity. *end example* `1.0 / 0.0` `-1.0 / 0.0`

- The **Not-a-Number** value, often abbreviated NaN. NaNs are produced by invalid floating-point operations, such as dividing zero by zero.
- The finite set of non-zero values of the form $s \times m \times 2^e$, where s is 1 or -1 , and m and e are determined by the particular floating-point type: For `float`, $0 < m < 2^{24}$ and $-149 \leq e \leq 104$, and for `double`, $0 < m < 2^{53}$ and $-1075 \leq e \leq 970$. Denormalized floating-point numbers are considered valid non-zero values. C# neither requires nor forbids that a conforming implementation support denormalized floating-point numbers.

The type can represent values ranging from approximately 1.5×10^{-45} to 3.4×10^{38} with a precision of 7 digits. `float`

The type can represent values ranging from approximately 5.0×10^{-324} to 1.7×10^{308} with a precision of 15-16 digits. `double`

If either operand of a binary operator is a floating-point type then standard numeric promotions are applied, as detailed in §12.4.7, and the operation is performed with or precision. `float` `double`

The floating-point operators, including the assignment operators, never produce exceptions. Instead, in exceptional situations, floating-point operations produce zero, infinity, or NaN, as described below:

- The result of a floating-point operation is rounded to the nearest representable value in the destination format.
- If the magnitude of the result of a floating-point operation is too small for the destination format, the result of the operation becomes positive zero or negative zero.
- If the magnitude of the result of a floating-point operation is too large for the destination format, the result of the operation becomes positive infinity or negative infinity.
- If a floating-point operation is invalid, the result of the operation becomes NaN.

- If one or both operands of a floating-point operation is NaN, the result of the operation becomes NaN.

Floating-point operations may be performed with higher precision than the result type of the operation. To force a value of a floating-point type to the exact precision of its type, an explicit cast (§12.9.7) can be used.

Example: Some hardware architectures support an “extended” or “long double” floating-point type with greater range and precision than the type, and implicitly perform all floating-point operations using this higher precision type. Only at excessive cost in performance can such hardware architectures be made to perform floating-point operations with *less* precision, and rather than require an implementation to forfeit both performance and precision, C# allows a higher precision type to be used for all floating-point operations. Other than delivering more precise results, this rarely has any measurable effects. However, in expressions of the form `double x * y / z`, where the multiplication produces a result that is outside the range, but the subsequent division brings the temporary result back into the range, the fact that the expression is evaluated in a higher range format can cause a finite result to be produced instead of an infinity. *end example*

8.3.8 The Decimal type

The type is a 128-bit data type suitable for financial and monetary calculations. The type can represent values including those in the range at least -7.9×10^{-28} to 7.9×10^{28} , with at least 28-digit precision. `decimal decimal`

The finite set of values of type are of the form $(-1)^v \times c \times 10^{-e}$, where the sign v is 0 or 1, the coefficient c is given by $0 \leq c < Cmax$, and the scale e is such that $Emin \leq e \leq Emax$, where $Cmax$ is at least 1×10^{28} , $Emin \leq 0$, and $Emax \geq 28$. The type does not necessarily support signed zeros, infinities, or NaN's. `decimal decimal`

A is represented as an integer scaled by a power of ten. For s with an absolute value less than `decimal 1.0m`, the value is exact to at least the 28th decimal place. For s with an absolute value greater than or equal to `decimal 1.0m`, the value is exact to at least 28 digits. Contrary to the `float` and `double` types, decimal fractional numbers such as `0.1` can be represented exactly in the decimal representation. In the `float` and `double` representations, such numbers often have non-terminating binary expansions, making those representations more prone to round-off errors. `decimal 1.0m decimal 1.0m float double 0.1 float double`

If either operand of a binary operator is of type `decimal` then standard numeric promotions are applied, as detailed in §12.4.7, and the operation is performed with `double` precision.

The result of an operation on values of type `decimal` is that which would result from calculating an exact result (preserving scale, as defined for each operator) and then rounding to fit the representation. Results are rounded to the nearest representable value, and, when a result is equally close to two representable values, to the value that has an even number in the least significant digit position (this is known as “banker’s rounding”). That is, results are exact to at least the 28th decimal place. Note that rounding may produce a zero value from a non-zero value.

If a arithmetic operation produces a result whose magnitude is too large for the format, a `System.OverflowException` is thrown.

The type `decimal` has greater precision but may have a smaller range than the floating-point types. Thus, conversions from the floating-point types to `decimal` might produce overflow exceptions, and conversions from `decimal` to the floating-point types might cause loss of precision or overflow exceptions. For these reasons, no implicit conversions exist between the floating-point types and `decimal`, and without explicit casts, a compile-time error occurs when floating-point and `decimal` operands are directly mixed in the same expression.

8.3.9 The `bool` type

The type `bool` represents Boolean logical quantities. The possible values of type `bool` are `true` and `false`. The representation of `bool` is described in §8.3.3. Although the representation of `bool` is unspecified, it shall be different from that of `int`.

No standard conversions exist between `bool` and other value types. In particular, the type `bool` is distinct and separate from the integral types, a `bool` value cannot be used in place of an integral value, and vice versa.

Note: In the C and C++ languages, a zero integral or floating-point value, or a null pointer can be converted to the Boolean value `false`, and a non-zero integral or floating-point value, or a non-null pointer can be converted to the Boolean value `true`. In C#, such conversions are accomplished by explicitly comparing an integral or floating-point value to zero, or by explicitly comparing an object reference to `null`.

8.3.10 Enumeration types

An enumeration type is a distinct type with named constants. Every enumeration type has an underlying type, which shall be `byte`, `sbyte`, `short`, `ushort`, `int`, `uint`, `long`, or `ulong`. The set of values of the enumeration type is the same as the set of values of the underlying type. Values of the enumeration type are not restricted to the values of the named constants. Enumeration types are defined through enumeration declarations (§19.2).

8.3.11 Tuple types

A tuple type represents an ordered, fixed-length sequence of values with optional names and individual types. The number of elements in a tuple type is referred to as its **arity**. A tuple type is written with $n \geq 2$, where the identifiers are optional ***tuple element names***. $(T_1, \dots, T_n \text{ In}) \text{ I1} \dots \text{In}$

This syntax is shorthand for a type constructed with the types from `T1` to `Tn`, which shall be a set of generic struct types capable of directly expressing tuple types of any arity between two and seven inclusive. There does not need to exist a declaration that directly matches the arity of any tuple type with a corresponding number of type parameters. Instead, tuples with an arity greater than seven are represented with a generic struct type that in addition to tuple elements has a field containing a nested value of the remaining elements, using another type. Such nesting may be observable in various ways, e.g. via the presence of a field.

Where only a single additional field is required, the generic struct type is used; this type is not considered a tuple type in itself. Where more than seven additional fields are required, `ValueTuple<T1, ..., T7, TRest>` is used

recursively. `T1...Tn System.ValueTuple<...> System.ValueTuple<...> System.ValueTuple<T1, ..., T7, TRest>` Rest `System.ValueTuple<...> Rest System.ValueTuple<T1> System.ValueTuple<T1, ..., T7, TRest>`

Element names within a tuple type shall be distinct. A tuple element name of the form `ItemX`, where `X` is any sequence of non--initiated decimal digits that could represent the position of a tuple element, is only permitted at the position denoted by `X`. `ItemX` $X \in \{0, \dots, n-1\}$

The optional element names are not represented in the types, and are not stored in the runtime representation of a tuple value. There is an identity conversion between all tuple types with the same arity and identity-convertible sequences of element types, as well as to and from the corresponding constructed type. `ValueTuple<...> ValueTuple<...>`

The operator §12.8.16.2 cannot be applied with the tuple type syntax . Tuple values can be created from tuple expressions (§12.8.6), or by applying the operator directly to a type constructed from .new new (T1, ..., Tn) new ValueTuple<...>

Tuple elements are public fields with the names , , etc., and can be accessed via a member access on a tuple value (§12.8.7. Additionally, if the tuple type has a name for a given element, that name can be used to access the element in question. Item1 Item2

Note: Even when large tuples are represented with nested values, each tuple element can still be accessed directly with the name corresponding to its position. *end*

note System.ValueTuple<...> Item...

Example: Given the following examples:

C#

```
(int, string) pair1 = (1, "One");
(int, string word) pair2 = (2, "Two");
(int number, string word) pair3 = (3, "Three");
(int Item1, string Item2) pair4 = (4, "Four");
// Error: "Item" names do not match their position
(int Item2, string Item123) pair5 = (5, "Five");
(int, string) pair6 = new ValueTuple<int, string>(6, "Six");
ValueTuple<int, string> pair7 = (7, "Seven");
Console.WriteLine($"{pair2.Item1}, {pair2.Item2}, {pair2.word}");
```

The tuple types for , , and are all valid, with names for no, some or all of the tuple type elements. pair1 pair2 pair3

The tuple type for is valid because the names and match their positions, whereas the tuple type for is disallowed, because the names and do not. pair4 Item1 Item2 pair5 Item2 Item123

The declarations for and demonstrate that tuple types are interchangeable with constructed types of the form , and that the operator is allowed with the latter syntax. pair6 pair7 ValueTuple<...> new

The last line shows that tuple elements can be accessed by the name corresponding to their position, as well as by the corresponding tuple element name, if present in the type. *end example* Item

8.3.12 Nullable value types

A nullable value type can represent all values of its underlying type plus an additional null value. A nullable value type is written `T?`, where `T` is the underlying type. This syntax is shorthand for `System.Nullable<T>`, and the two forms can be used interchangeably.

Conversely, a **non-nullable value type** is any value type other than `System.Nullable<T>` and its shorthand (for any `T`), plus any type parameter that is constrained to be a non-nullable value type (that is, any type parameter with a value type constraint (§15.2.5)). The type `T` specifies the value type constraint for `T`, which means that the underlying type of a nullable value type can be any non-nullable value type. The underlying type of a nullable value type cannot be a nullable value type or a reference type. For example, `int??` and `string?` are invalid types.

An instance of a nullable value type has two public read-only properties:

- A property of type `bool` named `HasValue`.
- A property of type `T` named `Value`.

An instance for which `HasValue` is `true` is said to be non-null. A non-null instance contains a known value and returns that value.

An instance for which `HasValue` is `false` is said to be null. A null instance has an undefined value. Attempting to read the `Value` property of a null instance causes a `InvalidOperationException` to be thrown. The process of accessing the `Value` property of a nullable instance is referred to as **unwrapping**.

In addition to the default constructor, every nullable value type has a public constructor with a single parameter of type `T`. Given a value `x` of type `T`, a constructor invocation of the form `new T?(x)`

C#

```
new T?(x)
```

creates a non-null instance of `T?` for which the `Value` property is `x`. The process of creating a non-null instance of a nullable value type for a given value is referred to as **wrapping**.

Implicit conversions are available from the literal `null` to `T?` (§10.2.7) and from `T?` to `Nullable<T>` (§10.2.6).

The nullable type implements no interfaces (§18). In particular, this means it does not implement any interface that the underlying type does. $T?$ T

8.3.13 Boxing and unboxing

The concept of boxing and unboxing provide a bridge between *value_types* and *reference_types* by permitting any value of a *value_type* to be converted to and from type `object`. Boxing and unboxing enables a unified view of the type system wherein a value of any type can ultimately be treated as an `object`.

Boxing is described in more detail in §10.2.9 and unboxing is described in §10.3.7.

8.4 Constructed types

8.4.1 General

A generic type declaration, by itself, denotes an **unbound generic type** that is used as a “blueprint” to form many different types, by way of applying **type arguments**. The type arguments are written within angle brackets (`<` and `>`) immediately following the name of the generic type. A type that includes at least one type argument is called a **constructed type**. A constructed type can be used in most places in the language in which a type name can appear. An unbound generic type can only be used within a *typeof_expression* (§12.8.17).

< >

Constructed types can also be used in expressions as simple names (§12.8.4) or when accessing a member (§12.8.7).

When a *namespace_or_type_name* is evaluated, only generic types with the correct number of type parameters are considered. Thus, it is possible to use the same identifier to identify different types, as long as the types have different numbers of type parameters. This is useful when mixing generic and non-generic classes in the same program.

Example:

```
C#  
  
namespace Widgets  
{  
    class Queue {...}  
    class Queue<TElement> {...}
```

```
}

namespace MyApplication
{
    using Widgets;

    class X
    {
        Queue q1;          // Non-generic Widgets.Queue
        Queue<int> q2;      // Generic Widgets.Queue
    }
}
```

end example

Las reglas detalladas para la búsqueda de nombres en las producciones *namespace_or_type_name* se describen en §7.8. La resolución de ambigüedades en estas producciones se describe en §6.2.5. Un *type_name* puede identificar un tipo construido aunque no especifique directamente los parámetros de tipo. Esto puede ocurrir cuando un tipo está anidado dentro de una declaración genérica y el tipo de instancia de la declaración contenedora se usa implícitamente para la búsqueda de nombres (§15.3.9.7). *class*

Ejemplo:

```
C#

class Outer<T>
{
    public class Inner {...}

    public Inner i; // Type of i is Outer<T>.Inner
}
```

Fin del ejemplo

Un tipo construido que no sea de enumeración no se utilizará como *unmanaged_type* (§8.8).

8.4.2 Argumentos de tipo

Cada argumento de una lista de argumentos de tipo es simplemente un *tipo*.

ANTLR

```
type_argument_list
    : '<' type_arguments '>'
    ;

type_arguments
    : type_argument (',' type_argument)*
    ;

type_argument
    : type
    ;
```

Cada argumento de tipo debe satisfacer las restricciones del parámetro de tipo correspondiente (§15.2.5).

8.4.3 Tipos abiertos y cerrados

Todos los tipos se pueden clasificar como **tipos abiertos** o **tipos cerrados**. Un tipo abierto es un tipo que implica parámetros de tipo. Más concretamente:

- Un parámetro de tipo define un tipo abierto.
- Un tipo de matriz es un tipo abierto si y solo si su tipo de elemento es un tipo abierto.
- Un tipo construido es un tipo abierto si y solo si uno o varios de sus argumentos de tipo son un tipo abierto. Un tipo anidado construido es un tipo abierto si y solo si uno o varios de sus argumentos de tipo o los argumentos de tipo de los tipos que lo contienen son un tipo abierto.

Un tipo cerrado es un tipo que no es un tipo abierto.

En tiempo de ejecución, todo el código de una declaración de tipo genérico se ejecuta en el contexto de un tipo construido cerrado que se creó mediante la aplicación de argumentos de tipo a la declaración genérica. Cada parámetro de tipo dentro del tipo genérico está enlazado a un tipo en tiempo de ejecución determinado. El procesamiento en tiempo de ejecución de todas las instrucciones y expresiones siempre se produce con tipos cerrados, y los tipos abiertos sólo se producen durante el procesamiento en tiempo de compilación.

Cada tipo construido cerrado tiene su propio conjunto de variables estáticas, que no se comparten con ningún otro tipo construido cerrado. Dado que no existe un tipo abierto en tiempo de ejecución, no hay variables estáticas asociadas a un tipo abierto. Dos tipos

construidos cerrados son el mismo tipo si se construyen a partir del mismo tipo genérico no enlazado y sus argumentos de tipo correspondientes son del mismo tipo.

8.4.4 Tipos enlazados y no enlazados

El término tipo no enlazado hace referencia a un tipo no genérico o a un ***tipo genérico no enlazado***. El término tipo ***enlazado*** hace referencia a un tipo no genérico o a un tipo construido.

Un tipo no enlazado hace referencia a la entidad declarada por una declaración de tipo. Un tipo genérico no enlazado no es en sí mismo un tipo y no se puede usar como tipo de variable, argumento o valor devuelto, ni como tipo base. La única construcción en la que se puede hacer referencia a un tipo genérico sin enlazar es la expresión (§12.8.17). `typeof`

8.4.5 Satisfying constraints

Whenever a constructed type or generic method is referenced, the supplied type arguments are checked against the type parameter constraints declared on the generic type or method (§15.2.5). For each clause, the type argument that corresponds to the named type parameter is checked against each constraint as follows: where A

- If the constraint is a type, an interface type, or a type parameter, let represent that constraint with the supplied type arguments substituted for any type parameters that appear in the constraint. To satisfy the constraint, it shall be the case that type is convertible to type by one of the following:


```
class C A C
```

 - An identity conversion (§10.2.2)
 - An implicit reference conversion (§10.2.8)
 - A boxing conversion (§10.2.9), provided that type is a non-nullable value type. A
 - An implicit reference, boxing or type parameter conversion from a type parameter to . A C
- If the constraint is the reference type constraint (), the type shall satisfy one of the following:


```
class A
```

 - A is an interface type, class type, delegate type, array type or the dynamic type.

Note: and are reference types that satisfy this constraint. *end*

note `System.ValueType` `System.Enum`

- A is a type parameter that is known to be a reference type (§8.2).

- If the constraint is the value type constraint (`struct`), the type shall satisfy one of the following:
 - `A` is a type or type, but not a nullable value type.

Note: `System.ValueType` and `System.Enum` are reference types that do not satisfy this constraint. *end note*

- `A` is a type parameter having the value type constraint (§15.2.5).
- If the constraint is the constructor constraint (`new()`), the type shall not be abstract and shall have a public parameterless constructor. This is satisfied if one of the following is true:
 - `A` is a value type, since all value types have a public default constructor (§8.3.3).
 - `A` is a type parameter having the constructor constraint (§15.2.5).
 - `A` is a type parameter having the value type constraint (§15.2.5).
 - `A` is a type that is not abstract and contains an explicitly declared public constructor with no parameters.
 - `A` is not abstract and has a default constructor (§15.11.5).

A compile-time error occurs if one or more of a type parameter's constraints are not satisfied by the given type arguments.

Since type parameters are not inherited, constraints are never inherited either.

Example: In the following, `B` needs to specify the constraint on its type parameter so that it satisfies the constraint imposed by the base `E`. In contrast, `D` need not specify a constraint, because `E` implements `IEnumerable` for any `T`.

C#

```
class B<T> where T: IEnumerable {...}
class D<T> : B<T> where T: IEnumerable {...}
class E<T> : B<List<T>> {...}
```

end example

8.5 Type parameters

A type parameter is an identifier designating a value type or reference type that the parameter is bound to at run-time.

ANTLR

```
type_parameter
    : identifier
    ;
```

Since a type parameter can be instantiated with many different type arguments, type parameters have slightly different operations and restrictions than other types.

Note: These include:

- A type parameter cannot be used directly to declare a base class (§15.2.4.2) or interface (§18.2.4).
- The rules for member lookup on type parameters depend on the constraints, if any, applied to the type parameter. They are detailed in §12.5.
- The available conversions for a type parameter depend on the constraints, if any, applied to the type parameter. They are detailed in §10.2.12 and §10.3.9.
- The literal cannot be converted to a type given by a type parameter, except if the type parameter is known to be a reference type (§10.2.12). However, a default expression (§12.8.20) can be used instead. In addition, a value with a type given by a type parameter *can* be compared with null using and (§12.12.7) unless the type parameter has the value type constraint. `null == !=`
- A expression (§12.8.16.2) can only be used with a type parameter if the type parameter is constrained by a *constructor_constraint* or the value type constraint (§15.2.5). `new`
- A type parameter cannot be used anywhere within an attribute.
- A type parameter cannot be used in a member access (§12.8.7) or type name (§7.8) to identify a static member or a nested type.
- A type parameter cannot be used as an *unmanaged_type* (§8.8).

end note

As a type, type parameters are purely a compile-time construct. At run-time, each type parameter is bound to a run-time type that was specified by supplying a type argument to the generic type declaration. Thus, the type of a variable declared with a type parameter will, at run-time, be a closed constructed type §8.4.3. The run-time execution of all

statements and expressions involving type parameters uses the type that was supplied as the type argument for that parameter.

8.6 Expression tree types

Expression trees permit lambda expressions to be represented as data structures instead of executable code. Expression trees are values of **expression tree types** of the form `Expression<TDelegate>`, where `TDelegate` is any delegate type. For the remainder of this specification these types will be referred to using the shorthand

`Expression<TDelegate>`

If a conversion exists from a lambda expression to a delegate type `TDelegate`, a conversion also exists to the expression tree type `Expression<TDelegate>`. Whereas the conversion of a lambda expression to a delegate type generates a delegate that references executable code for the lambda expression, conversion to an expression tree type creates an expression tree representation of the lambda expression. More details of this conversion are provided in

[§10.7.3.D Expression<TDelegate>](#)

Example: The following program represents a lambda expression both as executable code and as an expression tree. Because a conversion exists to `Func<int,int>`, a conversion also exists to `Expression<Func<int,int>>`

C#

```
Func<int,int> del = x => x + 1;           // Code
Expression<Func<int,int>> exp = x => x + 1; // Data
```

Following these assignments, the delegate references a method that returns `int`, and the expression tree `exp` references a data structure that describes the expression `del x + 1`

end example

`Expression<TDelegate>` provides an instance method which produces a delegate of type `TDelegate`

C#


```
Func<int,int> del2 = exp.Compile();
```

Invoking this delegate causes the code represented by the expression tree to be executed. Thus, given the definitions above, and are equivalent, and the following two statements will have the same effect: `del del2`

C#

```
int i1 = del(1);
int i2 = del2(1);
```

After executing this code, and will both have the value . `i1 i2 2`

The API surface provided by is implementation-specific beyond the requirement for a method described above. `Expression<TDelegate> Compile`

Note: While the details of the API provided for expression trees are implementation-specific, it is expected that an implementation will:

- Enable code to inspect and respond to the structure of an expression tree created as the result of a conversion from a lambda expression
- Enable expression trees to be created programatically within user code

end note

8.7 The dynamic type

The type uses dynamic binding, as described in detail in [§12.3.2](#), as opposed to static binding which is used by all other types. `dynamic`

`dynamic` is considered identical to `object` except in the following respects: `object`

- Operations on expressions of type `dynamic` can be dynamically bound ([§12.3.3](#)).
- Type inference ([§12.6.3](#)) will prefer `dynamic` over `object` if both are candidates.
- `dynamic` cannot be used as
 - the type in an *object_creation_expression* ([§12.8.16.2](#))
 - a *predefined_type* in a *member_access* ([§12.8.7.1](#))
 - the operand of the operator `typeof`
 - an attribute argument

- a constraint
- an extension method type
- any part of a type argument within *struct_interfaces* (§16.2.5) or *interface_type_list* (§15.2.4.1).

Because of this equivalence, the following holds:

- There is an implicit identity conversion between `dynamic` and `dynamic object`, and between constructed types that are the same when replacing `dynamic` with `dynamic object`.
- Implicit and explicit conversions to and from `dynamic` also apply to and from `dynamic object`.
- Signatures that are the same when replacing `dynamic` with `dynamic object` are considered the same signature.
- The type `dynamic` is indistinguishable from `dynamic object` at run-time.
- An expression of the type `dynamic` is referred to as a **dynamic expression**.

8.8 Unmanaged types

ANTLR

```
unmanaged_type
    : value_type
    | pointer_type      // unsafe code support
    ;
```

An *unmanaged_type* is any type that isn't a *reference_type*, a *type_parameter*, or a constructed type, and contains no instance fields whose type is not an *unmanaged_type*. In other words, an *unmanaged_type* is one of the following:

- `sbyte`, `byte`, `short`, `ushort`, `int`, `uint`, `long`, `ulong`, `char`, `float`, `double`, `decimal`, `bool`, or `string`.
- Any *enum_type*.
- Any user-defined *struct_type* that is not a constructed type and contains instance fields of *unmanaged_types* only.


 Colaborar con nosotros en GitHub




Comentarios de C# Standard documentation

El origen de este contenido se puede encontrar en GitHub, donde también puede crear y revisar problemas y solicitudes de incorporación de cambios. Para más información, consulte [nuestra guía para colaboradores](#).

C# Standard documentation es un proyecto de código abierto. Seleccione un vínculo para proporcionar comentarios:

 [Abrir incidencia con la documentación](#)

 [Proporcionar comentarios sobre el producto](#)