

NatStar

Version 6.00 Edition 1

NS-DK

Version 5.00 Edition 2

NatWeb

Version 5.00 Edition 2

ODBC

Information in this document is subject to change without notice as a result of changes in the product. The software described in this document is furnished under a license agreement. The software may be used or copied only in accordance with the terms of the agreement. It is illegal to reproduce the software on any medium unless specifically authorized within the terms of the agreement. No part of this manual may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, for any purpose other than the purchaser's personal use without the written permission of Nat System.

© 2009 Nat System, All rights reserved

Contents

About this Manual	iii
Supported configurations.....	iii
Development environment	iii
Client environment	iii
Server environment	iii
Relationship to other manuals	iii
Organization of the manual	iv
Conventions	v

Chapter 1 ODBC interface **1-1**

Introduction	1-3
Correspondence between drivers and ODBC versions	1-3
Installation	1-5
Implicit Output Data Conversions	1-6
Functional categories in the NSnnoDCx library	1-7
Initializing and stopping application use of the DBMS.....	1-7
Opening and closing a database.....	1-7
Managing the current database	1-7
Choose the DBMS and the base for an SQL command.....	1-7
Executing a SQL command: SELECT, INSERT, UPDATE, CREATE TABLE ...	1-7
Managing the cursor	1-7
Running a stored procedure.....	1-8
Recording and reexecuting an SQL command	1-8
Managing blobs	1-8
Managing connections.....	1-8
Configuring DBMS behavior	1-8
SQL query advanced management	1-9
Handling floating values.....	1-9
Handling errors.....	1-9
NSnnoDCx library reference	1-10
NS_FUNCTION extensions	1-47

About this Manual

This is the ODBC manual for Nat System's development tools. This manual describes the ODBC interface allowing the access to an ODBC database.

Supported configurations

Development environment

- Windows 32 bits: 95, 98, NT 4.0, 2000

Client environment

Operating system	DBMS drivers available
Windows 32 bits	ODBC 3.0

Server environment

Operating system	DBMS drivers available
Windows NT Windows 2000 32 bits	ODBC 3.0

Relationship to other manuals



Before reading this manual you are expected to have read the « Overview » and « Getting started » manuals. You should not need to use this manual unless you have been advised to do so or if you are already an experienced Nat System developer. If this is the case, you can use this manual to learn in detail about the components it describes.



Strictly speaking, in standard use of NatStar's Information Modeling tool, you don't have to program data accesses yourself. The Information Modeling engine takes care of that. In this case, you don't need to look at the libraries described in this manual. However this manual will prove useful if you want to program your applications' data accesses yourself.

Organization of the manual

This manual contains one chapter, which describes the set of API components of the ODBC interface.

Chapter 1

ODBC interface

Describes the functions of the NSnnODCx library associated with the ODBC database.

Conventions

Typographic conventions

Important term	Important terms are printed in bold .
<i>Interface component</i>	The names of windows, dialog boxes, controls, buttons, menus and options are printed in <i>italics</i> .
[F9]	Function key names appear in square brackets.
FILENAME	Filenames are printed in UPPERCASE.
syntax example	Syntax examples are printed in a fixed-width font.

Notational conventions

- A round bullet is used for lists
- ◆ A diamond is used for alternatives
- 1. Numbers are used to mark the steps in a procedure to be carried out in sequence

Operating conventions

Choose XXX \ YYY	This means you need to open the XXX menu, then choose the YYY command (option) from this menu. You can perform this action using the mouse or mnemonic characters on the keyboard.
Click the XXX \ YYY button	This means you need to display the tool bar named XXX, then click the YYY button in this tool bar (the name of each button is shown by its help bubble). You can only perform this action with the mouse.
Choose the XXX button	This means you need to choose the XXX button in a dialog box. You can perform this action using the mouse or mnemonic characters on the keyboard.

Icon codes



Comment, note, etc.



Reference to another part of the documentation



Danger: precaution to be taken, irreversible action, etc.



Suggestion: helpful hints, etc.



To go a step further: level of detail or expertise greater than the average level of the document



Indicates specific information on using the software under
DOS- Windows (all versions)



Indicates specific information on using the software under
DOS- Windows 32 bits



Indicates specific information on using the software under
OS/2- PM 2.x or DOS- Windows 32 bits



Indicates specific information on using the software under
Unix systems

Chapter 1

ODBC interface



The NSnnODCx library allows your applications built with Nat System development tools to interface with client versions of ODBC.



Nat System supports in Windows 32 bits environment: ODBC 3.0



To ease the writing in the documentation, NSnnODC3 and NSnnODC2 will be gathered in NSnnODCx generic name.

This chapter explains

- How to install this library
- The components in this library, arranged in functional categories
- The reference of the components in this library
- The reference of the NS_FUNCTION extensions in the library

Contents

Introduction	1-3
Correspondence between drivers and ODBC versions	1-3
Installation	1-5
Implicit Output Data Conversions	1-6
Functional categories in the NSnnODCx library	1-7
Initializing and stopping application use of the DBMS	1-7
Opening and closing a database	1-7
Managing the current database	1-7
Choose the DBMS and the base for an SQL command	1-7
Executing a SQL command: SELECT, INSERT, UPDATE, CREATE TABLE ...	1-7
Managing the cursor	1-7
Running a stored procedure	1-8
Recording and reexecuting an SQL command	1-8
Managing blobs	1-8
Managing connections	1-8
Configuring DBMS behavior	1-8
SQL query advanced management	1-9
Handling floating values	1-9
Handling errors	1-9
NSnnODCx library reference	1-10
NS_FUNCTION extensions	1-47

Introduction

The NSnnODCx library allows your applications built with Nat System's development tools to interface with client versions of ODBC.

NSnnODCx uses ODBC level 2 APIs. NSnnODCx includes the following new features:

- Remote procedure calls,
- Retrieval of information from system catalogs,
- etc.

It also supports the RECORD and REEXECUTE commands which combine the adaptability of dynamic SQL with the speed of static SQL. In fact, a dynamic SQL order is used when the RECORD command is executed. When the REEXECUTE command is executed, as the analysis of query has already been done by the motor, only the values of the host variables are set.

Correspondence between drivers and ODBC versions

The name of the driver is used with THINGS_DB_INIT instruction for NatStar and SQL_INIT instruction for NatStar, NatWeb and NS-DK.

The following table presents ODBC versions and the corresponding drivers.

ODBC's version	Driver
ODBC 2.0	NSnnODC2.dll
ODBC 3.0	NSnnODC3.dll

nn indicates the target platform:

- w2 for Windows 32 bits
- w4 for Windows 64 bits
- p2 for OS/2 32 bits
- 02 for OS/2 16 bits and Windows 16 bits



To ease the writing in the documentation, NSnnODC3 and NSnnODC2 will be gathered in NSnnODCx generic name.



Nat System supports the ODBC 2 database only in Windows 16 bit environment.




Previous versions of the drivers no longer supported by Nat System in the Windows 32 bit environment are installed in the CONTRIB(S) folder: NSw2ODC2.dll.

Installation

Copy the file NSnnODCx.DLL into the directory that contains the DLLs for your Nat System environment (C:\NATSTAR\BIN, C:\NATWEB\BIN, and so on.)

The SQL libraries supplied with your Nat System development tools interface with the DLLs supplied by the DBMS manufacturer. In some cases, a utility also needs to be run. Check your configuration using the manuals supplied by your DBMS vendor.

Implicit Output Data Conversions

 Refer to the User Manual of ODBC to see the allowing conversions.

Nevertheless, for certain data, use the following conversions :

ODBC	NCL
DECIMAL, NUMERIC	CSTRING (*), CHAR, INT, NUM
BINARY, VARBINARY	BLOBS, SEGMENT
TEXT, IMAGE	BLOBS, SEGMENT

(*) it is strongly recommended to use this type of data.

blob	- A blob (or Binary Large Object) corresponds to a field of a database - able to contain images, video and sound for multimedia applications.
-------------	--

Functional categories in the NSnnODCx library

Here is a list, arranged by functional category, of the instructions, functions and constants in the NSnnODCx library.

Initializing and stopping application use of the DBMS

SQL_INIT	1-11
SQL_STOP	1-12

Opening and closing a database

SQL_OPEN.....	1-13
SQL_CLOSE	1-16

Managing the current database

NS_FUNCTION CHANGEDBCNTX	1-53
NS_FUNCTION GETCURRENTDBCNTX.....	1-61
NS_FUNCTION GETDBNAME	1-62

Choose the DBMS and the base for an SQL command

AT command.....	1-17
-----------------	------

Executing a SQL command: SELECT, INSERT, UPDATE, CREATE TABLE ...

SQL_EXEC.....	1-18
SQL_EXECSTR	1-22
SQL_EXEC_LONGSTR	1-23

Managing the cursor

SQL_OPENCURSOR%	1-25
SQL_CLOSECURSOR.....	1-27
SQL_OPENTHECURSOR%	1-28
SQL_CLOSETHECURSOR.....	1-29

NS_FUNCTION SETCURSORMODE.....	1-92
NS_FUNCTION SETSTMTOPTION	1-98

Running a stored procedure

Stored procedure

A **stored procedure** is a bit of code, written in a owner database language, stored in base.

SQL_PROC.....	1-38
NS_FUNCTION GETPROCEDURE	1-70
NS_FUNCTION GETPROCEDURECOLUMN.....	1-71

Recording and reexecuting an SQL command

RECORD.....	1-42
REEXECUTE	1-42

Managing blobs

TYPE_SQL_INSERT_BLOB%	1-43
TYPE_SQL_SELECT_BLOB%	1-43

Managing connections

NS_FUNCTION SETTRANSACTIONMANAGER	1-95
NS_FUNCTION SETCONNECTOPTION	1-96

Configuring DBMS behavior

NS_FUNCTION ANSIOFF	1-48
NS_FUNCTION ANSION	1-48
NS_FUNCTION AUTOCOMMITOFF.....	1-49
NS_FUNCTION AUTOCOMMITON	1-49
NS_FUNCTION CHARTOHEXAOFF.....	1-55
NS_FUNCTION CHARTOHEXAON	1-55
NS_FUNCTION IMAGEOFF	1-87
NS_FUNCTION IMAGEON.....	1-87
NS_FUNCTION QUOTEON.....	1-89

NS_FUNCTION QUOTEON	1-89
NS_FUNCTION TRIMCHAROFF	1-100
NS_FUNCTION TRIMCHARON.....	1-100

SQL query advanced management

FOR UPDATE OF	1-45
WHERE CURRENT OF	1-45
NS_FUNCTION CHANGEOPTION	1-54
NS_FUNCTION GETCOLUMN	1-59
NS_FUNCTION GETINDEXCOLUMN	1-64
NS_FUNCTION GETINFO	1-66
NS_FUNCTION GETPRIMARYKEY	1-68
NS_FUNCTION GETTABLE	1-73
NS_FUNCTION GETTABLEINFO.....	1-75
NS_FUNCTION GETTYPEINFO	1-77
NS_FUNCTION GIVECOM.....	1-79
NS_FUNCTION ROWCOUNT	1-90
NS_FUNCTION STATEMENT.....	1-94

Handling floating values

NS_FUNCTION CLEANTFLOATVALUES	1-57
-------------------------------------	------

Handling errors

SQL_ERROR%	1-30
SQL_ERRMSG\$.....	1-37
SQL_RETURN	1-41
NS_FUNCTION CALLBACK	1-50
NS_FUNCTION ERRORCOUNT	1-58
NS_FUNCTION GETERROR	1-63
NS_FUNCTION RPCRETCODEOFF	1-91
NS_FUNCTION RPCRETCODEON.....	1-91

NSnnODCx library reference

SQL_INIT instruction

Loads the driver needed to use ODBC.

Syntax `SQL_INIT DLL_name`

Parameter `DLL_name` CSTRING I name of the driver to load

Notes

1. This must be the first SQL_ instruction called by any application that wants to use ODBC with NCL: it is responsible for loading the library.
2. Le paramètre *nom-DLL* doit contenir le nom de la DLL qui permet d'accéder à ODBC pour une cible donnée.
3. The *DLL-name* parameter should contain the name of the DLL used to access the ODBC database: **NSnnODCx**.
 - **nn** indicates the target platform: w2 for Windows 32 bits, p2 for OS/2 32 bits, 02 for OS/2 16 bits and Windows 16 bits.
 - **xx** indicates the installed version of ODBC.

Example

```
SQL_INIT "NSw2ODC3" ; Loads the DLL which interfaces with
                    ; the client version of DB2 1.2
                    ; on a Windows 3.x (16 bits) machine
...
SQL_STOP           ; Unloads the DLL
```

See also SQL_STOP, SQL_INITMULTIPLE%, SQL_STOPMULTIPLE, SQL_STOPALL, SQL_ERROR% , SQL_ERRMSG\$

SQL_STOP instruction

Unloads the current DBMS and closes simultaneously all opened databases and cursors.

Syntax **SQL_STOP**

Example

Refer to the example of SQL_INIT instruction.

See also SQL_INIT, SQL_INITMULTIPLE%, SQL_STOPMULTIPLE, SQL_STOPALL,
SQL_ERROR%, SQL_ERRMSG\$

SQL_OPEN instruction

Opens a database.

Syntax `SQL_OPEN logical-DBname, password-string`

Parameters	<i>logical-DBname</i>	CSTRING	I	logical name of the database to open
	<i>password-string</i>	CSTRING	I	password to connect to a server

Notes

1. ODBC could open several databases through the network.
2. The *logical-DBname* specified the logical database name. There are two possible cases :
3. The *logical-DBname* parameter specifies the logical database name. It can be split into two parts: The first part contains a name that identifies the SQL_OPEN statement. The second part allows you to connect in different ways.

- case 1 : `SQL_OPEN "myname" , "scott/tiger@LOCALDB2"`

This is the standard case for connecting to the database. The second parameter passed to SQL_OPEN must contain all the information required for the connection. The DATA SOURCE must be configured correctly.

- case 2 : `SQL_OPEN "myname/prompt " , "@LOCALDB2"`

In this case, the second parameter becomes optional. It initializes the DATA SOURCE and calls the selected driver's connection window.



You need an active window to use this mode.

- case 3 : `SQL_OPEN "myname/required" , "scott@LOCALDB2"`

In this case, if the second parameter is sufficient for connecting to the database, the connection will go ahead. Otherwise, the corresponding driver's connection window will be displayed automatically so that any missing information can be supplied.



You need an active window to use this mode.

- case 4 : `SQL_OPEN "myname/required" , "scott@MYACCESS!mars"`

In this case, connection is done by activating the MARS extension (“Multiple Activates Result Sets”) available since version SQL Server 2005. This extension allows you to work with more than one concurrent result set on a single connection. The use of this connection option causes a warning at the time of connection to a base other than SQL Server 2005.

- case 5 : **SQL_OPEN "pubs", "scott/tiger@AliasODBC!DYNCURS"**

Microsoft to avoid the error on the imbricated cursors when one cannot activate the **MARS** option proposes a new solution.

The **DYNCURS** option allows the cursors to open in dynamic mode on the server side when the target base supports it.

With this method, the client will be able to turn later in MARS mode if he wishes it, when it will be on a server 2005 with the Native client. That will not have effect on the clients who do not have this error today.

Example:

If for an unspecified need one wants to open a cursor in the normal old mode (the default mode), open it and apply it the NS_FUNCTION **SetStmtOption**:

```
Curs% = Sql_OpenTheCursor%
info% = 6 ;; SQL_ATTR_CURSOR_TYPE
value% = 0 ;; SQL_CURSOR_FORWARD_ONLY
Sql_Exec Ns_Function SetStmtOption :info%, :value% using Curs%
Sql_Exec Select x,y,z from TABLE using Curs%
While (Sql_Error%=0)
    Sql_Exec Fetch into :x$, :y$, :z$ using Curs%
    ...
EndWhile
...
Sql_CloseTheCursor Curs%
```

- case 6 : **SQL_OPEN "myname", "scott/tiger@driver={SQL SERVER};server=host;"**

In this last case, it is possible to establish an ODBC connection without defining a data source. This new functionality will facilitate the deployment of ns02ODC3 driver based applications.

The keyword "driver" indicates that there is no DSN or data source (Data Source Name) defined on the workstation.

{Sql Server} is the name of the database manager's ODBC DLL for the basic manager of data that one wants to interface. For some database managers, it could be useful to pass the name of the DLL as for Middleware Neon for DB2. The connection string becomes **"@Driver=SCOD32.DLL;HOST=10.28.1846;"**

server indicates the server machine. An IP address or an alias should be add after if the keyword "driver" is not mentioned. If you want a connection without DSN, use !NODSN in the name of the logical database. Thus, the general syntax becomes **SQL_EXEC "myname[/prompt or /required]!NODSN', 'user/pass@connectstring "**.

4. The *password-string* parameter specifies the command string used to connect to a local or remote database, as follows :

"USERID[/PASSWORD] [@<CONNECTOR>]

where :

[USERID] name of the user account on the server

optional if the data source does not require them or if the DATA SOURCE is correctly configured.

[PASSWORD] password for the user account

optional if the data source does not require them or if the DATA SOURCE is correctly configured.

[@<CONNECTOR>] used to specify which open database will receive the query.

If it is not specified, the default data source will be accessed. SQL_EXEC is used to specify which open database will receive the query.

5. If a password is not required to open the database, pass an empty string in *connection-string*.

Example

```
SQL_OPEN "BASE1", "@MYACCESS"
IF SQL_ERROR% <> 0
    MESSAGE "Error Base1", SQL_ERRMSG$(SQL_ERROR%)
ENDIF
SQL_OPEN "BASE2", "SCOTT/TIGER@MYORACLE"
IF SQL_ERROR% <> 0
    MESSAGE "Error Base 2", SQL_ERRMSG$(SQL_ERROR%)
ENDIF
...
SQL_CLOSE "BASE2"
SQL_CLOSE "BASE1"
```

See also

SQL_CLOSE, NS_FUNCTION CHANGEDBCNTX, AT, NS_FUNCTION
GETDBNAME, SQL_ERROR%, SQL_ERRMSG\$

SQL_CLOSE instruction

Closes a connection of a database.

Syntax **SQL_CLOSE** *logical-DBname*

Parameter *logical-DBname* CSTRING I logical name of the database to close

Notes

1. Although that you recommend that you close each of the databases opened by an application, an SQL_CLOSE instruction is automatically generated for each open database when an application is closed.

Example

Refer to the example of the SQL_OPEN instruction.

See also SQL_OPEN, NS_FUNCTION CHANGEDBCNTX, AT, NS_FUNCTION
GETDBNAME, SQL_ERROR%, SQL_ERRMSG\$


AT command

Specifies the name of the logical database affected by the SQL statement that follows..

Syntax **AT** *logical-DBname*, *SQL-statement*

Parameters	<i>logical-DBname</i>	CSTRING	I	logical database name
	<i>SQL-statement</i>	CSTRING	I	SQL statement to execute

Notes

1. *logical-DBname* was passed as the first parameter to the SQL_OPEN statement used to open the database.
2. If several databases have been opened simultaneously, the last database opened is taken as the default.
3.  To go from one database to another, we suggest using the NS_FUNCTION CHANGEDBCNTX command because the AT command may no longer be supported in future releases.

Example

```
SQL_OPEN "BASE1", "SCOTT/TIGER@ACCESS"
SQL_OPEN "BASE2", "SCOTT/TIGER@SYBASE"
SQL_OPEN "BASE3", "SCOTT/TIGER@ORACLE"
SQL_EXEC SELECT... ; SELECT on BASE3
SQL_EXEC AT BASE2 SELECT... ; SELECT on BASE2
SQL_EXEC AT BASE2 FETCH... ; FETCH on BASE2
SQL_EXEC FETCH... ; FETCH on BASE3
```

See also SQL_OPEN, SQL_CLOSE, NS_FUNCTION CHANGEDBCNTX, NS_FUNCTION GETDBNAME, SQL_ERROR%, SQL_ERRMSG\$

SQL_EXEC instruction

Executes an SQL command: SELECT, INSERT, UPDATE, CREATE TABLE ...

Syntax **SQL_EXEC** [**AT** *logical-DBname*] *SQL-command* [**USING** *cursor-handle*]

Parameters	<i>logical-DBname</i>	CSTRING	I	logical name of database
	<i>SQL-command</i>	CSTRING	I	SQL command to execute
	<i>cursor-handle</i>	INT(4)	I	cursor value

Notes

1. The SQL command is passed directly without quotes. It can correspond to any Oracle SQL command, whether it's a data definition command (CREATE TABLE, CREATE INDEX,) or a data manipulation command (SELECT, INSERT, UPDATE, ...).
2. The AT command can only be used with databases which allow several simultaneous connections. The query is sent to the database specified after the AT command (without quotes and *case-sensitive*). If the AT command isn't specified, the SQL_EXEC executes on the current database.
3. If USING *cursor-handle* is specified, it indicates which cursor previously opened by SQL_OPENCURSOR% must be used to execute the SQL command. If no cursor has been opened, the cursor's value is that of DEFAULT_CURSOR: -1.
4. The SQL command can return values in NCL variables. For this, just pass these variables in parameters.
5. It is possible to pass a segment's field as a data-receiving variable in an SQL query.
6. The commands SQL_EXEC, SQL_EXECSTR and SQL_EXEC_LONGSTR depend on the SQL language accepted by the DBMS in use (Refer to the DBMS documentation).
7. For SQL commands that are too long, it is possible to use the special continuation character "\":

```
SQL_EXEC UPDATE SAMPLE SET SOCIETE = :A$\n
                                WHERE VILLE = :C$\n
AND \n
                                PAYS = :D$
```
8. The types of variables recognized by the interface are:
 - INT(1), INT(2), and INT(4),
 - NUM(8), NUM(4),
 - STRING,
 - CSTRING,

- CHAR.
9. The INTO clause is used by the SELECT and FETCH commands. It defines a list of host variables. Its syntax is:
 INTO :var1 [:indic1] [, :var2 [:indic2] \
 [, ...]]
 10. We suggest using INTO in a SELECT to improve performance because during a FETCH, in each loop, the driver has to analyze the variables of the INTO clause. Using the INTO clause in a FETCH should be restricted to doing things like be entering elements into an array.
 11. Always put a ":" before the name of a variable or flag.
 12. A flag is an NCL integer variable which can have the following values:
 - ◆ NULL_VALUE_INDICATOR (i.e. -1) indicates that the associated NCL variable which precedes it has a NULL value.
 - ◆ Any other value indicates that the associated NCL variable which precedes it has a NOT NULL value, and can therefore be used.
 13. In SQL, NULL does not mean 0 or an empty string (""). However, to make it possible to assign a value in all cases, when a column contains a NULL value, a numeric target NCL variable will be assigned a 0 and a string target NCL variable will be assigned an empty string ("").
 14. If you want a connection without DSN, use !NODSN in the name of the logical base. Thus, the general syntax is **SQL_EXEC "myname[/prompt gold /required]!NODSN', ' user/pass@connectstring "**.

Example

```

LOCAL CODE%, I%, AGE%, IND1%, IND2%
LOCAL COUNTRY$, CITY$, A$, B$
LOCAL TCODE%[10]
LOCAL TCOUNTRY$[10]

CITY$ = "NEW YORK"

; =====
; 1st example
; =====
; ---- Select a subset
SQL_EXEC SELECT CODE, COUNTRY \
          FROM WORLD \
          WHERE TOWN =:CITY$
; ---- Read the first to last entry
WHILE SQL_ERROR% = 0
  SQL_EXEC FETCH INTO :CODE%, :COUNTRY$
  IF SQL_ERROR% = 0
    INSERT AT END CODE% && COUNTRY$ TO LBOX1
  ENDIF
ENDWHILE

; =====
; 2nd example(most efficient)
; =====
; ---- Select a subset
; and read the first entry
SQL_EXEC SELECT CODE, COUNTRY \

```

```

        FROM WORLD \
        INTO:CODE%, :COUNTRY$ \
        WHERE TOWN =:CITY$
; ---- Read the second to the last entry
WHILE SQL_ERROR% = 0
    INSERT AT END CODE% && COUNTRY$ TO LBOX1
    SQL_EXEC FETCH
ENDWHILE

; =====
; 3rd example
; =====
; ---- Select a subset
SQL_EXEC SELECT CODE, COUNTRY \
        FROM WORLD \
        WHERE TOWN =:CITY$
; ---- Read 1st entry to last entry
; by filling TCODE% and TCOUNTRY$ tables
I% = 0
WHILE (SQL_ERROR% = 0) AND (I% < 10)
    SQL_EXEC FETCH INTO :TCODE%[I%], :TCOUNTRY$[I%]
    I% = I% + 1
ENDWHILE

; =====
; Using flags
; =====
SQL_EXEC CREATE TABLE FAMILY( NAME          VARCHAR2(10), \
                                AGE           NUMBER,        \
                                CHILDNAME     VARCHAR2(10))

FATHER$ = "STEVE"
AGE%    = 35
SON$    = "PETER"
IND1%   = 0
IND2%   = 0
; --- Insert "STEVE", 35, "PETER" into table
SQL_EXEC INSERT INTO FAMILY\
        VALUES (:FATHER$:IND1%, :AGE%, :SON$:IND2%)

FATHER$ = "PETER"
AGE%    = 10
IND1%   = 0
IND2%   = NULL_VALUE_INDICATOR
; --- Insert "PETER", 10, NULL into table
SQL_EXEC INSERT INTO FAMILY VALUES (:FATHER$:IND1%, :AGE%, :SON$:IND2%)

; ---- The SELECT loop places the listbox LBOX
; 'STEVE's son is PETER'
; 'PETER does not have a son.'
SQL_EXEC SELECT NAME, AGE, CHILDNAME\
        INTO:FATHER$:IND1%, :AGE%, :SON$:IND2% \
        FROM FAMILY
WHILE SQL_ERROR% = 0
    ; ---- IND1% is always 0 here
    IF IND2% = -1
        INSERT AT END FATHER$ & "does not have a son." TO LBOX
    ELSE
        INSERT AT END FATHER$ & "'s son " & \
            "is" & SON$ TO LBOX
    ENDIF
    SQL_EXEC FETCH
ENDWHILE

```

See also SQL_EXECSTR, SQL_EXEC_LONGSTR, SQL_ERROR%, SQL_ERRMSG\$

SQL_EXEC_LONGSTR instruction

Executes a very long SQL command: SELECT, INSERT, UPDATE, CREATE TABLE ...

Syntax **SQL_EXEC_LONGSTR** *sql-string-address*, *var-array-address*, *cursor-num*

Parameters	<i>sql-string-address</i>	INT(4)	I	address of the character string containing the SQL statement to execute
	<i>var-array-address</i>	INT(4)	I	address of the array containing the host variables (or indicators)
	<i>cursor-num</i>	INT(2)	I	cursor value

Notes

1. The executed statement can contain any SQL command in the host language (DML or DDL). The size of the string depends on the RDBMS used; it is unlimited for certain database engines and limited to 4096 characters for others.
2. *sql-string-address* is the address of the string which contains the SQL command to execute.
3. *var-array-address* is an array of NCLVAR segments which describe the NCL host variables. If your SQL statement does not use any variables, pass 0 in *var-array-address*.
4. When you use the SQL_EXEC_LONGSTR instruction, each *host* variable is represented in the text of the query by a ":" character. The first ":" corresponds to the first *host* variable in the array of *host* variables, and so on.
5. The NCLVAR segment and any constants used are declared in the NSDBMS library as follows:

```

SEGMENT NCLVAR
  INT      PTR_VAR ( 4 )
  INT      TYPE_VAR ( 2 )
  INTEGER  SIZE_VAR
  INT      RESERVED ( 4 )
ENDSEGMENT

CONST TYPE_SQL_INT%           0
CONST TYPE_SQL_STRING%       1
CONST TYPE_SQL_CSTRING%      2
CONST TYPE_SQL_NUM%          3
CONST TYPE_SQL_SEGMENT%      10
CONST TYPE_SQL_IMAGE%        11
CONST TYPE_SQL_SELECT_BLOB%   12
CONST TYPE_SQL_INSERT_BLOB%   13

```

6. This array of segments should have an **index that is greater than** the number of variables used (the last element contains 0). You are therefore advised to fill this array initially (using the NCL FILL verb) to ensure that element 0 actually exists, since the end of the scan is determined by this element.
7. If no cursors have been opened, the cursor value must be set to that of the DEFAULT CURSOR: -1.
8. SQL_EXEC_LONGSTR replaces SQL_EXECLONGSTR%. To use this instruction, you will still find the code you need in the notes of NSDBMS.NCL.
9. The other function of SQL_EXEC_LONGSTR instruction are the same as SQL_EXEC.

Example

```
LOCAL NCLVAR VARLIST[3]      ; for 2 variables
LOCAL SQL_STR$              ; string to pass
LOCAL VAR1%, VAR2$          ; host variables
LOCAL CONDITION%           ; input variable

; ---- Set the array to 0
FILL @VARLIST, SIZEOF VARLIST, 0

SQL_STR$                    = "SELECT VCHAR, VINT " & "FROM TAB1 " & \ "WHERE VINT >= :"

VARLIST[0].PTR_VAR = @CONDITION%
varlist[0].TYPE_VAR = TYPE_SQL_INT%
VARLIST[0].SIZE_VAR = SIZEOF @CONDITION%

SQL_EXEC_LONGSTR @SQL_STR$, @VARLIST, DEFAULT_CURSOR
FILL @VARLIST, SIZEOF VARLIST, 0
SQL_STR$ = "FETCH INTO :, :"

VARLIST[0].PTR_VAR = @var2$
VARLIST[0].TYPE_VAR = TYPE_SQL_CSTRING%
VARLIST[0].SIZE_VAR = SIZEOF var2$
VARLIST[1].PTR_VAR = @var1%
VARLIST[1].TYPE_VAR = TYPE_SQL_INT%
VARLIST[1].SIZE_VAR = SIZEOF var1%

WHILE SQL_ERROR% = 0

    SQL_EXEC_LONGSTR @SQL_STR$, @VARLIST, DEFAULT_CURSOR
    IF SQL_ERROR% = 0
        MESSAGE "SELECT", VAR1% && VAR2$
    ENDIF
ENDWHILE
```

See also FILL (NCL), NSDBMS.NCL, SQL_EXEC, SQL_EXECSTR, SQL_ERROR%, SQL_ERRMSG\$

SQL_OPENCURSOR% function

Opens a cursor and returns its handle.

Syntax **SQL_OPENCURSOR%**

Returned value INT(4)

Notes

1. After opening the cursor, it can be used with the following instructions

```
SQL_EXEC SELECT ... USING handle-curseur
SQL_EXEC FETCH ... USING handle-curseur
```
2. A cursor is an internal resource managed by the NSnnODCx DLL and is used, for example, to store the current table row position for the next SQL call.
3. When the system is opened, only one cursor is defined, known as the DEFAULT_CURSOR.
4. If no cursors have been opened, this DEFAULT_CURSOR will be used to execute all SQL statements that maintain current positions within the database, including SELECT and FETCH statements.
5. A problem occurs if an SQL statement other than FETCH (for example UPDATE or INSERT) is embedded in a scanning sequence; the current position is lost and the FETCH statement that follows the embedded statement will terminate with the error.
SQL_OPENCURSOR% solves this problem by executing all SELECT and FETCH commands with the new cursor.
6. Generally speaking, a new cursor should be opened each time you wish to perform a SELECT FETCH scan while another similar scan is still in progress with the last cursor opened.
7. The NSnnODCx DLL specifically designed for the DBMS stores cursors in a LIFO (Last In First Out) stack: SQL_OPENCURSOR% stacks and SQL_CLOSECURSOR unstacks.
8. The following rules apply when executing a statement with a cursor:
 - Statements are always executed with the specified cursor.
 - If with SQL_EXEC, the USING clause isn't specified, the commands are executed with the DEFAULT_CURSOR.
9. When several databases are opened simultaneously, the cursor opened by SQL_OPENCURSOR% is immediately associated with the current database.
10. If you want to open a cursor in a database other than the current one, you must execute the SQL_EXEC CHANGEDBCNTX:otherbase\$ command to change databases before you execute SQL_OPENCURSOR%.

Example

See the example of the SQL_CLOSETHECURSOR instruction.

See also

SQL_CLOSECURSOR, SQL_OPENTHECURSOR%, SQL_CLOSETHECURSOR,
SQL_ERROR%, SQL_ERRMSG\$

SQL_CLOSECURSOR instruction

Closes the last cursor opened and the last occupied by SQL_OPENCURSOR%.

Syntax **SQL_CLOSECURSOR**

Notes

1. SQL_CLOSECURSOR closes the last cursor opened, situated at the top of the LIFO (Last In First Out) cursor stack.
2. SQL_CLOSECURSOR must only close cursors opened with SQL_OPENCURSOR%.
3. The error codes returned by SQL_ERROR% for this instruction are: -32003 or -32005.
4. The SQL_CLOSECURSOR instruction must not be used with the IM module of NatStar.
5. Nat System recommends you to use SQL_CLOSETHECURSOR instead of SQL_CLOSECURSOR.

Example

See the example of the SQL_CLOSETHECURSOR instruction.

See also SQL_OPENCURSOR%, SQL_OPENTHECURSOR%, SQL_CLOSETHECURSOR,
SQL_ERROR%, SQL_ERRMSG\$

SQL_OPENTHECURSOR% function

Opens a cursor and returns its handle.

Syntax **SQL_OPENTHECURSOR%**

Returned value INT(2)

Notes

1. After opening the cursor, it can be used with the following instructions:

```
SQL_EXEC SELECT ... USING handle-curseur
SQL_EXEC FETCH ... USING handle-curseur
```
2. A cursor is an internal resource managed by the NSnnODCx DLL and is used, for example, to store the current table row position for the next SQL call.
3. When the system is opened, only one cursor is defined, known as the DEFAULT_CURSOR.
4. If no cursors have been opened, this DEFAULT_CURSOR will be used to execute all SQL statements that maintain current positions within the database, including SELECT and FETCH statements.
5. A problem occurs if an SQL statement other than FETCH (for example UPDATE or INSERT) is embedded in a scanning sequence; the current position is lost and the FETCH statement that follows the embedded statement will terminate with the error.
SQL_OPENCURSOR% solves this problem by executing all SELECT and FETCH commands with the new cursor.
6. Generally speaking, a new cursor should be opened each time you wish to perform a SELECT FETCH scan while another similar scan is still in progress with the last cursor opened.
7. The following rules apply when executing a statement with a cursor:
 - Statements are always executed with the specified cursor.
 - If with SQL_EXEC, the USING clause isn't specified, the commands are executed with the DEFAULT_CURSOR.
8. When opening several databases at the same time, the cursor opened by SQL_OPENTHECURSOR% is immediately associated with the current database.
9. If you want to open a cursor in a database other than the current one, you must execute the SQL_EXEC CHANGEDBCNTX:otherbase\$ command to change databases before you execute SQL_OPENCURSOR%.

Example

Refer to the example of the SQL_CLOSETHECURSOR instruction.

See also SQL_OPENCURSOR%, SQL_CLOSECURSOR, SQL_CLOSETHECURSOR,
SQL_ERROR%, SQL_ERRMSG\$

SQL_CLOSETHECURSOR instruction

Closes the cursor associated with the given handle.

Syntax `SQL_CLOSETHECURSOR cursor-handle`

Parameter *cursor-handle* INT(4) I handle of cursor to close

Note

1. SQL_CLOSETHECURSOR can only close cursors opened with SQL_OPENTHECURSOR%.

Example

```
; ---- Example showing the two different types of
;       cursors (for clarity, we have not
;       included error test code)

SQL_EXEC ....           ; uses the default cursor
C1% = SQL_OPENCURSOR%    ; opens the C1% cursor
SQL_EXEC UPDATE ...      ; uses the default cursor
SQL_EXEC SELECT ...      ; uses the default cursor
SQL_CLOSETHECURSOR C1%   ; => error
C2% = SQL_OPENTHECURSOR% ; opens the C2% cursor
SQL_EXEC UPDATE ...      ; uses the default cursor
SQL_EXEC UPDATE ... USING C1% ; uses the C1% cursor
SQL_EXEC SELECT ... USING C2% ; uses the C2% cursor
SQL_EXEC SELECT ... USING C1% ; uses the C1% cursor
SQL_CLOSECURSOR          ; closes the C1% cursor
SQL_EXEC UPDATE ....     ; uses the default cursor
SQL_EXEC SELECT .... USING C2% ; uses the C2% cursor
SQL_CLOSECURSOR%         ; => error
SQL_CLOSETHECURSOR C2%   ; closes the C2% cursor
SQL_EXEC ....           ; uses the default cursor
```

See also SQL_OPENCURSOR%, SQL_CLOSECURSOR, SQL_OPENTHECURSOR%,
SQL_ERROR%, SQL_ERRMSG\$

SQL_ERROR% function

Returns the error code of the last SQL_ instruction executed.

Syntax **SQL_ERROR%**

Returned value INT(4)

Notes

1. SQL_ERROR% complies with SQL conventions. The function returns:
 - 0 if no errors occurred.
 - A positive number for non-fatal errors (the instruction was executed but issued a warning).
 - A negative number for fatal errors (the instruction could not be executed).
2. This function applies to all ODBC driver functions.
3. Deux types de codes retour sont renvoyés par l'interface :
 - Proprietary DBMS SQL error codes which are described in the editor's manuals.
 - Internal NAT SYSTEM error codes. They correspond to errors not handles by the host DBMS. These error messages are numbered and have the format "32XXX".

Example :

```
-32004 "NSSQLE004 ** NO MORE CURSORS AVAILABLE"
```

4. With the NSnnODCx DLL, the notion of errors and warnings are completely different from the previous versions (NSnnODBC). Now, most of the older warnings are errors.
5. List of internal Nat System errors common to ODBC :
 - 0 "NSSQLE000 ** UNUSED NATSYS ERROR CODE"**
 - Cause :** No error occurred, the execution was carried out correctly.
 - +100 "NSSQLW100 ** NO ROW WAS FOUND OR LAST ROW REACHED"**
 - Cause :** There are no rows or the last row was reached after a FETCH or SELECT.
 - 32001 "NSSQLE001 ** HEAP ALLOCATION ERROR"**
 - Cause :** Internal memory allocation/deallocation error
 - 32002 "NSSQLE002 ** DYNAMIC ALLOCATION ERROR"**
 - Cause :** Internal memory allocation/deallocation error

-32003 "NSSQLE003 ** DYNAMIC FREE STORAGE ERROR"

Cause : Internal memory allocation/deallocation error

-32004 "NSSQLE004 ** NO MORE CURSORS AVAILABLE"

Cause : Too many cursors opened simultaneously.

-32005 "NSSQLE005 ** NO MORE CURSORS OR TRYING TO DEALLOCATE ONLY CURSOR"**-32006 "NSSQLE006 ** INVALID INTO CLAUSE in FETCH/SELECT"**

Cause : Syntax error in the INTO clause of a SELECT or a FETCH statement

-32007 "NSSQLE007 ** TOO MANY VARIABLES IN INTO CLAUSE"

Cause : More than 200 in the INTO clause

-32008 "NSSQLE008 ** MISSING HOST VARIABLE AFTER ','"

Cause : Syntax error in the INTO clause. Variable missing after a continuation comma.

+32009 "NSSQLW009 ** INTO CLAUSE : NOT ENOUGH VARIABLES"

Cause : A SELECT statement contains an INTO clause with fewer variables than the number of variables returned by the query.

Warning : The system will still fill the host variables supplied to it.

+32010 "NSSQLW010 ** AN OPENED CURSOR WAS CLOSED BY SYSTEM"

Cause : Following the arrival of a new SQL command for a cursor, the system forced the closure of a cursor containing an active query.

-32011 "NSSQLE011 ** WHERE/VALUE CLAUSE : NOT ENOUGH VARIABLES"

Cause : Not enough host variables received in the table to be able to substitute the variables specified in the WHERE clause.

-32012 "NSSQLE012 ** INVALID INPUT VARIABLE DATA TYPE"

Cause : Invalid data type in a WHERE clause.

-32013 "NSSQLE013 ** MISSING 'OF' AFTER 'WHERE CURRENT'

Cause : Syntax error in UPDATE WHERE CURRENT OF.

-32014 "NSSQLE014 ** NO OUTPUT VARIABLES DEFINED FOR FETCH"

Cause : The FETCH and the prior SELECT have not defined any output variables (INTO clause).

-32015 "NSSQLE015 ** CURSOR NOT READY (MISSING SELECT) "

Cause : FETCH attempted without a prior SELECT or cursor closed by the system between the SELECT and the FETCH statements.

-32016 "NSSQLE016 ** INVALID SQL DATA TYPE"

Cause : Data type invalid for output.

-32017 "NSSQLE017 ** INVALID DATA CONVERSION REQUESTED"

Cause : Type conversion invalid for output.

STRING -> NUM

NUM -> STRING

REAL -> INTEGER

INTEGER -> REAL

-32018 "NSSQLE018 ** NUMERIC DATA TYPE : INVALID LENGTH"

Cause : Invalid length for the data type (for example, real number with a length of 48)

-32019 "NSSQLE019 ** INVALID DECIMAL PACKED FORMAT"

Cause : Unable to convert data to packed decimal format.

+32020 "NSSQLW020 ** STRING DATA TRUNCATED"

Cause : The string passed as a variable is shorter than the field received from the DBMS. The received field has been truncated.

-32021 "NSSQLE021 ** RESET STORAGE ERROR"

Cause : Deallocation error of the internal heap

+32022 "NSSQLW022 ** FUNCTION NOT SUPPORTED IN ODBC3 DATABASE"

Cause : The executed instruction is not available.

+32022 "NSSQLW022 ** FUNCTION NOT SUPPORTED IN ODBC2 DATABASE"

Cause : The executed instruction is not available.

-32023 "NSSQLE023 ** TOO MANY OPENED DATABASES"

Cause : More than 5 databases opened simultaneously.

+32024 "NSSQLW024 ** DB ALREADY OPENED"

Cause : The database used with SQL_OPEN has already been opened.

-32025 "NSSQLE025 ** DB NOT PREVIOUSLY OPENED"

Cause : Attempt to close a database that has not been happened.

-32026 "NSSQLE026 ** INVALID DATABASE NAME REF"

Cause : Unknown database name used in the AT clause of the SQL_EXEC statement (database not opened)

-32028 "NSSQLE028 ** UNABLE TO GET ODBC3 LOGIN"

Cause : Failed to connect to DB2 (e.g. server name error).

-32029 "NSSQLE029 ** ODBC3 VARIABLE INPUT BIND FAILED"

Cause : Type mismatch between a variable and a database field.

-32030 "NSSQLE030 ** ODBC3 VARIABLE OUTPUT BIND FAILED"

Cause : Type mismatch between a variable and a database field.

-32031 "NSSQLE031 ** ODBC2 BUFFER FILL ERROR"

Cause : Buffer overflow (due to data conversion,etc.)

-32032 "NSSQLE032 ** RPC PARAMETER NAME EXPECTED"

Cause : Remote procedure call : procedure name missing.

-32033 "NSSQLE033 ** TOO MANY RPC PARAMETERS"

Cause : Remote procedure call : procedure name missing.

-32034 "NSSQLE034 ** RPC PROCEDURE NAME EXPECTED"

Cause : Remote procedure call : procedure name missing.

-32035 "NSSQLE035 ** NOT ENOUGH PARAMETERS FOR RPC CALLS"

Cause : Remote procedure call : too many parameters specified

-32036 "NSSQLE036 ** INVALID RPC PARAMETERS SUPPLIED"

Cause : Remote procedure call : invalid parameters specified

-32037 "NSSQLE037 ** INVALID RPC PROCEDURE INITIALIZATION"

-32038 "NSSQLE038 ** RPC PROCEDURE EXECUTION FAILED"

-32039 "NSSQLE039 ** MEMORY CONSISTENT ERROR"

-32040 "NSSQLE040 ** INVALID TYPE FOR INDICATOR"

-32041 "NSSQLE041 ** CONTEXT NOT CREATED"

-32042 "NSSQLE042 ** CONTEXT NOT FOUND"

-32044 "NSSQLE044 ** NO SET LOGIN TIME"

-32045 "NSSQLE045 ** NO SET TIME"

-32046 "NSSQLE046 ** SET MAXPROCS FAILED"

-32047 "NSSQLE047 ** DB OPEN FAILED"

-32048 "NSSQLE048 ** DB NOT OPENED"

-32049 "NSSQLE049 ** LOGIN RECORD NOT ALLOCATED"

-32050 "NSSQLE050 ** MEMORY DEALLOCATION ERROR"

- 32051 "NSSQLE051 ** CURSOR NOT FOUND"
- 32052 "NSSQLE052 ** MUST EXECUTE SELECT BEFORE THE FETCH COMMAND"
- 32053 "NSSQLE053 ** ERROR IN CLOSING DATABASE"
- 32054 "NSSQLE054 ** ERROR IN EXECUTING SQL STATEMENT"
- 32055 "NSSQLE055 ** ERROR IN EXECUTING FETCH COMMAND"
- 32056 "NSSQLE056 ** INDICATOR'S SIZE TOO SMALL TO HOLD VALUE"
- 32057 "NSSQLE057 ** UNKNOWN NCL VARIABLE TYPE PASSED"
- 32058 "NSSQLE058 ** RPC : INIT ERROR"
- 32059 "NSSQLE059 ** RPC : PARAMETERS FOUND BUT NO VALUES CLAUSE"
- 32060 "NSSQLE060 ** RPC : PARAMETER TYPE MISMATCH"
- 32061 "NSSQLE061 ** RPC : PROCEDURE NAME MISSING"
- 32062 "NSSQLE062 ** RPC : INDICATORS MAY ONLY BE ON OUT VARIABLES"
- 32063 "NSSQLE063 ** RPC : SQL SERVER ERROR DURING RPC PREPARATION"
- 32064 "NSSQLE064 ** RPC : SQL SERVER ERROR DURING RPC EXECUTION"
- 32065 "NSSQLE065 ** RPC : SQL SERVER ERROR DURING RPC EXEC CHECK"
- 32066 "NSSQLE066 ** RPC : PROCEDURE NOT PREPARED"
- 32067 "NSSQLE067 ** LOGGER : CAN'T OPEN FILE"
- 32068 "NSSQLE068 ** PARSER : TOKEN TABLE FULL"
- 32069 "NSSQLE069 ** EXEC : INCOMPATIBLE CURSOR MODE"
- 32070 "NSSQLE070 ** EXEC : SQL SERVER ERROR DURING SIZE BUFFERING EXECUTION"
- 32071 "NSSQLE071 ** EXEC : SQL SERVER ERROR DURING SIZE BUFFERING DELETION"
- 32072 "NSSQLE072 ** EXEC : INVALID CURSOR MODE"
- 32073 "NSSQLE073 ** EXEC : THAT ROW IS NOT IN BUFFER"
- 32074 "NSSQLE074 ** EXEC : INCORRECT SYNTAX FOR THIS CURSOR MODE"

- 32075 "NSSQLE075 ** EXEC : MISSING INTO CLAUSE FOR THIS CURSOR MODE"
 - 32076 "NSSQLE076 ** EXEC : INVALID SIZE FOR ROW BUFFERING"
 - 32077 "NSSQLE077 ** EXEC : INVALID ROW NUMBER"
 - 32078 "NSSQLE078 ** EXEC : MEMORY DEALLOCATION ERROR FOR SCROLL STATUS"
 - 32079 "NSSQLE079 ** EXEC : SQL SERVER : ROW IS MISSING IN SCROLL BUFFER"
 - 32080 "NSSQLE080 ** NO STATEMENT IN PROGRESS"
 - 32081 "NSSQLE081 ** DATA NOT READY TO RESULT PROCESSING"
 - 32082 "NSSQLE082 ** INVALID WINDOW HANDLE"
 - 32083 "NSSQLE083 ** USER MESSAGE MUST BE RANGE IN 0 AND 15"
 - 32084 "NSSQLE084 ** INVALID STATEMENT SEND TO DLL"
 - 32085 "NSSQLE085 ** NO MORE RESULT TO FETCH"
 - 32086 "NSSQLE086 ** INVALID PARAMETER TO CHANGE OPTION"
 - 32087 "NSSQLE087 ** INVALID PARAMETER TO CHANGE OPTION VALUE"
 - 32088 "NSSQLE088 ** LOGIN TIME CHANGE FAILED"
 - 32089 "NSSQLE089 ** TIMEOUT CHANGE FAILED"
 - 32090 "NSSQLE090 ** INVALID NS_FUNCTION STATEMENT"
 - 32091 "NSSQLE091 ** INVALID DATABASE NAME"
 - 32092 "NSSQLE092 ** INVALID INTO CLAUSE WHEN ASYNCHRONOUS MODE"
 - 32093 "NSSQLE093 ** INVALID LENGTH FOR DATABASE NAME"
 - 32095 "NSSQLE095 ** INVALID LENGTH FOR USER NAME"
 - 32096 "NSSQLE096 ** INVALID LENGTH FOR PASSWORD"
 - 32097 "NSSQLE097 ** INVALID LENGTH FOR SERVER NAME"
 - 32098 "NSSQLE098 ** INVALID LENGTH FOR SERVER NAME"
 - 32099 "NSSQLE099 ** KEYWORD AT IS NOT SUPPORTED"
 - 32101 "NSSQLE101 ** UNABLE TO OPEN FILE"
 - 32102 "NSSQLE102 ** NO MEMORY AVAILABLE"
 - 32103 "NSSQLE103 ** NO CONNECTION AVAILABLE TO UPDATE IMAGE/TEXT"
-

-32200 "NSSQLE200 ** COMPUTE RESULT IN PROGRESS"

Example

```
...
SQL_EXEC SELECT ENO,ENAME INTO :NO%,:NAME$ FROM EMPLOYE
WHILE SQL_ERROR% = 0
  INSERT AT END "NO=" & NO% & " NAME=" & NAME$ TO LBOX1
  SQL_EXEC FETCH INTO :NO%,:NAME$
ENDWHILE
IF SQL_ERROR% < 0
  MESSAGE "Fatal Error", SQL_ERROR% && SQL_ERRMSG$(SQL_ERROR%)
ELSE
  IF SQL_ERROR% > 0
    MESSAGE "Warning", SQL_ERROR% && SQL_ERRMSG$(SQL_ERROR%)
  ELSE
    MESSAGE "OK no error", SQL_ERROR% && SQL_ERRMSG$(SQL_ERROR%)
  ENDIF
ENDIF
...
```

See Also *NSnn_SQL Library Error messages*

SQL_ERRMSG\$, NS_FUNCTION ERRORCOUNT, NS_FUNCTION GETERROR,
NS_FUNCTION CALLBACK

SQL_ERRMSG\$ function

Returns the error message (character string) for the last SQL_ instruction executed.

Syntax **SQL_ERRMSG\$** (*error-code*)

Parameter *error-code* INT(4) I error code

Returned value CSTRING

Notes

1. SQL_ERRMSG\$ returns the last message stored in a work area in the DLL when the error occurred.
2. This function applies to all ODBC driver functions.
3. See SQL_ERROR% for a detailed list of error codes and messages.

Example

See the example of the SQL_ERROR% instruction.

See also *NSnn_SQL Library Error messages*

SQL_PROC command

Executes a stored procedure.

Syntax **SQL_PROC** *procedure-name*
 [*SCHEMA*].[(@*Parameter-name1* [OUT] [, @*Parameter-name2* [OUT]...])
 VALUES (:Host-Variable1 [,:Host-Variable2...])]
By default, *SCHEMA* stands for the user name of the connection who has created a stored procedure/function.

Parameter *procedure-name* CSTRING I name of the procedure to call

Notes

1. The SQL_PROC keyword informs the parser that a procedure is being called. The word that follows SQL_PROC specifies the name of the called procedure.
2. If the called procedure has parameters, their names must be specified exactly as they are defined in the procedure.

Parameters

Input parameter

Output or Input/Output

Values of the procedure's Input parameters

Syntax

parameter-name in the parameter list.

parameter-name can be followed by IN which is the default in any case.

parameter-name must be followed by OUT

after the VALUES keyword, supply a list of host variables containing the values of the parameters

3. Host variables are preceded by a colon (:).
4. **Restrictions :**
 - The maximum size allowed for ALPHA host variables (CHAR, VARCHAR, etc) is 255 characters.
 - The size of the host variable must match the size of the parameter passed to the procedure. Therefore, when you declare a string host variable, you must also specify its size: LOCAL AS\$ (15).

- If the size of the character string retrieved in the host variable is less than the reserved size, any space that is not occupied by the data item will be padded with blanks (ASCII code 32). The NCL operator, SKIP, can be used to remove any unwanted spaces (cf. *NCL Programming Manual*).
- When a procedure is called with output parameters (OUT), you must use SQL_RETURN to retrieve any errors.

In this case, you have to use NS_FUNCTION RPCRETCODEON to activate the use of the return code.

There are FUNCTION or INSTRUCTION type stored procedures.

You can only use NS_FUNCTION RPCRETCODEON for FUNCTION type stored procedure.

5. The syntax checker does not check anything typed after 'SQL_EXEC'. So, if SQL_PROC is misspelled, a syntax error will not be generated but SQL errors will occur.

Example

```
;CREATION OF THE PROCEDURE
local s$

sql_exec drop procedure RPCTEST

IF SQL_ERROR% < 0
  MESSAGE "Error create proc with FETCH",SQL_ERRMSG$(SQL_ERROR%)
  sql_exec ns_function statement into :s$
  message "",s$
ENDIF

SQL_EXEC CREATE PROCEDURE RPCTEST(@PARAM1 INT OUT, \
                                   @PARAM2 INT OUT, \
                                   @PARAM3 INT OUT, \
                                   @PARAM4 INT OUT) \
AS \
BEGIN \
  SELECT @PARAM1 = @PARAM1 + @PARAM4 \
  SELECT @PARAM2 = @PARAM2 + @PARAM4 \
  SELECT @PARAM3 = @PARAM3 + @PARAM4 \
  SELECT PERE FROM BASE1 \
  RETURN 200 \
END

IF SQL_ERROR% <> 0
  MESSAGE "Error create proc with FETCH",SQL_ERRMSG$(SQL_ERROR%)
  sql_exec ns_function statement into :s$
  message "",s$
ENDIF
```

```

; Call RPCTEST procedure
LOCAL A%, B%, C%, D%, R%, h%
LOCAL A$, B$

A% = 2
B% = 3
C% = 4
D% = 1
; to get the return code
SQL_EXEC NS_FUNCTION RPCTESTCODEON
if SQL_ERROR% <> 0
    MESSAGE "Error RPCTESTCODEON",SQL_ERROR%&&SQL_ERRMSG$(SQL_ERROR%)
ENDIF
SQL_EXEC SQL_PROC RPCTEST (@PARAM1 OUT, @PARAM2 OUT, \
                           @PARAM3 OUT, @PARAM4 OUT ) \
    VALUES ( :A% , :B% , :C% , :D% )
if SQL_ERROR% <> 0
    MESSAGE "Error SQL_PROC RPCTEST",SQL_ERRMSG$(SQL_ERROR%)
ENDIF

; Retrieve the result of the procedure in NCL variables
; Here we retrieve the "Message retrieved by a FETCH" in A$
; Retrieve the result of a SELECT executed on AUTHORS
WHILE SQL_ERROR% = 0
    SQL_EXEC FETCH INTO :B$
    IF SQL_ERROR% <> 0
        if SQL_ERROR% < 0
            MESSAGE "Error AUTHORS:B$",SQL_ERRMSG$(SQL_ERROR%)
        ENDIF
    ELSE
        INSERT AT END B$ TO LISTBOX1
    ENDIF
ENDWHILE

; return code of the procedure
SQL_EXEC SQL_RETURN:R%
if SQL_ERROR% <> 0
    MESSAGE "Error SQL_RETURN:R%",SQL_ERRMSG$(SQL_ERROR%)
ENDIF

; Display the OUT parameters of the procedure
; A%, B%, C% have been incremented by 1 (by d%)
INSERT AT END "Result"&&A%&&B%&&C% TO LISTBOX1

; Display R% (= 200)
INSERT AT END "Return code from RPCTEST"&&R% TO LISTBOX1

SQL_EXEC NS_FUNCTION RPCTESTCODEOFF
if SQL_ERROR% <> 0
    MESSAGE "Error RPCTESTCODEOFF",SQL_ERROR%&&SQL_ERRMSG$(SQL_ERROR%)
ENDIF

```

See also

SQL_RETURN, NS_FUNCTION RPCTESTCODEON, NS_FUNCTION
RPCTESTCODEOFF, SQL_ERROR%, SQL_ERRMSG\$

SQL_RETURN command

Retrieves the error code from the last procedure executed by the SQL_EXEC SQL_PROC command.

Syntax **SQL_RETURN** : *return-code*

Parameter *return-code* INT(4) O return code

Note

1. This command **MUST** be used when you call procedures with OUT parameters (cf. SQL_PROC command).

In this case, you have to use NS_FUNCTION RPCRETCODEON to activate the use of the return code.

There are FUNCTION or INSTRUCTION type stored procedures.

You can only use NS_FUNCTION RPCRETCODEON for FUNCTION type stored procedure.

Example

See the example of the SQL_PROC instruction.

See also

SQL_PROC, NS_FUNCTION RPCRETCODEON, NS_FUNCTION
RPCRETCODEOFF, SQL_ERROR%, SQL_ERRMSG\$

RECORD, REEXECUTE commands

The RECORD command records an SQL sequence so that it can be re-executed using the REEXECUTE command. When you call REEXECUTE, you only supply new values.

Syntax **RECORD** *SQL-statement*

and

REEXECUTE

Parameter *SQL-statement* CSTRING I SQL sequence to record

Notes

1. The parameters in the SQL sequence must still be accessible when the command 'SQL_EXEC REEXECUTE' is issued.
2. After RECORD, any other SQL statement other than REEXECUTE cancels the current RECORD operation.
3. Using RECORD and REEXECUTE allows you to combine the adaptability of dynamic SQL with the speed of static SQL. In fact, a dynamic SQL order is used when the RECORD command is executed. When the REEXECUTE command is executed, as the analysis of query has already been done by the motor, only the values of the host variables are set.

Example

```
LOCAL CODE%
LOCAL NAME$(25)

SQL_EXEC CREATE TABLE EMP(EMPNO INTEGER,ENAME CHAR(25))

CODE = 1
NOM$ = "NAME1"
SQL_EXEC RECORD INSERT INTO EMP VALUES (:CODE%,:NAME$)
FOR I= 2 TO 100
    CODE = I
    NAME$ = "NAME" & I
    SQL_EXEC REEXECUTE
ENDFOR

; ---- The EMP table now contains
; ( 1, "NAME1")
; ( 2, "NAME2")
; ( 3, "NAME3")
; ...
; ( 99, "NAME99")
; (100, "NAME100")
```

TYPE_SQL_INSERT_BLOB%, TYPE_SQL_SELECT_BLOB% types for blobs

Enables management of binary large objects, larger than 32K but whose size remains limited by the DBMS.

Notes

1. Two new NCL data types have been added to NSDBMS.NCL and are to be declared in the Type_Var field of the NCLVAR structure:
 - **TYPE_SQL_INSERT_BLOB%**
 - **TYPE_SQL_SELECT_BLOB%**They are used for :
 - inserting a binary file into the database,
 - retrieving a binary file from the database
2. Images inserted with TYPE_SQL_INSERT_BLOB% are not limited in size.
3. Selection of images with TYPE_SQL_SELECT_BLOB% is limited by default to 1 Mb. However, this size may be changed using the NS_FUNCTION CHANGEOPTION TEXTSIZE instruction.
4. The cursor mode must be set on 3.

 For more informations, see NS_FUNCTION SETCURSORMODE.

Example

```
LOCAL NCLVAR HL[2]
LOCAL INT IMAGNO
LOCAL DESCRIP$
LOCAL FIMAGE$
LOCAL INT J
LOCAL SQL$
LOCAL BMP%
LOCAL CURSORMODE%
LOCAL Opt$
LOCAL Val%, i%
LOCAL CSTRING Req$(2000)

CURSORMODE% = DB_ODBC_CURSOR_BINDING ;3
SQL_EXEC NS_FUNCTION SETCURSORMODE :CURSORMODE%
```

```

SQL_EXEC DROP TABLE BIGIMAGE
IF SQL_ERROR% <> 0
    MESSAGE "Error ",SQL_ERRMSG$(SQL_ERROR%)
ENDIF
SQL_EXEC NS_FUNCTION Statement INTO :Req$
IF SQL_ERROR% <> 0
    MESSAGE "Error ",SQL_ERRMSG$(SQL_ERROR%)
ENDIF
Insert AT END Req$ TO LISTBOX1
; creation of the table
SQL_EXEC CREATE TABLE BIGIMAGE(NUMERO INTEGER, DESCRIPTION VARCHAR(255), \
COLIMAGE IMAGE)
IF SQL_ERROR% <> 0
    MESSAGE "Error ",SQL_ERRMSG$(SQL_ERROR%)
ENDIF
SQL_EXEC NS_FUNCTION Statement INTO :Req$
Insert AT END Req$ TO LISTBOX1

FILL @HL, SIZEOF HL, 0
FIMAGE$ = F_IMAGE
HL[0].PTR_VAR = @FIMAGE$
HL[0].TYPE_VAR = TYPE_SQL_INSERT_BLOB%
HL[0].SIZE_VAR = SIZEOF FIMAGE$

SQL$="INSERT INTO BIGIMAGE (NUMERO, DESCRIPTION, COLIMAGE) VALUES \
( 1,'This is a big picture > 32000 bytes', : )"
SQL_EXEC_LONGSTR @SQL$, @HL, DEFAULT_CURSOR
IF SQL_ERROR% <> 0
    MESSAGE "Error ",SQL$&&SQL_ERRMSG$(SQL_ERROR%)
ENDIF
SQL_EXEC NS_FUNCTION Statement INTO :Req$
Insert AT END Req$ TO LISTBOX1

; ---- SELECT with automatic writing in file EXTRACT.BMP
; ---- One & One column only in the SELECT clause , the IMAGE !!!!!
FILL @HL, SIZEOF HL, 0
FIMAGE$ = "C:\TEMP\EXTRACT.BMP"
FERASE FIMAGE$
HL[0].PTR_VAR = @FIMAGE$
HL[0].TYPE_VAR = TYPE_SQL_SELECT_BLOB%
HL[0].SIZE_VAR = SIZEOF FIMAGE$

SQL$="SELECT COLIMAGE INTO : FROM BIGIMAGE WHERE NUMERO = 1"
SQL_EXEC_LONGSTR @SQL$, @HL, DEFAULT_CURSOR

IF SQL_ERROR% <> 0
    MESSAGE "Error ",SQL$&&SQL_ERRMSG$(SQL_ERROR%)
ENDIF
SQL_EXEC NS_FUNCTION Statement INTO :Req$
Insert AT END Req$ TO LISTBOX1

; ---- Display of the picture
BMP% = CREATEBMP%(FIMAGE$)
MOVE BMP% TO BMPF

CURSORMODE% = DB_ODBC_CURSOR_DEFAULT ;0
SQL_EXEC NS_FUNCTION SETCURSORMODE :CURSORMODE%

```

See also

NSDBMS.NCL, SQL_ERROR%, SQL_ERRMSG\$, NS_FUNCTION IMAGEON,
NS_FUNCTION IMAGEOFF, NS_FUNCTION SETCURSORMODE

UPDATE, CURRENT clauses

Principle

1. **FOR UPDATE OF** is used to stop other users from modifying one or more columns for the duration of a transaction when they have been selected by a given user.

For example, in SQL pseudo code:

```
; ---- Select and lock the Col-list columns
SELECT ... WHERE ... FOR UPDATE OF Col-list
...
... SQL commands modifying contents of Col-list columns
...
; ---- End of transaction and unlock columns
; COMMIT or ROLLBACK
```

2. **WHERE CURRENT OF** is used to update a record which has been preceded by a SELECT command. This way, for this update command, no calculation of the cursor is required (evaluation of a Where-Clause) for the table, as the cursor is already on the record to update.

For example, in SQL pseudo code shows the use of the FOR UPDATE OF and WHERE CURRENT OF combination:

```
; ---- Select and lock
BEGIN TRANSACTION (NS_FUNCTION AUTOCOMMITOFF must be set)
SELECT COL1 FROM TABLE1 WHERE COL2 > 10 FOR UPDATE OF COL3
WHILE NOTFOUND% = FALSE
  ; ---- Already on the record to modify
  UPDATE TABLE1 SET COL3 = COL3 + 2 WHERE CURRENT OF
  ; ---- go to next record
  FETCH ...
ENDWHILE

; ---- End of transaction and unlock columns
; COMMIT or ROLLBACK
```

Use

1. When using the NSnnDB2x library, the commands are executed dynamically and use are based on the ODBC layer. Some SQL commands are not accessible by in *Transact SQL*, which is the case of the CURRENT OF clause
2. When using the NSnnODCx library, be sure to respect the following rules
 - You must be in a transaction before you can use **FOR UPDATE OF** or **WHERE CURRENT OF**.
 - The command selecting the record must be in the correct format, for example: SELECT ... WHERE ... **FOR UPDATE OF** Col-list in order to prevent other users from modifying the current record.

- When the modification is finished, the transaction must finish with a COMMIT or ROLLBACK, to remove the locks on the columns used.
- **FOR UPDATE** applies only to SELECT.
- **CURRENT OF** applies only to UPDATE or DELETE.

See also ODBC manuals documentation for more information about locking and transactions.

NS_FUNCTION extensions

The NS_FUNCTIONS correspond to new functionality developed by Nat System to extend database interface options.

The new functionalities can be accessed by the NCL language.


Some commands must be preceded compulsory by the keyword NS_FUNCTION:

Syntax SQL_EXEC NS_FUNCTION *command*

Note *command* is one of the commands described further on.

See also SQL_ERROR%, SQL_ERRMSG\$

NS_FUNCTION ANSIOFF, ANSION

 NS_FUNCTION ANSIOFF and ANSION have been created to bypass the following problem. The SQL_EXEC UPDATE ... WHERE ... command fix SQL_ERROR% to 0, even if there is no record.

In the ANSIOFF mode, if an UPDATE or DELETE statement does not affect any records, no errors are returned.

In the ANSION mode, if an UPDATE or DELETE statement does not affect any records, an error (warning) is returned with the code "100".

Syntax **NS_FUNCTION ANSIOFF**
 and
 NS_FUNCTION ANSION

Notes

1. ANSIOFF is the default mode.
2. SQL_ERROR% enables you to retrieve the warning returned.

Example

```
; ---- ANSIOFF mode by default
SQL_EXEC DELETE ... WHERE ...
; ---- even if no record has been removed, SQL_ERROR% equals zero.

; ---- ANSION mode
SQL_EXEC NS_FUNCTION ANSION
SQL_EXEC UPDATE ... WHERE ...
IF SQL_ERROR% = 100
    MESSAGE "No record updated", \
           SQL_ERROR% && SQL_ERRMSG$(SQL_ERROR%)
ENDIF

; ---- Return to default mode
SQL_EXEC NS_FUNCTION ANSIOFF
```

See also SQL_ERROR%, SQL_ERRMSG\$

NS_FUNCTION AUTOCOMMITOFF, AUTOCOMMITON


In AUTOCOMMITON mode, an implicit COMMIT command is automatically executed after each SQL command.

AUTOCOMMITOFF inactivates this mode.

Syntax **NS_FUNCTION AUTOCOMMITOFF**
 and
 NS_FUNCTION AUTOCOMMITON

Notes

1. AUTOCOMMITON is the default mode.
2. SQL_ERROR% can be used to verify the status of the AUTOCOMMITON or AUTOCOMMITOFF call.
3. After each SQL statement, or group of statements, a COMMIT or ROLLBACK must be executed to confirm or cancel the sequence.
4. The notion of "transactions" becomes operational once AUTOCOMMITOFF has been executed. After each COMMIT or ROLLBACK, a new transaction is started.

5.  Others drivers don't support this command.

Example

```
; start transactional mode
SQL_EXEC NS_FUNCTION AUTOCOMMITOFF
IF SQL_ERROR% <> 0
    MESSAGE "Problème NS_FUNCTION AUTOCOMMITOFF", \
           SQL_ERROR% && SQL_ERRMSG$(SQL_ERROR%)
ENDIF
SQL_EXEC INSERT ....
SQL_EXEC INSERT ....
SQL_EXEC INSERT ....
SQL_EXEC INSERT ....

; All INSERTs will be canceled
SQL_EXEC ROLLBACK
; end transactional mode
SQL_EXEC NS_FUNCTION AUTOCOMMITON
IF SQL_ERROR% <> 0
    MESSAGE "NS_FUNCTION AUTOCOMMITOFF Error", \
           SQL_ERROR% && SQL_ERRMSG$(SQL_ERROR%)
ENDIF
SQL_EXEC INSERT ....
; The INSERT is not canceled because the ROLLBACK
; does not have any effect outside of a transaction
SQL_EXEC ROLLBACK
```

See also SQL_ERROR%, SQL_ERRMSG\$

NS_FUNCTION CALLBACK

This function allows to reroute the error's messages of DB2 towards a window. Every time an error message appears, DB2 send an event to a window.

Lets you set up centralized management of errors for your application. You no longer need to call SQL_ERROR% and SQL_ERRMSG\$ after every command.

Syntax **NS_FUNCTION CALLBACK** :*window-handle*,:*user-event*

Parameters	<i>window-handle</i>	INT(4)	I	window handle
	<i>user-event</i>	INT(4)	I	user event (USER0 - USER15)

Notes

1. In UNIX, *window-handle* must use the NAT SYSTEM handle of the window that will receive a notification each time an error occurs.
2. For all other targets, *window-handle* must be assigned using the NCL GETCLIENTHWND%(...) function which receives as input the NAT SYSTEM handle of the window that will receive a notification each time an error occurs.
3. To determine the processing carried out, you must program the user event. To obtain the notification of the event in *user-event* must contain 0 for USER0, 1 for USER1,.... or 15 for USER15.
4. To cancel this function, set the window handle to zero.
5. Errors and warnings from the DBMS database being used are returned in their native, proprietary format (see the NSDBMS.NCL file for more information about these formats.)

```
SEGMENT DB_ODBC_CLIENT_STRUCT
  INT   errtype(4)
  INT   severity(4)
  CHAR  sqlstate(6)
  INT   msgCode(4)
  INT   nativeCode(4)
  CHAR  msgString(513)
  INT   msgStringLength(2)
ENDSEGMENT
```

6. The type of the error's message is sent to PARAM12%. The handle of the structure is sent to PARAM34%.

Example

```

; -----
; In the INIT event of the MAIN window
; -----
Global HDLE_CATCHERR%

; -----
; In the TERMINATE event of the MAIN window
; -----
IF HDLE_CATCHERR% <> 0
    CLOSE HDLE_CATCHERR%
    HDLE_CATCHERR%=0
ENDIF

; -----
; In the SELECTED event of the CKCALLBACK checkbox
; (input field to 0) of the MAIN window
; -----
LOCAL USER_EVENT%
LOCAL WINDOW_HANDLE%

IF CKCALLBACK = CHECKED%

    ; ---- Activate the handling error's mode

    IF HDLE_CATCHERR% = 0
        OPEN CATCHERR,0,HDLE_CATCHERR%    ; Window where will be centralized the ou
                                           ; errors
    ENDIF
    MOVE GETCLIENTHWNDC(HDLE_CATCHERR%) TO WINDOW_HANDLE%
    MOVE 1                                TO USER_EVENT%
    SQL_EXEC NS_FUNCTION CALLBACK :WINDOW_HANDLE%, :USER_EVENT%
    MESSAGE "START CALLBACK" && WINDOW_HANDLE% && USER_EVENT%,\
        SQL_ERROR% && SQL_ERRMSG$(SQL_ERROR%)
ELSE
    ; ---- Deactivate the handling error's mode centralized by CALLBACK

    MOVE 0 TO WINDOW_HANDLE%
    MOVE 1 TO USER_EVENT%
    SQL_EXEC NS_FUNCTION CALLBACK :WINDOW_HANDLE%, :USER_EVENT%
    MESSAGE "STOP CALLBACK" && WINDOW_HANDLE% && USER_EVENT%,\
        SQL_ERROR% && SQL_ERRMSG$(SQL_ERROR%)
    IF HDLE_CATCHERR% <> 0
        CLOSE HDLE_CATCHERR%
        HDLE_CATCHERR%=0
    ENDIF
ENDIF

; -----
; In the USER1 event of the CATCHERR window
; -----
; WARNING ! This example is for ODBC, because each DBMS has its own structure
; of error's handling

; ---- Definitions contained in NSDBMS.NCL
; CONST CLIENTMSG 1
; CONST SERVERMSG 2
;
; SEGMENT DB_ODBC_CLIENT_STRUCT
; INT          ERRTYPE(4)          ; Level of error's severity
; INT          SEVERITY(4)         ; Severity of the error
; CHAR         SQLSTATE(6)         ; SqlState
; INT          MSGCODE(4)          ; Code of ODBC error
; INT          NATIVECODE(4)       ; Code of driver's error
; CHAR         MSGSTRING(513)     ; Error message

```

```
; INT          MSGSTRINGLEN(2) ; Length of the error's message
;ENDSEGMENT

LOCAL MESSAGE% (4)
LOCAL PTR% (4)
LOCAL RDB$
RDB$ = SQL_GETNAME$
MOVE PARAM12% TO MESSAGE%
MOVE PARAM34% TO PTR%

IF MESSAGE% = CLIENTMSG
  EVALUATE DB_ODBC_CLIENT_STRUCT(PTR%).SEVERITY
  WHERE DB_ODBC_ERROR_WARNING
    INSERT AT END "WARNING : +" &DB_ODBC_CLIENT_STRUCT(PTR%).nativeCode TO SELF%
  ENDWHERE
  WHERE DB_ODBC_ERROR_ERROR
    INSERT AT END "ERROR : -" &DB_ODBC_CLIENT_STRUCT(PTR%).nativeCode TO SELF%
  ENDWHERE
ENDEVALUATE
IF (DB_ODBC_CLIENT_STRUCT(PTR%).MSGSTRINGLEN > 0)
  INSERT AT END "MSGSTRING " & DB_ODBC_CLIENT_STRUCT(PTR%).MSGSTRING TO self%
ENDIF
ELSE
  INSERT AT END "MESSAGE TYPE UNKNOWN" TO SELF%
ENDIF
```

See also NSDBMS.NCL, SQL_ERROR%, SQL_ERRMSG\$, NS_FUNCTION
 ERRORCOUNT, NS_FUNCTION GETERROR

NS_FUNCTION CHANGEDBCNTX

Sets the current database.



This function has been developed to manage several databases simultaneously.



To move from one database to another, we recommend using the command NS_FUNCTION CHANGEDBCNTX. It is likely that the AT command will not be supported in future versions.

Syntax **NS_FUNCTION CHANGEDBCNTX** : *logical-DBname*

Parameter *logical-DBname* CSTRING I logical name of the current database

Notes

1. The database specified in *logical-DBname* will become the current database.
2. If the specified database is invalid, the current database will not change.
3. If the SQL_OPENCURSOR command is called after NS_FUNCTION CHANGEDBCNTX, the new cursor will be associated with the database passed as an argument to this function.

Example

```
LOCAL LOGICALDBNAME$
SQL_OPEN "BASE1", "SCOTT/TIGER@SERVICE1"
SQL_EXEC .... ; BASE1 is the current database

SQL_OPEN "BASE2", "SCOTT/TIGER@SERVICE2"
SQL_EXEC .... ; BASE2 is the current database

LOGICALDBNAME$ = "BASE1"
SQL_EXEC NS_FUNCTION CHANGEDBCNTX :LOGICALDBNAME$
SQL_EXEC .... ; BASE1 is the current database
SQL_CLOSE "BASE1"
SQL_EXEC .... ; BASE2 is the current database

SQL_CLOSE "BASE2"
```

See also SQL_OPEN, SQL_CLOSE, AT, SQL_ERROR%, SQL_ERRMSG\$, SQL_EXEC

NS_FUNCTION CHANGEOPTION

Modifies the timeout for a SELECT statement or login.

Syntax **NS_FUNCTION CHANGEOPTION** *:parameter, :option*

Parameters	<i>parameter</i>	CSTRING	I	parameter to modify
	<i>option</i>	INT(4)	I	value to assign to the parameter

Notes

1. The *option* variable contains the TIMEOUT value in seconds. If an SQL statement fails, the DBMS will send a message when the timeout period specified by this variable expires. This feature can be useful when searching large databases.
2. The default value of the *option* variable is 120 seconds and the minimum value is 0.

Example

```
LOCAL TMPS%
LOCAL PARAMETRE$

MOVE 30          TO TMPS%
MOVE "TIMEOUT" TO PARAMETRE$

SQL_EXEC NS_FUNCTION CHANGEOPTION :PARAMETRE$, :TMPS%
SQL_EXEC SELECT * FROM TABLE
IF SQL_ERROR% <> 0
    MESSAGE "ERROR", SQL_ERRMSG$(SQL_ERROR%)
    ; on se retrouve ici si la requête dépasse 30 secondes
    ; pour s'exécuter
ENDIF
```

NS_FUNCTION CHARTOHEXAOFF, CHARTOHEXAON


The CHARTOHEXAON mode involves the automatic conversion into hexadecimal of the content of IN host chains of STRING or CSTRING type.

IN variables encompass variables of the WHERE clause for queries and the IN parameters for stored procedures.

The CHARTOHEXAOFF processes the host variable as a character string.

Syntax **NS_FUNCTION CHARTOHEXAOFF**
 and
 NS_FUNCTION CHARTOHEXAON

Notes

1. CHARTOHEXAOFF is the active mode by default.
2. In the CHARTOHEXAON mode, BINARY or VARBINARY types are recognized by analyzing the contents of STRING or CSTRING parameters. If the character string begins with 0x, then it is considered to contain a binary value.
3. Strains on the contents of STRING or CSTRING variables:
 - The first two characters must be "0x" or "0X".
 - The remaining characters must be in the range [0-9] or [A-F].
 - The number of characters must be even.
4.  In CHARTOHEXAON mode, the insertion in the column of the following string '0x11FF' is truncated : '0x11'.

Example


```
SQL_EXEC NS_FUNCTION CHARTOHEXAON
...
MOVE '0x11FF' TO A$
SELECT * FROM TABLE WHERE coll = :A$
; is considered as a SELECT * FROM TABLE WHERE coll = 0x11FF
SQL_EXEC NS_FUNCTION Statement INTO :Req$
Insert AT END Req$ TO LISTBOX1
; result of NS_FUNCTION Statement SELECT * FROM TABLE WHERE coll = 0x11FF
; return to the active mode by default
SQL_EXEC NS_FUNCTION CHARTOHEXAOFF
SELECT * FROM TABLE WHERE coll = :A$
```

```
SQL_EXEC NS_FUNCTION Statement INTO :Req$  
Insert AT END Req$ TO LISTBOX1  
; result of NS_FUNCTION Statement SELECT * FROM TABLE WHERE coll = 'Ox11FF'  
; 'Ox11FF' is considered as a string not as an Hexadecimal value
```

See also SQL_ERROR%, SQL_ERRMSG\$

NS_FUNCTION CLEANFLOATVALUES

Enables the conversion of the format of floating values.

 This function was developed to work round the conversion by DATACOM databases of 0.01 into 1^e-002 instead of 1^e-2.

Syntax **CLEANFLOATVALUES**

Note

1. This function is used exclusively with DATACOM databases which rejects numbers with more than two superior figures.

Example

```
; odbc driver transforms 0.01 into 1e-002 instead of 1e-2
; to trim the leading 00 after the exponent sign use the following NS-FUNCTION
; this is useful with some odbc drivers
Sql_EXEC NS_FUNCTION CleanFloatValues
value# = 0.01
Sql_EXEC insert into table_float (col_float) values (:value#)
IF SQL_ERROR% <> 0
    MESSAGE "Error ",SQL_ERRMSG$(SQL_ERROR%)
ENDIF
```

NS_FUNCTION ERRORCOUNT

Retrieves the number of errors or error messages encountered while executing a query. Message numbers start from 0.

Syntax	NS_FUNCTION ERRORCOUNT INTO : <i>nbr-errors</i>			
Parameter	<i>nbr-errors</i>	INT(4)	I/O	number of errors encountered while executing a query

Example

```
LOCAL ERRORCOUNT%  
  
SQL_EXEC NS_FUNCTION ERRORCOUNT INTO :ERRORCOUNT%  
...  
...  
MESSAGE "NUMBER OF ERRORS",ERRORCOUNT%
```

See also	NS_FUNCTION GETERROR, SQL_ERROR%, SQL_ERRMSG\$, NS_FUNCTION CALLBACK
-----------------	--

NS_FUNCTION GETCOLUMN

Retrieves the list of columns for a specified object or for all the objects in the database.

Syntax	NS_FUNCTION GETCOLUMN <i>:object-name, :owner-name, :column-name</i>		
Parameters	<i>object-name</i>	CSTRING I	object name (table or other)
	<i>owner-name</i>	CSTRING I	name of the object's owner
	<i>column-name</i>	CSTRING I	column name used by <i>object-name</i>

Notes

1. The parameters passed to NS_FUNCTION GETCOLUMN can be left blank, in which case it assumes that you require all the columns for all the objects in the database.
2. Data is retrieved by executing a FETCH INTO statement that must contain the following items in the order shown:

:TABLE_QUALIFIER\$(129)	ID of the object qualifier
:TABLE_OWNER\$(129)	Owner of the object
:TABLE_NAME\$(129)	Object name
:COLUMN_NAME\$(129)	Column name
:DATA_TYPE%(2)	Column type
:TYPE_NAME\$(129)	Name of the column type
:PRECISION%	Column precision
:LENGTH%	Column length
:SCALE%(2)	Column dimension
:RADIX%(2)	Column radix
:NULLABLE%(2)	0=not null, 1=null, 2= unknown
:REMARKS\$(255)	Column description

Example

```
LOCAL OBJECT_NAME$, OWNER_NAME$, REF_NAME$
LOCAL TABLE_QUALIFIER$(129), TABLE_OWNER$(129), TABLE_NAME$(129),
COLUMN_NAME$(129), DATA_TYPE%(2)
LOCAL TYPE_NAME$(129), PRECISION%, LENGTH%, SCALE%(2), RADIX%(2), NULLABLE%(2),
REMARKS$
sql_init 'NS02DB26'
```

```

if sql_error% <> 0
    message 'error' , sql_errmsg$(sql_error%)
endif
sql_open 'MyDataB', ' Scott/tiger@pubs '
if sql_error% <> 0
    message 'error' , sql_errmsg$(sql_error%)
endif

OBJECT_NAME$ =EF_TABLE ;''
OWNER_NAME$ =EF_OWNER ;' dbo '
REF_NAME$ = EF_COLUMN ;''

SQL_EXEC NS_FUNCTION GETCOLUMN :OBJECT_NAME$, :OWNER_NAME$, :REF_NAME$
if sql_error% <> 0
    message 'error GETCOLUMN' , sql_errmsg$(sql_error%)
endif

; retrieving data
SQL_EXEC FETCH INTO :TABLE_QUALIFIER$, :TABLE_OWNER$, :TABLE_NAME$,
:COLUMN_NAME$, :DATA_TYPE$, \
:TYPE_NAME$, :PRECISION%, :LENGTH%, :SCALE%, :RADIX%, :NULLABLE%, :REMARKS$
if sql_error% <> 0
    message 'error FETCH' , sql_errmsg$(sql_error%)
endif
WHILE SQL_ERROR% = 0
; always blank
    INSERT AT END "TABLE_QUALIFIER"&&TABLE_QUALIFIER$ TO LISTBOX1
    INSERT AT END "TABLE_OWNER"&&TABLE_OWNER$ TO LISTBOX1
    INSERT AT END "TABLE_NAME"&&TABLE_NAME$ TO LISTBOX1
    INSERT AT END "COLUMN_NAME"&&COLUMN_NAME$ TO LISTBOX1
    INSERT AT END "DATA_TYPE"&&DATA_TYPE$ TO LISTBOX1
    INSERT AT END "TYPE_NAME"&&TYPE_NAME$ TO LISTBOX1
    INSERT AT END "PRECISION"&&PRECISION% TO LISTBOX1
    INSERT AT END "LENGTH"&&LENGTH% TO LISTBOX1
    INSERT AT END "SCALE"&&SCALE% TO LISTBOX1
    INSERT AT END "RADIX"&&RADIX% TO LISTBOX1
    INSERT AT END "NULLABLE"&&NULLABLE% TO LISTBOX1
    INSERT AT END "REMARKS"&&REMARKS$ TO LISTBOX1
    SQL_EXEC FETCH INTO :TABLE_QUALIFIER$, :TABLE_OWNER$, :TABLE_NAME$,
:COLUMN_NAME$, :DATA_TYPE$, \
:TYPE_NAME$, :PRECISION%, :LENGTH%, :SCALE%, :RADIX%, :NULLABLE%, :REMARKS$
ENDWHILE

```

See also NS_FUNCTION GETINDEXCOLUMN

NS_FUNCTION GETCURRENTDBCNTX

Returns the logical name of the current database.

Syntax **NS_FUNCTION GETCURRENTDBCNTX INTO** *:logical-DBname*

Parameter *logical-DBname* CSTRING O logical database name

Note

1. *logical-DBname* was passed as the first parameter to the SQL_OPEN statement used to open the database.

Example

```
Local dbname$
Local open$

LOCAL HSqlServer%, hodb%

SETPTR GETSPTR%(SPTR_WAIT%) ; The mouse pointer is changed to
hodb% = SQL_INITMULTIPLE% ('NS02ODC3')
if sql_error% <> 0
    message 'error' , sql_errmsg$(sql_error%)
endif
open$= 'aelta'
sql_open open$, 'aelta/aelta@Pubs'
if sql_error% < 0
    message 'open' , sql_errmsg$(sql_error%)
endif

HSqlServer% = SQL_INITMULTIPLE% ('NS02MS2K')
if sql_error% <> 0
    message 'error' , sql_errmsg$(sql_error%)
endif
sql_open "pubs", "aelta/aelta@aelta\ADVW135"
if sql_error% < 0
    message 'open'&&sql_error% , sql_errmsg$(sql_error%)
endif
sql_use hodb%
INSERT AT END SQL_GETNAME$&&SQL_VERSION$ TO LISTBOX1
if sql_error% <> 0
    message 'error' , sql_errmsg$(sql_error%)
endif
sql_exec NS_FUNCTION GETCURRENTDBCNTX into :dbname$
if sql_error% <> 0
    message 'error' , sql_errmsg$(sql_error%)&&sql_error%
endif
INSERT AT END "GETCURRENTDBCNTX gives the logical name"&&dbname$ TO LISTBOX1
; gives aelta
SETPTR GETSPTR%(SPTR_ARROW%) ; sql_use
```

See also SQL_OPEN, SQL_CLOSE, NS_FUNCTION GETDBNAME

NS_FUNCTION GETDBNAME

Retrieves the physical name of the current database.

Syntax **NS_FUNCTION GETDBNAME INTO** : *physical-DBname*

Parameter *physical-DBname* CSTRING I/O physical name of the current database

Example

```
LOCAL DBNAME$,DBNAME2$

SQL_OPEN "BASE1",'SCOTT/TIGER@MYACCESS'
SQL_OPEN "BASE2",'SCOTT/TIGER@MYDB2'

IF SQL_ERROR% = 0
    SQL_EXEC NS_FUNCTION GETDBNAME INTO :DBNAME2$
    MESSAGE "THE CURRENT DATABASE IS :",DBNAME2$
    ;DBNAME2$ gives the physical name of Base2 for ex. ;C:\TEST\SAMPLE.MDB
ELSE
    MESSAGE "Access error to the database"
ENDIF

IF SQL_ERROR% = 0
    SQL_EXEC AT BASE1 NS_FUNCTION GETDBNAME INTO :DBNAME$
    MESSAGE "THE CURRENT DATABASE IS :",DBNAME$
    ; DBNAME$ gives the physical name of Base2 for ex. TESTDB2
ELSE
    MESSAGE "Access error to the database"
ENDIF
```

See also SQL_OPEN, SQL_CLOSE, NS_FUNCTION GETDBNAME

NS_FUNCTION GETERROR

Retrieves an error code based on its occurrence in the error list. Error numbers lie between 0 and the value returned by NS_FUNCTION ERRORCOUNT minus one.

Syntax **NS_FUNCTION GETERROR** *error-index%* **INTO** *error-nbr%*

Parameters	<i>error-index%</i>	INT(4)	I	index of the error number
	<i>error-nbr%</i>	INT(4)	O	error number

Example

```
LOCAL I%,ROW_COUNT%, ERROR%

MOVE 0 TO ROW_COUNT%

; Retrieve the number of errors in ROW_COUNT%
SQL_EXEC NS_FUNCTION ERRORCOUNT INTO :ROW_COUNT%

IF ROW_COUNT% <> 0
  MOVE 0 TO I%
  WHILE I% < ROW_COUNT%
    SQL_EXEC NS_FUNCTION GETERROR :I% INTO :ERROR%
    ; Retrieve for each error its number in ERROR%
    MESSAGE "ERROR" && I%,SQL_ERRMSG$(ERROR%)
    MOVE I%+1 TO I%
  ENDWHILE
ENDIF
```

See also NS_FUNCTION ERRORCOUNT

NS_FUNCTION GETINDEXCOLUMN



NS_FUNCTION GETINDEXCOLUMN does not work with ODBC databases.

Retrieves the list of index columns for a specified object or for all the objects in the database.



This function was developed to cope with the following problem: by clicking on the index in the window "Database catalog" (when it displays the primary keys), an error message is obtained.

Syntax **NS_FUNCTION GETINDEXCOLUMN** : *object-name*, :*owner-name*

Parameters	<i>object-name</i>	CSTRING I	object name (table or other)
	<i>owner-name</i>	CSTRING I	name of the object's owner

Notes

1. The parameters passed to NS_FUNCTION GETINDEXCOLUMN can be left blank, in which case it assumes that you require all the index columns for all the objects in the database.
2. Data is retrieved by executing a FETCH INTO statement that must contain the following items in the order shown:

:TABLE_QUALIFIER\$(129)	ID of the object qualifier
:TABLE_OWNER\$(129)	Owner of the object
:TABLE_NAME\$(129)	Object name
:NON_UNIQUE%(2)	1 = non-unique, 0 = unique
:INDEX_QUALIFIER\$(129)	ID of the index qualifier
:INDEX_NAME\$(129)	Index name
:TYPE%(2)	0=STAT, 1=CLUSTER, 2=HASH, 3=other
:SEQ_IN_INDEX%(2)	Column sequence number in the index (starts from 1)
:COLUMN_NAME\$(129)	Column name
:COLLATION\$(2)	A = Ascending, D = Descending
:CARDINALITY%	Cardinality of the table or index
:PAGES%	Number of pages for the index
:FILTER_CONDITION\$(129)	Filter condition for the index

Example

```
SQL_EXEC NS_FUNCTION GETINDEXCOLUMN :OBJECT_NAME$, :OWNER_NAME$

; Retrieving data
SQL_EXEC FETCH INTO :TABLE_QUALIFIER$, :TABLE_OWNER$,      \
                    :TABLE_NAME$, :NON_UNIQUE$,            \
                    :INDEX_QUALIFIER$, :INDEX_NAME$,        \
                    :TYPE$, :SEQ_IN_INDEX$, :COLUMN_NAME$, \
                    :COLLATION$, :CARDINALITY$, :PAGES$,    \
                    :FILTER_CONDITION$
```

See also

NS_FUNCTION GETCOLUMN

NS_FUNCTION GETINFO

Returns information about the ODBC drivers.

Syntax **NS_FUNCTION GETINFO** :infotype , :value

Parameters	<i>infotype</i>	INT(4)	I	Type of information
	<i>value</i>	INT(2)/INT(4)/CSTRING	I	Result buffer

Notes



The *value* parameter depends on the *infotype* parameter.



See the NSODBC.NCL file for more information about the available *infotype*.

Example

```
LOCAL INFOTYPE%
LOCAL VALUE$
;A character string with the name of the DBMS product accessed by the driver.
INFOTYPE% = DB_ODBC_DBMS_NAME
SQL_EXEC NS_FUNCTION GETINFO :INFOTYPE%, :VALUE$
IF SQL_ERROR% <> 0
  MESSAGE "Error " && SQL_ERROR% , SQL_ERRMSG$(SQL_ERROR%)
ENDIF
INSERT AT END 'DBMS Name '&& VALUE$ TO LISTBOX1

;A character string indicating the version of the DBMS product accessed by the
;driver.
INFOTYPE% = DB_ODBC_DBMS_VER
SQL_EXEC NS_FUNCTION GETINFO :INFOTYPE%, :VALUE$
IF SQL_ERROR% <> 0
  MESSAGE "Error " && SQL_ERROR% , SQL_ERRMSG$(SQL_ERROR%)
ENDIF
INSERT AT END 'DBMS Version '&& VALUE$ TO LISTBOX1

INFOTYPE% = DB_ODBC_DATABASE_NAME
;A character string with the name of the current database in use, if the data
;source defines a named object called "database."Note In ODBC 2.0, this value
;of fInfoType has been replaced by the DB_ODBC_CURRENT_QUALIFIER connection
;option.
SQL_EXEC NS_FUNCTION GETINFO :INFOTYPE%, :VALUE$
IF SQL_ERROR% <> 0
  MESSAGE "Error " && SQL_ERROR% , SQL_ERRMSG$(SQL_ERROR%)
ENDIF
INSERT AT END 'DATABASE Name '&& VALUE$ TO LISTBOX1

;A character string with the data source name used during connection. If the
```

```
;application called SQLConnect, this is the value of the szDSN argument.  
INFOTYPE% = DB_ODBC_DATA_SOURCE_NAME  
SQL_EXEC NS_FUNCTION GETINFO :INFOTYPE%, :VALUE$  
IF SQL_ERROR% <> 0  
    MESSAGE "Error " && SQL_ERROR% , SQL_ERRMSG$(SQL_ERROR%)  
ENDIF  
INSERT AT END 'DATA SOURCE Name '&& VALUE$ TO LISTBOX1
```

See also SQL_ERROR%, SQL_ERRMSG\$, NSODBC.NCL

NS_FUNCTION GETPRIMARYKEY

Retrieves the columns that form the primary key for an object or for all the objects in the database.

Syntax	NS_FUNCTION GETPRIMARYKEY : <i>object-name</i> , : <i>owner-name</i>		
Parameters	<i>object-name</i>	CSTRING I	object name (table or other)
	<i>owner-name</i>	CSTRING I	name of the object's owner

Notes

1. The parameters passed to NS_FUNCTION GETPRIMARYKEY can be left blank, in which case it assumes that you require the primary keys for all the objects in the database.



2. It is necessary to create a primary key correctly. An index is not a primary key by default.

```
SQL_EXEC CREATE TABLE EMP ( \
    EMPNO INTEGER NOT NULL PRIMARY KEY, \
    ENAME CHAR(25) )
```

3. The primary key must be integrated to the COLUMN_NAME\$ column.
4. Data is retrieved by executing a FETCH INTO statement that must contain the following items:

:TABLE_QUALIFIER\$(129)	ID of the object qualifier
:TABLE_OWNER\$(129)	Owner of the object
:TABLE_NAME\$(129)	Object name
:COLUMN_NAME\$(129)	Column name
:KEY_SEQ%(2)	Column sequence number in the primary key
:PK_NAME\$(129)	ID of the column qualifier

Example 1

```
SQL_EXEC NS_FUNCTION GETPRIMARYKEY :OBJECT_NAME$, :OWNER_NAME$

; Retrieving data
SQL_EXEC FETCH INTO :TABLE_QUALIFIER$, :TABLE_OWNER$, \
    :TABLE_NAME$, :COLUMN_NAME$, \
    :KEY_SEQ%(2), :PK_NAME$
```

Example 2

```
; Creation
sql_exec drop table EMP
if sql_error% <> 0
    message 'error drop' , sql_errmsg$(sql_error%)
endif
```

```

SQL_EXEC CREATE TABLE EMP ( \
    EMPNO INTEGER NOT NULL PRIMARY KEY, \
    ENAME CHAR(25))
if sql_error% <> 0
    message 'error create' , sql_errmsg$(sql_error%)
endif

;then GETPRIMARYKEY

LOCAL OBJECT_NAME$, OWNER_NAME$, REF_NAME$
LOCAL TABLE_QUALIFIER$(129), TABLE_OWNER$(129), TABLE_NAME$(129)
LOCAL COLUMN_NAME$(129), KEY_SEQ$(2), PK_NAME$(129)
OBJECT_NAME$ = 'EMP'
OWNER_NAME$ = 'Scott'

SQL_EXEC NS_FUNCTION GETPRIMARYKEY :OBJECT_NAME$, :OWNER_NAME$
if sql_error% <> 0
    message 'error GETPRIMARYKEY' , sql_error%&&sql_errmsg$(sql_error%)
endif

; retrieving data
SQL_EXEC FETCH INTO :TABLE_QUALIFIER$, :TABLE_OWNER$, :TABLE_NAME$,
:COLUMN_NAME$, KEY_SEQ$, :PK_NAME$
if sql_error% <> 0
    message 'error FETCH' , sql_error%&&sql_errmsg$(sql_error%)
endif
ENDIF
WHILE SQL_ERROR% = 0
    INSERT AT END "TABLE_QUALIFIER$" && TABLE_QUALIFIER$ TO LISTBOX1
    INSERT AT END "TABLE_OWNER$" && TABLE_OWNER$ TO LISTBOX1
    INSERT AT END "TABLE_NAME$" && TABLE_NAME$ TO LISTBOX1
    INSERT AT END "COLUMN_NAME$" && COLUMN_NAME$ TO LISTBOX1
    INSERT AT END "KEY_SEQ$" && KEY_SEQ$ TO LISTBOX1
    INSERT AT END "PK_NAME$" && PK_NAME$ TO LISTBOX1
    SQL_EXEC FETCH INTO :TABLE_QUALIFIER$, :TABLE_OWNER$, :TABLE_NAME$,
    :COLUMN_NAME$, KEY_SEQ$, :PK_NAME$
ENDWHILE

;and we retrieve the key COLUMN_NAME$

```

See also

NS_FUNCTION GETCOLUMN, NS_FUNCTION GETINDEXCOLUMN

NS_FUNCTION GETPROCEDURE

Retrieves the list of stored procedures and functions, if the DATA SOURCE supports these features.

Syntax **NS_FUNCTION GETPROCEDURE**

Notes

1. Data is retrieved by executing a FETCH INTO statement that must contain the following items in the order shown:

:PROCEDURE_QUALIFIER\$(129)	ID of the procedure qualifier
:PROCEDURE_OWNER\$(129)	Owner of the procedure
:PROCEDURE_NAME\$(129)	Procedure name
:NUM_INPUT_PARAMS%	Reserved
:NUM_OUPUT_PARAM%	Reserved
:NUM_RESULT_SETS%	Reserved
:REMARK\$(129)	Description of the procedure
:PROCEDURE_TYPE%(2)	0=unknown, 1=procedure, 2=function

Example

```
SQL_EXEC NS_FUNCTION GETPROCEDURE
; Retrieving data
SQL_EXEC FETCH INTO :PROCEDURE_QUALIFIER$, :PROCEDURE_OWNER$, \
                   :PROCEDURE_NAME$, :NUM_INPUT_PARAMS%, \
                   :NUM_OUPUT_PARAM%, :NUM_RESULT_SETS%, \
                   :REMARK$, :PROCEDURE_TYPE%
```

See also **NS_FUNCTION GETPROCEDURECOLUMN**

NS_FUNCTION GETPROCEDURECOLUMN

Retrieves the list of parameters for a specified procedure or for all procedures.

Syntax	NS_FUNCTION GETPROCEDURECOLUMN <i>:object-name, :owner-name, :parameter-name</i>		
Parameters	<i>object-name</i>	CSTRING I	procedure name
	<i>owner-name</i>	CSTRING I	owner name
	<i>parameter-name</i>	CSTRING I	parameter name used by <i>object-name</i>

Notes

1. The parameters passed to NS_FUNCTION GETPROCEDURECOLUMN can be left blank, in which case it assumes that you require all the parameters for all the procedures in the database.

2. Data is retrieved by executing a FETCH INTO statement that must contain the following items:

:PROCEDURE_QUALIFIER\$(129)	ID of the procedure qualifier
:PROCEDURE_OWNER\$(129)	Owner of the procedure
:PROCEDURE_NAME\$(129)	Procedure name
:COLUMN_NAME\$(129)	Procedure parameter name
:COLUMN_TYPE%(2)	0 = unknown, 1 = input parameter 2 = input/output parameter, 3 = output parameter, 4 = return code
:DATA_TYPE%(2)	Parameter type
:TYPE_NAME\$(129)	Type name
:PRECISION%	Parameter precision
:LENGTH%	Parameter length
:SCALE%(2)	Parameter's dimension
:RADIX%(2)	Parameter's radix
:NULLABLE%(2)	0 = not null, 1 = null, 2 = unknown
:REMARK\$(255)	Parameter description

Example

```
LOCAL OBJECT_NAME$, OWNER_NAME$, REF_NAME$
LOCAL PROCEDURE_QUALIFIER$(129), PROCEDURE_OWNER$(129), PROCEDURE_NAME$(129),
COLUMN_NAME$(129), COLUMN_TYPE%(2), DATA_TYPE%(2)
LOCAL TYPE_NAME$(129), PRECISION%, LENGTH%, SCALE%(2), RADIX%(2), NULLABLE%(2),
REMARKS$
OBJECT_NAME$ =EF_TABLE
OWNER_NAME$ =EF_OWNER
REF_NAME$ = EF_COLUMN

SQL_EXEC NS_FUNCTION GETPROCEDURECOLUMN :OBJECT_NAME$, :OWNER_NAME$, :REF_NAME$
if sql_error% <> 0
    message 'error GETPROCEDURECOLUMN' , sql_errmsg$(sql_error%)
endif

; Retrieving data
SQL_EXEC FETCH INTO :PROCEDURE_QUALIFIER$, :PROCEDURE_OWNER$, :PROCEDURE_NAME$,
:COLUMN_NAME$, :COLUMN_TYPE%, :DATA_TYPE%,\
:TYPE_NAME$, :PRECISION%, :LENGTH%, :SCALE%, :RADIX%, :NULLABLE%, :REMARKS$
if sql_error% <> 0
    message 'error FETCH' , sql_errmsg$(sql_error%)
endif
WHILE SQL_ERROR% = 0
; always blank
INSERT AT END "PROCEDURE_QUALIFIER$"&&PROCEDURE_QUALIFIER$ TO LISTBOX1
INSERT AT END "PROCEDURE_OWNER$"&&PROCEDURE_OWNER$ TO LISTBOX1
INSERT AT END "PROCEDURE_NAME$"&&PROCEDURE_NAME$ TO LISTBOX1
INSERT AT END "COLUMN_NAME$"&&COLUMN_NAME$ TO LISTBOX1
INSERT AT END "COLUMN_TYPE$"&&COLUMN_TYPE% TO LISTBOX1
INSERT AT END "DATA_TYPE$"&&DATA_TYPE% TO LISTBOX1
INSERT AT END "TYPE_NAME$"&&TYPE_NAME$ TO LISTBOX1
INSERT AT END "PRECISION$"&&PRECISION% TO LISTBOX1
INSERT AT END "LENGTH$"&&LENGTH% TO LISTBOX1
INSERT AT END "SCALE$"&&SCALE% TO LISTBOX1
INSERT AT END "RADIX$"&&RADIX% TO LISTBOX1
INSERT AT END "NULLABLE$"&&NULLABLE% TO LISTBOX1
INSERT AT END "REMARKS$"&&REMARKS$ TO LISTBOX1
SQL_EXEC FETCH INTO :PROCEDURE_QUALIFIER$, :PROCEDURE_OWNER$, :PROCEDURE_NAME$,
:COLUMN_NAME$, :COLUMN_TYPE%, :DATA_TYPE%,\
:TYPE_NAME$, :PRECISION%, :LENGTH%, :SCALE%, :RADIX%, :NULLABLE%, :REMARKS$
ENDWHILE
```

See also NS_FUNCTION GETPROCEDURE

NS_FUNCTION GETTABLE

Returns the list of objects of a given type.

Syntax **NS_FUNCTION GETTABLE** : *object-type*, :*owner-name*

Parameters	<i>object-type</i>	CSTRING	I	object type (TABLE, SYSTEM TABLE, etc.)
	<i>owner-name</i>	CSTRING	I	owner name

Notes

1. The parameters passed to NS_FUNCTION GETTABLE can be left blank, in which case it assumes that you require all the objects in the database for all types.
2. Data is retrieved by executing a FETCH INTO statement that must contain the following items:

:TABLE_QUALIFIER\$(129)	ID of the object qualifier
:TABLE_OWNER\$(129)	Owner of the object
:TABLE_NAME\$(129)	Object name
:TABLE_TYPE\$(129)	TABLE, VIEW, SYSTEM TABLE, GLOBAL TEMPORARY, LOCAL TEMPORARY, ALIAS, SYNONYM
:REMARKS\$(255)	Object description

Example

```
LOCAL OBJECT_NAME$, OWNER_NAME$, REF_NAME$
LOCAL TABLE_QUALIFIER$(129), TABLE_OWNER$(129), TABLE_NAME$(129)
LOCAL TABLE_TYPE$(129), REMARKS$
OBJECT_NAME$ =EF_TABLE
OWNER_NAME$ =EF_OWNER

SQL_EXEC NS_FUNCTION GETTABLE :OBJECT_NAME$, :OWNER_NAME$
if sql_error% <> 0
    message 'error GETTABLE' , sql_errmsg$(sql_error%)
endif
```

```
; Retrieving data
SQL_EXEC FETCH INTO :TABLE_QUALIFIER$, :TABLE_OWNER$, :TABLE_NAME$, \
:TABLE_TYPE$, :REMARKS$
if sql_error% <> 0
    message 'error FETCH' , sql_errmsg$(sql_error%)
endif
WHILE SQL_ERROR% = 0
    INSERT AT END "TABLE_QUALIFIER$"&&TABLE_QUALIFIER$ TO LISTBOX1
    INSERT AT END "TABLE_OWNER$"&&TABLE_OWNER$ TO LISTBOX1
    INSERT AT END "TABLE_NAME$"&&TABLE_NAME$ TO LISTBOX1
    INSERT AT END "TABLE_TYPE$"&&TABLE_TYPE$ TO LISTBOX1
    INSERT AT END "REMARKS$"&&REMARKS$ TO LISTBOX1
    SQL_EXEC FETCH INTO :TABLE_QUALIFIER$, :TABLE_OWNER$, :TABLE_NAME$, \
:TABLE_TYPE$, :REMARKS$
ENDWHILE
```

See also

NS_FUNCTION GETPROCEDURECOLUMN

NS_FUNCTION GETTABLEINFO

Returns the description of a given object.

Syntax	NS_FUNCTION GETTABLEINFO <i>:object-type, :owner-name, :object-name</i>		
Parameters	<i>object-type</i>	CSTRING I	object type (TABLE, SYSTEM TABLE, etc.)
	<i>owner-name</i>	CSTRING I	owner name
	<i>object-name</i>	CSTRING I	object name

Notes

1. Data is retrieved by executing a FETCH INTO statement that must contain the following items:

:TABLE_QUALIFIER\$(129)	ID of the object qualifier
:TABLE_OWNER\$(129)	Owner of the object
:TABLE_NAME\$(129)	Object name
:TABLE_TYPE\$(129)	TABLE, VIEW, SYSTEM TABLE, GLOBAL TEMPORARY, LOCAL TEMPORARY, ALIAS, SYNONYM
:REMARKS\$(255)	Object description

Example

```

LOCAL OBJECT_NAME$, OWNER_NAME$, REF_NAME$
LOCAL TABLE_QUALIFIER$(129), TABLE_OWNER$(129), TABLE_NAME$(129)
LOCAL TABLE_TYPE$(129), REMARKS$
OBJECT_NAME$ = EF_TABLE
OWNER_NAME$ = EF_OWNER
REF_NAME$ = EF_COLUMN

SQL_EXEC NS_FUNCTION GETTABLEINFO :OBJECT_NAME$, :OWNER_NAME$, :REF_NAME$
if sql_error% <> 0
    message 'error GETTABLEINFO' , sql_errmsg$(sql_error%)
endif

```

```
; Retrieving data
SQL_EXEC_FETCH INTO :TABLE_QUALIFIER$, :TABLE_OWNER$, :TABLE_NAME$,
:TABLE_TYPE$, :REMARKS$
if sql_error% <> 0
    message 'error FETCH' , sql_errmsg$(sql_error%)
endif
WHILE SQL_ERROR% = 0
; always blank
    INSERT AT END "TABLE_QUALIFIER$"&&TABLE_QUALIFIER$ TO LISTBOX1
    INSERT AT END "TABLE_OWNER$"&&TABLE_OWNER$ TO LISTBOX1
    INSERT AT END "TABLE_NAME$"&&TABLE_NAME$ TO LISTBOX1
    INSERT AT END "TABLE_TYPE$"&&TABLE_TYPE$ TO LISTBOX1
    INSERT AT END "REMARKS$"&&REMARKS$ TO LISTBOX1
    SQL_EXEC_FETCH INTO :TABLE_QUALIFIER$, :TABLE_OWNER$, :TABLE_NAME$, \
:TABLE_TYPE$, :REMARKS$
ENDWHILE
```

See also

NS_FUNCTION GETTABLE

NS_FUNCTION GETTYPEINFO

Retrieves the SQL data type.

Syntax **NS_FUNCTION GETTYPEINFO** : *object-type*

Parameter *object-type* INT(4) I SQL data type

Note

1. SQL data types can have the following values:

0	all data types
1	BIGINT
2	BINARY
3	BIT
4	CHAR
5	DATE
6	DECIMAL
7	DOUBLE
8	FLOAT
9	INTEGER
10	LONGVARBINARY
11	LONGVARCHAR
12	LONGVARBINARY
13	NUMERIC
14	REAL
15	SMALLINT
16	TIME
17	TIMESTAMP
18	TINYINT
19	VARBINARY
20	VARCHAR

2. Data is retrieved by executing a FETCH INTO statement that must contain the following items:

:TYPE_NAME\$(129)	Data type name used by the DATASOURCE
:DATA_TYPE\$(2)	SQL data type (DB2/CLI format)
:PRECISION\$(4)	Maximum precision value

:LITERAL_PREFIX\$(128)	Character (s) used to prefix a literal value (e.g. "" for CHAR)
:LITERAL_SUFFIX\$(128)	Character (s) used to suffix a literal value (e.g. "" for CHAR)
:CREATE_PARAMS\$(128)	List of parameters for this data type
:NULLABLE%(2)	0 = NULL not allowed, 1 = NULL allowed
:CASE_SENSITIVE%(2)	1 = case sensitive, 0 = non case sensitive
:SEARCHABLE%(2)	0 = data type incompatible with WHERE 1 = data type only compatible with LIKE 2 = data type incompatible with LIKE 3 = data type fully compatible with WHERE
:UNSIGNED_ATTRIBUTE%(2)	0 = data type does not support + or - sign 1 = data type supports + or - sign
:MONEY%(2)	0 = non-money data type, 1 = money data type
:AUTO_INCREMENT%(2)	0 = no auto increment, 1 = supports auto increment
:LOCAL_TYPE_NAME\$(128)	Data type name in SQL engine
:MINIMUM_SCALE%(2)	Minimum precision value
:MAXIMUM_SCALE%(2)	Maximum precision value

Example

```
; Retrieving all types of data of DATA SOURCE
MOVE 0 TO OBJECT_TYPE%
SQL_EXEC NS_FUNCTION GETTYPEINFO :OBJECT_TYPE%
SQL_EXEC FETCH INTO
```

See also SQL_ERROR%, SQL_ERRMSG\$, NSODBC.NCL

NS_FUNCTION GIVECOM

Retrieves in COM_AREA segment the characteristics of a table whose components are unknown when a SELECT statement is executed.

This function is particularly useful in the treatment of dynamic requests and avoid to define host variables and FETCH command.

Syntax **NS_FUNCTION GIVECOM INTO** : *table-characteristics*

Parameter *table-characteristics* INT(4) I/O pointer to the segment COM_AREA used to retrieve the table's characteristics

Note

1. The selection structure is retrieved in a segment COM_AREA (defined in the SQL_COM.NCL file). The host variable *table-characteristics* contains the pointer to this segment. This host segment comprises a number of field, including two pointers (HOST_PTR and SQL_PTR). These pointers can be retrieved in order to scan the two arrays that respectively contain the NCL variables and SQL variables affected by the query about to be executed.

```
; Definition of the communication structure (GIVECOM INTO:)
SEGMENT COM_AREA
    int reserved(4)           ;reserved
    int transaction(2)        ;reserved
    int statement(2)          ;reserved
    int host_ptr(4)           ;pointer to a segment of a NCLELEMENT type
                                ;(defining the NCL host variables)
    int sql_ptr(4)            ;pointer to a segment of a SQLELEMENT type
                                ;(defining the columns of the request tables)
    int com_ptr(4)            ;reserved
    int num_stat(2)           ;type of the request
                                ; 1 -> SELECT
                                ; 2 -> UPDATE
                                ; 3 -> DELETE
                                ; 4 -> INSERT
                                ; 5 -> Other
    int num_col(2)            ; number of the columns
    int num_col_compute(2)    ; number of the COMPUTE columns (not
                                ; applicable for Oracle)
    int len_buf_stat(2)       ; size of the buf_stat below
    int buf_stat(4)           ; pointer on a buffer containing
;the FETCH INTO [ :, ] instruction followed by « :, » as much as
;variables to go through in a SELECT case
    int initd(2)              ;TRUE if all is OK, FALSE otherwise.
                                ;Always to test if it's TRUE.
ENDSEGMENT
```

2. The SQL_COM.NCL library provides a set of functions required to make use of the NS_FUNCTION GIVECOM INTO function:
 - Communication structure.

- Functions that return the type of command to be executed.
 - All the functions used to retrieve pointers.
 - Types, sizes and names of the columns affected by the selection.
- 3.** Once the type of the command has been identified as a SELECT statement (after using the `SQL_GET_STATEMENT%` and `SQL_GET_STATEMENTS$` functions), the `SQL_EXEC_LONGSTR` command can execute the query that will fill the receiving field. The results can be extracted from this field using the functions in the NCL library.
- 4.** La liste des fonctions contenues dans la bibliothèque NCL est la suivante :

- **FUNCTION SQL_GET_HOSTPTR%**

Returns a pointer to an array of variables named COM_NCLEMENT (definition of NCL host variables).

Variable	<i>COM BUFFER%</i>	INT(4)	Pointer to COM AREA
-----------------	--------------------	--------	---------------------

Return value INT(4)

```

: Definition of the receiver NCL variables's structure
SEGMENT COM_NCLELEMENT
    int buffer_ptr(4)
    int ncltype(2)
    integer ncllength
    int reserved1(2)
    int reserved2(2)
ENDSEGMENT

```

- **FUNCTION SQL GET SOLPTR%**

Returns a pointer to an array of variables named COM SOLELEMENT.

Variable	<i>COM BUFFER%</i>	INT(4)	Pointer to COM AREA
-----------------	--------------------	--------	---------------------

Return value INT(4)

```

; Definition of the SQL column's structure
SEGMENT COM_SQLELEMENT
    CSTRING colname(64)           ; name of the column
    int collength(4)              ; size of the column
    int coltype(2)                ; type of the column
    int colservice(2)             ; service for this column
    int colcomputeref(2)          ; reference of the column having the compute
ENDSEGMENT

```


- **FUNCTION SQL_GET_STATEMENT%**

Returns the type of statement executed (integer value) from the num_stat buffer of COM_AREA segment.

Variable *COM_BUFFER%* INT(4) Pointer to COM_AREA

Return value INT(2)

- **FUNCTION SQL_GET_STATEMENT\$**

Returns the type of statement executed (alphanumeric value) from num_stat buffer of COM_AREA segment and converts it to a CSTRING value.

Variable *STATEMENT%* INT(4) SQL_GET_STATEMENT%
function

Return value CSTRING

The values of num_stat are the following :

- 1 for SELECT
- 2 for UPDATE
- 3 for DELETE
- 4 for INSERT
- 0 for any other type of request.

- **FUNCTION SQL_GET_NBCOL%**

Returns the number of columns retrieved by the statement.

Variable *COM_BUFFER%* INT(4) Pointer to COM_AREA

Return value INT(2)

- **FUNCTION SQL_GET_LENGTHFETCH%**

Returns the size of the fetch buffer..

Variable *COM_BUFFER%* INT(4) Pointer to COM_AREA

Return value INT(4)

- **FUNCTION SQL_GET_FETCHPTR%**

Returns the pointer to the fetch buffer.

Variable	<i>COM_BUFFER%</i>	INT(4)	Pointer to COM_AREA
-----------------	--------------------	--------	---------------------

Return value INT(4)

- **FUNCTION SQL_GET_HOSTCOLUMNPTR%**

Returns the pointer to the data in an element in the array of NCL variables.

Variable	<i>COM_BUFFER%</i>	INT(4)	Pointer to COM_AREA
	<i>COLUMN%</i>	INT(2)	Order of the NCL variable

Return value INT(4)

- **FUNCTION SQL_GET_HOSTCOLUMNTYPE%**

Returns the data type for an element in the array of NCL variables (integer value).

Variable	<i>COM_BUFFER%</i>	INT(4)	Pointer to COM_AREA
	<i>COLUMN%</i>	INT(2)	Order of the NCL variable

Return value INT(2)

- **FUNCTION SQL_GET_HOSTCOLUMNTYPE\$**

Returns the data type for an element in the array of NCL variables (alphanumeric value).

Variable	<i>TYPE%</i>	INT(4)	SQL_GET_HOSTCOLUMNLENGTH% function
-----------------	--------------	--------	---------------------------------------

Return value CSTRING(80)

- **FUNCTION SQL_GET_HOSTCOLUMNLENGTH%**

Returns the data size for an element in the array of NCL variables.

Variable	<i>COM_BUFFER%</i>	INT(4)	Pointer to COM_AREA
	<i>COLUMN%</i>	INT(2)	Order of the NCL variable

Return value INT(2)

- **FUNCTION SQL_GET_SQLCOLUMNNAME\$**

Returns the column name in the array of SQL columns.

Variable	<i>COM_BUFFER%</i>	INT(4)	Pointer to COM_AREA
	<i>COLUMN%</i>	INT(2)	Order of the NCL variable

Return value CSTRING(64)



The five following functions are not very useful with NS_FUNCTION GIVECOM. However, we let's them in the documentation to compatibility with older documentations.

- **FUNCTION SQL_GET_SQLCOLUMNTYPE%**

Returns the DBMS column type in the array of SQL columns.

```
FUNCTION SQL_GET_SQLCOLUMNTYPE% \
  (INT COM_BUFFER%(4),INT COLUMN%(2)) \
  RETURN INT(2)
```

- **FUNCTION SQL_GET_SQLCOLUMNLENGTH%**

Returns the DBMS column size in the array of SQL columns.

```
FUNCTION SQL_GET_SQLCOLUMNLENGTH% \
  (INT COM_BUFFER%(4),INT COLUMN%(2)) \
  RETURN INT(4)
```

- **FUNCTION SQL_GET_SQLCOLUMNSERVICE%**

Retrieves the DBMS column service in the array of SQL columns (integer value).

```
FUNCTION SQL_GET_SQLCOLUMNSERVICE% \
  (INT COM_BUFFER%(4),INT COLUMN%(2)) \
  RETURN INT(2)
```

- **FUNCTION SQL_GET_SQLCOLUMNREF%**

Retrieves the column number referenced by COMPUTE.

```
FUNCTION SQL_GET_SQLCOLUMNREF% \
  (INT COM_BUFFER%(4),INT COLUMN%(2)) \
  RETURN INT(2)
```

- **FUNCTION SQL_GET_SQLCOLUMNSERVICE\$**

Retrieves the DBMS service (alphanumeric value).

```
FUNCTION SQL_GET_SQLCOLUMNSERVICE$ \
  (INT service%(2)) \
  RETURN CSTRING(80)
```

Example

```

LOCAL COM_AREA_RET%, TOTAL_COL%, I%, NCL_PTR%, RET%, BUFFER_PTR%
LOCAL COMPUTE% , HEADER$

MOVE "SELECT * FROM AUTHORS" TO A$
SQL_EXECSTR A$

MOVE 0 TO RET%
MOVE 0 TO COM_AREA_RET%

WHILE RET% = 0
    SQL_EXEC NS_FUNCTION GIVECOM INTO:COM_AREA_RET%

    IF COM_AREA_RET% = 0
        BREAK
    ENDIF
    IF SQL_GET_STATEMENT%(COM_AREA_RET%) <> 1
        ; if the statement is not SELECT
        ; retrieve the statement string
        INSERT AT END SQL_GET_STATEMENT$ \
        (SQL_GET_STATEMENT%(COM_AREA_RET%) ) TO LIST_FETCH
        UPDATE LIST_FETCH
        RETURN 1
    ENDIF

    MOVE SQL_GET_HOSTPTR%(COM_AREA_RET%) TO NCL_PTR%
    ; retrieve the pointer to the array of NCL variables
    MOVE SQL_GET_NBCOL%(COM_AREA_RET%) + SQL_GET_NBCOMPUTE%(COM_AREA_RET%) \
    TO TOTAL_COL%
    ; retrieve the number of columns + the number of COMPUTE columns
    IF SQL_GET_LENGTHFETCH%(COM_AREA_RET%) <> 0
        ; if the Fetch buffer size <> 0
        SQL_EXEC_LONGSTR (SQL_GET_FETCHPTR%(COM_AREA_RET%) , NCL_PTR% , -1)
        ; retrieve the pointer to the Fetch buffer + execute
    ELSE
        BREAK
    ENDIF
    WHILE RET% = 0 OR RET% = 200
        ; +200 message returned by SELECT...COMPUTE
        IF RET% = 200
            MOVE 1 TO COMPUTE%
        ELSE
            MOVE 0 TO COMPUTE%
        ENDIF
        MOVE 0 TO I%
        WHILE I% < TOTAL_COL%
            MOVE SQL_GET_HOSTCOLUMNPTR%(COM_AREA_RET% ,i% ) TO BUFFER_PTR%
            ; retrieve a pointer to an NCL variable
            IF BUFFER_PTR% = 0
                MOVE I% + 1 TO I%
                CONTINUE
            ENDIF
            IF COMPUTE% = 1
                ; assign SQL table column name
                MOVE "COMPUTE OF " && SQL_GET_SQLCOLUMNNAME$(COM_AREA_RET% ,\
                SQL_GET_SQLCOLUMNREF% (COM_AREA_RET% ,i% ) -1 ) TO HEADER$
                ; store the column name retrieved from the SQL array
                IF SQL_GET_SQLCOLUMNSERVICE% (COM_AREA_RET% ,i%) <> 3
                    ; if the service is not COMPUTE
                    MOVE I% + 1 TO I%
                    CONTINUE
                ENDIF
            ELSE
                MOVE "" TO HEADER$
            ENDIF
        ENDIF
    ENDIF

```

```

        IF SQL_GET_SQLCOLUMNNSERVICE% (COM_AREA_RET%,i%) <> 1
        ; if the service is not a column
        MOVE I% + 1 TO I%
        CONTINUE
    ENDIF
ENDIF
EVALUATE SQL_GET_HOSTCOLUMNNTYPE%(COM_AREA_RET% ,i% )
; determine column type
WHERE 0 ; integer
    ; retrieve the size of the data item
    EVALUATE SQL_GET_HOSTCOLUMNLENGTH%(COM_AREA_RET% ,i%)
    WHERE 1 ; 1-byte integer
    ; retrieve column name
    INSERT AT END HEADER$ && SQL_GET_SQLCOLUMNNAME$\
    (COM_AREA_RET%, I% ) && ":" && ASC% \
    (COM_INT1(BUFFER_PTR%).i1) TO LIST_FETCH
    ENDWHERE
    WHERE 2 ; 2-byte integer
    ; retrieve column name
    INSERT AT END HEADER$ && \
    SQL_GET_SQLCOLUMNNAME$(COM_AREA_RET% ,i% )&&\
    ":" && COM_INT2(BUFFER_PTR%).i2 TO LIST_FETCH
    ENDWHERE
    WHERE 4 ; 4-byte integer
    INSERT AT END HEADER$ && \
    SQL_GET_SQLCOLUMNNAME$(COM_AREA_RET% ,i% )&&\
    ":" && COM_INT4(BUFFER_PTR%).i4 TO LIST_FETCH
    ENDWHERE
    ENDEVALUATE
    ENDWHERE
    WHERE 2 ; C string
    INSERT AT END HEADER$ && \
    SQL_GET_SQLCOLUMNNAME$(COM_AREA_RET%, I% ) &&\
    ":" && COM_STRING(BUFFER_PTR%).CS TO LIST_FETCH
    ENDWHERE
    WHERE 3 ; real
    EVALUATE SQL_GET_HOSTCOLUMNLENGTH%(COM_AREA_RET%, I%)
    ; retrieve column size
    WHERE 4 ;
    ; retrieve column name and real 4-byte value
    INSERT AT END HEADER$ && \
    SQL_GET_SQLCOLUMNNAME$(COM_AREA_RET%, I% ) &&\
    ":" && COM_FLOAT4(BUFFER_PTR%).f4 TO LIST_FETCH
    ENDWHERE
    WHERE 8 ;
    ; retrieve column name and 8-byte real value
    INSERT AT END HEADER$ && \
    SQL_GET_SQLCOLUMNNAME$(COM_AREA_RET%, I% ) &&\
    ":" && COM_FLOAT8(BUFFER_PTR%).f8 TO LIST_FETCH
    ENDWHERE
    ENDEVALUATE
    ENDWHERE
    ELSE
    ; retrieve type of NCL column
    INSERT AT END "NCLType" && "INVALID" && \
    SQL_GET_HOSTCOLUMNNTYPE%(COM_AREA_RET%, i%) TO LIST_FETCH
    ; retrieve NCL column type
    ENDEVALUATE
    MOVE I% + 1 to I%
    ENDWHILE

SQL_EXEC_LONGSTR SQL_GET_FETCHPTR%(COM_AREA_RET%),NCL_PTR%,-1
; execute FETCH using pointer to FETCH buffer

ENDWHILE

```

```
UPDATE LIST_FETCH
IF RET% = 100
    INSERT AT END "END OF FETCH" TO LIST_FETCH
    INSERT AT END "" TO LIST_FETCH
    MOVE 0 TO RET%
ENDIF
IF RET% <> 100
    IF RET% > 0
        MESSAGE "WARNING" && RET% , SQL_ERRMSG$(RET%)
    ENDIF
    IF RET% < 0
        IF RET% = -32085
            INSERT AT END "END OF RESULT" TO LIST_FETCH
        ELSE
            MESSAGE "ERROR" && RET% , SQL_ERRMSG$(RET%)
        ENDIF
    ENDIF
ENDIF
ENDIF
ENDWHILE
```

See also `SQL_EXEC_LONGSTR`.

NS_FUNCTION IMAGEOFF, IMAGEON

IMAGEON mode enables binary object management (for example bitmaps) of 32 000 bytes maximum size. This manipulation has been executed in NCL segment SQL_IMAGE defined in NSDMS.NCL.

IMAGEOFF mode inactivates this function.

Syntax **NS_FUNCTION IMAGEOFF**

and

NS_FUNCTION IMAGEON

1. IMAGEOFF is the mode by default.
2. Binary objects are manipulated using an NCL segment SQL_IMAGE:


```
SEGMENT SQL_IMAGE
  INT REALSIZE(4) ; size of buffer allocated
  INT LENGTH%(4) ; real size
                  ; (from SELECT)
  INT PTR%(4) ; Buffer address
ENDSEGMENT
```
3. The maximum authorized size is 32K. If you want to handle BLOBs (large images) see TYPE_SQL_INSERT_BLOB% and TYPE_SQL_SELECT_BLOB%.
4. Images are not the only type of binary objects. Any type of binary file can be stored.
5. Binary storage is not cross-platform. Therefore, if you store binary files using Windows (ANSI) and you want to retrieve it using OS/2, you will probably have problems.

Example

```
;creation of a table
SQL_EXEC CREATE TABLE T_IMAGE(NUMERO NUMBER(8), DESCRIPTION VARCHAR2(80)\
, IMAGE LONG RAW)
if sql_error% <> 0
  message 'error Create' , sql_errmsg$(sql_error%)
endif

;INSERT

LOCAL DEST$(80),DATA%,SIZE%(4),NBREAD%(2),FILE%,NIL%,FNAME$, hbmp%
LOCAL SQL_IMAGE LOCALIMAGE

SQL_EXEC NS_FUNCTION IMAGEON
IF SQL_ERROR% <> 0
  MESSAGE "IMAGEON", SQL_ERROR% && SQL_ERRMSG$(SQL_ERROR%)
  RETURN 1
ENDIF
FNAME$ = "(NS-BMP)\TINTIN.BMP"
HBMP%=CREATEBMP%(FNAME$)
BMPT = HBMP%
;FGETSIZE% does not accept environnement variables
FNAME$ = "D:\TESTS\BMP\TINTIN.BMP"
```

```

SIZE%=FGETSIZE%(FNAME$) INSERT AT END "SIZE "& SIZE% TO LISTBOX1
NEW SIZE%,DATA%
FILE%=F_OPEN%(1,FNAME$)
F_BLOCKREAD FILE%, DATA%, SIZE%, NBREAD%
IF F_ERROR%
  MESSAGE"ERROR", "Failed to load " & FNAME$ &"!"
  F_CLOSE FILE%
  DISPOSE DATA%
  RETURN 1
ENDIF
; ---- Insert into table t_image
LOCALIMAGE.REALSIZE = SIZE%
LOCALIMAGE.LENGTH% = SIZE%
LOCALIMAGE.PTR% = DATA%
SQL_EXEC INSERT INTO T_IMAGE VALUES (1,'Une île entre le ciel et l 'eau', \
:LOCALIMAGE)
IF SQL_ERROR% <> 0
  MESSAGE "INSERT IMAGE", SQL_ERROR% && SQL_ERRMSG$(SQL_ERROR%)
  F_CLOSE FILE%
  DISPOSE DATA%
  RETURN 1
ENDIF
F_CLOSE FILE%
DISPOSE DATA%

;SELECT
LOCAL DEST$(80),DATA%,SIZE%(4),NBREAD%(2),FILE%,NIL%,FNAME$, hbmp%
LOCAL SQL_IMAGE LOCALIMAGE

SQL_EXEC NS_FUNCTION IMAGEON
IF SQL_ERROR% <> 0
  MESSAGE "IMAGEON", SQL_ERROR% && SQL_ERRMSG$(SQL_ERROR%)
  RETURN 1
ENDIF

LOCALIMAGE.realsize = 30000
NEW LOCALIMAGE.realsize,LOCALIMAGE.PTR%
SQL_EXEC SELECT IMAGE INTO :LOCALIMAGE FROM T_IMAGE WHERE NUMERO = 1
IF SQL_ERROR% <> 0
  MESSAGE "SELECT IMAGE",SQL_ERROR% && SQL_ERRMSG$(SQL_ERROR%)
ELSE

FNAME$=" (NS-BMP)\SOUVENIR.BMP"
FILE%=F_CREATE%(1,FNAME$)
INSERT AT END "FILE% "& FILE% TO LISTBOX1
F_BLOCKWRITE FILE%, LOCALIMAGE.PTR%, LOCALIMAGE.REALSIZE, NBREAD%
IF F_ERROR%
  MESSAGE"ERROR", "Failed to write " & FNAME$ &"!"
  F_CLOSE FILE%
  DISPOSE LOCALIMAGE.PTR%
  RETURN 1
ENDIF
HBMP%=CREATEBMP%(FNAME$)
BMPF = HBMP%
F_CLOSE FILE%
DISPOSE LOCALIMAGE.PTR%
ENDIF
DISPOSE LOCALIMAGE.PTR%
; ---- default mode
SQL_EXEC NS_FUNCTION IMAGEOFF

```

See also

NSDBMS.NCL, SQL_ERROR%, SQL_ERRMSG\$,
TYPE_SQL_INSERT_BLOB%, TYPE_SQL_SELECT_BLOB%

NS_FUNCTION QUOTEOFF, QUOTEON

The QUOTEON mode automatically manages quotation marks in input parameters for string-type values. This function is used for replacing strings of characters at application runtime.

The QUOTEOFF mode disables this function.

Syntax **NS_FUNCTION QUOTEOFF**
 and
 NS_FUNCTION QUOTEON

Notes

1. QUOTEON is the mode by default.
2. Quotation marks must be entered by the user in QUOTEOFF mode and be handled automatically in QUOTEON mode.
3. With ODBC, the string must be in simple quotes ' '.
 A\$ = " ' "&'PETER'&" ' " gives 'PETER'

Example

```
; This example allows to use host variables to create a SQL request

LOCAL A$,B$,C$,D$

MOVE "COL1" TO A$
MOVE "COL2" TO B$
MOVE "TABLE" TO C$
MOVE ' ' && "HELLO" && ' ' TO D$

SQL_EXEC NS_FUNCTION QUOTEOFF
IF SQL_ERROR% <> 0
    MESSAGE "ERROR QUOTEOFF", \
           SQL_ERROR% && SQL_ERRMSG$(SQL_ERROR%)
ENDIF
SQL_EXEC SELECT :A$, :B$ FROM :C$ WHERE :A$=:D$
;Equal to SELECT COL1, COL2
;FROM TABLE WHERE COL1 = 'HELLO'
.....
SQL_EXEC NS_FUNCTION QUOTEON
IF SQL_ERROR% <> 0
    MESSAGE "ERROR QUOTEON", \
           SQL_ERROR% && SQL_ERRMSG$(SQL_ERROR%)
ENDIF
```

See also SQL_ERROR%, SQL_ERRMSG\$

NS_FUNCTION ROWCOUNT

Returns the number of rows affected by a query (SELECT, INSERT, UPDATE, etc.) or the number of the FETCH realized after a SELECT.

Syntax **NS_FUNCTION ROWCOUNT INTO** *:nbr-rows*

Parameter *nbr-rows* INT(4) I number of rows

Example 1

```
LOCAL ROWCOUNT%

SQL_EXEC DELETE FROM TABPRODUIT WHERE NOPROD >= 30 AND NOPROD < 40

SQL_EXEC NS_FUNCTION ROWCOUNT INTO :ROWCOUNT%
; If 10 records correpond to this filter, then 10 records will be delete, thus
; ROWCOUNT% will contain 10.
; If any record correspond to a filter thus ROWCOUNT% is equal to 0.
```

Example 2

```
local var1%
local test$
LOCAL ROWCOUNT%
SQL_EXEC SELECT NUM, COL1 FROM BASE
IF SQL_ERROR% <> 0
    MESSAGE "Error ",SQL_ERRMSG$(SQL_ERROR%)
ENDIF

WHILE SQL_ERROR% = 0
    SQL_EXEC FETCH INTO:var1%,:test$
    IF SQL_ERROR% <> 0
        BREAK
    ENDIF
    INSERT AT END "Var1"&&var1%&& "test"&&test$ TO LISTBOX1
ENDWHILE
SQL_EXEC NS_FUNCTION ROWCOUNT INTO :ROWCOUNT%
Message "Number of occurences = ", ROWCOUNT%
```

See also NS_FUNCTION ANSIOFF, NS_FUNCTION ANSION, SQL_ERROR%,
SQL_ERRMSG\$, COMPUTE

NS_FUNCTION RPCRETCODEOFF, RPCRETCODEON

The `RPCRETCODEOFF` mode lets you retrieve a return code during the execution of a stored procedure which does not return a code.

The `RPCRETCODEON` mode lets you specify the return code of `SQL_RETURN` directly in a stored procedure.

Syntax

```
NS_FUNCTION RPCRETCODEOFF
and
NS_FUNCTION RPCRETCODEON
```

Notes

1. `RPCRETCODEOFF` is the default mode. Using `SQL_RETURN` in this mode returns a 0.
2. `RPCRETCODEON` can only be used for `FUNCTIONS` and not for `INSTRUCTIONS`.
3. See `SQL_PROC`, for more information about using this function.

Example

```
; See the SQL_PROC example
SQL_EXEC NS_FUNCTION RPCRETCODEOFF
SQL_EXEC SQL_PROC ...
...
SQL_EXEC NS_FUNCTION RPCRETCODEON
SQL_EXEC SQL_PROC ....
```

See also `SQL_PROC`, `SQL_RETURN`

NS_FUNCTION SETCURSORMODE

Indicate the using mode of the cursor opened by the functions SQL_OPENCURSOR% or SQL_OPENTHECURSOR%.

Syntax **NS_FUNCTION SETCURSORMODE** :*mode*

Parameter *mode* INT(4) I cursor mode used

Notes

1. There is two using modes of the cursor : the **default mode** and the **binding mode**.
2. A value is associated to each mode and each mode has a default size.
 - **Default mode :**
CONST DB_ODBC_CURSOR_DEFAULT% 0
 - **Binding Mode:**
CONST DB_ODBC_CURSOR_BINDING% 3
3. The **default mode** is standard mode. Host input variables are replaced by their contents during preparation of the query and replace ": " in the SQL query.
4. **Binding** mode enables ODBC to retrieve, during execution of the SQL order, the contents of the host input variables by their memory address and to specify the type and size of the memory to be retrieved.
5. The using mode DB_ODBC_CURSOR_BINDING is indispensable when using RECORD, REEXECUTE commands or the handling of the segment or the image.

Example

```
LOCAL MODE%

; -----
;  Mode by default
; -----
MOVE 'DUPONT' TO A$
SELECT * FROM TABLE WHERE COL = :A$
; => becomes
;   SELECT * FROM TABLE WHERE COL = 'DUPONT'

; -----
;  Mode by binding
; -----
MOVE DB_ODBC_CURSOR_BINDING% TO MODE%
SQL_EXEC NS_FUNCTION SETCURSORMODE : MODE%
SELECT * FROM TABLE WHERE COL = :A$
; => becomes
;   SELECT * FROM TABLE WHERE COL = ?
; the searches will be carried out by the binding mode

; -----
;  Return to the default mode
; -----
MOVE DB_ODBC_CURSOR_DEFAULT% TO MODE%
SQL_EXEC NS_FUNCTION SETCURSORMODE : MODE%
```

See also

RECORD, REEXECUTE, TYPE_SQL_INSERT_BLOB%,
TYPE_SQL_SELECT_BLOB%

NS_FUNCTION STATEMENT

Récupère l’instruction exacte de la requête envoyée au moteur SQL.
Retrieves the full statement used in the query sent to the SQL engine.

Syntaxe	NS_FUNCTION STATEMENT INTO : <i>query-string</i>		
Parameter	<i>query-string</i>	CSTRING	I/O statement used in the query sent to the SQL engine

Note

1. The INTO clause, even if it is precised, is not traced.


Example

```
LOCAL VALUES$, PHRASE$  
MOVE "HELLO" TO VALUES$  
SQL_EXEC SELECT COL1 FROM TABLE WHERE COL2=:VALUES$  
  
SQL_EXEC NS_FUNCTION STATEMENT INTO :PHRASE$  
MESSAGE "the exact comand is :", PHRASE$  
  
;PHRASE$ = SELECT COL1 FROM TABLE WHERE COL2='HELLO'
```

NS_FUNCTION SETTRANSACTIONMANAGER

Enables and records transactional mode for the current connection. Two modes are possible (DTC and XA) but only DTC mode is supported by the nsw2odc3 driver.

The activation of a Transaction Manager enables COMMIT to be implemented in two phases. This activation is useful when it is a question of a distributed data model.



See ODBC and MSDN manuals for more informations.

Syntax **NS_FUNCTION SETTRANSACTIONMANAGER** :valueType%, :infoType%

Parameters	valuetype%	INT(4)	type of the value
	infotype%	INT(4)	information on the transaction mode

Note

1. The default mode of *valuetype%* is *false%* (transaction mode deactivated).

Example

```
local infoType%
local valueType%

infoType% = 1
;MS-DTC (Microsoft Distributed Transaction Coordinator)
;the only type of transaction manager supported

valueType% = true% ;or false% to deactivate (mode by default)

SQL_EXEC NS_FUNCTION SETTRANSACTIONMANAGER :valueType%, :infoType%
IF (SQL_ERROR%)
    MESSAGE SQL_ERROR%, SQL_ERRMSG$ (SQL_ERROR%)
ENDIF
```

NS_FUNCTION SETCONNECTOPTION

Allows assignment of the behavior of a connection regarding explicit or implicit closing of the cursors

Syntax	NS_FUNCTION SETCONNECTOPTION : <i>info%</i> , : <i>value_info%</i>			
Paramtere	<i>info%</i>	INT	I	information on the connection
	<i>value_info%</i>	INT	I	value linked to the connection
Notes				

1. *info%* can take the following values:

- `sql_preserve_cursor 1024`

cursors will not be closed implicitly after the commit.

- `sql_pc_on 1`

the default mode (cursors will be closed automatically after the commit)

2. *value_info%* is always equal to 1.

Example

```
Local STRING ENT_RAIS (35), STRING EMP_ID (4), STRING EMP_LIB (35)
Local STRING ENT_ID (10)
Local cur1%, cur2%, ret%
Local int option%(4), int value_opt%(4)
Local base$
;With Sql_server ODBC driver, Cursors are automatically closed if you commit
;or roll back a transaction.
;The SQL Server driver provides a driver-specific connection option,
;SQL_PRESERVE_CURSORS,
;to override this behavior for server cursors.
;From the NCL use the NS_FUNCTION SETCONNECTOPTION -specifies the connection
;options - with
;SQL_PRESERVE_CURSORS = 1024
;SQL_PC_ON = 1
;and the cursors will not be closed.
;See the example below.
option% =1024
value_opt%=1
sql_exec NS_FUNCTION SETCONNECTOPTION :option%, :value_opt%

; To forbid the implicit "COMMIT" after every sql statement
SQL_Exec NS_FUNCTION AUTOCOMMITOFF
if sql_error%
    message "Error SQL_Exec NS_FUNCTION
AUTOCOMMITOFF"&&sql_error%,sql_errmsg$(sql_error%)
endif

; Opening of the cursor cur1%
cur1% = SQL_OpenCursor%
if sql_error%
    message "Error Opencursor%"&&sql_error%,sql_errmsg$(sql_error%)
endif

;Lets you specify the behavior of a cursor.
option% = DB_ODBC_CURSOR_TYPE
```



```

value_opt% = DB_ODBC_CURSOR_DYNAMIC
SQL_EXEC NS_FUNCTION SETSTMTOPTION :option%, :value_opt% using cur1%
if sql_error%
    message "Error NS_FUNCTION
SETSTMTOPTION"&&sql_error%,sql_errmsg$(sql_error%)
endif
ret% = 0
SQL_EXEC select ENT_ID, ENT_RAIS from soc using cur1%
ret% = SQL_Error%
if ret%
    message "Error select"&&ret%,sql_errmsg$(ret%)
endif

While ret% = 0
    SQL_EXEC FETCH INTO ( :ENT_ID, :ENT_RAIS ) using cur1%
    ret% = SQL_Error%
    if ret% = 0
        ; Opening of cursor cur2%
        cur2% = SQL_OpenCursor%
        if sql_error%
            message "Error
Opencursor"&&sql_error%,sql_errmsg$(sql_error%)
        endif
        ;Sets the same behavior of the above cursor for the second one.
        SQL_EXEC NS_FUNCTION SETSTMTOPTION :option%, :value_opt% using cur2%
        if sql_error%
            message "Error NS_FUNCTION
SETSTMTOPTION"&&sql_error%,sql_errmsg$(sql_error%)
        endif

        SQL_EXEC Update emploi set EMP_LIB=:ENT_RAIS \
        Where ENT_ID=:ENT_ID using cur2%
        if sql_error%
            message "Error Update \
emploi"&&sql_error%,sql_errmsg$(sql_error%)
        else
            SQL_Exec Commit
            if sql_error%
                message "Error Commit"&&sql_error%,sql_errmsg$(sql_error%)
            endif
        endif
    endif
    IF cur2% <> 0
        ; Close explicitly the cursor because of SQL_PRESERVE_CURSORS

        SQL_Closecursor cur2%
        if sql_error%
            message "Error
SQL_Closecursor"&&sql_error%,sql_errmsg$(sql_error%)
        endif
    endif
endif
EndWhile
; Close explicitly the cursor because of SQL_PRESERVE_CURSORS

IF cur1% <> 0
    SQL_Closecursor cur1%
    if sql_error%
        message "Error
SQL_CLOSECURSOR"&&sql_error%,sql_errmsg$(sql_error%)
    endif
endif

```

NS_FUNCTION SETSTMTOPTION

Allows configuration of all possible options supported by the target database, in order to optimize the query on the execution and/or extraction of information.

Syntax NS_FUNCTION SETSTMTOPTION :fOption% , :vParam%

Parameters

:fOption%	INT(4)	Option to change
:vParam%	INT(4)	Value associated with option

Note

1. Use it with the following constants :

Option to change (fOption%)	Value of the option (vParam%)
Synchronous or asynchronous mode CONST DB_ODBC_ASYNC_ENABLE 4	CONST DB_ODBC_ASYNC_ENABLE_OFF 0 CONST DB_ODBC_ASYNC_ENABLE_ON 1
Bound column size for extented fetch CONST DB_ODBC_BIND_TYPE 5	CONST DB_ODBC_BIND_BY_COLUMN 0
Cursor concurrency CONST DB_ODBC_CONCURRENCY 7	CONST DB_ODBC_CONCUR_READ_ONLY 1 CONST DB_ODBC_CONCUR_LOCK 2 CONST DB_ODBC_CONCUR_ROWVER 3 CONST DB_ODBC_CONCUR_VALUES 4
Positionnement du type de curseur CONST DB_ODBC_CURSOR_TYPE 6	CONST DB_ODBC_CURSOR_FORWARD_ONLY 0 This constant corresponds to a dynamic cursor, but the FETCH is sequential at the start to the end, no return. CONST DB_ODBC_CURSOR_KEYSET_DRIV 1 The informations of columns are displayed, but not the insertions or suppressions executed after the SELECT statement. CONST DB_ODBC_CURSOR_DYNAMIC 2 The dynamic cursor displays the insertions and suppressions executed in the retrieved rows by SELECT statement. CONST DB_ODBC_CURSOR_STATIC 3 The cursor in static mode displays the row set retrieved by SELECT statement. Thus, the retrieved rows can not be modify.

Number of rows in keyset CONST DB_ODBC_KEYSET_SIZE 8	CONST DB_ODBC_KEYSET_SIZE_DEFAULT 0
Maximum amount of data that the driver returns from a character or binary column CONST DB_ODBC_MAX_LENGTH 3	CONST DB_ODBC_MAX_LENGTH_DEFAULT 0
Maximum number of rows to return to the application for a SELECT statement CONST DB_ODBC_MAX_ROWS 1	CONST DB_ODBC_MAX_ROWS_DEFAULT 0
Scan SQL strings for escape clauses CONST DB_ODBC_NOSCAN 2	CONST DB_ODBC_NOSCAN_OFF 0 CONST DB_ODBC_NOSCAN_ON 1
Number of seconds to wait for an SQL statement CONST DB_ODBC_QUERY_TIMEOUT 0	CONST DB_ODBC_QUERY_TIMEOUT_DEFAULT 0
Does/does not retrieve data after it positions the cursor CONST DB_ODBC_RETRIEVE_DATA 11	CONST DB_ODBC_RD_OFF 0 CONST DB_ODBC_RD_ON 1
The number of rows in the rowset CONST DB_ODBC_ROWSET_SIZE 9	CONST DB_ODBC_ROWSET_SIZE_DEFAULT 1
Pour simuler la position de mise à jour et détruire le mode d'instruction CONST DB_ODBC_SIMULATE_CURSOR 10	CONST DB_ODBC_SC_NON_UNIQUE 0 CONST DB_ODBC_SC_TRY_UNIQUE 1 CONST DB_ODBC_SC_UNIQUE 2
Use bookmarks with a cursor CONST DB_ODBC_USE_BOOKMARKS 12	CONST DB_ODBC_UB_OFF 0 CONST DB_ODBC_UB_ON 1

Example

```

LOCAL OPTION%, VALUE_OPTION%

OPTION% = DB_CURSOR_TYPE
VALUE_OPTION% = DB_CURSOR_FORWARD_ONLY

; the cursor should not be positioned in the rear
; this use a classical gestion of the internal cursor of the driver
SQL_EXEC NS_FUNCTION SETSTMTOPTION :OPTION%, :VALUE_OPTION%

```

See also

NSODBC.NCL for the constants.

NS_FUNCTION TRIMCHAROFF, TRIMCHARON

In TRIMCHARON mode, when a SELECT is executed, the blank spaces at the end of strings are removed. This is very useful when the array type is CSTRING or STRING, but it's not applicable with CHAR or VARCHAR2.

In TRIMCHAROFF mode, the blank spaces are kept.

Syntax **NS_FUNCTION TRIMCHAROFF**
 and
 NS_FUNCTION TRIMCHARON

Note

1. TRIMCHAROFF is the default mode.

Example

```
SQL_EXEC NS_FUNCTION TRIMCHARON
SQL_EXEC SELECT 'But string with blanks at the end' INTO :C$
INSERT AT END "{B[LIGHTBLUE]}CHAR=<" & C$ & ">"&" TO LISTBOX1
SQL_EXEC SELECT 'But string with blanks at the end' INTO :Str$
INSERT AT END "{B[GREEN]}CHAR=<" & Str$ & ">"&" TO LISTBOX1
; BLANKS are eliminated
SQL_EXEC NS_FUNCTION TRIMCHAROFF
SQL_EXEC SELECT 'But string with blanks at the end' INTO :C$
INSERT AT END "{B[LIGHTBLUE]}CHAR=<" & C$ & ">"&" TO LISTBOX1
SQL_EXEC SELECT 'But string with blanks at the end' INTO :Str$
INSERT AT END "{B[GREEN]}CHAR=<" & Str$ & ">"&" TO LISTBOX1
; BLANKS are present
```

See also SQL_ERROR%, SQL_ERRMSG\$