

№5

12.03.2024

, ,



-
- , -03-22
-
- 1032225355@pfur.ru





, SetUID- Sticky- .



```
Terminal - jose@Jose-IdeaPad-3-15ITL6: ~
Archivo Editar Ver Terminal Pestañas Ayuda
/var/lib/snapd/snaps/vlc_3721.snap on /snap/vlc/3721 type squashfs (ro,nodev,relatime,errors=continue,threads=
single,x-gdu.hide,x-gvfs-hide)
/var/lib/snapd/snaps/riseup-vpn_179.snap on /snap/riseup-vpn/179 type squashfs (ro,nodev,relatime,errors=cont
inue,threads=single,x-gdu.hide,x-gvfs-hide)
/var/lib/snapd/snaps/pycharm-community_378.snap on /snap/pycharm-community/378 type squashfs (ro,nodev,relati
me,errors=continue,threads=single,x-gdu.hide,x-gvfs-hide)
/dev/mapper/vgubuntu-root on /var/snap/firefox/common/host-hunspell type ext4 (ro,noexec,noatime,errors=remou
nt-ro)
/var/lib/snapd/snaps/telegram-desktop_5791.snap on /snap/telegram-desktop/5791 type squashfs (ro,nodev,relati
me,errors=continue,threads=single,x-gdu.hide,x-gvfs-hide)
/dev/sdal on /boot/efi type vfat (rw,relatime,fmask=0077,dmask=0077,codepage=437,iocharset=iso8859-1,shortnam
e=mixed,errors=remount-ro)
binfmt_misc on /proc/sys/fs/binfmt_misc type binfmt_misc (rw,nosuid,nodev,noexec,relatime)
ramfs on /run/credentials/systemd-tmpfiles-setup.service type ramfs (ro,nosuid,nodev,noexec,relatime,mode=700
)
ramfs on /run/credentials/systemd-resolved.service type ramfs (ro,nosuid,nodev,noexec,relatime,mode=700)
tmpfs on /run/snapd/ns type tmpfs (rw,nosuid,nodev,noexec,relatime,size=791544k,mode=755,inode64)
nsfs on /run/snapd/ns/cups.mnt type nsfs (rw)
nsfs on /run/snapd/ns/snapd-desktop-integration.mnt type nsfs (rw)
tmpfs on /run/user/1000 type tmpfs (rw,nosuid,nodev,relatime,size=791540k,nr_inodes=197885,mode=700,uid=1000,
gid=1000,inode64)
portal on /run/user/1000/doc type fuse.portal (rw,nosuid,nodev,relatime,user_id=1000,group_id=1000)
gvfsd-fuse on /run/user/1000/gvfs type fuse.gvfsd-fuse (rw,nosuid,nodev,relatime,user_id=1000,group_id=1000)
nsfs on /run/snapd/ns/firefox.mnt type nsfs (rw)
nsfs on /run/snapd/ns/whatsie.mnt type nsfs (rw)
nsfs on /run/snapd/ns/chromium.mnt type nsfs (rw)
nsfs on /run/snapd/ns/firmware-updater.mnt type nsfs (rw)
nsfs on /run/snapd/ns/zoom-client.mnt type nsfs (rw)
jose@jose-IdeaPad-3-15ITL6:~$
```

. 1:

```
jose@jose-IdeaPad-3-15ITL6:~$ setenforce 0
setenforce: SELinux is disabled
jose@jose-IdeaPad-3-15ITL6:~$ sudo su
[sudo] contraseña para jose:
root@jose-IdeaPad-3-15ITL6:/home/jose# setenforce 0
Orden «setenforce» no encontrada. Quizá quiso decir:
  la orden «setenforce» del paquete deb «selinux-utils (3.5-1)»
Pruebe con: apt install <nombre del paquete deb>
root@jose-IdeaPad-3-15ITL6:/home/jose# getenforce
Disabled
root@jose-IdeaPad-3-15ITL6:/home/jose# █
```


. 2: setenforce 0



```
jose@jose-IdeaPad-3-15ITL6:~$ su - guest  
Contraseña:
```

. 3:

[illegible]



```
jose@jose-IdeaPad-3-15ITL6: ~  
jose@jose-IdeaPad-3-15ITL6:~$ vi simpleid.c  
jose@jose-IdeaPad-3-15ITL6:~$ gcc simpleid.c -o simpleid  
jose@jose-IdeaPad-3-15ITL6:~$ ./simpleid  
uid=1000, gid=1000
```

. 5:

```
jose@jose-IdeaPad-3-15ITL6:~$ id  
uid=1000(jose) gid=1000(jose) grupos=1000(jose),4(adm),24(cdrom),27(sudo),30(dip),46(plugdev),100(users),118(lpadmin),130(smbashare)
```

. 6: id

```
jose@jose-IdeaPad-3-15ITL6: ~  
jose@jose-IdeaPad-3-15I... x jose@jose-IdeaPad-3-15I... x jose@jose-IdeaPad-3-15I... x  
#include <sys/types.h>  
#include <unistd.h>  
#include <stdio.h>  
#include <unistd.h>  
#include <stdio.h>  
  
int  
main ()  
{  
    uid_t real_uid = getuid ();  
    uid_t e_uid = geteuid ();  
    gid_t real_gid = getgid ();  
    gid_t e_gid = getegid ();  
    printf ("e_uid=%d, e_gid=%d\n", e_uid, e_gid);  
    printf ("real_uid=%d, real_gid=%d\n", real_uid,  
           real_gid);  
    return 0;  
}
```

"simpleid2.c" 19L, 355B 19,0-1 Todo

```
jose@jose-IdeaPad-3-15ITL6:~$ vi simpleid2.c
jose@jose-IdeaPad-3-15ITL6:~$ gcc simpleid2.c -o simpleid2
jose@jose-IdeaPad-3-15ITL6:~$ ./simpleid2
e_uid=1000, e_gid=1000
real_uid=1000, real_gid=1000
```

. 8:

```
jose@jose-IdeaPad-3-15ITL6:~$ sudo su
[sudo] contraseña para jose:
root@jose-IdeaPad-3-15ITL6:/home/jose# chown root:guest /home/guest/simpleid2
chown: no se puede acceder a '/home/guest/simpleid2': No existe el archivo o
el directorio
root@jose-IdeaPad-3-15ITL6:/home/jose# exit
exit
jose@jose-IdeaPad-3-15ITL6:~$ chown root:guest /home/guest/simpleid2
chown: no se puede acceder a '/home/guest/simpleid2': No existe el archivo o
el directorio
```

. 9:


```
jose@jose-IdeaPad-3-15ITL6:~$ sudo su
root@jose-IdeaPad-3-15ITL6:/home/jose# ls -li simpleid2
-rwxr-xr-x 1 root root 11282144 11282144 simpleid2
root@jose-IdeaPad-3-15ITL6:/home/jose# ./simpleid2
e_uid=0, e_gid=0
real_uid=0, real_gid=0
```

. 10: ls -li

```
root@jose-IdeaPad-3-15ITL6:/home/jose# id
uid=0(root) gid=0(root) grupos=0(root)
```

. 11:

```
#include <sys/types.h>
#include <sys/stat.h>
#include <fcntl.h>
#include <unistd.h>
#include <stdio.h>

int
main (int argc, char* argv[])
{
    unsigned char buffer[16];
    size_t bytes_read;
    int i;

    int fd = open (argv[1], O_RDONLY);
    do {
        bytes_read = read (fd, buffer, sizeof (buffer));
        for (i = 0; i < bytes_read; ++i) printf("%c", buffer[i]); }
    while (bytes_read == sizeof (buffer));
    close (fd);
    return 0;
}
```

. 12:

```

//...these guests are read here
#include <sys/types.h>
#include <sys/stat.h>
#include <fcntl.h>
#include <unistd.h>
#include <stdio.h>

int
main (int argc, char* argv[])
{
    unsigned char buffer[16];
    size_t bytes_read;
    int i;

    int fd = open (argv[1], O_RDONLY);
    do {
        bytes_read = read (fd, buffer, sizeof (buffer));
        for (i = 0; i < bytes_read; ++i) printf("%c", buffer[i]); }
    while (bytes_read == sizeof (buffer));
    close (fd);
    return 0;
}

```

. 13:

```
jose@jose-IdeaPad-3-15ITL6:~$ cat /home/guest/readfile.c
cat: /home/guest/readfile.c: No existe el archivo o el directorio
jose@jose-IdeaPad-3-15ITL6:~$ █
```

. 14:

```

t@p@p0 ****eh0 **** **** **** ****G ****G ****G ****gG ****nG ****S ****S ****S ****M ****M ****M ****
p ****p@ ****N ****N ****40 ****00 ****0 ****. ****S ****S ****d@8
♦
**** ****S ****S ****S ****S a **** ****86_64./readfile/etc/shadowSHELL=/bin/bashHISTCONTR
OL=ignoredupsHISTSIZ=1000HOSTNAME=localhostPWD=/home/guestLOGNAME=guestXAUTHORI
TY=/home/guest/.xauthkf0TjdHOME=/home/guestLANG=en_US.UTF-8LS_COLORS=rs=0:di=01;
34:ln=01;36:mh=00:pi=40;33:so=01;35:do=01;35:bd=40;33;01:cd=40;33;01:or=40;31;01
:mi=01;37;41:su=37;41:sg=30;43:ca=30;41:tw=30;42:ow=34;42:st=37;44:ex=01;32:*.ta
r=01;31:*.tgz=01;31:*.arc=01;31:*.arj=01;31:*.taz=01;31:*.lha=01;31:*.lz4=01;31:
*.lzh=01;31:*.lzma=01;31:*.tlz=01;31:*.txz=01;31:*.tzo=01;31:*.t7z=01;31:*.zip=0
1;31:*.z=01;31:*.dz=01;31:*.gz=01;31:*.lrz=01;31:*.lz=01;31:*.lzo=01;31:*.xz=01;
31:*.zst=01;31:*.tztst=01;31:*.bz2=01;31:*.bz=01;31:*.tbz=01;31:*.tbz2=01;31:*.t7

```

. 15:

```
root@jose-IdeaPad-3-15ITL6:/home/jose# ls -l / | grep tmp
drwxrwxrwt  22 root root 20480 abr 13 19:50 tmp
root@jose-IdeaPad-3-15ITL6:/home/jose# echo "test" > /tmp/file01.txt
root@jose-IdeaPad-3-15ITL6:/home/jose# ls -l /tmp/file01.txt
-rw-r--r--  1 root root 5 abr 13 19:55 /tmp/file01.txt
root@jose-IdeaPad-3-15ITL6:/home/jose# chmod o+rw /tmp/file01.txt
root@jose-IdeaPad-3-15ITL6:/home/jose# ls -l /tmp/file01.txt
-rw-r--rw-  1 root root 5 abr 13 19:55 /tmp/file01.txt
```

. 16:

```
root@jose-IdeaPad-3-15ITL6:/home/jose# echo "test" > /tmp/file01.txt
root@jose-IdeaPad-3-15ITL6:/home/jose# ls -l /tmp/file01.txt
-rw-r--r-- 1 root root 5 abr 13 19:55 /tmp/file01.txt
root@jose-IdeaPad-3-15ITL6:/home/jose# chmod o+rw /tmp/file01.txt
root@jose-IdeaPad-3-15ITL6:/home/jose# ls -l /tmp/file01.txt
-rw-r--rw- 1 root root 5 abr 13 19:55 /tmp/file01.txt
root@jose-IdeaPad-3-15ITL6:/home/jose# cat /tmp/file01.txt
test
root@jose-IdeaPad-3-15ITL6:/home/jose# echo "test2" > /tmp/file01.txt
root@jose-IdeaPad-3-15ITL6:/home/jose# cat /tmp/file01.txt
test2
root@jose-IdeaPad-3-15ITL6:/home/jose# echo "test3" > /tmp/file01.txt
root@jose-IdeaPad-3-15ITL6:/home/jose# cat /tmp/file01.txt
test3
root@jose-IdeaPad-3-15ITL6:/home/jose# rm /tmp/file0l.txt
rm: no se puede borrar '/tmp/file0l.txt': No existe el archivo o el directori
```

. 17:


```
jose@jose-IdeaPad-3-15ITL6:~$ ls /tmp
dbus-7mU2RtLM
dbus-AXjCbRlA
file01.txt
gdm3-config-err-iHWzMu
lu46305p3l.tmp
lu6719kjrj.tmp
OSL_PIPE_1000_SingleOfficeIPC_8fe2e4c27819f62b4f6b37cdf51ee64
snap-private-tmp
systemd-private-6460e344d3f54866a1ba99bd8a88dc34-bluetooth.service-VJ9oyy
systemd-private-6460e344d3f54866a1ba99bd8a88dc34-colord.service-9kvaWo
systemd-private-6460e344d3f54866a1ba99bd8a88dc34-fwupd.service-t54q2K
systemd-private-6460e344d3f54866a1ba99bd8a88dc34-geoclue.service-dGQs6d
systemd-private-6460e344d3f54866a1ba99bd8a88dc34-ModemManager.service-id7Lu4
systemd-private-6460e344d3f54866a1ba99bd8a88dc34-polkit.service-Vc5KfX
systemd-private-6460e344d3f54866a1ba99bd8a88dc34-power-profiles-daemon.service-t0NEr0
systemd-private-6460e344d3f54866a1ba99bd8a88dc34-switcheroo-control.service-MHM7xF
systemd-private-6460e344d3f54866a1ba99bd8a88dc34-systemd-logind.service-5CzErI
systemd-private-6460e344d3f54866a1ba99bd8a88dc34-systemd-sd.service-YBi480
```

. 18:

t

```
[1000] Contraseña para jose:  
root@jose-IdeaPad-3-15ITL6:/home/jose# chmod +t /tmp  
root@jose-IdeaPad-3-15ITL6:/home/jose# exit  
exit  
jose@jose-IdeaPad-3-15ITL6:~$ █
```

. 19: Sticky



, SetUID- Sticky- .

.