

# Minimum Cost Spanning Trees (MSTs)

Joseph Chuang-Chieh Lin (林莊傑)

Department of Computer Science & Engineering,  
National Taiwan Ocean University

Fall 2024



# Outline

1 Introduction

2 Kruskal's algorithm

3 Prim's algorithm

4 Sollin's algorithm

# Outline

1 Introduction

2 Kruskal's algorithm

3 Prim's algorithm

4 Sollin's algorithm

# Cost & Minimum-Cost Spanning Tree

- The cost of a spanning tree of a weighted undirected graph is the sum of the weights of the edges in the spanning tree.




# Cost & Minimum-Cost Spanning Tree

- The cost of a spanning tree of a weighted undirected graph is the sum of the weights of the edges in the spanning tree.
- A minimum-cost spanning tree is a spanning tree of least cost.



# Cost & Minimum-Cost Spanning Tree

- The cost of a spanning tree of a weighted undirected graph is the sum of the weights of the edges in the spanning tree.
- A minimum-cost spanning tree is a spanning tree of least cost.



$$\text{cost} = 10 + 25 + 22 + 12 + 16 + 14 = 99.$$

$$\text{cost} = 28 + 16 + 12 + 22 + 24 + 25 = 127.$$

# Greedy Methods

- We will introduce three different **greedy algorithms** can be used to obtain a minimum cost spanning tree of a connected undirected graph.

# Greedy Methods

- We will introduce three different **greedy algorithms** can be used to obtain a minimum cost spanning tree of a connected undirected graph.
  - Kruskal's algorithm
  - Prim's algorithm
  - Sollin's algorithm
- ★ Further reading: Greedy Algorithms & Matroids [[link](#)]

# Greedy Method (1/2)

- Construct an optimal solution in stages.
- A feasible solution is one which works within the constraints specified by the problem.
- At each stage, we make a decision that is **the best decision at that time**.
- Typically, The selection of an item at each stage is based on either **a least cost** or **a highest profit** criterion.



# Greedy Method (2/2)

- For minimum spanning trees, we use a least cost criterion. Our solution must satisfy the following constraints:

# Greedy Method (2/2)

- For minimum spanning trees, we use a least cost criterion. Our solution must satisfy the following constraints:
  - We must use only edges within the graph.



# Greedy Method (2/2)

- For minimum spanning trees, we use a least cost criterion. Our solution must satisfy the following constraints:
  - We must use only edges within the graph.
  - Exactly  $n - 1$  edges are used.

# Greedy Method (2/2)

- For minimum spanning trees, we use a least cost criterion. Our solution must satisfy the following constraints:
  - We must use only edges within the graph.
  - Exactly  $n - 1$  edges are used.
  - Never use edges that would produce a cycle.

# Outline

1 Introduction

2 Kruskal's algorithm

3 Prim's algorithm

4 Sollin's algorithm

## Kruskal's Algorithm

- Build a minimum cost spanning tree  $T$  by adding edges to  $T$  one at a time.

## Kruskal's Algorithm

- Build a minimum cost spanning tree  $T$  by adding edges to  $T$  one at a time.
- Select the edges for inclusion in  $T$  in nondecreasing order of their cost.

## Kruskal's Algorithm

- Build a minimum cost spanning tree  $T$  by adding edges to  $T$  one at a time.
- Select the edges for inclusion in  $T$  in nondecreasing order of their cost.
- An edge is added to  $T$  if it does not form a cycle with the edges that are already in  $T$ .

## Kruskal's Algorithm

- Build a minimum cost spanning tree  $T$  by adding edges to  $T$  one at a time.
- Select the edges for inclusion in  $T$  in nondecreasing order of their cost.
- An edge is added to  $T$  if it does not form a cycle with the edges that are already in  $T$ .
- Exactly  $n - 1$  edges will be selected for inclusion in  $T$ .



## Kruskal's Algorithm

- Build a minimum cost spanning tree  $T$  by adding edges to  $T$  one at a time.
- Select the edges for inclusion in  $T$  in nondecreasing order of their cost.
- An edge is added to  $T$  if it does not form a cycle with the edges that are already in  $T$ .
  - How to do this?
- Exactly  $n - 1$  edges will be selected for inclusion in  $T$ .



## Kruskal's Algorithm

- Build a minimum cost spanning tree  $T$  by adding edges to  $T$  one at a time.
- Select the edges for inclusion in  $T$  in nondecreasing order of their cost.
- An edge is added to  $T$  if it does not form a cycle with the edges that are already in  $T$ .
  - How to do this?  $\Rightarrow$  Union-Find Operations!
- Exactly  $n - 1$  edges will be selected for inclusion in  $T$ .




## Kruskal's Algorithm


- Build a minimum cost spanning tree  $T$  by adding edges to  $T$  one at a time.
- Select the edges for inclusion in  $T$  in nondecreasing order of their cost.
- An edge is added to  $T$  if it does not form a cycle with the edges that are already in  $T$ .
  - How to do this?  $\Rightarrow$  Union-Find Operations!
- Exactly  $n - 1$  edges will be selected for inclusion in  $T$ .
- Time complexity:  $O(e \log n)$  (assume using tree-based Union-Find).
  - Sorting the edges:  $\approx e \log e < e \log n^2 = O(e \log n)$ .
  - At most  $2e$  find operations  $\approx \log n$  time for each.
  - At most  $2n - 1$  union operations  $\approx n$  time.



# Illustration of Kruskal's Algorithm



# Illustration of Kruskal's Algorithm




# Union-Find Operations

- Union-Find Operations: to determine whether or not adding an edge would cause a cycle.

# Union-Find Operations


- Union-Find Operations: to determine whether or not adding an edge would cause a cycle.
- For example,



- $\{0, 5\}, \{1, 2, 3, 6\}, \{4\}$ : the sets corresponding to existing subtrees.

# Union-Find Operations

- Union-Find Operations: to determine whether or not adding an edge would cause a cycle.
- For example,



- $\{0, 5\}, \{1, 2, 3, 6\}, \{4\}$ : the sets corresponding to existing subtrees.
- Vertex 3 and 6 are already in the same set  $\Rightarrow$  edge  $(3, 6)$  is rejected!

# The Pseudo-code of Kruskal's Algorithm

```
T = { };
while (T contains fewer than n-1 edges && E is not empty) {
    choose a least cost edge (v,w) from E;
    delete (v,w) from E;
    if ((v,w) does not create a cycle in T)
        add (v,w) to T
    else
        discard (v,w);
}
if (T contains fewer than n-1 edges)
    printf("No spanning tree\n");
```

- How could “No spanning tree” happen?

# Outline

1 Introduction

2 Kruskal's algorithm

3 Prim's algorithm

4 Sollin's algorithm

# Prim's Algorithm (1/3)

- Another greedy MST algorithm.



# Prim's Algorithm (1/3)

- Another greedy MST algorithm.
- The main difference:

# Prim's Algorithm (1/3)

- Another greedy MST algorithm.
- The main difference:
  - The set of selected edges forms a **tree at all times** in Prim's algorithm.
  - The set of selected edges in Kruskal's algorithm forms a *forest at each stage*.

# Prim's Algorithm (2/3)

- Prim's algorithm begins with a tree  $T$  that contains **one arbitrary single vertex**.

## Prim's Algorithm (2/3)

- Prim's algorithm begins with a tree  $T$  that contains **one arbitrary single vertex**.
- Next, we add a **least cost edge**  $(u, v)$  to  $T$  such that  $T \cup (u, v)$  is also a tree.

## Prim's Algorithm (2/3)


- Prim's algorithm begins with a tree  $T$  that contains **one arbitrary single vertex**.
- Next, we add a **least cost edge**  $(u, v)$  to  $T$  such that  $T \cup (u, v)$  is **also a tree**.
- Repeat this edge addition until  $T$  contains  $n - 1$  edges.

## Prim's Algorithm (2/3)

- Prim's algorithm begins with a tree  $T$  that contains **one arbitrary single vertex**.
- Next, we add a **least cost edge**  $(u, v)$  to  $T$  such that  $T \cup (u, v)$  is **also a tree**.
- Repeat this edge addition until  $T$  contains  $n - 1$  edges.

Time complexity:  $O(n^2)$ .

# Illustration of Prim's Algorithm




## Prim's Algorithm (3/3)

```
T = {};
TV = {0};


while (T contains fewer than n-1 edges) {
    let (u,v) be a least cost edge such that u is in TV and
    v is not in TV;
    if (there is no such edge )
        break;
    add v to TV;
    add (u,v) to T;
}
if (T contains fewer than n-1 edges)
    printf("No spanning tree\n");
```

- Each vertex  $v \notin TV$  has a companion vertex “ $\text{near}(v)$ ” such that  $\text{near}(v) \in TV$  and  $\text{cost}(\text{near}(v), v)$  is minimum over all such choices for  $\text{near}(v)$ .
- Therefore, it takes  $O(n)$  time to choose an edge.
- We can implement Prim's algorithm in  $O(n^2)$  time.



	inMST	cost
w	F	$\infty$
x	F	$\infty$
y	F	$\infty$
z	F	$\infty$
p	F	$\infty$
q	F	$\infty$
r	F	$\infty$


TV = { }



	inMST	cost
w	T	$\infty$
x	F	10
y	F	$\infty$
z	F	$\infty$
p	F	$\infty$
q	F	25
r	F	$\infty$




$TV = \{ w \}$



	inMST	cost
w	T	$\infty$
x	T	10
y	F	28
z	F	$\infty$
p	F	$\infty$
q	F	25
r	F	$\infty$



TV = { w, x }



	inMST	cost
w	T	$\infty$
x	T	10
y	F	28
z	F	$\infty$
p	F	22
q	T	25
r	F	$\infty$



$TV = \{ w, x, q \}$

# Outline

1 Introduction

2 Kruskal's algorithm

3 Prim's algorithm

4 Sollin's algorithm

# Sollin's Algorithm (1/2)

- Sollin's algorithm selects several edges for inclusion in  $T$  at each stage.
- At the start of a stage, the selected edges, together with all the  $n$  vertices, form a spanning forest.
- During each stage, we select one edge for each tree in the forest.
  - This edge is a minimum cost edge that has exactly one vertex in the tree.

# Sollin's Algorithm (2/2)

- **Note:** two trees in the forest could select the same edge.

## Sollin's Algorithm (2/2)

- **Note:** two trees in the forest could select the same edge.
  - We need to **eliminate duplicate edges**.

## Sollin's Algorithm (2/2)


- **Note:** two trees in the forest could select the same edge.
  - We need to **eliminate duplicate edges**.
- At the start of the first stage the set of selected edges is empty.

## Sollin's Algorithm (2/2)

- **Note:** two trees in the forest could select the same edge.
  - We need to **eliminate duplicate edges**.
- At the start of the first stage the set of selected edges is empty.
- The algorithm terminates when there is **only one tree at the end of a stage** or **no edges remain for selection**.


We can implement Sollin's algorithm in  $O(e \log v)$  time (WHY?).

# Illustration of Sollin's Algorithm



- Stage 1:  $(0,5), (1,6), (2,3), (3,2), (4,3), (5,0)$ , and  $(6,1)$  are selected, and then duplicates are removed.

# Illustration of Sollin's Algorithm



- Stage 2:  $(5, 4), (1, 2)$ , and  $(2, 1)$  are selected, and then duplicates are removed.

# Discussions