Arrays and Structures: Structures and Unions

Joseph Chuang-Chieh Lin (林莊傑)

Department of Computer Science & Engineering, National Taiwan Ocean University

Fall 2024

Outline

- Arrays
- Structures

Unions

Arrays and Structures: Structures and Unions
Arrays

Outline

- Arrays
- 2 Structures
- Unions

The Arrays as An ADT

- Arrays.
 - a set of pairs <index, value>.
 - for each index, there is a value associated with that index.
 - a consecutive set of memory locations.
 - mathematical terms: correspondence, mapping, etc.

Implementation of 1-D Array

- int list[5]
 - Five consecutive memory locations are allocated.
 - The address of list[0]: base address.
- int list[5], *plist[5];
 - sample code for the second.

variable	memory address
list[0]	base address $= b$
list[1]	$b+1 \times \texttt{sizeof(int)}$
list[2]	$b+2 \times \texttt{sizeof(int)}$
list[3]	$b+3 \times \texttt{sizeof(int)}$
list[4]	$b+4 imes exttt{sizeof(int)}$

Array in C

- Compare int *list1 and int list2[5] in C.
 - Both list1 and list2 are pointers.
 - list2 reserves five memory locations.
- Some notations:
 - list2:
 - (list2+i):
 - *(list2+i):

Array in C

- Compare int *list1 and int list2[5] in C.
 - Both list1 and list2 are pointers.
 - list2 reserves five memory locations.
- Some notations:
 - list2: a pointer to list2[0]
 - (list2+i): &list2[i]
 - *(list2+i): list2[i]

Arrays and Structures: Structures and Unions
Structures

Outline

- Arrays
- 2 Structures
- Unions

Structures

An array is a collection of data of the same type.

```
• int arr[] = { 0, 1, 2, 3, 4 };
```

 A structure is a collection of data items, where each item is identified as to its type and name.

```
struct employee {
   char name[10];
   int age;
   double salary;
};
struct employee person;
struct employee {
   char name[10];
   int age;
   double salary;
}
```

Usage of a struct Variable

```
struct employee {
   char name[10];
   int age;
   double salary;
} person;

strcpy(person.name, "Peter");
person.age = 10;
person.salary = 80000;
```

```
struct employee {
    string name; // C++
    int age;
    double salary;
} person;

person.name = "Peter";
person.age = 10;
person.salary = 80000;
```

typedef

```
typedef int COUNT;
COUNT num1, num2;
typedef struct employee HUMAN_BEING;
HUMAN_BEING person1, person2;
strcpy(person1.name, "Peter");
person.age = 10;
person.salary = 80000;
```

A structure within a structure is possible

```
typedef struct {
    int month;
    int day;
    int year;
} date;

typedef struct {
    char name[10];
    int age;
    float salary;
    date birthday;
} HUMAN_BEING;
```

The usage:

```
HUMAN_BEING person;
person.birthday.month = 10;
person.birthday.day = 31;
person.birthday.year = 1979;
```

Arrays and Structures: Structures and Unions
Unions

Outline

Arrays

- 2 Structures
- Unions

Unions

- Similar to structures.
- The fields of a union must share their memory space.
- Only one field of the union is active at any given time.

```
typedef struct {
   int sex;
   union {
      int kid;
      int beard;
   } u;
} SEX_TYPE;
```

Characteristics of Unions (code)

- The size of the union is the size of the largest member.
- Only one member can contain data at the same time.

```
union union1 {
    int x;
    int y;
} U1;

union union2 {
    int arr[10];
    char y;
} U2;
```

```
int size1 = sizeof(U1);
int size2 = sizeof(U2);
printf("Sizeof U1: %d\n", size1);
printf("Sizeof U2: %d\n", size2);
```

An Application Example

*binary tree (only leaf nodes have data)

```
struct Node {
   bool is_leaf;
   struct Node* left;
   struct Node* right;
   double data;
};
```

```
struct Node {
   bool is_leaf;
   union {
      struct {
        struct Node* left;
        struct Node* right;
      } internal;
      double data;
   } info;
};
```

Reference: GeeksforGeeks

Arrays and Structures: Structures and Unions

Discussions