

Randomized Algorithms

— Randomized QuickSort

Joseph Chuang-Chieh Lin

Department of Computer Science & Information Engineering,
Tamkang University

Fall 2023

Illustration (a binary tree T demonstrating RandQS)



Illustration (a binary tree T demonstrating RandQS)




Illustration (a binary tree T demonstrating RandQS)




Illustration (a binary tree T demonstrating RandQS)




Illustration (a binary tree T demonstrating RandQS)





Illustration (a binary tree T demonstrating RandQS)



Algorithm RandQS

Input: A set of (distinct) numbers S

Output: The elements of S sorted in increasing order.

- ① Choose an element $y \in S$ uniformly at random;
- ② By comparing each element of S with y , compute
 - $S_1 := \{x \in S : x < y\}$;
 - $S_2 := \{x \in S : x > y\}$;
- ③ Recursively sort S_1 (i.e., run $\text{RandQS}(S_1)$) and S_2 (i.e., run $\text{RandQS}(S_2)$), and output the sorted version of S_1 , followed by y , and then the sorted version of S_2 .

Analysis (Expected Number of Comparisons)

- Comparisons are performed in Step 2.
- Let $S_{(i)}$ denote the element of rank i (i.e., the i th smallest in S).
- Define X_{ij} :
 - $X_{ij} = 1$ if $S_{(i)}$ and $S_{(j)}$ are compared in an execution.
 - $X_{ij} = 0$ otherwise.

Analysis (Expected Number of Comparisons)

- Comparisons are performed in Step 2.
- Let $S_{(i)}$ denote the element of rank i (i.e., the i th smallest in S).
- Define X_{ij} :
 - $X_{ij} = 1$ if $S_{(i)}$ and $S_{(j)}$ are compared in an execution.
 - $X_{ij} = 0$ otherwise.
- Thus, the total number of comparisons is $\sum_{i=1}^n \sum_{j>i} X_{ij}$,

Analysis (Expected Number of Comparisons)

- Comparisons are performed in Step 2.
- Let $S_{(i)}$ denote the element of rank i (i.e., the i th smallest in S).
- Define X_{ij} :
 - $X_{ij} = 1$ if $S_{(i)}$ and $S_{(j)}$ are compared in an execution.
 - $X_{ij} = 0$ otherwise.
- Thus, the total number of comparisons is $\sum_{i=1}^n \sum_{j>i} X_{ij}$, and its expected value is

$$\mathbb{E} \left[\sum_{i=1}^n \sum_{j>i} X_{ij} \right]$$

Analysis (Expected Number of Comparisons)

- Comparisons are performed in Step 2.
- Let $S_{(i)}$ denote the element of rank i (i.e., the i th smallest in S).
- Define X_{ij} :
 - $X_{ij} = 1$ if $S_{(i)}$ and $S_{(j)}$ are compared in an execution.
 - $X_{ij} = 0$ otherwise.
- Thus, the total number of comparisons is $\sum_{i=1}^n \sum_{j>i} X_{ij}$, and its expected value is

$$\mathbb{E} \left[\sum_{i=1}^n \sum_{j>i} X_{ij} \right] = \sum_{i=1}^n \sum_{j>i} \mathbb{E}[X_{ij}].$$

Analysis (contd.)

- Let p_{ij} denote the probability that $S_{(i)}$ and $S_{(j)}$ are compared in an execution.

Analysis (contd.)

- Let p_{ij} denote the probability that $S_{(i)}$ and $S_{(j)}$ are compared in an execution.
- Since X_{ij} is a Bernoulli random variable, we have

$$\mathbf{E}[X_{ij}] =$$

Analysis (contd.)

- Let p_{ij} denote the probability that $S_{(i)}$ and $S_{(j)}$ are compared in an execution.
- Since X_{ij} is a Bernoulli random variable, we have

$$\mathbf{E}[X_{ij}] = p_{ij} \times 1 + (1 - p_{ij}) \times 0$$

Analysis (contd.)

- Let p_{ij} denote the probability that $S_{(i)}$ and $S_{(j)}$ are compared in an execution.
- Since X_{ij} is a Bernoulli random variable, we have

$$\mathbf{E}[X_{ij}] = p_{ij} \times 1 + (1 - p_{ij}) \times 0 = p_{ij}.$$

Analysis (contd.)

- Let p_{ij} denote the probability that $S_{(i)}$ and $S_{(j)}$ are compared in an execution.
- Since X_{ij} is a Bernoulli random variable, we have

$$\mathbf{E}[X_{ij}] = p_{ij} \times 1 + (1 - p_{ij}) \times 0 = p_{ij}.$$

- Note: $S_{(i)}$ and $S_{(j)}$ are compared in an execution only when one of them is an ancestor of the other in the binary tree T .

Analysis (contd.)

$$\sum_{i=1}^n \sum_{j>i} p_{ij} = \sum_{i=1}^n \sum_{j>i} \frac{2}{j-i+1}$$

Analysis (contd.)

$$\begin{aligned}\sum_{i=1}^n \sum_{j>i} p_{ij} &= \sum_{i=1}^n \sum_{j>i} \frac{2}{j-i+1} \\ &= \sum_{i=1}^n \sum_{j=i+1}^n \frac{2}{j-i+1}\end{aligned}$$

Analysis (contd.)

$$\begin{aligned}\sum_{i=1}^n \sum_{j>i} p_{ij} &= \sum_{i=1}^n \sum_{j>i} \frac{2}{j-i+1} \\ &= \sum_{i=1}^n \sum_{j=i+1}^n \frac{2}{j-i+1} \\ &= \sum_{i=1}^n \sum_{k=2}^{n-i+1} \frac{2}{k}\end{aligned}$$

Analysis (contd.)

$$\begin{aligned}
 \sum_{i=1}^n \sum_{j>i} p_{ij} &= \sum_{i=1}^n \sum_{j>i} \frac{2}{j-i+1} \\
 &= \sum_{i=1}^n \sum_{j=i+1}^n \frac{2}{j-i+1} \\
 &= \sum_{i=1}^n \sum_{k=2}^{n-i+1} \frac{2}{k} \\
 &\leq 2 \sum_{i=1}^n \sum_{k=1}^n \frac{1}{k} .
 \end{aligned}$$

Analysis (contd.)

$$\begin{aligned}
 \sum_{i=1}^n \sum_{j>i} p_{ij} &= \sum_{i=1}^n \sum_{j>i} \frac{2}{j-i+1} \\
 &= \sum_{i=1}^n \sum_{j=i+1}^n \frac{2}{j-i+1} \\
 &= \sum_{i=1}^n \sum_{k=2}^{n-i+1} \frac{2}{k} \\
 &\leq 2 \sum_{i=1}^n \sum_{k=1}^n \frac{1}{k} .
 \end{aligned}$$

- Note that $H_n = \sum_{k=1}^n 1/k$

Analysis (contd.)

$$\begin{aligned}
 \sum_{i=1}^n \sum_{j>i} p_{ij} &= \sum_{i=1}^n \sum_{j>i} \frac{2}{j-i+1} \\
 &= \sum_{i=1}^n \sum_{j=i+1}^n \frac{2}{j-i+1} \\
 &= \sum_{i=1}^n \sum_{k=2}^{n-i+1} \frac{2}{k} \\
 &\leq 2 \sum_{i=1}^n \sum_{k=1}^n \frac{1}{k} = O(n \log n).
 \end{aligned}$$

- Note that $H_n = \sum_{k=1}^n 1/k \approx \Theta(\ln n)$.

Exercise (3%)

Using $O(n)$ Median-of-Medians Algorithm

- **Remark:** The Median-of-Medians algorithm (reference [here](#)) by Blum et al. can compute a median of an array of n numbers in a list in $O(n)$ time deterministically.
- Please prove that Algorithm MedianQS (next page) can sort an array of n numbers in $O(n \log n)$ time deterministically.

Algorithm MedianQS

Input: A set of (distinct) numbers S

Output: The elements of S sorted in increasing order.

- ① Compute the median y of S using the Median-of-Medians algorithm;
- ② By comparing each element of S with y , compute
 - $S_1 := \{x \in S : x < y\}$;
 - $S_2 := \{x \in S : x > y\}$;
- ③ Recursively sort S_1 (i.e., run MedianQS(S_1)) and S_2 (i.e., run MedianQS(S_2)), and output the sorted version of S_1 , followed by y , and then the sorted version of S_2 .

Discussions