

Stacks

Joseph Chuang-Chieh Lin (林莊傑)

Department of Computer Science & Engineering,
National Taiwan Ocean University

Fall 2024



Outline

1 Definition

2 Implementation



Outline


1 Definition

2 Implementation



Definition

- A stack is an ordered list in which **insertions** and deletions are made at the end “top”.
 - insertions: push/add
 - deletions: pop/remove
- Last-In-First-Out (LIFO).



Outline


1 Definition

2 Implementation



Stack Implementation: Array


- The easiest way to implement the stack ADT is using one-dimensional array.



- An example in C++

Stack Implementation: Array

- The easiest way to implement the stack ADT is using one-dimensional array.



- An example in C++ (another way: using a linked list; will be introduced in the future).

Functions for Stacks

- Create a stack.
 - Create an empty stack with maximum size MAX_STACK_SIZE.

```
#define MAX_STACK_SIZE 101

typedef struct {
    int key; // can be of other types...
    /* other fields? */
} element;

element stack a[MAX_STACK_SIZE];
int top = -1; // initially no element
```



Functions for Stacks (2/2)

- **IsEmpty**
 - Return TRUE if the stack is empty and FALSE otherwise.



Functions for Stacks (2/2)

- **IsEmpty**
 - Return TRUE if the stack is empty and FALSE otherwise.
 $top < 0$
- **IsFull**
 - Return TRUE if the stack is full and FALSE otherwise.



Functions for Stacks (2/2)

- IsEmpty
 - Return TRUE if the stack is empty and FALSE otherwise.
 $top < 0$
- IsFull
 - Return TRUE if the stack is full and FALSE otherwise.
 $top \geq MAX_STACK_SIZE-1$
- Push (or Add)
 - Insert the element into the top of the stack.



Functions for Stacks (2/2)

- IsEmpty

- Return TRUE if the stack is empty and FALSE otherwise.

`top < 0`

- IsFull

- Return TRUE if the stack is full and FALSE otherwise.

`top >= MAX_STACK_SIZE-1`

- Push (or Add)

- Insert the element into the `top` of the stack.

`stack[++top] = element;`

- Pop (or Delete)

- Remove and return the item on the top of the stack.



Functions for Stacks (2/2)

- IsEmpty

- Return TRUE if the stack is empty and FALSE otherwise.

`top < 0`

- IsFull

- Return TRUE if the stack is full and FALSE otherwise.

`top >= MAX_STACK_SIZE-1`

- Push (or Add)

- Insert the element into the `top` of the stack.

`stack[++top] = element;`

- Pop (or Delete)


- Remove and return the item on the top of the stack.

`return stack[top--];`




Supplementary: System Stack

- Stack frame of a function call



system stack **before** a_1 is invoked



system stack **after** a_1 is invoked



Discussions

