

# Randomized Algorithms

## — Randomized QuickSort

Joseph Chuang-Chieh Lin

Department of Computer Science & Information Engineering,  
Tamkang University

Fall 2023

# Motivation

- We are concerned with prediction of future events and decision making.
- We build models that describe the **generative process** that generates the observed data.
- For example, consider the outcome of a coin-flip experiment (“heads” or “tails”).

# Motivation

- We are concerned with prediction of future events and decision making.
- We build models that describe the **generative process** that generates the observed data.
- For example, consider the outcome of a coin-flip experiment (“heads” or “tails”).
  - Define a parameter  $\mu$  which describes the probability of “heads” (the parameter of a Bernoulli distribution).

# Motivation

- We are concerned with prediction of future events and decision making.
- We build models that describe the **generative process** that generates the observed data.
- For example, consider the outcome of a coin-flip experiment (“heads” or “tails”).
  - Define a parameter  $\mu$  which describes the probability of “heads” (the parameter of a Bernoulli distribution).
  - Then, we can sample an outcome  $x \in \{\text{head}, \text{tail}\}$  from the Bernoulli distribution  $p(x \mid \mu) = \text{Ber}(\mu)$ .

# Motivation

- We are concerned with prediction of future events and decision making.
- We build models that describe the **generative process** that generates the observed data.
- For example, consider the outcome of a coin-flip experiment (“heads” or “tails”).
  - Define a parameter  $\mu$  which describes the probability of “heads” (the parameter of a Bernoulli distribution).
  - Then, we can sample an outcome  $x \in \{\text{head}, \text{tail}\}$  from the Bernoulli distribution  $p(x \mid \mu) = \text{Ber}(\mu)$ .
- **Note:**  $\mu$  is **unknown** in advance and can **never be observed directly**.


# Motivation

- We are concerned with prediction of future events and decision making.
- We build models that describe the **generative process** that generates the observed data.
- For example, consider the outcome of a coin-flip experiment (“heads” or “tails”).
  - Define a parameter  $\mu$  which describes the probability of “heads” (the parameter of a Bernoulli distribution).
  - Then, we can sample an outcome  $x \in \{\text{head}, \text{tail}\}$  from the Bernoulli distribution  $p(x \mid \mu) = \text{Ber}(\mu)$ .
- **Note:**  $\mu$  is **unknown** in advance and can **never be observed directly**.
- We need mechanisms to learn something about  $\mu$  given observed outcomes of coin-flip.

# Illustration (a binary tree $T$ demonstrating RandQS)




# Illustration (a binary tree $T$ demonstrating RandQS)







# Illustration (a binary tree $T$ demonstrating RandQS)




# Illustration (a binary tree $T$ demonstrating RandQS)



# Illustration (a binary tree $T$ demonstrating RandQS)



# Illustration (a binary tree $T$ demonstrating RandQS)



# Algorithm RandQS

**Input:** A set of (distinct) numbers  $S$

**Output:** The elements of  $S$  sorted in increasing order.

- ① Choose an element  $y \in S$  uniformly at random;
- ② By comparing each element of  $S$  with  $y$ , compute
  - $S_1 := \{x \in S : x < y\}$ ;
  - $S_2 := \{x \in S : x > y\}$ ;
- ③ Recursively sort  $S_1$  (i.e., run  $\text{RandQS}(S_1)$ ) and  $S_2$  (i.e., run  $\text{RandQS}(S_2)$ ), and output the sorted version of  $S_1$ , followed by  $y$ , and then the sorted version of  $S_2$ .

## Analysis (Expected Number of Comparisons)

- Comparisons are performed in Step 2.
- Let  $S_{(i)}$  denote the element of rank  $i$  (i.e., the  $i$ th smallest in  $S$ ).
- Define  $X_{ij}$ :
  - $X_{ij} = 1$  if  $S_{(i)}$  and  $S_{(j)}$  are compared in an execution.
  - $X_{ij} = 0$  otherwise.

## Analysis (Expected Number of Comparisons)

- Comparisons are performed in Step 2.
- Let  $S_{(i)}$  denote the element of rank  $i$  (i.e., the  $i$ th smallest in  $S$ ).
- Define  $X_{ij}$ :
  - $X_{ij} = 1$  if  $S_{(i)}$  and  $S_{(j)}$  are compared in an execution.
  - $X_{ij} = 0$  otherwise.
- Thus, the total number of comparisons is  $\sum_{i=1}^n \sum_{j>i} X_{ij}$ ,

## Analysis (Expected Number of Comparisons)

- Comparisons are performed in Step 2.
- Let  $S_{(i)}$  denote the element of rank  $i$  (i.e., the  $i$ th smallest in  $S$ ).
- Define  $X_{ij}$ :
  - $X_{ij} = 1$  if  $S_{(i)}$  and  $S_{(j)}$  are compared in an execution.
  - $X_{ij} = 0$  otherwise.
- Thus, the total number of comparisons is  $\sum_{i=1}^n \sum_{j>i} X_{ij}$ , and its expected value is

$$\mathbb{E} \left[ \sum_{i=1}^n \sum_{j>i} X_{ij} \right]$$



## Analysis (Expected Number of Comparisons)

- Comparisons are performed in Step 2.
- Let  $S_{(i)}$  denote the element of rank  $i$  (i.e., the  $i$ th smallest in  $S$ ).
- Define  $X_{ij}$ :
  - $X_{ij} = 1$  if  $S_{(i)}$  and  $S_{(j)}$  are compared in an execution.
  - $X_{ij} = 0$  otherwise.
- Thus, the total number of comparisons is  $\sum_{i=1}^n \sum_{j>i} X_{ij}$ , and its expected value is

$$\mathbb{E} \left[ \sum_{i=1}^n \sum_{j>i} X_{ij} \right] = \sum_{i=1}^n \sum_{j>i} \mathbb{E}[X_{ij}].$$

## Analysis (contd.)

- Let  $p_{ij}$  denote the probability that  $S_{(i)}$  and  $S_{(j)}$  are compared in an execution.

## Analysis (contd.)

- Let  $p_{ij}$  denote the probability that  $S_{(i)}$  and  $S_{(j)}$  are compared in an execution.
- Since  $X_{ij}$  is a Bernoulli random variable, we have

$$\mathbf{E}[X_{ij}] =$$

## Analysis (contd.)

- Let  $p_{ij}$  denote the probability that  $S_{(i)}$  and  $S_{(j)}$  are compared in an execution.
- Since  $X_{ij}$  is a Bernoulli random variable, we have

$$\mathbf{E}[X_{ij}] = p_{ij} \times 1 + (1 - p_{ij}) \times 0$$

## Analysis (contd.)

- Let  $p_{ij}$  denote the probability that  $S_{(i)}$  and  $S_{(j)}$  are compared in an execution.
- Since  $X_{ij}$  is a Bernoulli random variable, we have

$$\mathbf{E}[X_{ij}] = p_{ij} \times 1 + (1 - p_{ij}) \times 0 = p_{ij}.$$

## Analysis (contd.)

- Let  $p_{ij}$  denote the probability that  $S_{(i)}$  and  $S_{(j)}$  are compared in an execution.
- Since  $X_{ij}$  is a Bernoulli random variable, we have

$$\mathbf{E}[X_{ij}] = p_{ij} \times 1 + (1 - p_{ij}) \times 0 = p_{ij}.$$

- Note:  $S_{(i)}$  and  $S_{(j)}$  are compared in an execution only when one of them is an ancestor of the other in the binary tree  $T$ .

## Analysis (contd.)

$$\sum_{i=1}^n \sum_{j>i} p_{ij} = \sum_{i=1}^n \sum_{j>i} \frac{2}{j-i+1}$$

## Analysis (contd.)

$$\begin{aligned}\sum_{i=1}^n \sum_{j>i} p_{ij} &= \sum_{i=1}^n \sum_{j>i} \frac{2}{j-i+1} \\ &= \sum_{i=1}^n \sum_{j=i+1}^n \frac{2}{j-i+1}\end{aligned}$$



## Analysis (contd.)

$$\begin{aligned}\sum_{i=1}^n \sum_{j>i} p_{ij} &= \sum_{i=1}^n \sum_{j>i} \frac{2}{j-i+1} \\ &= \sum_{i=1}^n \sum_{j=i+1}^n \frac{2}{j-i+1} \\ &= \sum_{i=1}^n \sum_{k=1}^{n-i+1} \frac{2}{k}\end{aligned}$$

# Analysis (contd.)

$$\begin{aligned}
 \sum_{i=1}^n \sum_{j>i} p_{ij} &= \sum_{i=1}^n \sum_{j>i} \frac{2}{j-i+1} \\
 &= \sum_{i=1}^n \sum_{j=i+1}^n \frac{2}{j-i+1} \\
 &= \sum_{i=1}^n \sum_{k=1}^{n-i+1} \frac{2}{k} \\
 &\leq 2 \sum_{i=1}^n \sum_{k=1}^n \frac{1}{k} .
 \end{aligned}$$

# Analysis (contd.)

$$\begin{aligned}
 \sum_{i=1}^n \sum_{j>i} p_{ij} &= \sum_{i=1}^n \sum_{j>i} \frac{2}{j-i+1} \\
 &= \sum_{i=1}^n \sum_{j=i+1}^n \frac{2}{j-i+1} \\
 &= \sum_{i=1}^n \sum_{k=1}^{n-i+1} \frac{2}{k} \\
 &\leq 2 \sum_{i=1}^n \sum_{k=1}^n \frac{1}{k} .
 \end{aligned}$$

- Note that  $H_n = \sum_{k=1}^n 1/k$

# Analysis (contd.)

$$\begin{aligned}
 \sum_{i=1}^n \sum_{j>i} p_{ij} &= \sum_{i=1}^n \sum_{j>i} \frac{2}{j-i+1} \\
 &= \sum_{i=1}^n \sum_{j=i+1}^n \frac{2}{j-i+1} \\
 &= \sum_{i=1}^n \sum_{k=1}^{n-i+1} \frac{2}{k} \\
 &\leq 2 \sum_{i=1}^n \sum_{k=1}^n \frac{1}{k} = O(n \log n).
 \end{aligned}$$

- Note that  $H_n = \sum_{k=1}^n 1/k \approx \Theta(\ln n)$ .

# Discussions