

Connected Components & Spanning Trees

Joseph Chuang-Chieh Lin (林莊傑)

Department of Computer Science & Engineering,
National Taiwan Ocean University

Fall 2024

Outline

1 Connected Components

- Finding the articulation points

Outline

1 Connected Components

- Finding the articulation points

Connectivity

Problem I

Determine if an (un)directed graph is connected.

Connectivity

Problem I

Determine if an (un)directed graph is connected.

We can solve this problem by calling either $\text{dfs}(v)$ or $\text{bfs}(v)$ for an arbitrary vertex $v \in V(G)$, and then determining if there are **any unvisited vertices**.

Connectivity

Problem I

Determine if an (un)directed graph is connected.

We can solve this problem by calling either $\text{dfs}(v)$ or $\text{bfs}(v)$ for an arbitrary vertex $v \in V(G)$, and then determining if there are **any unvisited vertices**.

Problem II

List all connected components of an (un)directed graph.

Connectivity

Problem I

Determine if an (un)directed graph is connected.

We can solve this problem by calling either $\text{dfs}(v)$ or $\text{bfs}(v)$ for an arbitrary vertex $v \in V(G)$, and then determining if there are **any unvisited vertices**.

Problem II

List all connected components of an (un)directed graph.

This can be done by making repeated calls to either $\text{dfs}(v)$ or $\text{bfs}(v)$ where v is an **unvisited vertex**.




Finding articulation points (1/3)

We can find biconnected components of a graph G using any depth-first spanning of G .


Back edges

- Tree edges: DFS
- Nontree edges: we call them **back edges**



Observations


- The root of a depth first spanning tree is an articulation point if and only if it has ≥ 2 children.
- Any other vertex u is an articulation point if and only if it has ≥ 1 child w such that we cannot reach an ancestor of u using that consists of only w , descendants of w , and a single back edge.



- v_5 is an articulation point

Observations

- The root of a depth first spanning tree is an articulation point if and only if it has ≥ 2 children.
- Any other vertex u is an articulation point if and only if it has ≥ 1 child w such that we cannot reach an ancestor of u using that consists of only w , descendants of w , and a single back edge.



- v_5 is an articulation point, but v_6 is NOT.

Finding articulation points (2/3)

$\text{dfn}(v)$

The depth first numbers, or dfn , of the vertices give the sequence in which the vertices are visited during the depth first search.



Finding articulation points (2/3)

$\text{dfn}(v)$

The depth first numbers, or dfn , of the vertices give the sequence in which the vertices are visited during the depth first search.


- If u is an ancestor of v in the depth first spanning tree, then $\text{dfn}(u) < \text{dfn}(v)$.

$\text{low}(v)$

The $\text{low}(u)$ value of vertex u is the lowest depth first number that we can reach from u using a path of descendants followed by at most 1 back edge:

$$\text{low}(u) = \min \left\{ \begin{array}{l} \text{dfn}(u), \\ \min\{\text{low}(w) \mid w \text{ is a child of } u\}, \\ \min\{\text{dfn}(w) \mid (u, w) \text{ is a back edge}\} \end{array} \right.$$

Example of Computing dfn and low values



vertex	0	1	2	3	4	5	6	7	8	9
dfn	4	3	2	0	1	5	6	7	9	8
low	4	0	0	0	0	5	5	5	9	8

The codes for computing dfn and low

Time complexity: $O(e)$.

```
void dfn_low(int u, int v) {
    /* compute dfn and low while performing a dfs
    search beginning at vertex u, v is the parent
    of u (if any) */
    node_pointer ptr;
    int w;
    dfn[u] = low[u] = num++;
    for (ptr = graph[u]; ptr; ptr = ptr->link) {
        w = ptr ->vertex;
        if (dfn[w] < 0) {
            /*w is an unvisited vertex */
            dfn_low(w, u);
            low[u] = MIN2(low[u], low[w]);
        } else if (w != v)
            low[u] = MIN2(low[u], dfn[w]);
    }
}
```

```
short int dfn [MAX_VERTICES];
short int low[MAX_VERTICES];
int num = 0;

void init(void) {
    int i;
    for(i = 0; i < n; i++) {
        visited[i] = FALSE;
        dfn[i] = low[i] = -1;
    }
    num = 0;
}
```

bootstrapping by

`dfn_low(x, -1)`



Finding articulation points (3/3)

articulation points

u is an articulation point iff one of the following conditions are satisfied:

- u is the root of the spanning tree and has two or more children.
- u is not the root of the spanning tree and u has a child w such that $\text{low}(w) \geq \text{dfn}(u)$.




Finding articulation points (3/3)

articulation points

u is an articulation point iff one of the following conditions are satisfied:

- u is the root of the spanning tree and has two or more children.
- u is not the root of the spanning tree and u has a child w such that $\text{low}(w) \geq \text{dfn}(u)$.




vertex	0	1	2	3	4	5	6	7	8	9
dfn	4	3	2	0	1	5	6	7	9	8
low	4	0	0	0	0	5	5	5	9	8

Finding articulation points (3/3)

articulation points

u is an articulation point iff one of the following conditions are satisfied:

- u is the root of the spanning tree and has two or more children.
- u is not the root of the spanning tree and u has a child w such that $\text{low}(w) \geq \text{dfn}(u)$.



vertex	0	1	2	3	4	5	6	7	8	9
dfn	4	3	2	0	1	5	6	7	9	8
low	4	0	0	0	0	5	5	5	9	8

- articulation points: 1, 3, 5, 7.

Algorithm for Finding Biconnected Components

If we have $\text{low}[w] \geq \text{dfn}(v)$ when $\text{dfn_low}(u, w)$ returns.



Code for Biconnected Components ($O(n + e)$ time)


```

void bicon(int u, int v) { /* dfn[] = -1, num = 0, s is an empty stack initially*/
    nodePointer ptr;
    int w, x , y;
    dfn[u] = low[u] = num++;
    for (ptr = graph[u]; ptr; ptr = ptr->link) {
        w = ptr->vertex;
        if (v != w && dfn[w] < dfn[u]) {
            push(u,w); /* add edge (u,w) into stack s */
            if (dfn[w] < 0) { /* w is not visited yet */
                bicon(w, u);
                low[u] = MIN2(low[u],low[w]);
                if (low[w] >= dfn[u]) {
                    printf("New biconnected component:");
                    do { /* pop an edge from stack s */
                        pop(&x, &y);
                        printf("<%d,%d>",x, y);
                    } while (!(x == u) && (y == w));
                    printf("\n");
                }
            } else if (w != v)
                low[u] = MIN2(low[u],dfn[w]);
        }
    }
}


```




Illustration




Illustration




Illustration




Illustration




Illustration




Illustration




Illustration




Illustration




Illustration




Illustration




Illustration




Illustration




Illustration




Illustration




Illustration




Illustration




Illustration




Illustration




Illustration




Illustration




Illustration




Illustration




Illustration




Illustration




Illustration




Illustration




Illustration




Illustration




Illustration




Illustration




Illustration




Illustration




Illustration




Illustration




Illustration




Illustration




Illustration




Illustration




Illustration



Illustration



Illustration



Discussions