C++

程式語言 (二)


Introduction to Programming (II)

Inheritance

Joseph Chuang-Chieh Lin

Dept. CSE, NTOU

Platform/IDE



OnlineGDB (https://www.onlinegdb.com/)



• Real-Time Collaborative Online IDE (https://ide.usaco.guide/)



Textbooks (We focusing on C++11)

- Learn C++ Programming by Refactoring (由重構學習 C++ 程式設計). Pang-Feng Liu (劉邦鋒). NTU Press. 2023.
- C++ Primer. 5th Edition. Stanley B. Lippman, Josée Lajoie, Barbara E. Moo. 2019.
- *Effective C++*. Scott Meyers. O'Reilly. 2016.
- *Thinking in C++*. *Vol. 1: Introducing to Standard C++*. 2nd Edition. Bruce Eckel. Prentice Hall PTR. 2000.

Useful Resources

- Tutorialspoint
 - https://www.tutorialspoint.com/cplusplus/index.htm
 - Online C++ Compiler
- Programiz
 - https://www.programiz.com/cpp-programming
- LEARN C++
 - https://www.learncpp.com/
- MIT OpenCourseWare Introduction to C++
 - https://ocw.mit.edu/courses/6-096-introduction-to-c-january-iap-2011/pages/lecture-notes/
- Learning C++ Programming
 - https://www.programiz.com/cpp-programming
- GeeksforGeeks
 - https://www.geeksforgeeks.org/c-plus-plus/

Inheritance


Inheritance

https://www.geeksforgeeks.org/inheritance-in-c/?ref=lbp

- Get rid of duplication of the same codes.
- Decrease the chance of error.
- Increase code and data reusability.
- Abstraction + Hierarchy

Class Car Class Bus

Class Track



An Easy Illustrating Example

```
class A
public:
    int x;
protected:
    int y;
                       access mode_
private:
    int z;
};
class B (: public )A
    // x is public
    // y is protected
    // z is not accessible from B
};
```

```
class C (: protected )A
    // x is protected
    // y is protected
    // z is not accessible from C
class D : private A
// 'private' is default for classes
    // x is private
    // y is private
    // z is not accessible from D
};
```

Modes of Inheritance

Just like going through a mask...


Public

Example: https://onlinegdb.com/Z7tf4BU0x

- public member of the base class => public in the derived class.
- protected members of the base class => protected in derived class.
- private members of the base class => not accessible.
- Protected
 - public member of the base class => protected in the derived class.
 - protected members of the base class => protected in derived class.
 - private members of the base class => not accessible.
- Private
 - public member of the base class => private in the derived class.
 - protected members of the base class => private in derived class.
 - private members of the base class => not accessible.

Single Inheritance

```
#include<iostream>
using namespace std;
class Vehicle {
public:
    Vehicle() {
      cout << "This is a Vehicle.\n";</pre>
};
class Car : public Vehicle {
// nothing to do here so far...
};
```



```
int main()
{
    // invoke the constructors
    Car obj;
    return 0;
}
```

Output:

This is a Vehicle.


ming Languages, CSE, NTOU, Taiwan

Multiple Inheritance

```
#include<iostream>
using namespace std;
class Vehicle {
public:
    Vehicle() {
      cout << "This is a Vehicle.\n";</pre>
};
class FourWheeler {
public:
    FourWheeler() {
         cout << "This is a 4 wheeler
                  Vehicle.\n";
};
```

```
class Car : public Vehicle, public FourWheeler {
    // nothing to do here so far...
};
                                Class
                                            Class
```

Vehicle



Output:

C++ Programmi

This is a Vehicle.

This is a 4 wheeler Vehicle.

FourWheeler

Class

Car

Multilevel Inheritance

```
#include<iostream>
                                                 class Car: public FourWheeler {
                                                 public:
using namespace std;
                                                      Car() {
                                                        cout << "A Car has 4 Wheels.\n";</pre>
class Vehicle {
public:
    Vehicle() {
                                                 };
      cout << "This is a Vehicle.\n";</pre>
                                                                                         Class
                                                                                        Vehicle
                                                 int main()
} ;
class FourWheeler: public Vehicle {
                                                     // invoke the constructors
public:
                                                     Car obj;
    FourWheeler() {
                                                                                         Class
                                                     return 0;
         cout << "A 4 wheeler Vehicle.\n":
                                                                                     FourWheeler
};
                                                                                         Class
```

Output:

This is a Vehicle. A 4 wheeler Vehicle. A Car has 4 Wheels.

Car

More Details in Examples

• https://www.programiz.com/cpp-programming/public-protected-private-inheritance

Class Exercise (1%)

```
class Shape {
                                       int main()
public:
    string type;
                                           Circle obj;
protected:
                                           obj.setRadius();
    double parameter;
                                           obj.compute area();
};
                                           return 0;
class Circle : protected Shape {
private:
    double area = 0.0;
public:
   void compute area()
                                                          Sample Input & Output:
/* please implement this member function */
   void setRadius()
/* please implement this member function */
    double getArea() {
/* please implement this member function */
```

cout << "Area: " << obj.getArea();</pre>

3.2 Area: 32.1699

Exercise

```
class A {
public:
    int x = 0;
    int get_pvt() { return z; }
protected:
    int y = 1;
private:
    int z = 2;
};

class B : public A {
    // x is public
    // y is protected
    // z is not accessible from B
};
```

Please modify the code here by "adding appropriate member functions" in the the classes B, C, and D.

```
class C : protected A {
    // x is protected
    // y is protected
    // z is not accessible from C
};

class D : private A {
    // 'private' is default for classes
        // x is private
        // y is private
        // z is not accessible from D
};
```

```
int main () {
    B obj1;
    C obj2;
    D obj3;
    cout << obj1.x << obj2.y << obj3.y;
    // try to print these values
    // by adding appropriate member
    // functions
}</pre>
```

Discussions & Questions