Trees

Trees, Binary Trees & Representations

Joseph Chuang-Chieh Lin (林莊傑)

Department of Computer Science & Engineering,
National Taiwan Ocean University

Fall 2026




Outline

1. Introduction
   - Representation of Trees
2. Binary Trees
   - Binary Tree Representations




Outline

1. Introduction
   - Representation of Trees
2. Binary Trees
   - Binary Tree Representations





Introduction

- Intuitively, a tree structure organized data in a hierarchical manner.




Example: Pedigree Chart




Example: Mathematical Genealogy Project

Figure reference: https://www.mathgenealogy.org/



Example: Mathematical Genealogy Project

Figure reference: https://www.mathgenealogy.org/



Well, actually it is not a tree...

Definitions

Tree


- A tree is a finite set of one or more nodes such that:
  - There is a specially designated node called root.
  - The remaining nodes are partitioned into $n \geq 0$ disjoint sets, $T_1, T_2, \ldots, T_n$, where each of these sets is a tree.
  - $T_1, T_2, \ldots, T_n$: subtrees of the root.



Definitions

Node

- A node stands for the item of information plus the branches to other nodes.



Definitions

Degree


- The number of subtrees of a node is called its degree.




Definitions

Degree

- The number of subtrees of a node is called its degree.
  - $\deg(A) = 3$, $\deg(C) = 1$, $\deg(F) = 0$.



Definitions

Leaf, children, parent


- A node that has degree 0 is called a leaf or terminal.



Definitions

Leaf, children, parent


- A node that has degree 0 is called a leaf or terminal.
- The roots of the subtrees of a node X are the children of X. X is the parent of its children.



Definition

Siblings, degree, ancestors


- Children of the same parent are said to be siblings.
  - Example: H, I and J are siblings; B, C and D are siblings.
- The degree of a tree is the **maximum** of the degree of the nodes in the tree.
  - The tree in this example has degree 3.
- The ancestors of a node are all the nodes along the path from the root to that node.
  - The ancestors of M are A, D, and H.



Definition

Level & depth


- The level of a node:
  - the root: 1.
  - if a node is at level k, then its children are at level $k+1$.
- The depth of a node (number of edges from the node to the root).
  - the root: $\mathbf{0}$.
  - if a node is at depth k, then its children are at level $k+1$.
- Example: level$(A) = 1$, level$(H) = 3$, level$(L) = 4$, depth$(A) = 0$, depth$(H) = 2$, depth$(L) = 3$.



Definition

Height

- The height of a node:
  - the number of edges on the longest path from the node to a leaf.
  - Example: hight$(A) = 3$, hight$(H) = 1$, hight$(L) = 0$.
- The height or depth of a **tree** is defined to be the depth of the tree's root.
  - The depth of the tree in this example is 3.




Representation of Trees

- The tree in the example can be written as

$$(A(B(E(K, L), F), C(G), D(H(M), I, J))).$$

- **Rule:** root node $\rightarrow$ list of its subtrees.



A Possible Node Structure of a Tree of Degree k

- The degree of each tree node may be different.



A Possible Node Structure of a Tree of Degree k

- The degree of each tree node may be different.
  - we may be tempted to use memory nodes with a varying number of pointer fields.
- However, one only uses nodes of a fixed size to represent tree nodes in practice.

data	child 1	child 2	$\cdots$	child k



A Possible Node Structure of a Tree of Degree k

- The degree of each tree node may be different.
  - we may be tempted to use memory nodes with a varying number of pointer fields.
- However, one only uses nodes of a fixed size to represent tree nodes in practice.

data	child 1	child 2	$\cdots$	child k

- Then, how to choose such a fixed size?



Waste of Space

Lemma 5.1

If T is a k-ary tree (i.e., a tree of degree k) with n nodes ($n \geq 1$), each having a fixed size, then $n(k-1)+1$ of the nk child fields are 0.

data	child 1	child 2	$\cdots$	child k

Proof

- The number of edges of T: $n-1$
  - Hence, the number of non-zero child fields in T is exactly $n-1$.




Waste of Space

Lemma 5.1

If T is a k-ary tree (i.e., a tree of degree k) with n nodes ($n \geq 1$), each having a fixed size, then $n(k-1)+1$ of the nk child fields are 0.

data	child 1	child 2	$\cdots$	child k

Proof

- The number of edges of T: $n-1$
  - Hence, the number of non-zero child fields in T is exactly $n-1$.
  - The total number of child fields in a k-ary tree with n nodes is nk.




Waste of Space

Lemma 5.1

If T is a k-ary tree (i.e., a tree of degree k) with n nodes ($n \geq 1$), each having a fixed size, then $n(k-1)+1$ of the nk child fields are 0.

data	child 1	child 2	$\cdots$	child k

Proof

- The number of edges of T: $n-1$
  - Hence, the number of non-zero child fields in T is exactly $n-1$.
  - The total number of child fields in a k-ary tree with n nodes is nk.
  - Thus, the number of zero fields is $nk-(n-1) = n(k-1)+1$.





Left Child-Right Sibling Representation


- Every node has ≤ 1 leftmost child and ≤ 1 closest right sibling.
- The **left child field** of each node points to its leftmost child (if any)
- The **right sibling field** points to its closest right sibling (if any).

data	
left child	right sibling









left child

right sibling

Outline

1. Introduction
   - Representation of Trees
2. Binary Trees
   - Binary Tree Representations




Binary Trees

Binary Trees

A binary tree is a finite set of nodes that

- consists of a root
- two disjoint binary trees: the left subtree and the right subtree.




Trees vs. Binary Trees

Notice

In a binary tree we distinguish between the order of the children while in a tree we do not.

- The following two binary trees are different.
  - the first binary tree has an empty right subtree
  - the second has an empty left subtree.




Trees vs. Binary Trees

Notice


In a binary tree we distinguish between the order of the children while in a tree we do not.

- The following two binary trees are different.
  - the first binary tree has an empty right subtree
  - the second has an empty left subtree.



Skew Binary Trees & Complete Binary Trees

- skew: only left (or right) subtrees for each node
- complete: all leaf nodes of these trees are on two adjacent levels (its formal definition will be given later).



(a): skewed tree


(b): complete binary tree

Properties of Binary Trees

Lemma 5.2 [Maximum Number of Nodes]

- The maximum number of nodes on level i of a binary tree is 2^{i-1}, for $i \geq 1$.
- The maximum number of nodes in a binary tree of depth k is $2^{k+1} - 1$, for $k \geq 0$.

- On level 2: 2 nodes; on level 3: 4 nodes.
- Totally $2^3 - 1 = 7$ nodes in the binary tree.



Proof of Lemma 5.2

- Induction Base:
  - The root is the only node on level 1. $2^{1-1} = 2^0 = 1$.
- Induction Hypothesis: Assume that the maximum number of nodes on level $i-1$ is 2^{i-2}.
- Induction Step:
  - The maximum number of nodes on level $i-1$ (i.e., depth $i-2$) is 2^{i-2} by the induction hypothesis.
  - Since each node in a binary tree has a maximum degree of 2, the maximum number of nodes on level i (i.e., depth $i-1$) is $2^{i-2} \cdot 2 = 2^{i-1}$.



Proof of Lemma 5.2

- Induction Base:
  - The root is the only node on level 1. $2^{1-1} = 2^0 = 1$.
- Induction Hypothesis: Assume that the maximum number of nodes on level $i-1$ is 2^{i-2}.
- Induction Step:
  - The maximum number of nodes on level $i-1$ (i.e., depth $i-2$) is 2^{i-2} by the induction hypothesis.
  - Since each node in a binary tree has a maximum degree of 2, the maximum number of nodes on level i (i.e., depth $i-1$) is $2^{i-2} \cdot 2 = 2^{i-1}$.
- The maximum number of nodes in a binary tree of depth k is

$$1 + 2 + 2^2 + \cdots + 2^k = \sum_{i=0}^{k} 2^i = 2^{k+1} - 1.$$



Full Binary Tree

Full Binary Tree

A full binary tree of depth k is a binary tree of depth k having $2^{k+1} - 1$ nodes, for $k \geq 0$.

Complete Binary Tree

A binary tree with n nodes and depth k is complete iff its nodes correspond to the nodes numbered from 1 to n in the full binary tree of depth k.

- From Lemma 5.2, we know that

The height of a complete binary tree with n nodes is $\lceil \lg(n+1) \rceil - 1$.




Full Binary Tree

Full Binary Tree

A full binary tree of depth k is a binary tree of depth k having $2^{k+1} - 1$ nodes, for $k \geq 0$.

Complete Binary Tree

A binary tree with n nodes and depth k is complete iff its nodes correspond to the nodes numbered from 1 to n in the full binary tree of depth k.


- From Lemma 5.2, we know that

The height of a complete binary tree with n nodes is $\lceil \lg(n+1) \rceil - 1$.


- ⋆ **Note:** A complete binary tree is NOT necessarily a full binary tree!
- $\lg n := \log_2 n$.




Complete Binary Tree



Clarification of Complete Binary Trees



NOT a complete binary tree




a complete binary tree

Binary Tree Array Representation


Lemma 5.4

If a complete binary tree with n nodes is represented sequentially, then for any node with index i, $1 \leq i \leq n$, we have

- parent(i) is at $\lfloor i/2 \rfloor$ if $i \neq 1$. If $i = 1$, i is at root so it has no parent.
- leftChild(i) is at $2i$ if $2i \leq n$. If $2i > n$, then i has no left child.
- rightChild(i) is at $2i + 1$ if $2i + 1 \leq n$. If $2i + 1 > n$, then i has no right child.




Binary Tree Representation: Examples



tree

[0]	
[1]	A
[2]	B
[3]	
[4]	C
[5]	
[6]	
[7]	
[8]	D
[9]	
...	
[16]	E

Binary Tree Representation: Examples



tree

[0]	
[1]	A
[2]	B
[3]	C
[4]	D
[5]	E
[6]	F
[7]	G
[8]	H
[9]	I


Drawbacks of the Array Representation

- Waste memory space for most binary trees.
- In the worst case, a skewed tree of depth k requires $2^k - 1$ spaces.
  - Only k spaces is occupied.
- Insertion or deletion of nodes from the middle of a tree requires the movement of potentially many nodes.




Try Linked List Representation

```
typedef struct node *treePointer;
typedef struct node {
    int data;
    treePointer leftChild, rightChild;
};
```




leftChild	data	rightChild

Example




Example




Comparisons and Recall




tree




left child-right sibling




binary tree



tree



left child-right sibling



binary tree

Discussions

