

Arrays and Structures

Matrix Transpose & Multiplication

Joseph Chuang-Chieh Lin (林莊傑)

Department of Computer Science & Engineering,
National Taiwan Ocean University

Fall 2026



Outline

- 1 Matrix Transpose
 - Fast Matrix Transpose
- 2 Matrix Multiplication



Outline

- 1 Matrix Transpose
 - Fast Matrix Transpose
- 2 Matrix Multiplication



Transposing a Matrix (1/4)

$M \in \mathbb{Z}^{6 \times 6}$:

$$\begin{bmatrix} 15 & 0 & 0 & 22 & 0 & -15 \\ 0 & 11 & 3 & 0 & 0 & 0 \\ 0 & 0 & 0 & -6 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 \\ 91 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 28 & 0 & 0 & 0 \end{bmatrix}$$

Transposing a Matrix (1/4)

$M \in \mathbb{Z}^{6 \times 6}$:

$$\begin{bmatrix} 15 & 0 & 0 & 22 & 0 & -15 \\ 0 & 11 & 3 & 0 & 0 & 0 \\ 0 & 0 & 0 & -6 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 \\ 91 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 28 & 0 & 0 & 0 \end{bmatrix}$$

$M^T \in \mathbb{Z}^{6 \times 6}$:

$$\begin{bmatrix} 15 & 0 & 0 & 0 & 91 & 0 \\ 0 & 11 & 0 & 0 & 0 & 0 \\ 0 & 3 & 0 & 0 & 0 & 28 \\ 22 & 0 & -6 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 \\ -15 & 0 & 0 & 0 & 0 & 0 \end{bmatrix}$$

Transposing a Matrix (2/4)

$M \in \mathbb{Z}^{6 \times 6}$:

	Row	Col	Value
A[0]	6	6	8
A[1]	0	0	15
A[2]	0	3	22
A[3]	0	5	-15
A[4]	1	1	11
A[5]	1	2	3
A[6]	2	3	-6
A[7]	4	0	91
A[8]	5	2	28

Transposing a Matrix (2/4)

$M \in \mathbb{Z}^{6 \times 6}$:

	Row	Col	Value
A[0]	6	6	8
A[1]	0	0	15
A[2]	0	3	22
A[3]	0	5	-15
A[4]	1	1	11
A[5]	1	2	3
A[6]	2	3	-6
A[7]	4	0	91
A[8]	5	2	28

$M^T \in \mathbb{Z}^{6 \times 6}$:

	Row	Col	Value
A[0]	6	6	8
A[1]	0	0	15
A[2]	0	4	91
A[3]	1	1	11
A[4]	2	1	3
A[5]	2	5	28
A[6]	3	0	22
A[7]	3	2	-6
A[8]	5	0	-15



Transposing a Matrix (3/4)

Algorithm 1

- for each row i ,
 - place element $\langle i, j, \text{value} \rangle$ in element $\langle j, i, \text{value} \rangle$

Algorithm 2

- for each column j ,
 - place element $\langle i, j, \text{value} \rangle$ in element $\langle j, i, \text{value} \rangle$



Transposing a Matrix (3/4)

Algorithm 1

- for each **row** i ,
 - place element $\langle i, j, \text{value} \rangle$ in element $\langle j, i, \text{value} \rangle$

Algorithm 2

- for each **column** j ,
 - place element $\langle i, j, \text{value} \rangle$ in element $\langle j, i, \text{value} \rangle$
- What's the difficulty for Algorithm 1?



Transposing a Matrix (4/4) $O(\text{columns} \times \text{elements})$

```

void transpose(term a[], term b[]) { // b is set to the transpose of a
    int n, i, j, currentb;
    n = a[0].value; // total number of elements
    b[0].row = a[0].col; // rows in b = columns in a
    b[0].col = a[0].row; // columns in b = rows in a
    b[0].value = n;
    if (n > 0) { // dealing with a nonzero matrix
        currentb = 1;
        for (i=0; i<a[0].col; i++) // transpose by the columns in a
            for (j=1; j<=n; j++) // find elements from the current column
                if (a[j].col == i) { // element is in current column, add it to b
                    b[currentb].row = a[j].col;
                    b[currentb].col = a[j].row;
                    b[currentb].value = a[j].value;
                    currentb++;
                }
    }
}

```



Time Complexity of the Transpose Algorithm

- For matrices represented as 2-D arrays, the time complexity for computing a matrix transpose is $O(\text{columns} \times \text{rows})$.



Time Complexity of the Transpose Algorithm

- For matrices represented as 2-D arrays, the time complexity for computing a matrix transpose is $O(\text{columns} \times \text{rows})$.
- The complexity of the previous transpose algorithm:
 - $O(\text{columns} \times \text{elements})$.
 - $O(\text{columns} \times \text{columns} \times \text{rows})$ if $\text{elements} \approx \text{columns} \times \text{rows}$.



Time Complexity of the Transpose Algorithm

- For matrices represented as 2-D arrays, the time complexity for computing a matrix transpose is $O(\text{columns} \times \text{rows})$.
- The complexity of the previous transpose algorithm:
 - $O(\text{columns} \times \text{elements})$.
 - $O(\text{columns} \times \text{columns} \times \text{rows})$ if $\text{elements} \approx \text{columns} \times \text{rows}$.
- **Issue:** Scan the array for “#columns” times.



Alternative Solution

- Determine the starting positions of each row in the transpose matrix.
- Determine the number of elements in each column of the original matrix.

	[0]	[1]	[2]	[3]	[4]	[5]
row_terms	2	1	2	2	0	1
starting_pos	1	3	4	6	8	8

- Scan over `a[0].value` times to count `row_terms`.

	Row	Col	Value
A[0]	6	6	8
A[1]	0	0	15
A[2]	0	3	22
A[3]	0	5	-15
A[4]	1	1	11
A[5]	1	2	3
A[6]	2	3	-6
A[7]	4	0	91
A[8]	5	2	28

Alternative Solution

- Determine the starting positions of each row in the transpose matrix.
- Determine the number of elements in each column of the original matrix.

	[0]	[1]	[2]	[3]	[4]	[5]
row_terms	2	1	2	2	0	1
starting_pos	1	3	4	6	8	8

- Scan over `a[0].value` times to count `row_terms`.

$$\text{start} + \text{row_terms} = 1 + 2 = 3$$

	Row	Col	Value
A[0]	6	6	8
A[1]	0	0	15
A[2]	0	3	22
A[3]	0	5	-15
A[4]	1	1	11
A[5]	1	2	3
A[6]	2	3	-6
A[7]	4	0	91
A[8]	5	2	28

Alternative Solution

- Determine the starting positions of each row in the transpose matrix.
- Determine the number of elements in each column of the original matrix.

	[0]	[1]	[2]	[3]	[4]	[5]
row_terms	2	1	2	2	0	1
starting_pos	1	3	4	6	8	8

- Scan over `a[0].value` times to count `row_terms`.

$$\text{start} + \text{row_terms} = 1 + 2 = 3$$

	Row	Col	Value
A[0]	6	6	8
A[1]	0	0	15
A[2]	0	3	22
A[3]	0	5	-15
A[4]	1	1	11
A[5]	1	2	3
A[6]	2	3	-6
A[7]	4	0	91
A[8]	5	2	28

Alternative Solution

- Determine the starting positions of each row in the transpose matrix.
- Determine the number of elements in each column of the original matrix.

	[0]	[1]	[2]	[3]	[4]	[5]
row_terms	2	1	2	2	0	1
starting_pos	1	3	4	6	8	8

- Scan over `a[0].value` times to count `row_terms`.

$$\text{start} + \text{row_terms} = 3 + 1 = 4.$$

	Row	Col	Value
A[0]	6	6	8
A[1]	0	0	15
A[2]	0	3	22
A[3]	0	5	-15
A[4]	1	1	11
A[5]	1	2	3
A[6]	2	3	-6
A[7]	4	0	91
A[8]	5	2	28

Alternative Solution

- Determine the starting positions of each row in the transpose matrix.
- Determine the number of elements in each column of the original matrix.

	[0]	[1]	[2]	[3]	[4]	[5]
row_terms	2	1	2	2	0	1
starting_pos	1	3	4	6	8	8

- Scan over `a[0].value` times to count `row_terms`.

$$\text{start} + \text{row_terms} = 3 + 1 = 4.$$

	Row	Col	Value
A[0]	6	6	8
A[1]	0	0	15
A[2]	0	3	22
A[3]	0	5	-15
A[4]	1	1	11
A[5]	1	2	3
A[6]	2	3	-6
A[7]	4	0	91
A[8]	5	2	28

Outline

- 1 Matrix Transpose
 - Fast Matrix Transpose
- 2 Matrix Multiplication

Fast Transposing a Matrix ($O(\text{columns} + \text{elements})$)

```
void fast_transpose(term a[], term b[]) { // b is set to the transpose of a  
    int row_terms[MAX_COL], starting_pos[MAX_COL];  
    int i, j, num_cols = a[0].col, num_terms = a[0].value;  
    b[0].row = num_cols; b[0].col = a[0].row; b[0].value = num_terms;  
    if (num_terms > 0) { // nonzero matrix  
        for (i = 0; i < num_cols; i++)  
            row_terms[i] = 0; // initialization for the counting  
        for (i = 1; i <= num_terms; i++)  
            row_terms[a[i].col]++; // counting the row items  
        starting_pos[0] = 1;  
        for (i = 1; i < num_cols; i++) // calculate the starting positions  
            starting_pos[i] = starting_pos[i-1] + row_terms[i-1];  
        for (i = 1; i <= num_terms; i++) {  
            j = starting_pos[a[i].col]++;  
            b[j].row = a[i].col;  
            b[j].col = a[i].row;  
            b[j].value = a[i].value;  
        }  
    }  
}
```

Time Complexity of the Fast Transpose Algorithm

- $O(\text{columns} + \text{elements})$.
- $O(\text{columns} + \text{columns} \times \text{rows})$ if $\text{elements} \approx \text{columns} \times \text{rows}$.
- ★ Additional `row_terms` and `starting_pos` arrays are required.



Outline

- 1 Matrix Transpose
 - Fast Matrix Transpose
- 2 Matrix Multiplication



Matrix Multiplication

Matrix Multiplication

Given an $m \times n$ matrix A and an $n \times p$ matrix B , the product $D = A \times B$ is of shape $m \times p$, such that its (i, j) -th element is

$$d_{ij} = \sum_{k=0}^{n-1} a_{ik} b_{kj}$$

for $0 \leq i \leq m$ and $0 \leq j \leq p$.

- For example,

$$\begin{bmatrix} 1 & 0 & -2 \\ 0 & 3 & -1 \end{bmatrix} \begin{bmatrix} 0 & 3 \\ -2 & -1 \\ 0 & 4 \end{bmatrix} = \begin{bmatrix} 0 & -5 \\ -6 & -7 \end{bmatrix}$$



Matrix Multiplication

Matrix Multiplication

Given an $m \times n$ matrix A and an $n \times p$ matrix B , the product $D = A \times B$ is of shape $m \times p$, such that its (i, j) -th element is

$$d_{ij} = \sum_{k=0}^{n-1} a_{ik} b_{kj}$$

for $0 \leq i \leq m$ and $0 \leq j \leq p$.

- For example,

$$\begin{bmatrix} 1 & 0 & -2 \\ 0 & 3 & -1 \end{bmatrix} \begin{bmatrix} 0 & 3 \\ -2 & -1 \\ 0 & 4 \end{bmatrix} = \begin{bmatrix} 0 & -5 \\ -6 & -7 \end{bmatrix}$$



Matrix Multiplication

Matrix Multiplication

Given an $m \times n$ matrix A and an $n \times p$ matrix B , the product $D = A \times B$ is of shape $m \times p$, such that its (i, j) -th element is

$$d_{ij} = \sum_{k=0}^{n-1} a_{ik} b_{kj}$$

for $0 \leq i \leq m$ and $0 \leq j \leq p$.

- For example,

$$\begin{bmatrix} 1 & 0 & -2 \\ 0 & 3 & -1 \end{bmatrix} \begin{bmatrix} 0 & 3 \\ -2 & -1 \\ 0 & 4 \end{bmatrix} = \begin{bmatrix} 0 & -5 \\ -6 & -7 \end{bmatrix}$$



Matrix Multiplication

Matrix Multiplication

Given an $m \times n$ matrix A and an $n \times p$ matrix B , the product $D = A \times B$ is of shape $m \times p$, such that its (i, j) -th element is

$$d_{ij} = \sum_{k=0}^{n-1} a_{ik} b_{kj}$$

for $0 \leq i \leq m$ and $0 \leq j \leq p$.

- For example,

$$\begin{bmatrix} 1 & 0 & -2 \\ 0 & 3 & -1 \end{bmatrix} \begin{bmatrix} 0 & 3 \\ -2 & -1 \\ 0 & 4 \end{bmatrix} = \begin{bmatrix} 0 & -5 \\ -6 & -7 \end{bmatrix}$$



Matrix Multiplication

Matrix Multiplication

Given an $m \times n$ matrix A and an $n \times p$ matrix B , the product $D = A \times B$ is of shape $m \times p$, such that its (i, j) -th element is

$$d_{ij} = \sum_{k=0}^{n-1} a_{ik} b_{kj}$$

for $0 \leq i \leq m$ and $0 \leq j \leq p$.

- For example,

$$\begin{bmatrix} 1 & 0 & -2 \\ 0 & 3 & -1 \end{bmatrix} \begin{bmatrix} 0 & 3 \\ -2 & -1 \\ 0 & 4 \end{bmatrix} = \begin{bmatrix} 0 & -5 \\ -6 & -7 \end{bmatrix}$$



Using Matrix Transpose

$$A = \begin{bmatrix} -27 & 6 \\ 82 & 0 \\ 109 & -64 \end{bmatrix} :$$

	Row	Col	Value
A[0]	3	2	5
A[1]	0	0	-27
A[2]	0	1	6
A[3]	1	0	82
A[4]	2	0	109
A[5]	2	1	-64
A[6]	3		

$$B = \begin{bmatrix} 21 & 27 & 0 \\ 5 & 0 & -71 \end{bmatrix} :$$

	Row	Col	Value
B[0]	2	3	4
B[1]	0	0	21
B[2]	0	1	27
B[3]	1	0	5
B[4]	1	2	-71

Using Matrix Transpose

$$A = \begin{bmatrix} -27 & 6 \\ 82 & 0 \\ 109 & -64 \end{bmatrix} :$$

	Row	Col	Value
A[0]	3	2	5
A[1]	0	0	-27
A[2]	0	1	6
A[3]	1	0	82
A[4]	2	0	109
A[5]	2	1	-64
A[6]	3		

$$B = \begin{bmatrix} 21 & 27 & 0 \\ 5 & 0 & -71 \end{bmatrix} :$$

	Row	Col	Value
B[0]	2	3	4
B[1]	0	0	21
B[2]	0	1	27
B[3]	1	0	5
B[4]	1	2	-71

$$B^T = \begin{bmatrix} 21 & 5 \\ 27 & 0 \\ 0 & -71 \end{bmatrix} :$$

	Row	Col	Value
B ^T [0]	3	2	4
B ^T [1]	0	0	21
B ^T [2]	0	1	5
B ^T [3]	1	0	27
B ^T [4]	2	1	-71
B ^T [5]	3	-1	

boundary condition

Sparse Matrix Multiplication

$$A = \begin{bmatrix} -27 & 6 \\ 82 & 0 \\ 109 & -64 \end{bmatrix} :$$

	Row	Col	Value
A[0]	3	2	5
A[1]	0	0	-27
A[2]	0	1	6
A[3]	1	0	82
A[4]	2	0	109
A[5]	2	1	-64
A[6]	3		

$$B = \begin{bmatrix} 21 & 27 & 0 \\ 5 & 0 & -71 \end{bmatrix} :$$

	Row	Col	Value
B[0]	2	3	4
B[1]	0	0	21
B[2]	0	1	27
B[3]	1	0	5
B[4]	1	2	-71

$$B^T = \begin{bmatrix} 21 & 5 \\ 27 & 0 \\ 0 & -71 \end{bmatrix} :$$

	Row	Col	Value
B ^T [0]	3	2	4
B ^T [1]	0	0	21
B ^T [2]	0	1	5
B ^T [3]	1	0	27
B ^T [4]	2	1	-71
B ^T [5]	3	-1	

Sparse Matrix Multiplication

$$A = \begin{bmatrix} -27 & 6 \\ 82 & 0 \\ 109 & -64 \end{bmatrix} :$$

	Row	Col	Value
A[0]	3	2	5
A[1]	0	0	-27
A[2]	0	1	6
A[3]	1	0	82
A[4]	2	0	109
A[5]	2	1	-64
A[6]	3		

$$B = \begin{bmatrix} 21 & 27 & 0 \\ 5 & 0 & -71 \end{bmatrix} :$$

	Row	Col	Value
B[0]	2	3	4
B[1]	0	0	21
B[2]	0	1	27
B[3]	1	0	5
B[4]	1	2	-71

$$B^T = \begin{bmatrix} 21 & 5 \\ 27 & 0 \\ 0 & -71 \end{bmatrix} :$$

	Row	Col	Value
B ^T [0]	3	2	4
B ^T [1]	0	0	21
B ^T [2]	0	1	27
B ^T [3]	1	0	5
B ^T [4]	2	1	-71
B ^T [5]	3	-1	

- Procedure: Fix a row of A and find all elements in column j of B , for $j = 0, 1, \dots, p - 1$.



Sparse Matrix Multiplication

$$A = \begin{bmatrix} -27 & 6 \\ 82 & 0 \\ 109 & -64 \end{bmatrix} :$$

	Row	Col	Value
A[0]	3	2	5
A[1]	0	0	-27
A[2]	0	1	6
A[3]	1	0	82
A[4]	2	0	109
A[5]	2	1	-64
A[6]	3		

$$B = \begin{bmatrix} 21 & 27 & 0 \\ 5 & 0 & -71 \end{bmatrix} :$$

	Row	Col	Value
B[0]	2	3	4
B[1]	0	0	21
B[2]	0	1	27
B[3]	1	0	5
B[4]	1	2	-71

$$B^T = \begin{bmatrix} 21 & 5 \\ 27 & 0 \\ 0 & -71 \end{bmatrix} :$$

	Row	Col	Value
B ^T [0]	3	2	4
B ^T [1]	0	0	21
B ^T [2]	0	1	27
B ^T [3]	1	0	5
B ^T [4]	2	1	-71
B ^T [5]	3	-1	

- Procedure: Fix a row of A and find all elements in column j of B , for $j = 0, 1, \dots, p - 1$.
- Compute B^T (column elements are placed consecutively).



Sparse Matrix Multiplication

$$A = \begin{bmatrix} -27 & 6 \\ 82 & 0 \\ 109 & -64 \end{bmatrix} :$$

	Row	Col	Value
A[0]	3	2	5
A[1]	0	0	-27
A[2]	0	1	6
A[3]	1	0	82
A[4]	2	0	109
A[5]	2	1	-64
A[6]	3		

$$B = \begin{bmatrix} 21 & 27 & 0 \\ 5 & 0 & -71 \end{bmatrix} :$$

	Row	Col	Value
B[0]	2	3	4
B[1]	0	0	21
B[2]	0	1	27
B[3]	1	0	5
B[4]	1	2	-71

$$B^T = \begin{bmatrix} 21 & 5 \\ 27 & 0 \\ 0 & -71 \end{bmatrix} :$$

	Row	Col	Value
B ^T [0]	3	2	4
B ^T [1]	0	0	21
B ^T [2]	0	1	5
B ^T [3]	1	0	27
B ^T [4]	2	1	-71
B ^T [5]	3	-1	

- Procedure: Fix a row of A and find all elements in column j of B , for $j = 0, 1, \dots, p - 1$.
- Compute B^T (column elements are placed consecutively).



Sparse Matrix Multiplication

$$A = \begin{bmatrix} -27 & 6 \\ 82 & 0 \\ 109 & -64 \end{bmatrix} :$$

	Row	Col	Value
A[0]	3	2	5
A[1]	0	0	-27
A[2]	0	1	6
A[3]	1	0	82
A[4]	2	0	109
A[5]	2	1	-64
A[6]	3		

$$B = \begin{bmatrix} 21 & 27 & 0 \\ 5 & 0 & -71 \end{bmatrix} :$$

	Row	Col	Value
B[0]	2	3	4
B[1]	0	0	21
B[2]	0	1	27
B[3]	1	0	5
B[4]	1	2	-71

$$B^T = \begin{bmatrix} 21 & 5 \\ 27 & 0 \\ 0 & -71 \end{bmatrix} :$$

	Row	Col	Value
B ^T [0]	3	2	4
B ^T [1]	0	0	21
B ^T [2]	0	1	5
B ^T [3]	1	0	27
B ^T [4]	2	1	-71
B ^T [5]	3	-1	

- Procedure: Fix a row of A and find all elements in column j of B , for $j = 0, 1, \dots, p - 1$.
- Compute B^T (column elements are placed consecutively).



Sparse Matrix Multiplication

$$A = \begin{bmatrix} -27 & 6 \\ 82 & 0 \\ 109 & -64 \end{bmatrix} :$$

	Row	Col	Value
A[0]	3	2	5
A[1]	0	0	-27
A[2]	0	1	6
A[3]	1	0	82
A[4]	2	0	109
A[5]	2	1	-64
A[6]	3		

$$B = \begin{bmatrix} 21 & 27 & 0 \\ 5 & 0 & -71 \end{bmatrix} :$$

	Row	Col	Value
B[0]	2	3	4
B[1]	0	0	21
B[2]	0	1	27
B[3]	1	0	5
B[4]	1	2	-71

$$B^T = \begin{bmatrix} 21 & 5 \\ 27 & 0 \\ 0 & -71 \end{bmatrix} :$$

	Row	Col	Value
B ^T [0]	3	2	4
B ^T [1]	0	0	21
B ^T [2]	0	1	5
B ^T [3]	1	0	27
B ^T [4]	2	1	-71
B ^T [5]	3	-1	

- Procedure: Fix a row of A and find all elements in column j of B , for $j = 0, 1, \dots, p - 1$.
- Compute B^T (column elements are placed consecutively).



Sparse Matrix Multiplication

$$A = \begin{bmatrix} -27 & 6 \\ 82 & 0 \\ 109 & -64 \end{bmatrix} :$$

	Row	Col	Value
A[0]	3	2	5
A[1]	0	0	-27
A[2]	0	1	6
A[3]	1	0	82
A[4]	2	0	109
A[5]	2	1	-64
A[6]	3		

$$B = \begin{bmatrix} 21 & 27 & 0 \\ 5 & 0 & -71 \end{bmatrix} :$$

	Row	Col	Value
B[0]	2	3	4
B[1]	0	0	21
B[2]	0	1	27
B[3]	1	0	5
B[4]	1	2	-71

$$B^T = \begin{bmatrix} 21 & 5 \\ 27 & 0 \\ 0 & -71 \end{bmatrix} :$$

	Row	Col	Value
B ^T [0]	3	2	4
B ^T [1]	0	0	21
B ^T [2]	0	1	5
B ^T [3]	1	0	27
B ^T [4]	2	1	-71
B ^T [5]	3	-1	

- Procedure: Fix a row of A and find all elements in column j of B , for $j = 0, 1, \dots, p - 1$.
- Compute B^T (column elements are placed consecutively).



Sparse Matrix Multiplication

$$A = \begin{bmatrix} -27 & 6 \\ 82 & 0 \\ 109 & -64 \end{bmatrix} :$$

	Row	Col	Value
A[0]	3	2	5
A[1]	0	0	-27
A[2]	0	1	6
A[3]	1	0	82
A[4]	2	0	109
A[5]	2	1	-64
A[6]	3		

$$B = \begin{bmatrix} 21 & 27 & 0 \\ 5 & 0 & -71 \end{bmatrix} :$$

	Row	Col	Value
B[0]	2	3	4
B[1]	0	0	21
B[2]	0	1	27
B[3]	1	0	5
B[4]	1	2	-71

$$B^T = \begin{bmatrix} 21 & 5 \\ 27 & 0 \\ 0 & -71 \end{bmatrix} :$$

	Row	Col	Value
B ^T [0]	3	2	4
B ^T [1]	0	0	21
B ^T [2]	0	1	5
B ^T [3]	1	0	27
B ^T [4]	2	1	-71
B ^T [5]	3	-1	

- Procedure: Fix a row of A and find all elements in column j of B , for $j = 0, 1, \dots, p - 1$.
- Compute B^T (column elements are placed consecutively).



Sparse Matrix Multiplication

$$A = \begin{bmatrix} -27 & 6 \\ 82 & 0 \\ 109 & -64 \end{bmatrix} :$$

	Row	Col	Value
A[0]	3	2	5
A[1]	0	0	-27
A[2]	0	1	6
A[3]	1	0	82
A[4]	2	0	109
A[5]	2	1	-64
A[6]	3		

$$B = \begin{bmatrix} 21 & 27 & 0 \\ 5 & 0 & -71 \end{bmatrix} :$$

	Row	Col	Value
B[0]	2	3	4
B[1]	0	0	21
B[2]	0	1	27
B[3]	1	0	5
B[4]	1	2	-71

$$B^T = \begin{bmatrix} 21 & 5 \\ 27 & 0 \\ 0 & -71 \end{bmatrix} :$$

	Row	Col	Value
B ^T [0]	3	2	4
B ^T [1]	0	0	21
B ^T [2]	0	1	27
B ^T [3]	1	0	5
B ^T [4]	2	1	-71
B ^T [5]	3	-1	

- Procedure: Fix a row of A and find all elements in column j of B , for $j = 0, 1, \dots, p - 1$.
- Compute B^T (column elements are placed consecutively).



Sparse Matrix Multiplication

$$A = \begin{bmatrix} -27 & 6 \\ 82 & 0 \\ 109 & -64 \end{bmatrix} :$$

	Row	Col	Value
A[0]	3	2	5
A[1]	0	0	-27
A[2]	0	1	6
A[3]	1	0	82
A[4]	2	0	109
A[5]	2	1	-64
A[6]	3		

$$B = \begin{bmatrix} 21 & 27 & 0 \\ 5 & 0 & -71 \end{bmatrix} :$$

	Row	Col	Value
B[0]	2	3	4
B[1]	0	0	21
B[2]	0	1	27
B[3]	1	0	5
B[4]	1	2	-71

$$B^T = \begin{bmatrix} 21 & 5 \\ 27 & 0 \\ 0 & -71 \end{bmatrix} :$$

	Row	Col	Value
B ^T [0]	3	2	4
B ^T [1]	0	0	21
B ^T [2]	0	1	5
B ^T [3]	1	0	27
B ^T [4]	2	1	-71
B ^T [5]	3	-1	

- Procedure: Fix a row of A and find all elements in column j of B , for $j = 0, 1, \dots, p - 1$.
- Compute B^T (column elements are placed consecutively).



Sparse Matrix Multiplication

$$A = \begin{bmatrix} -27 & 6 \\ 82 & 0 \\ 109 & -64 \end{bmatrix} :$$

	Row	Col	Value
A[0]	3	2	5
A[1]	0	0	-27
A[2]	0	1	6
A[3]	1	0	82
A[4]	2	0	109
A[5]	2	1	-64
A[6]	3		

$$B = \begin{bmatrix} 21 & 27 & 0 \\ 5 & 0 & -71 \end{bmatrix} :$$

	Row	Col	Value
B[0]	2	3	4
B[1]	0	0	21
B[2]	0	1	27
B[3]	1	0	5
B[4]	1	2	-71

$$B^T = \begin{bmatrix} 21 & 5 \\ 27 & 0 \\ 0 & -71 \end{bmatrix} :$$

	Row	Col	Value
B ^T [0]	3	2	4
B ^T [1]	0	0	21
B ^T [2]	0	1	5
B ^T [3]	1	0	27
B ^T [4]	2	1	-71
B ^T [5]	3	-1	

- Procedure: Fix a row of A and find all elements in column j of B , for $j = 0, 1, \dots, p-1$.
- Compute B^T (column elements are placed consecutively).



Rough Code HERE (Exercise)

C Functions for Sparse Matrix Multiplication

```
void mat_mult(term a[], term b[], term d[]) { //multiply two sparse matrices
    int i, j, column, totalA = a[0].value, totalB = b[0].value, totalD = 0;
    int rowsA = a[0].row, colsA = a[0].col, colsB = b[0].col;
    int row_begin = 1, row = a[1].row, sum = 0;
    term b_T[MAX_TERMS][3];
    if (colsA != b[0].row) {
        fprintf(stderr, "incompatible matrices\n");
        exit(0);
    }
    fast_transpose(b, b_T); // get a transpose b_T of b
    // set boundary conditions
    a[totalA+1].row = rowsA;
    b_T[totalB+1].row = colsB;
    b_T[totalB+1].col = -1;
```



```

for (i=1; i<=totalA; ) {
    column = b_T[1].row;
    for (j=1; j<=totalB+1; ) {
        // multiply row of a by column of b
        if (a[i].row != row) { // a new row to consider; "row" is initialized to be a[1].row
            storeSum(d, &totalD, row, column, &sum);
            i = row_begin; // jump to the start of current row of A
            for (; b_T[j].row == column; j++); // moving j until the next column of B
            column = b_T[j].row;
        } else if (b_T[j].row != column) { // columns of the current row have been all scanned
            storeSum(d, &totalD, row, column, &sum);
            i = row_begin; // jump to the start of current row of A
            column = b_T[j].row;
        } else switch (COMPARE(a[i].col, b_T[j].col)) {
            case -1: // go to next term of a
                i++; break;
            case 0: // add terms, go to next term in a and b
                sum += (a[i++].value * b_T[j++].value); break;
            case 1: // advance to next term in b
                j++;
        }
    } // end of for j <= totalB+1
    for (; a[i].row == row; i++); // moving i until the next row of A
    row_begin = i; // go to the next row of A
    row = a[i].row; // reset the "row"
} // end of for i<= totalA
d[0].row = rowsA;
d[0].col = colsB;
d[0].value = totalD;
}

```

```
void storeSum(term d[], int *totalD, int row, int column, int *sum) {  
    /* if *sum != 0, then it along with its row and column  
       position is stored as the *totalD+1 entry in d */  
    if (*sum) { // Remember, we only store nonzero entries  
        if (*totalD < MAX_TERMS) {  
            ++*totalD;  
            d[*totalD].row = row;  
            d[*totalD].col = column;  
            d[*totalD].value = *sum;  
            *sum = 0;  
        } else {  
            fprintf(stderr, "Numbers of terms in product exceeds %d\n",  
                MAX_TERMS);  
            exit(1);  
        }  
    }  
}
```



Asymptotic Time Complexity (1/2)

- $\text{cols}B$: the number of columns in matrix B .
 $\text{rows}A$: the number of rows in matrix A .
 termsRow_i : the number of terms in row i of A .
 termsCol_j : the number of terms in column j of B .
 $\text{total}B$: the number of elements in matrix B .
- For each row i of A , the algorithm compares it with each column j of B using two pointers. Processing column j of B takes



Asymptotic Time Complexity (1/2)

- $\text{cols}B$: the number of columns in matrix B .
 $\text{rows}A$: the number of rows in matrix A .
 termsRow_i : the number of terms in row i of A .
 termsCol_j : the number of terms in column j of B .
 $\text{total}B$: the number of elements in matrix B .
- For each row i of A , the algorithm compares it with each column j of B using two pointers. Processing column j of B takes

$$O(\text{termsRow}_i + \text{termsCol}_j).$$



Asymptotic Time Complexity (1/2)

- $\text{cols}B$: the number of columns in matrix B .
 $\text{rows}A$: the number of rows in matrix A .
 termsRow_i : the number of terms in row i of A .
 termsCol_j : the number of terms in column j of B .
 $\text{total}B$: the number of elements in matrix B .
- For each row i of A , the algorithm compares it with each column j of B using two pointers. Processing column j of B takes

$$O(\text{termsRow}_i + \text{termsCol}_j).$$

- Summing over all columns of B gives



Asymptotic Time Complexity (1/2)

- $\text{cols}B$: the number of columns in matrix B .
 $\text{rows}A$: the number of rows in matrix A .
 termsRow_i : the number of terms in row i of A .
 termsCol_j : the number of terms in column j of B .
 $\text{total}B$: the number of elements in matrix B .
- For each row i of A , the algorithm compares it with each column j of B using two pointers. Processing column j of B takes

$$O(\text{termsRow}_i + \text{termsCol}_j).$$

- Summing over all columns of B gives

$$O\left(\text{cols}B \cdot \text{termsRow}_i + \sum_{j=1}^{\text{cols}B} \text{termsCol}_j\right) = O(\text{cols}B \cdot \text{termsRow}_i + \text{total}B).$$



Asymptotic Time Complexity (2/2)

- $\text{cols}B$: the number of columns in matrix B
 $\text{rows}A$: the number of rows in matrix A
 termsRow_i : the number of terms in row i of A
 termsCol_j : the number of terms in column j of B .
 $\text{total}B$: the number of elements in matrix B .
- Thus,



Asymptotic Time Complexity (2/2)

- $\text{cols}B$: the number of columns in matrix B
 $\text{rows}A$: the number of rows in matrix A
 termsRow_i : the number of terms in row i of A
 termsCol_j : the number of terms in column j of B .
 $\text{total}B$: the number of elements in matrix B .

- Thus,

$$\begin{aligned} & \text{cols}B \times \text{termsRow}_1 + \text{total}B \\ + & \text{cols}B \times \text{termsRow}_2 + \text{total}B \\ & \vdots \\ + & \text{cols}B \times \text{termsRow}_m + \text{total}B \end{aligned}$$



Asymptotic Time Complexity (2/2)

- $\text{cols}B$: the number of columns in matrix B
 $\text{rows}A$: the number of rows in matrix A
 termsRow_i : the number of terms in row i of A
 termsCol_j : the number of terms in column j of B .
 $\text{total}B$: the number of elements in matrix B .

- Thus,

$$\begin{aligned} & \text{cols}B \times \text{termsRow}_1 + \text{total}B \\ & + \text{cols}B \times \text{termsRow}_2 + \text{total}B \\ & \vdots \\ & + \text{cols}B \times \text{termsRow}_m + \text{total}B \\ & = \text{cols}B \times \sum_{i=1}^{\text{rows}A} \text{termsRow}_i + \text{rows}A \times \text{total}B \\ & = \text{cols}B \times \text{total}A + \text{rows}A \times \text{total}B. \end{aligned}$$



Comparing with the classic matrix multiplication...

```
for (i=0; i<rowsA; i++) {  
    for (j=0; j<colsB; j++) {  
        sum = 0; // reset  
        for (k=0; k<colsA; k++) {  
            sum += (a[i][k]*b[k][j]);  
        }  
        d[i][j] = sum;  
    }  
}
```

- The time complexity: $O(\text{rowsA} \times \text{colsB} \times \text{colsA})$.
- Sparse matrix multiplication: $O(\text{colsB} \times \text{totalA} + \text{rowsA} \times \text{totalB})$.
 - Optimal when $\text{totalA} < \text{rowsA} \times \text{colsA}$ and $\text{totalB} < \text{colsA} \times \text{colsB}$.
 - Worse when $\text{totalA} \geq \text{rowsA} \times \text{colsA}$ or $\text{totalB} \geq \text{colsA} \times \text{colsB}$.



Discussions

