



A flat quadrilateral plate finite element is shown.


- Describe and perform a test, using two cross products that will verify if all four nodes (corners) lie in the same plane.
- Determine the unit outward normal direction to the surface (i.e., pointing away from the origin).
- Determine the surface area of the element.



- Determine the resultant \vec{R} of the three forces $\vec{F} + \vec{P} + \vec{Q}$.
- If an additional force \vec{T} in the $\pm x$ direction is to be added, determine the magnitude it should have so that the magnitude of the resultant is as small as possible.




In a machining setup, workpiece B , which weighs 20 lb, is supported by a fixed V block E and a clamp at A . All contact surfaces are frictionless, and the clamp applies a vertical force of 35 lb to the workpiece. Determine the reactions at points C and D between the V block and the workpiece.




Blocks A and B each have 5 kg mass, and all contact surfaces are frictionless.

- Determine the force F needed to keep the blocks in static equilibrium and the forces on all contact surfaces.
- If the value of F determined in Part (a) is applied, will the blocks move? Explain.
- If F is smaller than the value determined in Part (a), describe what happens.



Bead A has 1 kg mass and slides without friction on bar BC .

- Determine the force F needed to keep the bead in static equilibrium and the reaction force between the bead and bar.
- If the value of F determined in Part (a) is applied, will the bead move? Explain.
- If F is larger than the value determined in Part (a), describe what happens.



Blocks A and B each weigh 100 lb and rest on frictionless surfaces. They are connected to one another by cable AB . Determine the force P required to hold the blocks in the equilibrium position shown and the reactions between the blocks and surfaces.

