

Angular

2021/03/03

王晨帆 - Joseph



主題

- ▶ 1. Angular 簡介、Typescript介紹、Component
- ▶ 2. Service、Pipe、HttpClient與 Rxjs
- ▶ 3. Workshop

Angular 簡介



Angular 簡介

- ▶ 預設使用 Typescript 作為開發語言，搭配 RxJS 處理非同步事件
- ▶ 搭配 Angular CLI 協助打包與專案開發
- ▶ Angular 內建已存在相當多功能，如 i18N、SSR、PWA 等

Angular 簡介

- ▶ Angular 2 以後版本皆稱為 Angular，語法上差異不大，大多為底層效能優化
- ▶ 版本升級指南：[NgUpgradeGuide](#)
- ▶ Debug工具：[Augury](#)

IE Support

- ▶ Angular 10 Deprecating support IE 9 、 IE 10 、 IE mobile
- ▶ IE9, IE10 and IE mobile are no longer officially supported with Angular v11 and higher.
- ▶ IE 9, 10, and IE mobile support


Typescript



Typescript



- ▶ Typescript = Javascript + 型別系統
- ▶ 協助在開發時期找出錯誤與降低錯誤，但無法100%避免錯誤
- ▶ 透過type 宣告偵測程式碼
- ▶ 只存在於開發時期，最終會被編譯成javascript
- ▶ 提供程式碼自動補完功能、定義跳轉與重構功能

TypeScript



Stackblitz

- ▶ Chrome 上需要允許3rd party cookie 才可正常使用



Typescript

- ▶ Typescript in Angular demo
- ▶ Typescript Playground

v4.0.5 ▾ Run Export ▾ Share **Typescript** →

```
1  const names:string[] = ['Peter', 'Jenny'];
2
3  class Member{
4      name: string = '';
5      age: number = 20;
6
7      displayName = () => `This is my name: ${this.name}`;
8
9      getName():string{
10         return this.name;
11     }
12
13     getAge(): number{
14         return this.age;
15     }
16 }
17
18 const user: Member = new Member();
19
```

ES5 .JS

```
"use strict";
var names = ['Peter', 'Jenny'];

var Member = /** @class */ (function () {
    function Member() {
        var _this = this;
        this.name = '';
        this.age = 20;
        this.displayName = function () { return "This is my name: " + _this.name; };
    }
    Member.prototype.getName = function () {
        return this.name;
    };
    Member.prototype.getAge = function () {
        return this.age;
    };
    return Member;
})();

var user = new Member();
```


Typescript 相關網站

- ▶ [Typescript](#)
- ▶ [Typescript新手指南](#)

Angular Component

The background of the slide is composed of several geometric elements. On the left, there is a solid green vertical bar. The central area is white, containing the text 'Angular Component'. To the right of the text, there is a large, complex geometric pattern made of many small triangles in various shades of green and white, creating a 3D effect. The triangles are arranged in a way that they appear to be stacked or layered, with some pointing towards the viewer and others away from it. The overall design is modern and tech-oriented.

Component



Component

```
import { Component, OnInit } from '@angular/core';

@Component({
  selector: 'app-my-app',
  templateUrl: './my-app.component.html',
  styleUrls: ['./my-app.component.css']
})
export class MyAppComponent implements OnInit {}

constructor() { }

ngOnInit(): void {
}
```

► 使用方式：在 html上使用
`<app-my-app> </app-my-app>`

Component

import statement

- import 相關 type

Metadata/ Decorator

- 宣告 component selector
- 指定 component template url 或是 inline template
- 指定 component css 檔案或是 inline style

Typescript class


- 主要程式邏輯
- 呈現於畫面上之變數

Component建立

- ▶ 透過 ng generate component my-app
 - ▶ 建立my-app目錄
 - ▶ 建立 my-app.component.(ts| html|spec|css)
 - ▶ 更新Module.declarations
 - ▶ 指令可簡寫為 ng g c my-app

Component Lifecycle Hooks

- ▶ **ngOnInit**: 當 Angular 完成目前 component 下所有 @Input() 初始化後觸發
- ▶ **ngOnDestroy**: 當 Component 要被銷毀時觸發



這張相片 (作者: 未知的作者) 已透過 [CC BY-SA](#) 授權。

Component

資料呈現與綁定

Interpolation

- ▶ 使用 `{{ expression }}` 可在畫面上呈現 expression 結果
- ▶ Interpolation 範例
- ▶ 官網

Attribute Binding

- ▶ 使用 `[attr] = "expression"` 讓HTML屬型參考到 expression 結果
- ▶ Attribute Binding 範例
- ▶ 官網

Event Binding

- ▶ 以 (event) = “expression” 方式處理事件觸發，
- ▶ Event 發出的內容會指派到 \$event 變數
- ▶ Event Binding 範例
- ▶ 官網

Two-way Binding

- ▶ 使用 [(ngModel)] = "variable" 建立雙向連結，主用於 html input element 上，如 input、select
- ▶ *必須先在 Module import 處加入 FormsModule，否則會出現錯誤
- ▶ Two-way Binding 範例
- ▶ 官網

```
Can't bind to 'ngModel' since it isn't a known property of 'input'. ng
Peek Problem (⌘F8) No quick fixes available
<input [(ngModel)]="title" />
```

```
@NgModule({
  declarations: [
    AppComponent,
    Comp1Component,
    Comp2Component,
  ],
  imports: [
    BrowserModule,
    FormsModule
  ],
  providers: [],
  bootstrap: [AppComponent]
})
export class AppModule { }
```

Structural Directives

- ▶ 在 template 上會刪除或新增 element 至 DOM 中的語法，稱為 structural directive
 - ▶ `*ngIf`
 - ▶ `*ngFor`
- ▶ 加上 `*` 表示為語法糖，是簡寫過後的語法，如 `*ngIf`
- ▶ 同一個 element 上 **只可存在一個** structural directive
- ▶ Structural Directives

*ngIf

- ▶ 在給定條件滿足時，才將 element 加入 DOM中
- ▶ `<elem *ngIf="condition | expression">Hello
World</elem>`
- ▶ *ngIf 範例程式

*ngIf

```
▼ <app-root _ngghost-kxn-c40="" ng-version="11.1.2">  
  <label _ngcontent-kxn-c40="" for="">NgIf Test</label>  
  <!--bindings={ "ng-reflect-ng-if": "true" }--> 點擊前  
  <button _ngcontent-kxn-c40="">Click me</button> event  
</app-root>
```

```
▼ <app-root _ngghost-nao-c40="" ng-version="11.1.2">  
  <!--bindings={ "ng-reflect-ng-if": "false" }-->  
  <button _ngcontent-nao-c40="">Click me</button> event 點擊後  
</app-root>
```

*ngFor

- ▶ 使用迴圈遍歷資料並運用於 template
- ▶ `<elem *ngFor="let item of items">{{item}}</elem>`
- ▶ *ngFor 範例程式

@Input 接收外部參數

- ▶ 自定義 component 接收外部傳入參數
 - ▶ 如 `<app-my-comp1 [title]="This is title"></app-my-comp1>`
- ▶ 在 component內變數加入 `@Input()` 於變數前即可
 - ▶ `@Input() name: string;`
- ▶ @Input() 範例

@Output 輸出事件

- ▶ 自訂 component 提供 event binding 方法
 - ▶ 如 `<app-my-comp1 (btnClicked)="onBtnClicked()" > </app-my-comp1>`
- ▶ 在 component 變數前加入 `@Output()`，資料型別為 `EventEmitter`
- ▶ @Output 範例程式

Pipe

Pipe

- ▶ 可用來將資料轉換為其他形式呈現於畫面上，並且不異動原本之資料
- ▶ 用法為在 template 上加入 `value | pipeName[:params]`
- ▶ Angular Builtin Pipes

```
{{ 20000000 | number }} <= 2,000,000
```

```
{{ 20000000 | currency }} <= $2,000,000.00
```

自訂Pipe

- ▶ `ng g p myCustomPipe`
- ▶ 透過Angular-CLI會自動在 module **declaration**處加入 pipe 資訊
- ▶ 實做PipeTransform interface
- ▶ Pipe 範例程式

The background features a white space on the left and a large green area on the right, separated by a diagonal line. A thin green line also runs diagonally across the white space. The word "Service" is centered in the white area.

Service

Service

- ▶ Service負責處理複雜邏輯與儲存共用資料
- ▶ Component中以 DI 方式使用Service
- ▶ 依照 Service 註冊方式差異，會有所不同

Service

- ▶ ng g s service-name
- ▶ Service宣告方式：
 - ▶ 在Module.providers中註冊
 - ▶ Decorator中設定 ProvidedIn

註冊 Service


```
@Injectable({  
  providedIn: 'root'  
})  
export class AuthService {  
  
  constructor() { }  
}
```

註冊 Service

```
imports: [  
  BrowserModule,  
  FormsModule  
],  
providers: [AuthService],  
bootstrap: [AppComponent]  
})  
export class AppModule { }
```

```
@Injectable()  
export class AuthService {  
  
  constructor() { }  
}
```


註冊 Service



Service

- ▶ 在 component **constructor** 參數中加入service資訊即可將service 注入 component
 - ▶ constructor(**private authService: AuthService**){}
 - ▶ 如果沒有加入 private或 public，則只能在 constructor中使用

- ▶ Service範例程式



HttpClient & RxJS

HttpClient

- ▶ Angular透過HttpClient 處理 HTTP請求
- ▶ Module中必須import **HttpClientModule**，後續才可將 HttpClient注入 component或 service中
- ▶ 以DI方式注入 component或 service中
- ▶ Angular httpClient 使用 Rxjs處理非同步請求

HttpClient

- ▶ GET:

- ▶ `httpClient.get<any>('Your url', options).subscribe(x => {...})`

- ▶ POST:

- ▶ `httpClient.post<any>('Your url', body, options).subscribe(x => {...})`

- ▶ HttpClient範例程式

RxJS 簡介

- ▶ *ReactiveX is a combination of the best ideas from the Observer pattern, the Iterator pattern, and functional programming*
- ▶ *要執行訂閱(subscribe) 才會執行
- ▶ 如果有未結束的 Observable，在component destroy phase 中要記得取消訂閱(unsubscribe)

Observer

- ▶ Observer物件包含 next, error 與 complete 三個callback 提供給Observable 做使用
- ▶ next: 當observable 發出data時，會使用此 next callback
- ▶ error: Observable 中出錯即會使用 error function callback
- ▶ complete: 當 Observable 完成後，會使用 complete callback

Observable訂閱

- ▶ `someObservable.subscribe(nextCallback, errorCallback, completeCallback)`
- ▶ Observable 範例


Operator

► 常用 Operator:


- map: 將傳入的資料做轉換，並將轉換後資料往下繼續傳遞
- filter: 篩選符合條件的資料才往下傳遞
- tap: 可在此 operator處理任何事情，並以同一個 Observable繼續往下傳遞

Marble diagram

► Filter



► map



Operator

► Operator 範例

0 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16...

take(10)

0 1 2 3 4 5 6 7 8 9

filter(x => x % 2 == 0)

0 2 4 6 8

map(x => x * 2)

0 4 8 12 16




map  => 



tap x => 品質檢測/ 秤重



filter x => x === 



take(10)



最後只會拿到10筆結果


RxJS 相關資源


- ▶ 希望是最淺顯易懂的 RxJS 教學
- ▶ Observable on Angular
- ▶ 30 天精通 RxJS (01) : 認識 RxJS
- ▶ Marble Diagram


Workshop





News List


- 


New charges allege Proud Boys prepped for Capitol insurrection - CNN
- 


New charges allege Proud Boys prepped for Capitol insurrection - CNN
- 

Covid trial in UK examines mixing different vaccines - BBC News
- 

'The Democratic version of John McCain' - POLITICO
- 

More COVID-19 vaccine megasites open nationwide, including at Yankee Stadium - CBS News
- California's governor, once praised, faces backlash over pandemic response - The Guardian
- 

Chiefs QB Patrick Mahomes expected to have toe surgery following season - NFL.com
- 

As Vaccines Raise Hope, Cold Reality Dawns: Covid-19 Is Likely Here to Stay - The Wall Street Journal
- 

Dear Dr. Li: Chinese Netizens Confess To The Late Coronavirus Whistleblower - NPR

文章列表抓取API資料，並標示目前檢視項目



New charges allege Proud Boys prepped for Capitol insurrection - CNN

Evan Perez, Katelyn Polantz and Mallory Simon, CNN 4 hours ago

Two prominent affiliates of the Proud Boys face new conspiracy charges related to the US Capitol riot, and another was arrested Wednesday, as the Justice Department laid out a planning and funding effort within the far-right extremist group in a major court d...

News List



New charges allege Proud Boys prepped for Capitol
insurrection - CNN



New charges allege Proud Boys prepped for Capitol
insurrection - CNN



Covid trial in UK examines mixing different vaccines -
BBC News



'The Democratic version of John McCain' -
POLITICO



More COVID-19 vaccine megasites open nationwide,
including at Yankee Stadium - CBS News



California's governor, once praised, faces backlash over
pandemic response - The Guardian



As Vaccines Raise Hope, Cold Reality Dawns: Covid-19 Is
Likely Here to Stay - The Wall Street Journal



Dear Dr. Li: Chinese Netizens Confess To The Late Coronavirus
Whistleblower - NPR

選取文章後，呈現至右側區塊





New charges allege Proud Boys prepped for Capitol insurrection - CNN


Evan Perez, Katelyn Polantz and Mallory Simon, CNN 4 hours ago


Two prominent affiliates of the Proud Boys face new conspiracy charges related to the US Capitol riot, and another was arrested Wednesday, as the Justice Department laid out a planning and funding effort within the far-right extremist group in a major court d...


News List


- 


New charges allege Proud Boys prepped for Capitol insurrection - CNN
- 


New charges allege Proud Boys prepped for Capitol insurrection - CNN
- 

Covid trial in UK examines mixing different vaccines - BBC News
- 

'The Democratic version of John McCain' - POLITICO
- 

More COVID-19 vaccine megasites open nationwide, including at Yankee Stadium - CBS News
- California's governor, once praised, faces backlash over pandemic response - The Guardian
- 

Chiefs QB Patrick Mahomes expected to have toe surgery following season - NFL.com
- 

As Vaccines Raise Hope, Cold Reality Dawns: Covid-19 Is Likely Here to Stay - The Wall Street Journal
- 

Dear Dr. Li: Chinese Netizens Confess To The Late Coronavirus Whistleblower - NPR



New charges allege Proud Boys prepped for Capitol insurrection - CNN

Evan Perez, Katelyn Polantz and Mallory Simon, CNN 4 hours ago

Two prominent affiliates of the Proud Boys face new conspiracy charges related to the US Capitol riot, and another was arrested Wednesday, as the Justice Department laid out a planning and funding effort within the far-right extremist group in a major court d...

News List



New charges allege Proud Boys prepped for Capitol insurrection - CNN



New charges allege Proud Boys prepped for Capitol insurrection - CNN



Covid trial in UK examines mixing different vaccines - BBC News



'The Democratic version of John McCain' - POLITICO



More COVID-19 vaccine megasites open nationwide, including at Yankee Stadium - CBS News



California's governor, once praised, faces backlash over pandemic response - The Guardian



As Vaccines Raise Hope, Cold Reality Dawns: Covid-19 Is Likely Here to Stay - The Wall Street Journal



Dear Dr. Li: Chinese Netizens Confess To The Late Coronavirus Whistleblower - NPR



國家資訊切換後重新抓取文章

New charges allege Proud Boys prepped for Capitol insurrection - CNN

Evan Perez, Katelyn Polantz and Mallory Simon, CNN 4 hours ago

Two prominent affiliates of the Proud Boys face new conspiracy charges related to the US Capitol riot, and another was arrested Wednesday, as the Justice Department laid out a planning and funding effort within the far-right extremist group in a major court d...

News List

Keyword



New charges allege Proud Boys prepped for Capitol insurrection - CNN



New charges allege Proud Boys prepped for Capitol insurrection - CNN



Covid trial in UK examines mixing different vaccines - BBC News



'The Democratic version of John McCain' - POLITICO



More COVID-19 vaccine megasites open nationwide, including at Yankee Stadium - CBS News

California's governor, once praised, faces backlash over pandemic response - The Guardian



Chiefs QB Patrick Mahomes expected to have toe surgery following season - NFL.com



As Vaccines Raise Hope, Cold Reality Dawns: Covid-19 Is Likely Here to Stay - The Wall Street Journal



Dear Dr. Li: Chinese Netizens Confess To The Late Coronavirus Whistleblower - NPR



The Hopes That Rose and Fell With GameStop - The New York Times



New charges allege Proud Boys prepped for Capitol insurrection - CNN

Evan Perez, Katelyn Polantz and Mallory Simon, CNN 4小時前


Two prominent affiliates of the Proud Boys face new conspiracy charges related to the US Capitol riot, and another was arrested Wednesday, as the Justice Department laid out a planning and funding effort within the far-right extremist group in a major court d...

Previous

Origin Post

Next

Component 設計



Header

- ▶ 1. 紀錄目前選擇國家，下次進入時畫面時套用相同國家設定，預設為美國(us)
- ▶ 2. 切換國家時，連動切換文章列表內容

Main-Component

- ▶ 1. 預設顯示Business 類別
- ▶ 2. 頁籤切換時，連動切換文章列表內容

Main-Component

- ▶ 透過 DI注入 NewsService
- ▶ 透過 getCategory取得類別
- ▶ 透過 ngFor呈現類別資訊
- ▶ 透過 click事件紀錄目前選項
- ▶ 使用 [class.is-active]="true/false" attribute binding來決定 element 是否套用 class

News-List

- ▶ 1. 自API 抓取新聞資料
- ▶ 2. 抓完文章後，預設選取第一則新聞，並標示目前被選取到的新聞

News-List

- ▶ 將 news 資料呈現至畫面上
- ▶ 記錄目前選取資料，預設為第一筆資料
- ▶ 透過 click 事件記錄目前 index (ngFor 中可取得目前資料 index => *ngFor="let item of items; let i = index")
- ▶ 被選取項目套用 class.has-background-primary 與 class.has-text-white-bis


News-Content

- ▶ 1. 顯示目前被選擇到的新聞內容
- ▶ 2. 發佈時間顯示規則：N 秒前、N分鐘前、N小時前、N天前、N月前、N年前
- ▶ 3. 新聞無圖片時，不顯示圖片

News-Content

- ▶ 從 NewsList中透過 `newsChangedSubject.next`方法送出資料
- ▶ 從 NewsContent中訂閱 `newsChanged$`
- ▶ 套用 NewsContent版型
- ▶ 使用 `publishAt` pipe

Subject



News API

- ▶ API 連結：<https://newsapi.org/docs/endpoints/top-headlines>
- ▶ API key更新至 environment.ts

News API

► 開啟 environment.ts

序號	員工編號
1	87005
2	89002
3	97029
4	97060
5	99023
6	A4027
7	A9012
8	A9013
9	A9032
10	A0057
11	A9017
12	A9018
13	A9019

```
/**
 *
1: 87766146f8c44bc5abf6e30f19557a39
2: b73772ea993b4ac686aea7ccfd29a60f
3: da6264ab02ac4209aa6f571a5796156d
4: c1b17b93430c4b5db260c2f9292439f6
5: 373d6941579a44968e4e75665e6a2ebd
6: f3a45eeca2154c3984de5e85b65e46b4
7: 2ba2934ab6ee40c79f68dac51c9d8524
8: 1cce5b28383240c9b9a2600c163e66e2
9: 19d534dc985b4b5383ff6e1313765aab
10: de1019e54bb045408cfbc5c5d21e1d59
11: b074733a290641fdaff52e08c34c03f6
12: 49dfc7ea47554e89b1bd5bfe5140024d
13: 5fc4dc6e50ec47dcae93a62fe366a663
```

News API

- ▶ API網站: <https://newsapi.org/docs/endpoints/top-headlines>
- ▶ Url: <https://newsapi.org/v2/top-headlines>
- ▶ 查詢條件 :
 - ▶ country: 2-letter [ISO 3166-1](#) code
 - ▶ category: 類別(business, entertainment, general, health, science and technology)
 - ▶ pageSize: 每頁筆數(開發模式下最多100筆)


API Source

- ▶ import HttpClientModule in AppModule
- ▶ 使用 httpClient 測試抓取資料
 - ▶ `https://newsapi.org/v2/top-headlines?country=us&category=general&q=&apikey=${apikey}&pageSize=100`


NgNews

- ▶ NewsService updateParamData中發送 next
- ▶ Header component中使用 newsService.updateParamData
- ▶ Main component中使用 newsService.updateParamData
- ▶ News-List 訂閱與取消訂閱


Component 資料傳遞




Component 資料傳遞



Component 資料傳遞



Component 資料傳遞



程式打包設定

IE不能動

- ▶ 如果要支援 IE，需要至 polyfills.ts 中開啟設定
- ▶ 調整 tsconfig.json，target 設定為 es5
- ▶ 調整.browserslistrc，移除 IE 前驚嘆號

```
/**
 * IE11 requires the following for NgClass support on SVG elements
 */
// import 'classlist.js'; // Run `npm install --save classlist.js`.

/**
 * Web Animations `@angular/platform-browser/animations`
 * Only required if AnimationBuilder is used within the application and using IE/Edge or Safari.
 * Standard animation support in Angular DOES NOT require any polyfills (as of Angular 6.0).
 */
// import 'web-animations-js'; // Run `npm install --save web-animations-js`.
```

baseHref

- ▶ 預設Angular 運行在 / 路徑下，如 <https://helloworld.com/>
- ▶ 如果要運行在 /app1 路徑下，
如 <https://helloworld.com/app1/>，需要調整 baseHref 設定為 /app1/，否則會出現JS載入失敗之錯誤
 - ▶ 在angular.json上加入 baseHref，設定為 /app1/

environment

- ▶ 環境差異設定放於 environment.ts 中
- ▶ environment.ts 會在打包階段提換內容
- ▶ 需要在 angular.json 中定義不同環境所使用的 environment

```
    "configurations": {  
      "production": {  
        "fileReplacements": [  
          {  
            "replace": "src/environments/environment.ts",  
            "with": "src/environments/environment.prod.ts"  
          }  
        ],  
        "optimization": true,  
        "outputHashing": "all",  
        "sourceMap": false,  
        "namedChunks": false,  
      }  
    }  
  }  
}
```

調整package.json

- ▶ --configuration 對應到 angular.json 中build設定
- ▶ 執行 npm run build/uat/sit
- ▶ build 官方文件

```
"scripts": {  
  "ng": "ng",  
  "start": "ng serve",  
  "build": "ng build --configuration=production",  
  "uat": "ng build --configuration=uat",  
  "test": "ng test",  
  "lint": "ng lint",  
  "e2e": "ng e2e"  
},
```

其他主題

▶ Routing

▶ Directive

▶ Forms

▶ Testing

Angular 相關 Library

- ▶ Angular-Material
- ▶ Ng-Bootstrap
- ▶ Ngx-Bootstrap
- ▶ PrimeNG
- ▶ NG-ZORRO
- ▶ Nebular

Thank you

- ▶ [Angular.tw](http://angular.tw)
- ▶ [Angular Taiwan 論壇](#)