

Physonomicon

Brasides

March 1, 2024

Contents

1	Derivations for One Dimensional Motion	3
1.1	Average velocity \bar{v} vs Instantaneous velocity v	3
1.1.1	tl;dr	3
1.1.2	Defining \bar{v}	3
1.2	Average acceleration \bar{a} vs Instantaneous acceleration a	4
1.2.1	tl;dr	4
1.2.2	Defining average velocity \bar{a}	4
1.3	Notation	5
1.4	Deriving the first kinematic equation	5
1.4.1	Position x as a function of \bar{v}	5
1.4.2	Final Velocity v as a function of time t and acceleration $a = \bar{a}$	5
1.4.3	Final Velocity v as a function of distance x and acceleration $a = \bar{a}$	5
1.4.4	Deriving position x as a function of velocity v , time t , and acceleration $a = \bar{a}$	6
1.5	Kinematic Equations from Integral Calculus	7
1.5.1	$v(t) = v_0 + at$ by Integration	7
1.5.2	$x(t)$ by Integration	7
2	Projectile Motion Derivations	8
2.1	Defining vector quantities of motion for two dimensional vectors	8
2.2	Rewriting kinematic equations for x and y directions where $a_x = 0$	9
2.3	Derivations of Projectile Motion Equations	9
2.3.1	Maximum height h	9
2.3.2	Direction of velocity θ_v	9
2.3.3	Time of Flight T_{tof}	10
2.3.4	Trajectory y as a function of x without time t	10
2.3.5	Range	11

1 Derivations for One Dimensional Motion

1.1 Average velocity \bar{v} vs Instantaneous velocity v

1.1.1 $\Delta t; \Delta x$

$$\bar{v} = \frac{x_2 - x_1}{t_2 - t_1} \quad \text{avg velocity}$$

$$x(t) = At^n \quad \text{position as function of time}$$

$$\bar{v} = \frac{x(t_2) - x(t_1)}{t_2 - t_1}$$

$$\text{Definition of } v(t): \quad v(t) = \lim_{\Delta t \rightarrow 0} \frac{x(t + \Delta t) - x(t)}{\Delta t} \iff v(t) = \frac{dx}{dt}$$

Where A is a constant and n is an integer.

1.1.2 Defining \bar{v}

Average velocity \bar{v} is defined for position x_1 at time t_1 and position x_2 at time t_2 :

$$\bar{v} = \frac{x_2 - x_1}{t_2 - t_1}$$

Because we may consider the position x to be a function of time, we may instead choose to rewrite this as:

$$\bar{v} = \frac{x(t_2) - x(t_1)}{t_2 - t_1}$$

Where $x(t) = At^n$

In order to go from \bar{v} to instantaneous velocity v , we swap in values that are more appropriate for calculus:

Let $t_1 = t$ and $t_2 = t + \Delta t$

Now we may consider the limit as $\Delta t \rightarrow 0$, which we shall define as instantaneous velocity $v(t)$:

$$v(t) = \lim_{\Delta t \rightarrow 0} \frac{x(t + \Delta t) - x(t)}{\Delta t} \iff v(t) = \frac{dx}{dt} = \frac{d}{dt}x(t) \quad (1.1)$$

Where the function $x(t)$ has the form: Where A is a constant and n is an integer.

1.2 Average acceleration \bar{a} vs Instantaneous acceleration a

1.2.1 $\Delta t; \Delta x$

$$\bar{a} = \frac{v_2 - v_1}{t_2 - t_1} \quad \text{avg velocity}$$

$$v(t) = \frac{dx}{dt} \quad \text{inst. velocity as function of time}$$

$$\bar{a} = \frac{v(t_2) - v(t_1)}{t_2 - t_1}$$

$$\text{Definition of } a(t) : a(t) = \lim_{\Delta t \rightarrow 0} \frac{v(t + \Delta t) - v(t)}{\Delta t} \iff a(t) = \frac{d}{dt}v(t) = \frac{d^2x}{dt^2}$$

1.2.2 Defining average velocity \bar{a}

The definition of acceleration has a similar form to the definition of velocity above, and is written in its most simple terms as:

$$\bar{a} = \frac{v_2 - v_1}{t_2 - t_1}$$

Because we may consider instantaneous velocity as a function of time $v(t)$, we may instead choose to write this as:

$$\bar{a} = \frac{v(t_2) - v(t_1)}{t_2 - t_1}$$

Now we define the terms differently to more clearly apply the limit to arrive at the derivative:

$$t_1 = t, \quad t_2 = t + \Delta t$$

Now we may define the instantaneous acceleration a to be the limit of the instantaneous velocity when the $\Delta t \rightarrow 0$:

$$a = \lim_{\Delta t \rightarrow 0} \frac{v(t + \Delta t) - v(t)}{\Delta t} \iff a = \frac{d}{dt}v(t) \quad (1.2)$$

1.3 Notation

As a simplification, we always take the initial time $t_0 = 0$ and define our equations with the supposition that acceleration is constant. Thus we write:

$$\begin{aligned}t &= t_f \\t &= t + 0 = t - t_0 = \Delta t \\ \boxed{\Delta t = t} \\ \Delta x &= \Delta x - x_0 \\ \Delta v &= v - v_0 \\ \bar{a} &= a = \text{constant}\end{aligned}\tag{1.3}$$

1.4 Deriving the first kinematic equation

1.4.1 Position x as a function of \bar{v}

$$\begin{aligned}\bar{v} &= \frac{\Delta x}{\Delta t} \\ \bar{v} &= \frac{x - x_0}{t} \\ x &= x_0 + \bar{v}t\end{aligned}$$

1.4.2 Final Velocity v as a function of time t and acceleration $a = \bar{a}$

$$\begin{aligned}a &= \frac{\Delta v}{\Delta t} \quad t = \Delta t \\ a &= \frac{v - v_0}{t} \\ v &= v_0 + at\end{aligned}\tag{1.4}$$

1.4.3 Final Velocity v as a function of distance x and acceleration $a = \bar{a}$

Starting with

$$v = v_0 + at$$

Rearranging for t

$$t = \frac{v - v_0}{a}$$

By definition \bar{v}

$$\bar{v} = \frac{v_0 + v}{2}$$

Now substitute into equation for position

$$x = x_0 + \bar{v}t$$

$$x = x_0 + \frac{v_0 + v}{2} * \frac{v - v_0}{a}$$

$$x = x_0 + \frac{v^2 - v_0^2}{2a}$$

Solving for v^2

$$v^2 = v_0^2 + 2a(x - x_0)$$

Or

$$\boxed{v^2 = v_0^2 + 2a\Delta x}$$

1.4.4 Deriving position x as a function of velocity v , time t , and acceleration $a = \bar{a}$

We begin with position as a function of \bar{v} :

$$x = x_0 + \bar{v}t$$

We know we want v , t , and a , so we start with the equation for v and rearrange to substitute \bar{v} :

$$v = v_0 + at$$

add v_0 to both sides

$$v + v_0 = 2v_0 + at$$

$$\frac{v + v_0}{2} = v_0 + \frac{at}{2}$$

$$\text{substitute } \bar{v} = \frac{v + v_0}{2}$$

$$\bar{v} = v_0 + \frac{1}{2}at$$

substitute

$$x = x_0 + (v_0 + \frac{1}{2}at)t$$

$$\boxed{x = x_0 + v_0t + \frac{1}{2}at^2}$$

1.5 Kinematic Equations from Integral Calculus

1.5.1 $v(t) = v_0 + at$ by Integration

We defined the relationship between acceleration and velocity in (1.2) as:

$$a = \frac{d}{dt}v(t)$$

Switching sides, as we are more interested in $v(t)$, and rewriting a as a function of time $a(t)$:

$$\begin{aligned}\frac{d}{dt}v(t) &= a(t) \\ \int \frac{d}{dt}v(t) dt &= \int a(t) dt + C_1 \\ v(t) &= \int a(t) dt + C_1\end{aligned}\tag{1.5}$$

For constant acceleration in (1.5):

$$\begin{aligned}v(t) &= \int a dt = at + C_1 \\ v(0) &= v_0 = a(0) + C_1 \\ v_0 &= C_1 \\ \therefore \boxed{v(t) = v_0 + at}\end{aligned}\tag{1.6}$$

1.5.2 $x(t)$ by Integration

We defined the function of position in (1.1) as:

$$\begin{aligned}\frac{d}{dt}x(t) &= v(t) \\ \int \frac{d}{dt}x(t) dt &= \int v(t) dt \\ x(t) &= \int v(t) dt + C_2\end{aligned}\tag{1.7}$$

Substitute equation for $v(t)$ from (1.6) in (1.7)

$$\begin{aligned}
x(t) &= \int v_0 + at \, dt \\
x(t) &= v_0 t + \frac{1}{2} at^2 + C_2 \\
x(0) = x_0 &= v_0(0) + \frac{1}{2} a(0)^2 + C_2 \\
x_0 &= C_2 \\
\therefore \boxed{x(t) = x_0 + v_0 t + \frac{1}{2} at^2} & \qquad (1.8)
\end{aligned}$$

Example on pg 136 of the textbook.

2 Projectile Motion Derivations

Motion of an object when:

$$a_x = 0$$

2.1 Defining vector quantities of motion for two dimensional vectors

Where $x(t)$ and $y(t)$ are defined for two dimensional position vector $\vec{r}(t)$ and similarly $v_x(t)$ and $v_y(t)$ are defined for velocity vector $\vec{v}(t)$, while \vec{a} is similar but with $a_x = 0$:

$$\vec{r}(t) = x(t)\hat{i} + y(t)\hat{j}$$

$$\vec{v}(t) = v_x(t)\hat{i} + v_y(t)\hat{j}$$

$$\vec{a}(t) = 0\hat{i} + a_y(t)\hat{j}$$

2.2 Rewriting kinematic equations for x and y directions where $a_x = 0$

$$x(t) = x_0 + \bar{v}_x t$$

$$v_x(t) = v_{0,x}$$

$$x(t) = x_0 + v_{0,x}t + \frac{1}{2}a_x t^2$$

$$v_x^2(t) = v_{0,x}^2$$

$$y(t) = y_0 + \bar{v}_y t$$

$$v_y(t) = v_{0,y} + a_y t$$

$$y(t) = y_0 + v_{0,y}t + \frac{1}{2}a_y t^2$$

$$v_y^2(t) = v_{0,y}^2 + 2a_y(y - y_0)$$

2.3 Derivations of Projectile Motion Equations

2.3.1 Maximum height h

Requires knowing two of three: y , $v_{0,y}^2$, g

For $v_y = 0$, $y_0 = 0$, $a_y = -g$:

$$v_y^2 = v_{0,y}^2 + 2a_y(y - y_0)$$

$$0 = v_{0,y}^2 + 2(-g)(y - 0)$$

$$0 = v_{0,y}^2 - 2gy$$

$$\therefore \boxed{y = \frac{v_{0,y}^2}{2g}} \quad (2.1)$$

2.3.2 Direction of velocity θ_v

The direction of velocity does not need to be derived, as it relies on the triangle formed by v_x and v_y :

$$\theta = \tan^{-1} \left(\frac{v_y}{v_x} \right) \quad (2.2)$$

2.3.3 Time of Flight T_{tof}

For $y = y_0$, $a_y = -g$:

$$\begin{aligned}
 y - y_0 &= v_{0,y}t + \frac{1}{2}a_yt^2 \\
 0 &= v_{0,y}t + \frac{1}{2}(-g)t^2 \\
 0 &= v_{0,y}t - \frac{1}{2}gt^2 & v_{0,y} &= \sin(\theta_0)v_0 \\
 0 &= \sin(\theta_0)v_0t - \frac{1}{2}gt^2 \\
 0 &= t\left(\sin(\theta_0)v_0 - \frac{1}{2}gt\right) \\
 0 &= \sin(\theta_0) - \frac{1}{2}gt \\
 \frac{1}{2}gt &= \sin(\theta_0) \\
 t &= \frac{2\sin(\theta_0)}{g} \\
 \boxed{T_{tof} = \frac{2\sin(\theta_0)}{g}} & \tag{2.3}
 \end{aligned}$$

2.3.4 Trajectory y as a function of x without time t

Need three of four: y , v_0 , θ_0 , x For $a = -g$

$$x = v_{0,x}t$$

Solving for t :

$$\begin{aligned}
 t &= \frac{x}{v_{0,x}} \\
 t &= \frac{x}{\cos(\theta_0)v_0}
 \end{aligned}$$

y -position:

$$y = v_{0,y}t + \frac{1}{2}at^2y = v_0\sin(\theta_0)t - \frac{1}{2}gt^2$$

Substitute t :

$$y = v_0 \sin(\theta_0) \left(\frac{x}{\cos(\theta_0) v_0} \right) - \frac{1}{2} g \left(\frac{x}{\cos(\theta_0) v_0} \right)^2$$
$$\boxed{y = \tan(\theta_0) x - x^2 \left(\frac{g}{2(v_0 \cos \theta_0)^2} \right)}$$
(2.4)

2.3.5 Range

Starting with trajectory equation (2.4) where $y = 0$:

$$0 = \tan(\theta_0) x - x^2 \left(\frac{g}{2(v_0 \cos \theta_0)^2} \right)$$
$$x^2 \left(\frac{g}{2(v_0 \cos \theta_0)^2} \right) = \tan(\theta_0) x$$
$$x = \tan(\theta_0) \left(\frac{2(v_0 \cos(\theta_0)^2)}{g} \right)$$
$$x = \frac{v_0^2 2 \sin(\theta_0) \cos(\theta_0)}{g}$$
$$\boxed{x = R = \frac{v_0^2 \sin(2\theta_0)}{g}}$$
(2.5)