



Zookeeper - Super User Authentication and Authorization



(/users/2035/aromero.html)

aromero (/users/2035/aromero.html) created · Apr 27, 2016 at 06:57 PM · **edited** (/revisions/29900.html) · Jul 07, 2016 at 12:30 PM



Short Description:

To overcome authorization issues ("Authentication is not valid" or "NoAuthException") when deleting znodes or changing their Acls.

Article

Introduction

By default, Zookeeper runs without the option of becoming a superuser to administrate znodes in the ZK ensemble, for example, to fix ACLs, remove znodes that are not required anymore, or create new ones in specific locations. Zookeeper grants permissions through ACLs through different schemas or authentication methods, such as 'world', 'digest', or 'sas' if we use Kerberos. We can potentially we locked out if we were to grant everyone just read permissions to a znode, as we would not be able to delete it or modify it anymore.

Example of the problem

For example, we connect to Zookeeper through zkCli:

```
/usr/hdp/current/zookeeper-client/bin/zkCli.sh -server `hostname -f`:2181

[zk: sandbox.hortonworks.com:2181(CONNECTED) 1] getAcl /config/topics
'world,'anyone
: r
```

If we need to modify that znode so that, for example, user 'kafka' can have access to it to create new topics:

```
[zk: sandbox.hortonworks.com:2181(CONNECTED) 2] setAcl /config/topics world:anyone:r sasl:kafka:cdrwa
Authentication is not valid : /config/topics
```

Using superDigest to become a Zookeeper superuser

The following can be done to run as a Zookeeper superuser and be able to make ACL changes or delete/modify znodes. We can run the DigestAuthenticationProvider to get the digest of a given password. For example, if we want our superuser 'super' to have the password 'super123' we can:

```
export ZK_CLASSPATH=/etc/zookeeper/conf:/usr/hdp/current/zookeeper-server/lib/*:/usr/hdp/current/zookeeper-server/*

java -cp $ZK_CLASSPATH org.apache.zookeeper.server.auth.DigestAuthenticationProvider super:super123

OUTPUT:
super:super123->super:UdxDQ14f9v5oITwcAs09bmWgHSI=
```

From the output we can just add the following to SERVER_JVMFLAGS and restart Zookeeper:

```
SERVER_JVMFLAGS=-Dzookeeper.DigestAuthenticationProvider.superDigest=super:UdxDQ14f9v5oITwcAs09bmWgHSI=
```

Then, in zkCli do:

```
[zk: sandbox.hortonworks.com:2181(CONNECTED) 1] addauth digest super:super123
```


Now, we can perform the action we couldn't before:

```
[zk: sandbox.hortonworks.com:2181(CONNECTED) 1] setAcl /config/topics world:anyone:cdrwa,sasl:kafka:cdrwa

cZxid = 0x29
ctime = Tue Jul 21 18:46:36 UTC 2015
mZxid = 0x29
mtime = Tue Jul 21 18:46:36 UTC 2015
pZxid = 0x22410
cversion = 4
dataVersion = 0
aclVersion = 9
```


```
[zk: sandbox.hortonworks.com:2181(CONNECTED) 3] getAcl /config/topics
'world,'anyone
: cdrwa
'sasl,'kafka
: cdrwa
```

[How-To/Tutorial \(/topics/How-To%2FTutorial.html\)](#) [authentication \(/topics/authentication.html\)](#) [authorization \(/topics/authorization.html\)](#) [superuser \(/topics/superuser.html\)](#) [zookeeper \(/topics/zookeeper.html\)](#)

Add comment ·  Show 2

ARTICLE

Contributors

 (/users/2035/aromero.html)

FOLLOW

 FOLLOW (/FOLLOW/29900/KBENTRY.HTML)

    
(/users/29900/saichon.html) (/users/29900/saichon.html) (/users/29900/saichon.html) (/users/29900/saichon.html) (/users/29900/saichon.html)

NAVIGATION

[Zookeeper - Super User Authentication and Authorization \(/articles/29900/zookeeper-using-superdigest-to-gain-full-access-to.html\)](#)

RELATED ARTICLES

[Load Balance Zookeeper using HAProxy \(/articles/139439/load-balance-zookeeper-using-haproxy.html\)](#)

[Proof-of-concept username/password authentication for the Phoenix Query Server \(/articles/70935/proof-of-concept-usernamepassword-authentication-f.html\)](#)

[Alarm Fatigue Demo - Installation via Cloudbreak \[Part 2\] \(/articles/142501/alarm-fatigue-demo-installation-via-cloudbreak-par.html\)](#)

[Marathon - PaaS to deploy applications \(/articles/43453/marathon-paas-to-deploy-applications.html\)](#)

[HBase Disaster Recovery Architecture Examples \(/articles/89512/hbase-disaster-recovery-architecture-examples.html\)](#)

[hive jdbc in zeppelin throwing permission error to anonymous user \(/articles/149046/hive-jdbc-in-zeppelin-throwing-permission-error-to.html\)](#)

[Apache Chronos \(/articles/43493/apache-chronos.html\)](#)

[Trying to use sudo to run commands\(as root\) in a cluster gives error " Stderr: Pseudo-terminal will not be allocated because stdin is not a terminal. sudo: sorry, you must have a tty to run sudo" \(/articles/92868/trying-to-use-sudo-to-run-commandsas-root-in-a-clu.html\)](#)

[Map Hive jobs to YARN queues \(/articles/24009/map-hive-jobs-to-yarn-queues.html\)](#)

[Ambari Workflow views to schedule a Hive Query \(/articles/155006/apache-ambari-workflow-manager-view-for-hive-actio.html\)](#)

