

 mlbarrow Fix typo in template-resources.md

3e77ab8 on Apr 24, 2016

4 contributors    

41 lines (31 sloc) 1.22 KB

# Template Resources

Template resources are written in TOML and define a single template resource. Template resources are stored under the `/etc/confd/conf.d` directory by default.

## Required

- `dest` (string) - The target file.
- `keys` (array of strings) - An array of keys.
- `src` (string) - The relative path of a [configuration template](#).

## Optional

- `gid` (int) - The gid that should own the file. Defaults to the effective gid.
- `mode` (string) - The permission mode of the file.
- `uid` (int) - The uid that should own the file. Defaults to the effective uid.
- `reload_cmd` (string) - The command to reload config.
- `check_cmd` (string) - The command to check config. Use `{{.src}}` to reference the rendered source template.
- `prefix` (string) - The string to prefix to keys.

## Notes

When using the `reload_cmd` feature it's important that the command exits on its own. The reload command is not managed by confd, and will block the configuration run until it exits.

## Example

```
[template]
src = "nginx.conf.tmpl"
dest = "/etc/nginx/nginx.conf"
uid = 0
gid = 0
mode = "0644"
keys = [
    "/nginx",
]
check_cmd = "/usr/sbin/nginx -t -c {{.src}}"
reload_cmd = "/usr/sbin/service nginx restart"
```