

SAFE OPERATING PROCEDURE

Hand Power Drill – mains or battery operated

LOCATION: Various

PERSONAL PROTECTIVE EQUIPMENT



Version: 2	Key Contact: George Fisher
Effective Date: 18/09/2020	Speciality/Position: Technician
Review Date: Sept 2022	Contact number: 021 190 4236
Permits required	Confined space ☐ Hot Works ☐ Working at Heights ☐

HAZARDS ASSOCIATED WITH THIS EQUIPMENT

PERMANENT HAZARDS Remove as necessary	List	Control Method	Lock out Yes or No
Electric shock	Power cord	Test and tag, RCD if using outside, or in damp conditions. Check condition of power cord if using.	If cord faulty, remove from service until repaired
Moving Machinery	Hand piece and attachments	Check drill bit is tight and secure. If it has chuck key remove before use. Secure and fit correctly. Ensure hair is tied up securely and you have no loose clothing	No
Noise	Drill motor and operation	Use ear protection	No
Vibration	Drill bit and handle	Ensure drill bit is securely in material before increasing power.	No
Dust	Material dust, swarf and chips from drilling	Use drill in well ventilated areas, remove dust as it accumulates, eye protection	No
Sharp objects	Fast moving drill bit	Keep fingers clear of rotating drill bit	No
Hot objects	Hot drill bit and work piece	Allow drill to cool before making adjustments.	No
Cuts/lacerations	Loose material	Secure work piece	No

PURPOSE/PROCESS

Drilling holes. Could be wood, steel, concrete, plastic

PROCEDURES:

DO NOT use this machine unless you have proven to your trainer that you are competent in its safe use and operation

Pre Start Check

1. Check operating area is uncluttered and well lit
2. Visual check of condition of equipment
3. Use correct drill bit for the job. Drill bit must be sharp. If showing signs of being worn, discard and replace with new bit
4. Check drill trigger lock is not on (if so pull switch trigger fully then release it)
5. Select rotation – forward or reverse
6. Select speed (1 for slow, 2 for fast)

Operation

1. Hold drill with both hands
2. Let drill reach operating speed before applying pressure, do not force drill and let it work into the material
3. Ensure drill goes straight in and does not enter at an angle which may cause drill bit to break.
4. When drill bit is nearly through, reduce pressure. Drill bit can catch and break or it can kick back the drill in operators hands.



	Name	Title/Position	Signature	Date
Author	George Fisher	Technician		
Reviewed by	Marie Dennis	HSW Manager		
Reviewed by	Tony Middlemass	Health and safety rep		
Manager	Joe Nathan			

Document Control

Date	Revision number	Modifications	Revised by	Approved by
3/12/2019	1	New Template and photos	George Fisher	Marie Dennis
17/03/2020	2	Updated	George Fisher	