

SAFE OPERATING PROCEDURE

Hot Water Cleaner LOCATION: Automotive Workshop

TOI-OHOMAI
Institute of Technology

PERSONAL PROTECTIVE EQUIPMENT



Version: 2	Key Contact: George Fisher
Effective Date: 18/09/2020	Speciality/Position: Technician
Review Date: Sept 2022	Contact number: 021 190 4236
Permits required	Confined space ☐ Hot Works ☐ Working at Heights ☐

HAZARDS ASSOCIATED WITH THIS EQUIPMENT

PERMANENT HAZARDS Remove as necessary	List	Control Method	Lock out Yes or No
Electric shock	Power cord, plugs and switches.	Test and tag equipment and check for any wear and tear or defects before use.	
Slips and trips	Floor can become slippery during use	Wear protective footwear with good grip and take care on slippery surfaces	
Hot surfaces	Hot water can cause burns	Keep clear of water being directed from hose, do not touch hose when in use and be aware lance can get hot during use – wear heat protective gloves if necessary. Eye protection.	
High pressure	Water coming out of hose is at high pressure and can cause dirt or particles to be airborne.	Wear eye protection and avoid direct contact with water stream.	

PURPOSE/PROCESS

Cleaning of greasy/oily dirty equipment.

PROCEDURES:

DO NOT use this machine unless you have proven to your trainer that you are competent in its safe use and operation

Pre Start Check

1. Check the area is clear of any clutter to avoid slips, trips or falls.
2. Check the diesel is full located at the left end of the cleaner.

3. Check the soap (detergent) located at the right end of the cleaner
4. Check the hose is not tangled.

Operation

1. Turn on the water tap at the wall.
2. Turn on the power at the wall socket.
3. Set the temperature to the desired setting.
4. Set the soap setting (if required).
5. Unloop the hose and hold firmly onto the lance.
6. Turn on the power switch on the machine.
7. Direct the lance at the object to be washed and pull the trigger firmly.
8. Do not direct the lance at people.
9. Wash and clean item.

Close Down

1. Turn off soap and turn down temperature.
2. Run cold water through the system until it has cooled down.
3. Turn off machine.
4. Turn power off at the wall.
5. Turn off water.
6. Hang up hose and lance.

Routine maintenance

Lock out and/or isolate any equipment before inspection or maintenance

	Name	Title/Position	Signature	Date
Author	George Fisher	Technician		
Reviewed by	Marie Dennis	HSW Manager		
Reviewed by	Tony Middlemiss	Health and safety rep		
Manager	Joe Nathan			

Document Control

Date	Revision number	Modifications	Revised by	Approved by
16/12/2019	1	New Template	George Fisher	Marie Dennis
17/03/2020	2	Updated	George Fisher	