

SAFE OPERATING PROCEDURE

CEMB Tyre Changer

LOCATION: Automotive Workshop

TOI-OHOMAI
Institute of Technology

PERSONAL PROTECTIVE EQUIPMENT



Version: 2	Key Contact: George Fisher
Effective Date: 18/09/2020	Speciality/Position: Technician
Review Date: September 2022	Contact number: 021 190 4236
Permits required	Confined space ☐ Hot Works ☐ Working at Heights ☐

HAZARDS ASSOCIATED WITH THIS EQUIPMENT

PERMANENT HAZARDS Remove as necessary	List	Control Method	Lock out Yes or No
Electric shock	Power cord	Test and tag, RCD if using outside or in damp conditions	Yes
Moving Machinery	Rotating wheel and movement of work piece		Yes
Manual handling	Heavy wheels		Yes
Sharp objects	Wire protruding through tyre.	Gloves	Yes

PURPOSE/PROCESS

Changing vehicle tyres

PROCEDURES:

DO NOT use this machine unless you have proven to your trainer that you are competent in its safe use and operation

Pre Start Check

1. Check the area is uncluttered and free from slips, trips and falls
2. Check the electrical test tag is current.
3. Ensure the wheel to be changed is the right size for the machine.
4. Ensure the wheel is clean (no mud) and the weights have been removed from the rim.
5. Check there is no wire sticking out of the tyre.

Operation

1. Remove tyre valve .
2. Brake wheel bead.
3. Fit tyre to machine.
4. Set arm.
5. With tyre lever remove outer bead.
6. With tyre lever remove inner bead.

7. To fit new tyre lube edges.
8. Fit inner bead with machine.
9. Fit outer bead.
10. Blow up with compressed air until bead seals on rim.
11. Fit valve and blow to manufactures tyre pressure.

Close Down

1. Remove from machine and clean area.

Routine maintenance

Lock out and/or isolate any equipment before inspection or maintenance

	Name	Title/Position	Signature	Date
Author	George Fisher	Technician		
Reviewed by	Marie Dennis	HSW Manager		
Reviewed by	Tony Middlemiss	Health and safety rep		
Manager	Joe Nathan			

Document Control

Date	Revision number	Modifications	Revised by	Approved by
17/08/20	1	New format	George	Marie