

# HMMA 308 : Machine learning

Lasso vs FoBa

**Ophélie Coiffier**

<https://github.com/opheliecoiffier/LASSOvsFoBa>

Université de Montpellier



# Table of Contents

Mathematics approach

Examples

Conclusion

# Table of Contents

## Mathematics approach

- The Lasso method

- The OMP method

- The FoBa algorithm (Lars method)

## Examples

## Conclusion

# Introduction

To measure the quality of prediction, we use linear prediction model :

$$f(x) = \beta^\top x$$

With

$$\hat{\beta} = \arg \min_{\beta \in \mathbb{R}^d} \sum_{i=1}^n \Phi(\beta^\top x_i, y_i) + \lambda g(\beta)$$

# The Lasso method

Method uses  $L_1$  regularization.

We have

$$\hat{\beta} = \arg \min_{\beta \in \mathbb{R}^d} \sum_{i=1}^n \Phi(\beta^\top x_i, y_i) + \lambda \|\beta\|_1$$

2 issues :

- ▶ strong assumptions
- ▶ large regularization parameter ( $\lambda$ )

# The OMP method

"Orthogonal Match Pursuit" : forward greedy algorithm

# The OMP method

"Orthogonal Match Pursuit" : forward greedy algorithm

**Principle** : Add feature at every step to reduce the squared error  
& Calculate its error

# The OMP method

"Orthogonal Match Pursuit" : forward greedy algorithm

**Principle** : Add feature at every step to reduce the squared error  
& Calculate its error

**Ability** : Select relevant features



# The OMP method

"Orthogonal Match Pursuit" : forward greedy algorithm

**Principle** : Add feature at every step to reduce the squared error  
& Calculate its error

**Ability** : Select relevant features

**Main issue** : Never correct mistakes made earlier steps

# The OMP method

"Orthogonal Match Pursuit" : forward greedy algorithm

**Principle** : Add feature at every step to reduce the squared error  
& Calculate its error

**Ability** : Select relevant features

**Main issue** : Never correct mistakes made earlier steps

**Solution** : Backward greedy algorithm ?

# The FoBa algorithm (Lars method)

"Forward-Backward" greedy algorithm

**Principle :**

# The FoBa algorithm (Lars method)

"Forward-Backward" greedy algorithm

**Principle :**

1) Use Forward greedy step

# The FoBa algorithm (Lars method)

"Forward-Backward" greedy algorithm

## **Principle :**

- 1) Use Forward greedy step
- 2) Until squared error increase is no more than half of the squared error decrease in the earlier forward step

# The FoBa algorithm (Lars method)

"Forward-Backward" greedy algorithm

## **Principle :**

- 1) Use Forward greedy step
- 2) Until squared error increase is no more than half of the squared error decrease in the earlier forward step
- 3) Use Backward greedy step & adaptive Backward step

# The FoBa algorithm (Lars method)

"Forward-Backward" greedy algorithm

## Principle :

- 1) Use Forward greedy step
- 2) Until squared error increase is no more than half of the squared error decrease in the earlier forward step
- 3) Use Backward greedy step & adaptive Backward step

## \*) **Adaptive backward functions :**

- ▶ Make sure that we progress

# Comparison between Lasso and FoBa

Similarity	Difference
Path-following algorithm Large regularization parameter Mistakes in earlier step	Conditions to find threshold Bias



# Table of Contents

Mathematics approach

## Examples

*Boston Housing* data

*Ionosphere* data

Conclusion

# Introduction

Loss function used :

$$MSE = \frac{1}{n} \sum_{i=1}^n (\hat{Y}_i - Y_i)^2$$

**Principle :**

- ▶ Randomly partition into 50 training points and  $nb$  test points
- ▶ Predict variable
- ▶ Compare MSE for each methods and for each groups



## ***Boston Housing data***

**Data :** 506 census tracts from 1970 census  
14 features

**Y :** housing price

**Principle :** 50 training points / 456 test points  
We repeat 50 times MSE calculations and compare MSE obtained  
With a sparsity between 1 and 10.

# Boston Housing data



**Figure:** MSE depending on sparsity for the 3 methods and for the 2 groups.



# *Ionosphere data*

**Data :** 351 data points  
35 features

**Y :** binary variable ( $Y \in \{0, 1\}$ )

**Principle :** 50 training points / 301 test points  
We repeat 50 times MSE calculations and compare MSE obtained  
With a sparsity between 1 and 10.


# Ionosphere data



**Figure:** MSE depending on sparsity for the 3 methods and for the 2 groups.

# Issues

## ► Representation of Lasso



alpha	Nb non-zero coefs
0.400	1
0.300	2
0.250	2
0.200	4
0.150	4
0.100	4
0.050	8
0.010	13
0.006	15
0.004	18

**Figure:** Lasso path and non-zero coefficients for Ionosphere data

## ► Differences between our algorithms and these in the article

# Table of Contents

Mathematics approach

Examples

Conclusion



# Conclusion

The main question is about the learning sparse representations using greedy algorithms.

FoBa is useful with training points.

We need to use a novel combination of the forward-greedy and backward-greedy algorithms to obtain a smaller error.

But, it depends on the data : with lonosphere data (test points), with the L1 regularization, the "bias" is an advantageous.

Finally, we must choose the best algorithm and the best method depending on data, sparsity and mathematics conditions that we can check.

# Bibliography

- ▶ (BSD License), scikit-learn developers. *scikit-learn*.  
[https://scikit-learn.org/stable/modules/classes.html/module-sklearn.linear\\_model](https://scikit-learn.org/stable/modules/classes.html/module-sklearn.linear_model).  
2020.
- ▶ Coiffier, Ophélie. *Github LASSOvsFoBa*.  
<https://github.com/opheliecoiffier/LASSOvsFoBa>. 2020.
- ▶ Salmon, Joseph. *HMMA 308 - Apprentissage statistique*. 2019.
- ▶ Sigillito, Vince. *Ionosphere Data Set*.  
<https://archive.ics.uci.edu/ml/datasets/ionosphere>.
- ▶ University, Johns Hopkins. *Index of*  
*/ml/machine-learning-databases/housing*.  
<https://archive.ics.uci.edu/ml/machine-learning-databases/housing/>.
- ▶ Zhang, Tong. *Adaptive Forward-Backward Greedy Algorithm for Learning Sparse Representations*.  
<http://tongzhang-ml.org/papers/it11-foba.pdf>.