

# HMMA 308 : Machine Learning

Lasso vs FoBa

**Ophélie Coiffier**

<https://github.com/opheliecoiffier/LASSOvsFoBa>

Université de Montpellier



# Table of Contents

Mathematics approach

Examples

Conclusion

# Table of Contents

## Mathematics approach

- The Lasso method

- The OMP method

- The FoBa algorithm (Lars method)

## Examples

## Conclusion

# Introduction

To measure the quality of prediction, we use linear prediction model :

$$f(x) = \beta^T x$$

With

$$\hat{\beta} = \arg \min_{\beta \in \mathbb{R}^d} \sum_{i=1}^n \Phi(\beta^T x_i, y_i) + \lambda g(\beta)$$

# The Lasso method

Method uses  $L_1$  regularization.

We have

$$\hat{\beta} = \arg \min_{\beta \in \mathbb{R}^d} \sum_{i=1}^n \Phi(\beta^\top x_i, y_i) + \lambda \|\beta\|_1$$

2 issues :

- ▶ strong assumptions
- ▶ large regularization parameter ( $\lambda$ )

# The OMP method

"Orthogonal Match Pursuit" : forward greedy algorithm

# The OMP method

"Orthogonal Match Pursuit" : forward greedy algorithm

**Principle** : Add feature at every step to reduce the squared error  
& Calculate its error

# The OMP method

"Orthogonal Match Pursuit" : forward greedy algorithm

**Principle** : Add feature at every step to reduce the squared error  
& Calculate its error

**Ability** : Select relevant features



# The OMP method

"Orthogonal Match Pursuit" : forward greedy algorithm

**Principle** : Add feature at every step to reduce the squared error  
& Calculate its error

**Ability** : Select relevant features

**Main issue** : Never correct mistakes made earlier steps

# The OMP method

"Orthogonal Match Pursuit" : forward greedy algorithm

**Principle** : Add feature at every step to reduce the squared error  
& Calculate its error

**Ability** : Select relevant features

**Main issue** : Never correct mistakes made earlier steps

**Solution** : Backward greedy algorithm ?

# The FoBa algorithm (Lars method)

"Forward-Backward" greedy algorithm

**Principle :**

# The FoBa algorithm (Lars method)

"Forward-Backward" greedy algorithm

**Principle :**

1) Use Forward greedy step

# The FoBa algorithm (Lars method)

"Forward-Backward" greedy algorithm

## **Principle :**

- 1) Use Forward greedy step
- 2) Until squared error increase is no more than half of the squared error decrease in the earlier forward step

# The FoBa algorithm (Lars method)

"Forward-Backward" greedy algorithm

## **Principle :**

- 1) Use Forward greedy step
- 2) Until squared error increase is no more than half of the squared error decrease in the earlier forward step
- 3) Use Backward greedy step & adaptive Backward step

# The FoBa algorithm (Lars method)

"Forward-Backward" greedy algorithm

## Principle :

- 1) Use Forward greedy step
- 2) Until squared error increase is no more than half of the squared error decrease in the earlier forward step
- 3) Use Backward greedy step & adaptive Backward step

## \*) **Adaptive backward function :**

- ▶ Make sure that we progress

# Comparison between Lasso and FoBa

Similarity	Difference
Path-following algorithm Large regularization parameter Mistakes in earlier step	Conditions to find threshold Bias



# Table of Contents

Mathematics approach

## Examples

*Boston Housing* data

*Ionosphere* data

Conclusion

# Introduction

Loss function used :

$$MSE = \frac{1}{n} \sum_{i=1}^n (\hat{Y}_i - Y_i)^2$$

**Principle :**

- ▶ Randomly partition into 50 training points and  $nb$  test points
- ▶ Predict variable
- ▶ Compare MSE for each methods and for each groups



## *Boston Housing data*

**Data :** 506 census tracts from 1970 census  
14 features

**Y :** housing price

**Principle :** 50 training points / 456 test points  
We repeat 50 times MSE calculations and compare MSE obtained  
With a sparsity between 1 and 10.

# Boston Housing data



**Figure:** MSE depending on sparsity for the 3 methods and for the 2 groups.



# *Ionosphere data*

**Data :** 351 data points  
35 features

**Y :** binary variable ( $Y \in \{0, 1\}$ )

**Principle :** 50 training points / 301 test points  
We repeat 50 times MSE calculations and compare MSE obtained  
With a sparsity between 1 and 10.


# Ionosphere data



**Figure:** MSE depending on sparsity for the 3 methods and for the 2 groups.

# Issues

## ► Representation of Lasso



alpha	Nb non-zero coefs
0.400	1
0.300	2
0.250	2
0.200	4
0.150	4
0.100	4
0.050	8
0.010	13
0.006	15
0.004	18

Figure: Lasso path and non-zero coefficients for lonosphere data

## ► Differences between our algorithms and these in the article

# Table of Contents

Mathematics approach

Examples

Conclusion



# Conclusion

We find these results :

- ▶ **Test points** : FoBa for *lonosphere* data & FoBa/OMP for *Boston Housing* data
- ▶ **Training points** : OMP (depending on sparsity for *lonosphere* data

The article finds :

- ▶ **Test points** : FoBa for small sparsity and for *Boston housing* data & Lasso for *lonosphere* data
- ▶ **Training points** : the mixed algorithm (FoBa)

Finally, we must choose the best algorithm and the best method depending on data, sparsity and mathematics conditions that we can check.

# Bibliography