

HMMA 308 : Machine Learning

Lasso vs FoBa

Ophélie Coiffier

<https://github.com/opheliecoiffier/LASSOvsFoBa>

Université de Montpellier



Table of Contents

Mathematics approach

Examples

Conclusion

Table of Contents

Mathematics approach

- The Lasso method

- The OMP method

- The FoBa algorithm (Lars method)

Examples

Conclusion

Introduction

To measure the quality of prediction, we use linear prediction model :

$$f(x) = \beta^\top x$$

With

$$\hat{\beta} = \arg \min_{\beta \in \mathbb{R}^d} \sum_{i=1}^n \Phi(\beta^\top x_i, y_i) + \lambda g(\beta)$$

The Lasso method

Method uses L_1 regularization.

We have

$$\hat{\beta} = \arg \min_{\beta \in \mathbb{R}^d} \sum_{i=1}^n \Phi(\beta^\top x_i, y_i) + \lambda \|\beta\|_1$$

2 issues :

- ▶ strong assumptions
- ▶ large regularization parameter (λ)

The OMP method

"Orthogonal Match Pursuit" : forward greedy algorithm

The OMP method

"Orthogonal Match Pursuit" : forward greedy algorithm

Principle : Add feature at every step to reduce the squared error
& Calculate its error

The OMP method

"Orthogonal Match Pursuit" : forward greedy algorithm

Principle : Add feature at every step to reduce the squared error
& Calculate its error

Ability : Select relevant features

The OMP method

"Orthogonal Match Pursuit" : forward greedy algorithm

Principle : Add feature at every step to reduce the squared error
& Calculate its error

Ability : Select relevant features

Main issue : Never correct mistakes made earlier steps

The OMP method

"Orthogonal Match Pursuit" : forward greedy algorithm

Principle : Add feature at every step to reduce the squared error
& Calculate its error

Ability : Select relevant features

Main issue : Never correct mistakes made earlier steps

Solution : Backward greedy algorithm ?

The FoBa algorithm (Lars method)

"Forward-Backward" greedy algorithm

Principle :

The FoBa algorithm (Lars method)

"Forward-Backward" greedy algorithm

Principle :

- 1) Use Forward greedy step

The FoBa algorithm (Lars method)

"Forward-Backward" greedy algorithm

Principle :

- 1) Use Forward greedy step
- 2) Until squared error increase is no more than half of the squared error decrease in the earlier forward step

The FoBa algorithm (Lars method)

"Forward-Backward" greedy algorithm

Principle :

- 1) Use Forward greedy step
- 2) Until squared error increase is no more than half of the squared error decrease in the earlier forward step
- 3) Use Backward greedy step & adaptive Backward step

The FoBa algorithm (Lars method)

"Forward-Backward" greedy algorithm

Principle :

- 1) Use Forward greedy step
- 2) Until squared error increase is no more than half of the squared error decrease in the earlier forward step
- 3) Use Backward greedy step & adaptive Backward step

*) **Adaptive backward function :**

- ▶ Make sure that we progress

Comparison between Lasso and FoBa

Similarity	Difference
Path-following algorithm Large regularization parameter Mistakes in earlier step	Conditions to find threshold Bias

Table of Contents

Mathematics approach

Examples

Boston Housing data

Ionosphere data

Conclusion

Introduction

Loss function used :

$$MSE = \frac{1}{n} \sum_{i=1}^n (\hat{Y}_i - Y_i)^2$$

Principle :

- ▶ Randomly partition into 50 training points and nb test points
- ▶ Predict variable
- ▶ Compare MSE for each methods and for each groups

Boston Housing data

Data : 506 census tracts from 1970 census
14 features

Y : housing price

Principle : 50 training points / 456 test points
We repeat 50 times MSE calculations and compare MSE obtained
With a sparsity between 1 and 10.

Boston Housing data





Figure: MSE depending on sparsity for the 3 methods and for the 2 groups.

Ionosphere data

Data : 351 data points
35 features

Y : binary variable ($Y \in \{0, 1\}$)

Principle : 50 training points / 301 test points
We repeat 50 times MSE calculations and compare MSE obtained
With a sparsity between 1 and 10.

Ionosphere data






Figure: MSE depending on sparsity for the 3 methods and for the 2 groups.

Issues

► Representation of Lasso



alpha	Nb non-zero coefs
0.400	1
0.300	2
0.250	2
0.200	4
0.150	4
0.100	4
0.050	8
0.010	13
0.006	15
0.004	18

Figure: Lasso path and non-zero coefficients for lonosphere data

► Differences between our algorithms and these in the article

Table of Contents

Mathematics approach

Examples

Conclusion

Conclusion

We find these results :

- ▶ **Test points** : FoBa for *lonosphere* data & FoBa/OMP for *Boston Housing* data
- ▶ **Training points** : OMP (depending on sparsity for *lonosphere* data

The article finds :

- ▶ **Test points** : FoBa for small sparsity and for *Boston housing* data & Lasso for *lonosphere* data
- ▶ **Training points** : the mixed algorithm (FoBa)

Finally, we must choose the best algorithm and the best method depending on data, sparsity and mathematics conditions that we can check.

Bibliography