

HMMA 308 : Machine learning

Lasso vs FoBa

Ophélie Coiffier

<https://github.com/opheliecoiffier/LASSOvsFoBa>

Université de Montpellier



Table of Contents

Mathematics approach

Examples

Conclusion

Table of Contents

Mathematics approach

- The Lasso method

- The OMP method

- The FoBa algorithm (Lars method)

Examples

Conclusion

Introduction

To measure the quality of prediction, we use linear prediction model :

$$f(x) = \beta^\top x$$

With

$$\hat{\beta} = \arg \min_{\beta \in \mathbb{R}^d} \sum_{i=1}^n \Phi(\beta^\top x_i, y_i) + \lambda g(\beta)$$

The Lasso method

Method uses L_1 regularization.

We have

$$\hat{\beta} = \arg \min_{\beta \in \mathbb{R}^d} \sum_{i=1}^n \Phi(\beta^\top x_i, y_i) + \lambda \|\beta\|_1$$

2 issues :

- ▶ strong assumptions
- ▶ large regularization parameter (λ)

The OMP method

"Orthogonal Match Pursuit" : forward greedy algorithm

The OMP method

"Orthogonal Match Pursuit" : forward greedy algorithm

Principle : Add feature at every step to reduce the squared error
& Calculate its error

The OMP method

"Orthogonal Match Pursuit" : forward greedy algorithm

Principle : Add feature at every step to reduce the squared error
& Calculate its error

Ability : Select relevant features

The OMP method

"Orthogonal Match Pursuit" : forward greedy algorithm

Principle : Add feature at every step to reduce the squared error
& Calculate its error

Ability : Select relevant features

Main issue : Never correct mistakes made earlier steps

The OMP method

"Orthogonal Match Pursuit" : forward greedy algorithm

Principle : Add feature at every step to reduce the squared error
& Calculate its error

Ability : Select relevant features

Main issue : Never correct mistakes made earlier steps

Solution : Backward greedy algorithm ?

The FoBa algorithm (Lars method)

"Forward-Backward" greedy algorithm

Principle :

The FoBa algorithm (Lars method)

"Forward-Backward" greedy algorithm

Principle :

1) Use Forward greedy step

The FoBa algorithm (Lars method)

"Forward-Backward" greedy algorithm

Principle :

- 1) Use Forward greedy step
- 2) Until squared error increase is no more than half of the squared error decrease in the earlier forward step

The FoBa algorithm (Lars method)

"Forward-Backward" greedy algorithm

Principle :

- 1) Use Forward greedy step
- 2) Until squared error increase is no more than half of the squared error decrease in the earlier forward step
- 3) Use Backward greedy step & adaptive Backward step

The FoBa algorithm (Lars method)

"Forward-Backward" greedy algorithm

Principle :

- 1) Use Forward greedy step
- 2) Until squared error increase is no more than half of the squared error decrease in the earlier forward step
- 3) Use Backward greedy step & adaptive Backward step

*) **Adaptive backward functions :**

- ▶ Make sure that we progress

Comparison between Lasso and FoBa

Similarity	Difference
Path-following algorithm Large regularization parameter Mistakes in earlier step	Conditions to find threshold Bias

Table of Contents

Mathematics approach

Examples

Boston Housing data

Ionosphere data

Conclusion

Introduction

Loss function used :

$$MSE = \frac{1}{n} \sum_{i=1}^n (\hat{Y}_i - Y_i)^2$$

Principle :

- ▶ Randomly partition into 50 training points and nb test points
- ▶ Predict variables
- ▶ Compare MSE for each methods and for each groups

Boston Housing data

Data : 506 census tracts from 1970 census
14 features

Y : housing price

Principle : 50 training points / 456 test points
We repeat 50 times MSE calculations and compare MSE obtained
With a sparsity between 1 and 10.

Boston Housing data





Figure: MSE depending on sparsity for the 3 methods and for the 2 groups.

Ionosphere data

Data : 351 data points
35 features

Y : binary value ($Y \in \{0, 1\}$)

Principle : 50 training points / 301 test points
We repeat 50 times MSE calculations and compare MSE obtained
With a sparsity between 1 and 10.

Ionosphere data






Figure: MSE depending on sparsity for the 3 methods and for the 2 groups.

Issues

► Representation of Lasso



alpha	Nb non-zero coefs
0.400	1
0.300	2
0.250	2
0.200	4
0.150	4
0.100	4
0.050	8
0.010	13
0.006	15
0.004	18

Figure: Lasso path and non-zero coefficients for Ionosphere data

► Differences between our algorithms and these in the article

Table of Contents

Mathematics approach

Examples

Conclusion

Conclusion

The main question is about the learning sparse representations using greedy algorithms.

FoBa is useful with training points.

We need to use a novel combination of the forward-greedy and backward-greedy algorithms to obtain a smaller error.

But, it depends on the data : with lonosphere data (test points), with the L1 regularization, the "bias" is an advantageous.

Finally, we must choose the best algorithm and the best method depending on data, sparsity and mathematics conditions that we can check.

Bibliography

- ▶ (BSD License), scikit-learn developers. *scikit-learn*.
https://scikit-learn.org/stable/modules/classes.html/module-sklearn.linear_model.
2020.
- ▶ Coiffier, Ophélie. *Github LASSOvsFoBa*.
<https://github.com/opheliecoiffier/LASSOvsFoBa>. 2020.
- ▶ Salmon, Joseph. *HMMA 308 - Apprentissage statistique*. 2019.
- ▶ Sigillito, Vince. *Ionosphere Data Set*.
<https://archive.ics.uci.edu/ml/datasets/ionosphere>.
- ▶ University, Johns Hopkins. *Index of*
/ml/machine-learning-databases/housing.
<https://archive.ics.uci.edu/ml/machine-learning-databases/housing/>.
- ▶ Zhang, Tong. *Adaptive Forward-Backward Greedy Algorithm for Learning Sparse Representations*.
<http://tongzhang-ml.org/papers/it11-foba.pdf>.