

Music & the Internet

MUMT301

Gabriel Vigliensoni
Schulich School of Music
McGill University

Plan

- Review of last class and assignment #3
- Internet technologies (i.e., Ethernet, TCP/IP, IP Headers, TCP Header, DNS, Ports, DHCP, FTP, SSH, HTTP)
- Sound file formats
- Audio compression
- Introduction to JavaScript
- Assignment #4

Assignment 3

- music.mcgill.ca/~backer
- music.mcgill.ca/~davis
- music.mcgill.ca/~hecht
- music.mcgill.ca/~hiebert
- music.mcgill.ca/~smith
- music.mcgill.ca/~szeto
- music.mcgill.ca/~akdag

Sound file formats

- Exponential growth of audio material on the Internet since 1995
- “.mp3” most searched term in 1999
- Big impact of coded audio: mostly everybody is using MPEG-1/2 Layer-3
 - also known as MP3
- Broadly speaking, sound content is delivered in two format categories:
 - As recorded sound:
 - often called *waveform* sound
 - As structured audio:
 - Sounds are generated in a dynamic manner at runtime
 - MIDI, MODs (e.g., trackers)

Structured Audio

- Structured audio formats provide data to support **dynamic construction of sound** through hardware and software
- *Sequencers* and *trackers* control
 - the **timing of sounds**, i.e., when individual sound elements start or stop
 - **sound attributes** such as volume, pitch, or other effects
- *Sound elements* can be
 - short sections of **sound samples or loops** or
 - **data elements that characterize a sound** so that a *synthesizer* can produce the actual sound

Structured Audio

- Structured audio does not convey audio, the sounds are generated in a dynamic manner at *runtime*. Most common formats are:
- MIDI (1983)
 - technical standard to allow the communication between electronic music instruments (and computers)
 - Organized by the MIDI association
 - MIDI 1.0 Detailed specification
 - MIDI classical archives
 - MIDI world
- Module files or MODs (late 80s) are used in music *tracker* software
 - Arrangement of discrete musical notes positioned at discrete chronological positions on a timeline
 - E.g., OpenMPT, 16bitshock, Soundbox, FruityLoops, Renoise
 - <http://modarchive.org/>

Recorded sound

- Audio file data is stored in a binary representation
 - it is necessary to have a format specification in order to know how to read a given format's data
- Sustainability of Digital Formats. Planning for Library of Congress Collections
- Comprehensive list of audio file formats
- The most common audio file formats are/were:
 - SND or AU (NeXT, Sun)
 - AIFF (Apple, SGI)
 - WAV (Microsoft)
 - MP3 (MPEG)
 - FLAC (OpenSource)
- Audio data can be stored in compressed or uncompressed formats

Uncompressed formats

- LPCM (Linear Pulse Code Modulation Audio):
 - digital representation of analog signal
 - magnitude of the signal is sampled regularly at uniform intervals
 - quantized to a series of values in binary code
 - used for uncompressed encoding of audio data in the Compact disc Red Book Standard (i.e., Audio CD, 1982)
 - defining characteristics:
 - sampling rate (44.1kHz, 48kHz, 88.2kHz, 96kHz, 176.4kHz, 192kHz)
 - bit depth (8, 16, 20, 24, 32 bits per sample)


Compact Disc

- Optical storage of digital audio (data)
- Sony and Phillips together, introduced in 1982
- Originally for sound only, but later for all types of data
- 74–80 minutes of audio (44.1KHz/16bit/stereo)
- 783–847 MBytes

Uncompressed formats

IFF File formats

- Interchange File Format
- Generic container file format (AIFF, WAVE, RIFF, SMF)
- Aimed to facilitate data transfer between different software and companies
- Based on IFF (“EA IFF 85” standard)
 - Electronic Arts Interchange File Format (developed by the gaming company!)
 - Base of other formats such as RIFF and SMF
 - Generic wrapper format for data interchange
 - Based on headers pointing to “chunks” of data




Uncompressed formats

IFF File formats

- AIFF (Audio Interchange File Format, 1989)
- WAVE (Waveform Audio File Format, 1991)

Uncompressed formats


The Canonical WAVE file format



Taken from <http://soundfile.sapp.org/doc/WaveFormat/>

Uncompressed formats


The Canonical WAV file format



Taken from <http://soundfile.sapp.org/doc/WaveFormat/>

Endianness

- In WAVE files, data bytes are “little endian” ordered, When looking at multiple bytes, the first byte is smallest.
- In AIFF files, data bytes are “big endian” ordered. When looking at multiple bytes, the first byte (lowest address) is the biggest.



Taken from <http://en.wikipedia.org/wiki/Endianness>

Compressed sound file formats

- Lossy and Lossless
- Lossy compression: only an approximation of the original data can be reconstructed after decompression, usually with a higher compression rate
 - Common lossy formats
 - MP3
 - Vorbis (aka Ogg Vorbis), xiph.org webpage (free and open source) (V1.0 2002)
 - WMA
- Lossless compression: data can be perfectly reconstructed after decompression
 - Lossless formats
 - Monkey's Audio, ATRAC, Apple Lossless
 - FLAC, xiph.org webpage
 - non-proprietary
 - no patent restricted
 - open-source

Audio compression

- Basic task of audio compression?
 - to compress the digital audio data in a way that
 - compression as efficient as possible, i.e., file **size as small as possible**
 - the decoded audio should be **as close as possible to the original** audio before compression
- **Perceptual audio coding** is the technique to accomplish it
 - research topic since the late 70's, and exploded since 1986
 - uses **knowledge from psychoacoustics** to reach the target of efficient but inaudible compression
 - is a *lossy* compression technique
 - the decoded file **is not a bit-exact replica of the original** digital audio data

The MPEG and MPEG-1, -2

- Reasons why MPEG-1/2 Layer-3 has emerged as the main tool for Internet audio delivery
 - Open standard
 - format is well defined
 - no problems with interoperability of equipment and software
 - specification is available to everybody interested in implementing the standard (for a fee)
- MPEG (Moving Pictures Expert Group) has been in charge of developing generic standards for the coded representation of moving pictures and associated audio
 - standardization of compression techniques for video and audio
- MPEG-1 was the first phase of MPEG work in 1988. Became an ISO standard in 1992
 - Generic coding system with three layers: Layer-1 to Layer-3
 - Layer-3 is the highest complexity mode: to provide highest quality at low bit-rates
- MPEG-2 was the second phase of MPEG (1994). No new coding algorithms, but
 - coding of multichannel signals (including 5.1)
 - coding efficiency at very low rates (lower sampling frequencies, e.g., 16Khz)
 - it is backwards compatible with MPEG-1
 - its main application is digital television
 - named MPEG-2 Advanced Audio Coding (AAC)
 - second generation audio coding scheme for generic coding of stereo and multichannel signals

MPEG-3, -4, -7

- MPEG-3 development was rolled into MPEG-2
 - MPEG-1/2 Layer-3 (MP3) is misnamed MPEG-3
- MPEG-4 (1998) is standard in the world of multimedia
 - emphasis on new functionalities rather than compression efficiency
 - family of audio coding algorithms from low bit-rate speech coding (down to 2 kbit/s) up to high quality audio coding at 64 kbit/s per channel and above
 - generic audio coding at medium to high bit-rates is done by AAC
- MPEG-7 (2001) does not define compression algorithms
 - content representation standard for multimedia information search, filtering, management, and processing

MPEG-1 Layer-3 audio standard

- MPEG audio standard is **informative instead of normative**
 - minimum amount of **normative elements**:
 - the **data representation** (i.e., format of the compressed audio)
 - the **decoder** (however there is freedom in how to implement it)
- **Encoding** of MPEG audio is **left to the implementer**
 - the standard only gives description of example encoders
 - MPEG audio **encoders can vary in quality**

MPEG-1 Layer-3 characteristics

- Flexibility
 - Operating mode:
 - Single channel
 - Dual channel (two independent channels, e.g., two different language versions of an audio piece)
 - Stereo (no joint stereo coding, the two channels are encoded independently)
 - Joint stereo (information about differences from each channel is stored in one channel, whilst identical information is stored in the other. Help to reduce bit-rate)
- Sampling frequency
 - MPEG-1: 32kHz, 44.1kHz, 48kHz
 - MPEG-2: extends MPEG-1 to half rates: 16kHz, 22.05kHz, 24kHz
 - MPEG-2.5: Fraunhofer-proprietary: 8kHz, 11.05kHz, 12kHz
- Bit-rate
 - the MPEG-1 standard defined a range of bit-rates from 32 kbits/s up to 320k bits/s
 - MPEG-2 standard extends the bit-rate to 8 kbits/s
 - selection of bit-rate left to the operator of the audio coder


MPEG-1 Layer-3 perceptual model

- PCM digitally reproduces the waveform of an incoming signal as accurately as possible
- Human aural perception works different, our ears and brain are imperfect and biased
- Sounds can be masked in frequency and/or time
- The theory behind perceptual coding uses the idea that **our aural perception doesn't need the actual bit-to-bit waveform representation, but only the properties of the waveform that are most important for the listener**, and prioritize the recording of these properties
- In other words, PCM attempts to capture a waveform *as it is*, an MP3 attempts to capture *as it sounds*

MPEG-1 Layer-3

perceptual model


- Perceptual coding basic concept: **irrelevancy**
 - Certain properties of any given waveform will be not perceived by a human listener, and so it will be **meaningless to store them**
- Perceptual model depends on peculiarity of human auditory perception: **auditory masking**
 - in the temporal domain it is called **temporal masking**: a sudden stimulus makes inaudible other sounds immediately preceding or following the stimulus
 - in the frequency domain, it is called **frequency masking**: the threshold of hearing for one sound is raised by the presence of another sound
- Masking enables perceptual coding to get away much of the data that conventional waveform coding (e.g., PCM) stores
- **Not all irrelevant data is discarded, but fewer bits are assigned to the masked elements than to relevant ones**
- This process introduces distortion, but it will be hopefully confined to the masked zone, and hopefully will be imperceptible on playback.



Taken from Brandenburg, K. 1999. MP3 and AAC explained. In Proceedings of the AES 17th International Conference on High Quality Audio Coding



MP3 header



Bits	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20			
Binary	1	1	1	1	1	1	1	1	1	1	1	1	1	0	1	1	1	0	1	0			
Hex	F				F				F				B				A						
Meaning	MP3 Sync Word												Version	Layer		Error Protection		Bit Rate					
Value	Sync Word												1 = MPEG	01 = Layer 3		1 = No		1010 = 160					


21	22	23	24	25	26	27	28	29	30	31	32
0	0	0	0	0	1	0	0	0	0	0	0
0				4				0			
Frequency	Pad. Bit	Priv. Bit	Mode	Mode Extension (Used With Joint Stereo)		Copy	Original	Emphasis			
00 = 44100 Hz	0 = Frame is not padded	Unknown	01 = Joint Stereo	0 = Intensity Stereo Off	0 = MS Stereo Off	0 = Not Copy-righted	0 = Copy Of Original Media	00 = None			

Taken from <http://en.wikipedia.org/wiki/MP3>

MPEG-2 AAC

- Same paradigm as MPEG-1 Layer-3, but
 - higher frequency resolution (1024 instead of 576 frequency lines)
 - improved joint stereo coding
 - improved Huffman coding
- AAC reaches the same quality as Layer-3 at 70% of the bit-rate
- Do not confuse MPEG-2 with MP2 (MPEG-1 Layer-2). MPEG-2 is standard for video (and associated audio), whose audio can be in a number of formats, including AC3 and AAC

MP3 comparison



BREAK

Introduction to JavaScript

<https://mumt301.github.io>

Git & GitHub

- Version control system for software development
- Every directory under Git control is a repository with complete history and full version-tracking capabilities
- Github is a Web-based Git repository hosting service
- Distributed version control and code management

Github setup

- Download and install Github Desktop
- Login with your credentials
- Press the '+' sign and clone the mumt301/2016 repo to your local machine
- Add the folder where you have done all your development to your folder within the cloned repository (its name should be www/)
- Commit and Push your changes ("Sync"). Check if the changes appeared on Github
- Clone the Github repo into your home directory in the dev server (use HTTPS)

Today's class

- Review of last class and assignment #3
- Sound file formats
- Audio compression
- Introduction to JavaScript
- Git and Github
- Assignment #4

HTTP requests

- Request messages are at the heart of web communications using HTTP
- These messages are sent using URLs (Uniform Resource Locators)

<https://www.google.ca/search?q=Allison+Hecht+McGill>

Complete Ethernet Packet

Taken from openmicrolab.com

