Tag, push, and pull your image

Estimated reading time: 6 minutes

In this section, you tag and push your `docker-whale` image to your new repository, then test the repository by pulling your new image.

Step 1: Tag and push the image

1. If you don't already have a terminal open, open one now.

2. Run `docker images` to list the images stored locally:

```
$ docker images

REPOSITORY          TAG         IMAGE ID        CREATED          SIZE
docker-whale        latest      7d9495d03763    38 minutes ago   273.7 MB
<none>              <none>      5dac217f722c    45 minutes ago   273.7 MB
docker/whalesay     latest      fb434121fc77    4 hours ago      247 MB
hello-world         latest      91c95931e552    5 weeks ago      910 B
```

3. Find the image ID for the `docker-whale` image, in the second column. In this example, the id is `7d9495d03763`, but yours will be different.

   > **Note**: Currently, the repository shows the repo name `docker-whale` with no namespace. You need to include the `namespace` for Docker Hub to associate it with your account. The `namespace` is the same as your Docker Hub account name. The next step adds the namespace to the image name, like `YOUR_DOCKERHUB_NAME/docker-whale`.

4. Tag the `docker-whale` image using the `docker tag` command and the image ID.

   The command you type looks like this:

   Make sure to use your own Docker Hub account name.

```
$ docker tag 7d9495d03763 maryatdocker/docker-whale:latest
```

5. Run `docker images` again to verify that the `docker-whale` image has been tagged.

```
$ docker images

REPOSITORY                  TAG        IMAGE ID        CREATED          SIZE
maryatdocker/docker-whale   latest     7d9495d03763    5 minutes ago    273.7 MB
docker-whale                latest     7d9495d03763    2 hours ago      273.7 MB
<none>                      <none>     5dac217f722c    5 hours ago      273.7 MB
docker/whalesay             latest     fb434121fc77    5 hours ago      247 MB
hello-world                 latest     91c95931e552    5 weeks ago      910 B
```

   The same image ID actually now exists in two different repositories.

6. Before you can push the image to Docker Hub, you need to log in, using the `docker login` command. The command doesn't take any parameters, but prompts you for the username and password, as below:

```
$ docker login

    Username: *****
    Password: *****
    Login Succeeded
```

7. Push your tagged image to Docker Hub, using the `docker push` command. A lot of output is generated, as each layer is pushed separately. That output is truncated in the example below.

```
$ docker push maryatdocker/docker-whale

The push refers to a repository [maryatdocker/docker-whale] (len: 1)
7d9495d03763: Image already exists
...
e9e06b06e14c: Image successfully pushed
Digest: sha256:ad89e88beb7dc73bf55d456e2c600e0a39dd6c9500d7cd8d1025626c4b985011
```

8. Go back to the Docker Hub website to see the newly-pushed image.

Step 2: Pull your new image

The goal of pushing the image to Docker Hub is so that you can access it from any Docker host using `docker pull`. First, though, you need to remove the local copy. Otherwise, `docker pull` will not have any work to do, because it will see that you already have the latest version of the image locally.

1. If you don't already have a terminal open, open one now.

2. Use `docker images` to list the images you have locally.

```
$ docker images

REPOSITORY                TAG        IMAGE ID       CREATED         SIZE
maryatdocker/docker-whale latest     7d9495d03763   5 minutes ago   273.7 MB
docker-whale              latest     7d9495d03763   2 hours ago     273.7 MB
<none>                    <none>     5dac217f722c   5 hours ago     273.7 MB
docker/whalesay           latest     fb434121fc77   5 hours ago     247 MB
hello-world               latest     91c95931e552   5 weeks ago     910 B
```

In the next step, you will remove both versions of the `docker-whale` image from your local system. They share the same ID. Make a note of it.

3. Use the `docker image rm` command to remove the images. You can refer to an image by its ID or its name. Since they share an ID, if you wanted to keep one of them, you'd need to refer to the other one by name. For this example, use the ID to remove both of them. Your ID will be different from the one below.

```
$ docker image rm -f 7d9495d03763
```

4. When you use `docker run` it automatically downloads (pulls) images that don't yet exist locally, creates a container, and starts it. Use the following command to pull and run the `docker-whale` image, substituting your Docker Hub username.

```
$ docker run yourusername/docker-whale
```

Since the image is no longer available on your local system, Docker downloads it. The output below is truncated.

```
$ docker run maryatdocker/docker-whale

Unable to find image 'maryatdocker/docker-whale:latest' locally
latest: Pulling from maryatdocker/docker-whale
eb06e47a01d2: Pull complete
c81071adeeb5: Pull complete
        ...
fb434121fc77: Already exists
Digest: sha256:ad89e88beb7dc73bf55d456e2c600e0a39dd6c9500d7cd8d1025626c4b985011
Status: Downloaded newer image for maryatdocker/docker-whale:latest
  _____
/ Having wandered helplessly into a       \
| blinding snowstorm Sam was greatly      |
| relieved to see a sturdy Saint Bernard  |
| dog bounding toward him with the        |
| traditional keg of brandy strapped to   |
| his collar.                             |
|                                         |
| "At last," cried Sam, "man's best       |
\ friend -- and a great big dog, too!"    /
  ----------------------------------------
               \
                \
                 \
                      ##        .
                ## ## ##       ==
             ## ## ## ##      ===
          /""""""""""""""""___/ ===
     ~~~ {~~ ~~~~ ~~~ ~~~~ ~~ ~ /  ===- ~~~
          _____ o          __/
            \    \        __/
             _____/
```

Next steps

After finishing this tutorial, you've done all of the following fundamental Docker tasks.

- You installed Docker.
- You ran a software image in a container.
- You located an interesting image on Docker Hub and ran it on your own machine.
- You modified an image to create your own, and created and ran a container based on that image.
- You created a Docker Hub account and repository.
- You pushed your custom image to Docker Hub, and made it available both for yourself and other Docker users.

Tweet #dockerdocs

You've only scratched the surface of what Docker can do. Learn more (https://docs.docker.com/engine/getstarted/last_page/) about where to go next.

Feedback? Suggestions? Can't find something in the docs?
Edit this page (https://github.com/docker/docker.github.io/edit/master/engine/getstarted/step_six.md) • Request docs changes
(https://github.com/docker/docker.github.io/issues/new?title=Feedback for:
engine/getstarted/step_six.md&assignee=mstanleyjones&body=File: [engine/getstarted/step_six.md]
(https://docs.docker.com/engine/getstarted/step_six/)) • Get support (https://www.docker.com/docker-support-services)
Rate this page:
98   3

What is Docker (https://www.docker.com/what-docker)

http: http: https   https   https   https   http: http:

Edit this page
(https://github.com/docker/docke

✔ Request docs changes
(https://github.com/docker/docke
title=Feedback for:
engine/getstarted/step_six.md&a

On this page: