



.com

SAMBA4 ACTIVE DIRECTORY

 34I ♥ TecMint :     

Create an Active Directory Infrastructure with Samba4 on Ubuntu – Part 1

by Matei Cezar | Published: November 21, 2016 |
Last Updated: May 10, 2017

 AdChoices

Free Install

Ubur

Download Your Free eBooks NOW - [10 Free](#)[Linux eBooks for Administators](#) | [4 Free Shell](#)[Scripting eBooks](#)[18 Tar Command Examples in Linux](#)BEGINNER'S GUIDE FOR LINUX 

Start learning Linux in minutes →

Vi/Vim Editor BEGINNER'S GUIDE Learn vi/vim as a Full Text Editor 

Samba is a free Open Source software which provides a standard interoperability between **Windows OS** and **Linux/Unix** Operating Systems.

Samba can operate as a standalone file and print server for Windows and Linux clients through the **SMB/CIFS** protocol suite or can act as an **Active Directory Domain Controller** or joined into a **Realm** as a **Domain Member**. The highest **AD DC** domain and forest level that currently **Samba4** can emulate is **Windows 2008 R2**.

The series will be titled **Setting Up Samba4 Active Directory Domain Controller**, which covers following topics for **Ubuntu**, **CentOS**, and **Windows**:

Part 1: Install Active Directory Infrastructure with SAMBA4 on Ubuntu

Part 2: **Manage Samba4 AD**
Infrastructure from Linux

SHARE

+



+



 **Linux Foundation Certification** 
Exam Study Guide to **LFCS** and **LFCE**

18 Tar Command Examples in Linux

Command Line

Part 3: Manage Samba4 Active Directory Infrastructure from Windows10 via RSAT

Part 4: Manage Samba4 AD Domain Controller DNS and Group Policy from Windows

Part 5: Join an Additional Ubuntu DC to Samba4 AD DC

Part 6: Setup SysVol Replication Across Two Samba4 AD DC with Rsync

Part 7: Create a Shared Directory on Samba AD DC and Map to Windows/Linux Clients

Part 8: Integrate Ubuntu 16.04 to AD as a Domain Member with Samba and Winbind

Part 9: Integrate CentOS 7 Desktop to Samba4 AD as a Domain Member



How to Add Linux Host to Nagios Monitoring Server Using NRPE Plugin

Nagios 4.2.0 Released – Install on RHEL/CentOS 7.x/6.x/5.x and Fedora 24-19

Install Cacti (Network Monitoring) on RHEL/CentOS 7.x/6.x/5.x and Fedora 24-12

Google Chrome 58 Released – Install on RHEL/CentOS 7/6 and Fedora 25-20

18 Tar Command Examples in Linux

Part 10: **How to Install iRedMail on CentOS 7 for Samba4 AD Integration**

Part 11: **Integrate iRedMail Services to Samba4 AD DC**

Part 12: Configure Roundcube with Samba4 AD DC

Part 13: Configure Thunderbird Client for Samba4 AD DC Mail System with LDAP

Part 14: Integrate Ubuntu 16.04 to Samba4 AD DC with SSSD and Realm

Part 15: Integrate CentOS 7 from Command Line to Samba AD DC as a Domain Member

Part 16: Integrate VMware ESXI Host to Samba4 AD DC Infrastructure

How to Install Ubuntu 16.10/16.04 Alongside With Windows 10 or 8 in Dual-Boot

Tecmint's Guide to Red Hat RHCSA / RHCE Certification Preparation Study Guide

STEPHEN SAYS:

Thank you VERY much for this free & detailed guide. ...

SANDEEP SAYS:

Hi Ravi, Good article but I have complied apache2.4 and installed...

MIKE WILL SAYS:

I don't agree with using single "=" in string comparison. What...

HENRY SAYS:

I've been using BeyondCompare for years and although it's not free...

KUMAR SAYS:

I followed your steps .. Its working fine .. Thanks.



BEERBARON23 SAYS:

Lightworks on Linux can keep up with FCPX and Premiere, so...

This tutorial will start by explaining all the steps you need to take care off in order to install and

configure Samba4 as a

18 Tar Command Examples in Linux

Domain Controller on Ubuntu 16.04 and Ubuntu 14.04.

This configuration will provide a central management point for users, machines, volume shares, permissions and other resources in a mixed-up Windows – Linux infrastructure.

Requirements:

- [Ubuntu 16.04 Server Installation.](#)
- [Ubuntu 14.04 Server Installation.](#)
- [A static IP Address configured](#) for your AD DC server.

Step 1: Initial Configuration for Samba4

1. Before proceeding your Samba4 AD DC installation first let's run a few pre-

18 Tar Command Examples in Linux

Tecmint
Linux Mentor's Guide

**Red Hat RHCSA/RHCE Certification
Preparation Study Guide**

RedHat RHCSA / RHCE 7
RHCSA (EX200) and RHCE (EX300) exams

* EX200 - Red Hat Certified System Administrator (RHCSA)
* EX300 - Red Hat Certified Engineer (RHCE)

Buy Now \$35.00

**Linux System Administrator Bundle
with 7-Courses (96% off)**

Add to Cart - \$69

🕒 Ending In: 3 days

**Computer Hacker Professional
Certification Course (96% Off)**

Add to Cart - \$59

🕒 Ending In: 4 days

DOWNLOAD FREE LINUX EBOOKS


- Complete Linux Command Line Cheat Sheet
- The GNU/Linux Advanced Administration Guide
- Securing & Optimizing Linux Servers

required steps. First make sure the system is up to date with the last security features, kernels and packages by issuing the below command:

```
$ sudo apt-get update
$ sudo apt-get upgrade
$ sudo apt-get dist-upg
```

2. Next, open machine `/etc/fstab` file and assure that your partitions file system has **ACLs** enabled as illustrated on the below screenshot.

Usually, common modern Linux file systems such as **ext3**, **ext4**, **xfs** or **btrfs** support and have ACLs enabled by default. If that's not the case with your file system just open `/etc/fstab` file for editing and add `acl` string at the end of third column and **reboot** the machine in order to apply changes.



- Linux Patch Management: Keeping Linux Up To Date
- Introduction to Linux – A Hands on Guide
- Understanding the Linux® Virtual Memory Manager
- Getting Started with Ubuntu 16.04
- A Newbie's Getting Started Guide to Linux
- Linux from Scratch – Create Your Own Linux OS
- Linux Shell Scripting Cookbook, Second Edition
- Securing & Optimizing Linux: The Hacking Solution
- User Mode Linux – Understanding and Administration



Never Miss Any Linux Tutorials, Guides, Tips and Free eBooks

Join Our Community Of **150,000+ Linux Lovers** and get a weekly newsletter in your inbox

YES! SIGN ME UP

3. Finally setup your machine hostname with a descriptive name, such as `adc1` used in this example, by editing `/etc/hostname` file or by issuing.

```
$ sudo hostnamectl set-
```


A **reboot** is necessary after you've changed your machine name in order to apply changes.

Step 2: Install Required Packages for Samba4 AD DC

4. In order to transform your server into an **Active Directory Domain Controller**, install **Samba** and all the required packages on your machine by issuing the below command with **root** privileges in a console.

```
$ sudo apt-get install
```


18 Tar Command Examples in Linux



Install Samba on Ubuntu


5. While the installation is running a series of questions will be asked by the installer in order to configure the domain controller.

On the first screen you will need to add a name for **Kerberos** default **REALM** in uppercase. Enter the name you will be using for your domain in uppercase and hit **Enter** to continue..




Configuring Kerberos Authentication

6. Next, enter the **hostname** of **Kerberos** server for your domain. Use the same name as for your domain, with lowercases this time and hit **Enter** to continue.



Set Hostname Kerberos Server


7. Finally, specify the **hostname** for the administrative server of your **Kerberos** realm. Use the same as your domain and hit **Enter** to finish the installation.



Set Hostname Administrative Server

Step 3: Provision Samba AD DC for Your Domain

8. Before starting to configure **Samba** for your domain, first run the below commands in order to stop and disable all samba daemons.



9. Next, rename or remove samba original configuration. This step is absolutely required before provisioning **Samba AD**

because at the provision

18 Tar Command Examples in Linux

time **Samba** will create a new configuration file from scratch and will throw up some errors in case it finds an old `smb.conf` file.

```
$ sudo mv /etc/samba/smb.conf
```

10. Now, start the domain provisioning interactively by issuing the below command with root privileges and accept the default options that Samba provides you.

Also, make sure you supply the IP address for a DNS forwarder at your premises (or external) and choose a strong password for Administrator account. If you choose a weak password for Administrator account the domain provision will fail.

```
$ sudo samba-tool domain
```

[illegible]

Samba Domain Provisioning

11. Finally, rename or remove Kerberos main configuration file from **/etc** directory and replace it using a symlink with Samba newly generated Kerberos file located in **/var/lib/samba/private** path by issuing the below commands:

```
$ sudo mv /etc/krb6.com
$ sudo ln -s /var/lib/s
```


```
qweezar@adali-1:~$ sudo mv /etc/krb5.conf /etc/krb5.conf.initial
qweezar@adali-1:~$ sudo ln -s /var/lib/samba/private/krb5.conf /etc/
krb5.conf
qweezar@adali-1:~$ ls -la /etc/krb5.conf
lrwxrwxrwx 1 root root 32 Oct 10 18:28 /etc/krb5.conf -> /var/lib/samba/private/krb5.conf
qweezar@adali-1:~$
```

Create Kerberos Configuration

12. Start and enable Samba Active Directory Domain Controller daemons.

```
$ sudo systemctl start
$ sudo systemctl status
$ sudo systemctl enable
```

18 Tar Command Examples in Linux



```
$ sudo netstat -tulnp|
```



14. At this moment **Samba** should be fully operational at your premises. The

<https://www.tecmint.com/install-samba4-active-directory-ubuntu/>

highest domain level **Samba**
is emulating should be
Windows AD DC 2008 R2.

It can be verified with the
help of **samba-tool** utility.

```
$ sudo samba-tool domain
```

Verify Samba Domain Level

15. In order for **DNS**
resolution to work locally,
you need to open and edit
network interface settings
and point the DNS
resolution by modifying **dns-**
nameservers statement to
the IP Address of your
Domain Controller (use
127.0.0.1 for local DNS
resolution) and **dns-search**
statement to point to your
realm.

```
$ sudo cat /etc/network  
$ sudo cat /etc/resolv.
```

Configure DNS for Samba AD

When finished, **reboot** your server and take a look at your resolver file to make sure it points back to the right DNS name servers.

16. Finally, test the DNS resolver by issuing queries and pings against some **AD DC** crucial records, as in the below excerpt. Replace the domain name accordingly.

```
$ ping -c3 tecmint.lan  
$ ping -c3 adc1.tecmint  
$ ping -c3 adc1
```

Check Samba AD DNS Records

Run following few queries
against Samba Active
Directory Domain
Controller..

```
$ host -t A tecmint.lan  
$ host -t A adc1.tecmir  
$ host -t SRV _kerberos  
$ host -t SRV _ldap._tc
```

17. Also, verify **Kerberos**
authentication by requesting
a ticket for the domain
administrator account and
list the cached ticket. Write
the domain name portion
with uppercase.

```
$ kinit administrator@T  
$ klist
```


*Check Kerberos Authentication on
Domain*

That's all! Now you have a fully operational **AD Domain Controller** installed in your network and you can start integrate **Windows** or **Linux** machines into **Samba AD**.

On the next series we'll cover other **Samba AD** topics, such as how to manage you're the domain controller from Samba command line, how to integrate Windows 10 into the domain name and manage Samba AD remotely using RSAT and other important topics.

**If You Appreciate
What We Do Here On**

18 Tar Command Examples in Linux

TecMint, You Should Consider:

1. Stay Connected to: [Twitter](#) | [Facebook](#) | [Google Plus](#)
2. Subscribe to our email updates: [Sign Up Now](#)
3. Get your own [self-hosted blog with a Free Domain](#) at (\$3.95/month).
4. Become a Supporter - [Make a contribution via PayPal](#)
5. Support us by [purchasing our premium books](#) in PDF format.
6. Support us by taking our [online Linux courses](#)

We are thankful for your never ending support.

Tags: Samba Active Directory

Matei Cezar [View all Posts](#)




I'am a computer addicted guy, a fan of open source and linux based system

software, have about 18 Tar Command Examples in Linux

experience with Linux
distributions desktop, servers
and bash scripting.

**Your name can also be
listed here. Got a tip?**

**[Submit it here](#) to
become an TecMint
author.**



PREVIOUS

STORY



How to Install
and Use MS
SQL Server on
Linux

NEXT STORY

Deal: Get 2017
IT Security &
Ethical
Hacking
Certification
Training
Course (98%
Off)



YOU MAY ALSO LIKE...

10

0

2

Create a
Shared

Manage
Samba4


Manage
Samba4 AD

18 Tar Command Examples in Linux

Directory on Samba AD DC and Map to Windows/Li nux Clients – Part 7	Active Directory Infrastructu re from Windows10 via RSAT – Part 3	Domain Controller DNS and Group Policy from Windows – Part 4
22 FEB, 2017	5 DEC, 2016	7 DEC, 2016

34 RESPONSES

 **Comments** 16  **Pingbacks** 0

Sharif Qaysari  May 16, 2017 at 7:30 am
Hello everyone !

I have passed the all the procedure to setup the Samba as ADDC and it was successful. now I am trying to integrate the Samba with OpenLdap, I've searched a lot in google but have found no any guide or documentation about setting up OpenLDAP with Samba backed on Ubuntu 16.04.

could you please help to setup that or reference any resource?


Reply

Matei Cezar

 May 16, 2017 at 12:53 pm

That's because Samba4 has LDAP ad schema integrated. If you can't find it in official samba docs, than it's not officially supported.

Reply

jokerZD  May 6, 2017 at 2:15 pm

This works super.

Windows server upon Linux stability

what else to say and you  18 Tar Command Examples in Linux

possibilities here, mdadm, rsync.

Reply

Paulo ☺ May 5, 2017 at 1:22 am

Excellent guide!!! Congratulations. I really need part 14. and also 13. When will be your publication? Thank you.

Reply

corpusdilecti ☺ April 29, 2017 at 11:30 pm

I'm running to an issue with resolving my domain name. I can ping the FQDN and Host, but not the domain name.

Here is my setup:

Hostname:

adc1

Hosts file:

127.0.0.1 localhost

127.0.1.1 adc1.tirnanog.local adc1

The following lines are desirable for IPv6 capable hosts

::1 localhost ip6-localhost ip6-loopback

ff02::1 ip6-allnodes

ff02::2 ip6-allrouters

/etc/network/interfaces

This file describes the network interfaces available on your system
and how to activate them. For more information, see interfaces(5).

source /etc/network/interfaces.d/*

The loopback network interface

auto lo

iface lo inet loopback

Wired network connection

auto eno1

iface eno1 inet static

address 192.168.1.200

netmask 255.255.255.0

broadcast 192.168.1.254

gateway 192.168.1.1

[dns-nameservers 127.0.0.1](#) 18 Tar Command Examples in Linux

```
192.168.1.200 192.168.1.1
```

```
dns-search tirnanog.local
```

```
/etc/resolv.conf
```

```
# Dynamic resolv.conf(5) file for glibc  
resolver(3) generated by resolvconf(8)
```

```
# DO NOT EDIT THIS FILE BY HAND –  
YOUR CHANGES WILL BE  
OVERWRITTEN
```

```
nameserver 127.0.0.1
```

```
search tirnanog.local
```

When I try to ping, these are the results
that I get:

```
root@adc1:/# ping -c3 tirnanog.local  
ping: unknown host tirnanog.local
```

```
root@adc1:/# ping -c3  
adc1.tirnanog.local  
PING adc1.tirnanog.local (127.0.1.1)  
56(84) bytes of data.  
64 bytes from adc1.tirnanog.local  
(127.0.1.1): icmp_seq=1 ttl=64  
time=0.049 ms  
64 bytes from adc1.tirnanog.local  
(127.0.1.1): icmp_seq=2 ttl=64  
time=0.060 ms  
64 bytes from adc1.tirnanog.local  
(127.0.1.1): icmp_seq=3 ttl=64  
time=0.061 ms
```

```
– adc1.tirnanog.local ping statistics –  
3 packets transmitted, 3 received, 0%  
packet loss, time 1998ms  
rtt min/avg/max/mdev =  
0.049/0.056/0.061/0.010 ms
```

```
root@adc1:/# ping -c3  
adc1.tirnanog.local  
PING adc1.tirnanog.local (127.0.1.1)  
56(84) bytes of data.  
64 bytes from adc1.tirnanog.local  
(127.0.1.1): icmp_seq=1 ttl=64  
time=0.052 ms  
64 bytes from adc1.tirnanog.local  
(127.0.1.1): icmp_seq=2 ttl=64
```

18 Tar Command Examples in Linux

```
time=0.061 ms
64 bytes from adc1.tirnanog.local
(127.0.1.1): icmp_seq=3 ttl=64
time=0.062 ms

- adc1.tirnanog.local ping statistics -
3 packets transmitted, 3 received, 0%
packet loss, time 1998ms
rtt min/avg/max/mdev =
0.052/0.058/0.062/0.007 ms
```

Can anyone give me a hand and let me know what I'm doing wrong? I have a good feeling it is something to do with the dns-nameservers, but I've tried changing them a few time in /etc/network/interfaces and I can't seem to get anything to work.

By the way, this is what I'm running:

Distributor ID: Ubuntu
Description: Ubuntu 16.04.2 LTS
Release: 16.04
Codename: xenial

Please, let me know if there is any other info needed. Thanks!

Reply

corpusdilecti

🕒 April 30, 2017 at 11:12 pm

Well! It seems I didn't install/configure DNS before starting this tutorial.. that would have helped :)

Reply

Matei Cezar

🕒 May 2, 2017 at 11:50 am

If your machine is a Samba4 DC then remove **127.0.1.1** **adc1.tirnanog.local** from hosts file and point to **adc1** only before provisioning the domain.

I see you have three DNS entries

on interfaces file, use only dns-

18 Tar Command Examples in Linux

nameservers 127.0.0.1 and
other DNS server provisioned on
your domain if that's the case
after you've provisioned the
samba domain.

Reply

Hannes van Vuuren

🕒 April 6, 2017 at 3:44 pm

Thanks a lot for this article! After going through the domain provision process a few times this seems to me the most solid article about the process. There is plenty of outdated information around the net, and Samba wiki is often confusing (if not outright down on a given day).

Reply

unknownen 🕒 March 31, 2017 at 1:34 pm

Hello,

I have reached to the step below and I have encountered one failure! any idea, please?

```
$ sudo samba-tool domain provision --use-rfc2307 -interactive
```

Usage: samba-tool domain provision
[options]

samba-tool domain provision: error: no
such option: -i

Reply

Matei Cezar

🕒 March 31, 2017 at 4:53 pm

Use **-interactive**. While editing with microsoft word a ' - ' has been suppressed.

Reply

Matei Cezar

🕒 March 31, 2017 at 4:57 pm

Double hyphen.

Reply

Matei Cezar

18 Tar Command Examples in Linux

⌚ April 15, 2017 at 10:56 pm

–interactive

Reply

Dave ⌚ March 24, 2017 at 11:16 am

Hi guys.

After running through the guide in the office, I took the server on site to a client with a different network.

When changing the IP address and DNS entries the lookup of domain.local returns the IP address the box had in our office.

Tried flushing the DNS and a bunch of things and nothing has worked so far.

How would I get around this?

Reply

Matei Cezar

⌚ March 24, 2017 at 12:22 pm

You must manually update all IP's addresses on your machine (hosts, network interfaces, samba IP forwarders, resolvers) and samba DNS records to fit new IP range.

Reply

Dave

⌚ March 28, 2017 at 6:08 pm

Where do I edit the samba dns records and IP forwarders? In the smb.conf file?

Where do i edit the resolvers as well. I have set the rest, I have also set the IP's in the smb.conf file.

Reply

Dave ⌚ March 13, 2017 at 12:24 pm

Hi there,

18 Tar Command Examples in Linux

I have set up an active directory domain controller according to your guide in a test environment in our office.

When I took it on site to a different IP range, I changed the IP address. Changed the DNS according to the site. When i ping the domain name it returns the old IP address. When I do an NSlookup it also returns the IP address I had set up the machine on in the office.

I have set it up on Ubuntu 16.10

Reply

« Older Comments

GOT SOMETHING TO SAY? JOIN THE DISCUSSION.

Comment

Name *

Email *

Website

☐

Notify me of followup comments via e-mail. You can also [subscribe](#) without commenting.

Post Comment

LINUX MONITORING TOOLS

Block SSH Server Attacks (Brute Force Attacks) Using DenyHosts

30 NOV, 2012

Psensor – A Graphical Hardware Temperature Monitoring Tool for Linux

2 JUL, 2015

20 Command Line Tools to Monitor Linux Performance

27 APR, 2014

20 Netstat Commands for Linux Network Management

8 AUG, 2012

LINUX INTERVIEW QUESTIONS

10 Useful “Squid Proxy Server” Interview Questions and Answers in Linux

28 JUL, 2014

Nishita Agarwal Shares Her Interview Experience on Linux ‘iptables’ Firewall

4 JUN, 2015

11 Basic Linux Interview Questions and Answers

18 NOV, 2013

10 Useful SSH (Secure Shell) Interview Questions and Answers

15 MAR, 2014

OPEN SOURCE TOOLS

How to Install GoLang (Go Programming Language) in Linux

18 NOV, 2016

Create Your Own Video Sharing Website using ‘CumulusClips Script’ in Linux

28 MAY, 2014

12 Open Source Cloud Storage Software to Store and Sync Your Data Quickly and Safely

12 NOV, 2015

Screenlets: An Amazing Tool to Add Desktop Gadgets/Widgets in Linux

13 APR, 2015



Tecmint: Linux Howtos, Tutorials & Guides © 2017.
All Rights Reserved.

This work is licensed under a (cc) BY-NC

The material in this site cannot be republished

either online or offline, without our 18 Tar Command Examples in Linux



