

Jest Test Documentation

SaltOS 4.1 r2678

September 2026

Contents

1	Jest Libraries	11
1.1	Setup file for the unit tests	11
1.1.1	Detect what type of test is running, and load the needed setup	11
1.2	Setup file for the unit tests	11
1.2.1	Needed by all user interface features	11
1.2.2	Needed by bootstrap, core and proxy modules	11
1.2.3	Needed by bootstrap module	11
1.2.4	This is the same that object.js for the global scope	11
1.2.5	Load all files of the project	11
1.2.6	My Require	11
1.3	Setup file for the unit tests	12
1.3.1	This is the same that object.js for the global scope	12
1.3.2	Needed by core module	12
1.3.3	Needed by core module	12
1.3.4	Load all files of the project	12
1.3.5	My Pause	12
1.4	Puppeteer loader	12
2	Jest Code	12
2.1	Apps unit tests	12
2.1.1	Puppeteer setup	12
2.1.2	Global variables	13
2.1.3	Before All	13
2.1.4	After All	13
2.1.5	App Login	13
2.1.6	Action Login	13
2.1.7	Action Login Ko Red	13
2.1.8	Action Login Ko Green	13
2.1.9	Action Dashboard	13
2.1.10	Action Reload	14
2.1.11	Action Logout	14
2.2	Bootstrap unit tests	14
2.2.1	Puppeteer setup	14
2.2.2	Global variables	14
2.2.3	Before All	14
2.2.4	After All	14

2.2.5	Bootstrap	14
2.2.6	Prepare the test.each iterator	15
2.2.7	Real test	15
2.3	Core unit tests	15
2.3.1	Load all needed files of the project	15
2.3.2	Reset mocks before each test	15
2.3.3	Restore mocks after each test	15
2.3.4	Test suite for error and log reporting	15
2.3.5	Setup before each test in this suite	15
2.3.6	Test error reporting functionality	15
2.3.7	Test log reporting functionality	16
2.3.8	Test suite for global error handling	16
2.3.9	Setup before each test in this suite	16
2.3.10	Test global error handling	16
2.3.11	Test unhandled promise rejection handling	16
2.3.12	Test parameter validation functionality	16
2.3.13	Test unique ID generation	16
2.3.14	Test suite for visibility detection	16
2.3.15	Setup before each test in this suite	16
2.3.16	Cleanup after each test in this suite	17
2.3.17	Test basic visibility detection	17
2.3.18	Test visibility detection with ID	17
2.3.19	Test visibility detection with string ID	17
2.3.20	Test invalid input handling	17
2.3.21	Test delayed element attachment	17
2.3.22	Test element removal handling	17
2.3.23	Test key code extraction	17
2.3.24	Test key name resolution	17
2.3.25	Test suite for HTML element creation	18
2.3.26	Test single argument usage	18
2.3.27	Test two argument usage	18
2.3.28	Test HTML trimming	18
2.3.29	Test multiple children handling	18
2.3.30	Test single child optimization	18
2.3.31	Test suite for AJAX functionality	18
2.3.32	Test successful GET request	18
2.3.33	Test error response handling	18

2.3.34	Test POST request handling	19
2.3.35	Test request abortion	19
2.3.36	Test network failure handling	19
2.3.37	Test unexpected error handling	19
2.3.38	Test unsupported method handling	19
2.3.39	Test XML response handling	19
2.3.40	Test plain text response handling	19
2.3.41	Test key normalization	19
2.3.42	Test object copying	19
2.3.43	Test suite for resource loading	20
2.3.44	Setup before each test in this suite	20
2.3.45	Cleanup after each test in this suite	20
2.3.46	Test JavaScript file loading	20
2.3.47	Test CSS file loading	20
2.3.48	Test cached resource handling	20
2.3.49	Test pending resource handling	20
2.3.50	Test module file loading	20
2.3.51	Test hashed resource loading	20
2.3.52	Test boolean evaluation	21
2.3.53	Test string conversion	21
2.3.54	Test attribute value detection	21
2.3.55	Test attribute-value joining	21
2.3.56	saltos.core.encode_bad_chars	21
2.3.57	saltos.core.__get_code_from_file_and_line	21
2.3.58	saltos.core.timestamp	21
2.3.59	saltos.core.human_size	21
2.3.60	saltos.core.is_number	21
2.3.61	saltos.core.is_function	22
2.3.62	Core Module Tests	22
2.3.63	Test service worker registration	22
2.3.64	Test proxy function messaging	22
2.3.65	Test proxy synchronization on online events	22
2.3.66	Test network protocol detection	22
2.4	Customers unit tests	22
2.4.1	Puppeteer setup	22
2.4.2	Global variables	23
2.4.3	Before All	23

2.4.4	After All	23
2.4.5	App Customers	23
2.4.6	Action List	23
2.4.7	Action List	23
2.4.8	Action Reset	23
2.4.9	Action Create	23
2.4.10	Action Cancel	24
2.4.11	Action View	24
2.4.12	Action Close	24
2.4.13	Action Edit	24
2.4.14	Action Go Back	24
2.4.15	Action Insert	24
2.4.16	Action Insert	24
2.4.17	Action Update	24
2.4.18	Action Update	24
2.4.19	Action Delete	25
2.4.20	Action Delete	25
2.5	Emails unit tests	25
2.5.1	Puppeteer setup	25
2.5.2	Global variables	25
2.5.3	Before All	25
2.5.4	After All	25
2.5.5	App Emails	25
2.5.6	Action List	26
2.5.7	Action Control F	26
2.5.8	Action Control F	26
2.5.9	Action Profile	26
2.5.10	Action Help	26
2.5.11	Action About	26
2.5.12	Action Filter	26
2.5.13	Action Create	26
2.5.14	Action View	26
2.6	Filter unit tests	27
2.6.1	Load all needed files of the project	27
2.6.2	Reset mocks before each test	27
2.6.3	Restore mocks after each test	27
2.6.4	Test suite for filter initialization	27

2.6.5	Setup before each test in this suite	27
2.6.6	Test filter cache initialization	27
2.6.7	Test cache reuse	27
2.6.8	Test suite for filter loading	27
2.6.9	Setup before each test in this suite	28
2.6.10	Test loading existing filter	28
2.6.11	Test loading non-existent filter	28
2.6.12	Test suite for filter updates	28
2.6.13	Test updating filter cache	28
2.6.14	Test suite for filter saving	28
2.6.15	Test saving new filter	28
2.6.16	Test updating existing filter	28
2.6.17	Test unchanged filter	28
2.6.18	Test filter deletion	29
2.6.19	Test deleting non-existent filter	29
2.6.20	Test suite for filter UI buttons	29
2.6.21	Setup before each test in this suite	29
2.6.22	Test load action	29
2.6.23	Test update action	29
2.6.24	Test delete action	29
2.6.25	Test create action	29
2.6.26	Test rename action	29
2.6.27	Test invalid action	30
2.6.28	Test suite for filter selection UI	30
2.6.29	Setup before each test in this suite	30
2.6.30	Test UI update	30
2.6.31	Test missing tree element	30
2.6.32	Test missing select element	30
2.6.33	Test missing form elements	30
2.7	Core unit tests	30
2.7.1	Load all needed files of the project	30
2.7.2	beforeEach used in this test	31
2.7.3	afterEach used in this test	31
2.7.4	saltos.getText.bootstrap.set/get/get_short/unset	31
2.7.5	saltos.getText.bootstrap.field	31
2.7.6	saltos.getText.bootstrap.modal	31
2.7.7	saltos.getText.bootstrap.toast	31

2.7.8	saltos.gettext.bootstrap.menu	31
2.7.9	saltos.gettext.bootstrap.offcanvas	31
2.8	Hash unit tests	31
2.8.1	Load all needed files of the project	32
2.8.2	Reset mocks before each test	32
2.8.3	Restore mocks after each test	32
2.8.4	Test suite for hash helper function	32
2.8.5	Test hash with leading #	32
2.8.6	Test hash with leading /	32
2.8.7	Test hash with leading #/	32
2.8.8	Test empty hash	32
2.8.9	Test clean hash	32
2.8.10	Test suite for hash getter function	33
2.8.11	Test getting current hash	33
2.8.12	Test getting empty hash	33
2.8.13	Test getting hash with leading /	33
2.8.14	Test suite for hash setter function	33
2.8.15	Test setting new hash	33
2.8.16	Test setting same hash	33
2.8.17	Test setting hash with #	33
2.8.18	Test setting hash with /	33
2.8.19	Test setting empty hash	34
2.8.20	Test suite for hash adder function	34
2.8.21	Test adding new hash	34
2.8.22	Test adding same hash	34
2.8.23	Test adding hash with #	34
2.8.24	Test adding hash with /	34
2.8.25	Test adding empty hash	34
2.8.26	Test suite for URL hash extraction	34
2.8.27	Test extracting hash from URL	34
2.8.28	Test extracting hash with /	35
2.8.29	Test URL without hash	35
2.8.30	Test suite for hash change events	35
2.8.31	Test triggering hash change	35
2.9	Invoices unit tests	35
2.9.1	Puppeteer setup	35
2.9.2	Global variables	35

2.9.3	Before All	35
2.9.4	After All	36
2.9.5	App Invoices	36
2.9.6	Action List	36
2.9.7	Action List	36
2.9.8	Action List	36
2.9.9	Action Create	36
2.9.10	Action View	36
2.9.11	Action Edit	36
2.10	Proxy unit tests	37
2.10.1	beforeEach used in this test	37
2.10.2	afterEach used in this test	37
2.10.3	Load the needed environment of the proxy part	37
2.10.4	md5	37
2.10.5	human_size	37
2.10.6	service-worker-mock@2.0.5's Headers stub deviates from the spec in two ways	37
2.11	Push unit tests	37
2.11.1	Load all needed files of the project	37
2.11.2	Reset mocks before each test	38
2.11.3	Restore mocks after each test	38
2.11.4	Test suite for saltos.push.fn functionality	38
2.11.5	Setup before each test in this suite	38
2.11.6	Test push function when already executing	38
2.11.7	Test push function without token	38
2.11.8	Test push function when offline	38
2.11.9	Test push function with positive count	38
2.11.10	Test push function with successful response	38
2.11.11	Test push function with error response	39
2.11.12	Test suite for saltos.favicon.fn functionality	39
2.11.13	Test favicon function activation	39
2.11.14	Test favicon function deactivation	39
2.12	Screenshots unit tests	39
2.12.1	Puppeteer setup	39
2.12.2	Global variables	39
2.12.3	Before All	39
2.12.4	After All	40
2.12.5	App Customers	40

2.12.6	Action List	40
2.13	Storage unit tests	40
2.13.1	Load all needed files of the project	40
2.13.2	berofeEach used in this test	40
2.13.3	afterEach used in this test	40
2.13.4	saltos.storage	40
2.14	Tester unit tests	40
2.14.1	Puppeteer setup	41
2.14.2	Global variables	41
2.14.3	Before All	41
2.14.4	After All	41
2.14.5	App Tester	41
2.14.6	Action Init	41
2.14.7	Action Disabled	41
2.14.8	Action Enabled	41
2.14.9	Prepare the test.each iterator	42
2.14.10	Visual Theme Combinations	42
2.15	Token unit tests	42
2.15.1	Load all needed files of the project	42
2.15.2	berofeEach used in this test	42
2.15.3	afterEach used in this test	42
2.15.4	saltos.token	42
2.16	Window unit tests	42
2.16.1	Load all needed files of the project	42
2.16.2	Reset mocks before each test	43
2.16.3	Restore mocks after each test	43
2.16.4	Test suite for window open/close functionality	43
2.16.5	Setup before each test in this suite	43
2.16.6	Test opening app URLs	43
2.16.7	Test opening HTTP URLs	43
2.16.8	Test opening HTTPS URLs	43
2.16.9	Test unsupported URL protocols	43
2.16.10	Test window closing	43
2.16.11	Test suite for window event listeners	44
2.16.12	Test setting event listeners	44
2.16.13	Test removing event listeners	44
2.16.14	Test sending events to current tab	44

2.16.15	Test sending events to other tabs	44
2.16.16	Test sending events to all tabs	44
2.16.17	Test sessionStorage event filtering	44
2.16.18	Test event key filtering	44
2.16.19	Test unregistered event filtering	44

1 Jest Libraries

1.1 Setup file for the unit tests

```
lib/jest.setup.js
```

This file contains the code that initialize the unit tests

1.1.1 Detect what type of test is running, and load the needed setup

```
if ('fetch' in global) {
```

1.2 Setup file for the unit tests

```
lib/jsdom.setup.js
```

This file contains the code that initialize the unit tests

1.2.1 Needed by all user interface features

```
global.bootstrap = require('../..../code/web/lib/bootstrap/bootstrap.bundle.min.js');
```

1.2.2 Needed by bootstrap, core and proxy modules

```
global.md5 = require('../..../code/web/lib/md5/md5.min.js');
```

1.2.3 Needed by bootstrap module

```
global.window.matchMedia = function() {
```

1.2.4 This is the same that object.js for the global scope

```
global.saltos = {};
```

1.2.5 Load all files of the project

```
/*const files = `core,bootstrap,storage,hash,token,auth>window,
```

1.2.6 My Require

```
global.myrequire = (file, fns)
```

This function is intended to add the needed module.exports at the end of the file that you want to process, this is a temporary action used only for the require action, and at the end, before the return, the original code is saved as a restore action to maintain the original code file

1.3 Setup file for the unit tests

```
lib/node.setup.js
```

This file contains the code that initialize the unit tests

1.3.1 This is the same that object.js for the global scope

```
global.saltos = {};
```

1.3.2 Needed by core module

```
global.window = {
```

1.3.3 Needed by core module

```
global.document = {
```

1.3.4 Load all files of the project

```
require(`../../code/web/js/core.js`);
```

1.3.5 My Pause

```
global.mypause = (page, delay)
```

This function is intended to do a pause inside the browser, to do it, we use a string instead of real code because istanbul tries to inject code and fails in runtime, one solution can be to put "istanbul ignore next" in a comment before the next `page.evaluate`, but I prefer to use a string in the `page.evaluate` because it is more simple for me

1.4 Puppeteer loader

```
lib/puppeteer.setup.js
```

puppeteer is loaded here via dynamic import because since v25 it ships as an ESM-only package and `require()` can no longer load it, this file is the only place using that syntax because jscs still relies on an old parser that can not tokenize the dynamic `import()` expression

2 Jest Code

2.1 Apps unit tests

```
test_apps.js
```

This file contains the apps unit tests

2.1.1 Puppeteer setup

```
const pti = require('puppeteer-to-istanbul');
```

This lines contain the needed setup for run puppeteer and take screenshots

2.1.2 Global variables

```
let puppeteer;
```

This variables contains the browser and page links

2.1.3 Before All

```
beforeAll(async ()
```

This function contains all code executed before all tests, in this case the features provided by this function includes the launch of the browser, set the screen size and start the javascript coverage

2.1.4 After All

```
afterAll(async ()
```

This function contains all code executed after all tests, in this case the features provided by this function include the stop of the javascript coverage recording, the save feature to the desired storage path and the browser close

2.1.5 App Login

```
describe('App Login', ()
```

This test is intended to validate the correctness of the login screen and their particularities, too tries to check the dashboard and the logout to close the loop of tests

2.1.6 Action Login

```
test('Action Login', async ()
```

This function tries to do a test to validate that the login screen appear correctly without issues

2.1.7 Action Login Ko Red

```
test('Action Login Ko Red', async ()
```

This function tries to validate the form when no data is found

2.1.8 Action Login Ko Green

```
test('Action Login Ko Green', async ()
```

This function tries to validate the form when invalid data is found

2.1.9 Action Dashboard

```
test('Action Dashboard', async ()
```

This function tries to execute the login with valid credentials, to validate the correctness, the dashboard will appear

2.1.10 Action Reload

```
test('Action Reload', async ()
```

This function tries to do a reload of the previous page, the validation of this test must accomplish when a valid dashboard appear

2.1.11 Action Logout

```
test('Action Logout', async ()
```

This test is intended to check the correctness of the logout feature, to do it the test tries to locate the logout button placed in the dropdown menu of the navbar and click to the third element

2.2 Bootstrap unit tests

```
test_bootstrap.js
```

This file contains the bootstrap unit tests

2.2.1 Puppeteer setup

```
const pti = require('puppeteer-to-istanbul');
```

This lines contain the needed setup for run puppeteer and take screenshots

2.2.2 Global variables

```
let puppeteer;
```

This variables contains the browser and page links

2.2.3 Before All

```
beforeAll(async ()
```

This function contains all code executed before all tests, in this case the features provided by this function includes the launch of the browser, set the screen size and start the javascript coverage

2.2.4 After All

```
afterAll(async ()
```

This function contains all code executed after all tests

2.2.5 Bootstrap

```
describe('Bootstrap', ()
```

This test contains the code needed to create all widgets and validate the correctness of them

2.2.6 Prepare the test.each iterator

```
const fs = require('fs');
```

2.2.7 Real test

```
test.each(cases)('$label', async ({mode, field, label})
```

This function executes the real test for each json item, its able to create a widget and validate the correctness of the widget comparing the new widget screenshot to the backup widget screenshot

2.3 Core unit tests

```
test_core.js
```

This file contains comprehensive unit tests for the core functionality of the SaltOS framework, including error handling, AJAX operations, utility functions, and service worker integration.

2.3.1 Load all needed files of the project

```
const files = `core,gettext,token`.split(',');
```

2.3.2 Reset mocks before each test

```
beforeEach(()
```

Initializes mock implementations for console.log and fetch API before each test case runs

2.3.3 Restore mocks after each test

```
afterEach(()
```

Restores original implementations of mocked functions after each test case completes

2.3.4 Test suite for error and log reporting

```
describe('saltos.core.adderror/addlog', ()
```

Contains tests for core error handling and logging functionality

2.3.5 Setup before each test in this suite

```
beforeEach(()
```

Mocks core dependencies including AJAX, token, and gettext functions

2.3.6 Test error reporting functionality

```
test('saltos.core.adderror should send error details to the server', async ()
```

Verifies that error details including stack traces are properly processed and sent to the server

2.3.7 Test log reporting functionality

```
test('saltos.core.addlog should send log message to the server', ()
```

Verifies that log messages are properly formatted and sent to the server

2.3.8 Test suite for global error handling

```
describe('window.addEventListener for error and unhandledrejection', ()
```

Contains tests for window-level error and unhandled promise rejection handlers

2.3.9 Setup before each test in this suite

```
beforeEach(()
```

Mocks the core error reporting function

2.3.10 Test global error handling

```
test('should call saltos.core.adderror when an error occurs', ()
```

Verifies that window error events are properly captured and reported

2.3.11 Test unhandled promise rejection handling

```
test('should call saltos.core.adderror when an unhandledrejection occurs', ()
```

Verifies that unhandled promise rejections are properly captured and reported

2.3.12 Test parameter validation functionality

```
test('saltos.core.check_params', ()
```

Verifies that missing parameters are properly initialized with default values

2.3.13 Test unique ID generation

```
test('saltos.core.uniqid', ()
```

Verifies that generated IDs are unique and follow expected format

2.3.14 Test suite for visibility detection

```
describe('when_visible', ()
```

Contains tests for the when_visible utility function

2.3.15 Setup before each test in this suite

```
beforeEach(()
```

Configures fake timers and clears DOM

2.3.16 Cleanup after each test in this suite

```
afterEach(()
```

Clears timers and restores real timer implementation

2.3.17 Test basic visibility detection

```
test('executes the callback when the object becomes visible', ()
```

Verifies callback is executed when element becomes visible

2.3.18 Test visibility detection with ID

```
test('works setting the id as test-div', ()
```

Verifies function works with elements that have IDs

2.3.19 Test visibility detection with string ID

```
test('works with an string id instead of an object', ()
```

Verifies function works when passed an element ID string

2.3.20 Test invalid input handling

```
test('throws an error for unsupported obj type', ()
```

Verifies function throws error for unsupported input types

2.3.21 Test delayed element attachment

```
test('append the object after some iterations', ()
```

Verifies function works when element is added to DOM after initialization

2.3.22 Test element removal handling

```
test('throws an error if the object disappears before being visible', ()
```

Verifies function throws error if element is removed before becoming visible

2.3.23 Test key code extraction

```
test('saltos.core.get_keycode', ()
```

Verifies function correctly extracts key codes from different event properties

2.3.24 Test key name resolution

```
test('saltos.core.get_keyname', ()
```

Verifies function correctly maps key codes to common key names

2.3.25 Test suite for HTML element creation

```
describe('saltos.core.html', ()
```

Contains tests for the html utility function

2.3.26 Test single argument usage

```
test('creates a div with inner HTML when only one argument is passed', ()
```

Verifies function creates element from HTML string with optimization

2.3.27 Test two argument usage

```
test('creates the specified element with inner HTML when two arguments are passed', ()
```

Verifies function creates specified element type with content

2.3.28 Test HTML trimming

```
test('trims the inner HTML before setting it', ()
```

Verifies function trims whitespace from HTML content

2.3.29 Test multiple children handling

```
test('does not optimize if there are multiple children', ()
```

Verifies function preserves container element when multiple children exist

2.3.30 Test single child optimization

```
test('optimizes and returns the single child if present', ()
```

Verifies function optimizes by returning single child element directly

2.3.31 Test suite for AJAX functionality

```
describe('saltos.core.ajax', ()
```

Contains comprehensive tests for the core AJAX implementation

2.3.32 Test successful GET request

```
test('makes a successful GET request and calls success callback', async ()
```

Verifies proper request construction and success callback handling

2.3.33 Test error response handling

```
test('handles non-200 responses and calls error callback', async ()
```

Verifies proper error callback invocation for non-200 responses

2.3.34 Test POST request handling

```
test('makes a POST request with a body', async ()
```

Verifies proper construction of POST requests with body content

2.3.35 Test request abortion

```
test('calls abort callback when request is aborted', async ()
```

Verifies proper handling of aborted requests

2.3.36 Test network failure handling

```
test('calls error callback on network failure', async ()
```

Verifies proper error callback invocation for network failures

2.3.37 Test unexpected error handling

```
test('throws an error for unexpected failures', async ()
```

Verifies proper propagation of unexpected errors

2.3.38 Test unsupported method handling

```
test('throws an error for unsupported HTTP method', ()
```

Verifies proper error throwing for unsupported HTTP methods

2.3.39 Test XML response handling

```
test('handles XML response correctly', async ()
```

Verifies proper parsing of XML response content

2.3.40 Test plain text response handling

```
test('handles plain text response correctly', async ()
```

Verifies proper handling of plain text responses

2.3.41 Test key normalization

```
test('saltos.core.fix_key', ()
```

Verifies function properly removes suffixes from keys

2.3.42 Test object copying

```
test('saltos.core.copy_object', ()
```

Verifies function creates proper shallow copies of objects

2.3.43 Test suite for resource loading

```
describe('saltos.core.require', ()
```

Contains tests for the require functionality

2.3.44 Setup before each test in this suite

```
beforeEach(()
```

Configures fake timers for testing asynchronous operations

2.3.45 Cleanup after each test in this suite

```
afterEach(()
```

Restores real timer implementation

2.3.46 Test JavaScript file loading

```
test('loads a JavaScript file successfully', async ()
```

Verifies proper loading and injection of JavaScript files

2.3.47 Test CSS file loading

```
test('loads a CSS file successfully', async ()
```

Verifies proper loading and injection of CSS files

2.3.48 Test cached resource handling

```
test('does not reload already loaded files', async ()
```

Verifies that already loaded resources are not reloaded

2.3.49 Test pending resource handling

```
test('waits when file is already loading', async ()
```

Verifies proper waiting behavior for resources already being loaded

2.3.50 Test module file loading

```
test('loads a JavaScript module file successfully', async ()
```

Verifies proper handling of JavaScript module files

2.3.51 Test hashed resource loading

```
test('loads a CSS file with hash successfully', async ()
```

Verifies proper handling of resources with cache-busting hashes

2.3.52 Test boolean evaluation

```
test('saltos.core.eval_bool', ()
```

Verifies proper conversion of various values to boolean

2.3.53 Test string conversion

```
test('saltos.core.toString', ()
```

Verifies proper string conversion of various values

2.3.54 Test attribute value detection

```
test('saltos.core.is_attr_value', ()
```

Verifies proper identification of attribute-value objects

2.3.55 Test attribute-value joining

```
test('saltos.core.join_attr_value', ()
```

Verifies proper merging of attribute and value objects

2.3.56 saltos.core.encode_bad_chars

```
test('saltos.core.encode_bad_chars', ()
```

This function performs the test of the encode_bad_chars function

2.3.57 saltos.core.__get_code_from_file_and_line

```
test('saltos.core.__get_code_from_file_and_line', ()
```

This function performs the test of the __get_code_from_file_and_line function

2.3.58 saltos.core.timestamp

```
test('saltos.core.timestamp', ()
```

This function performs the test of the timestamp function

2.3.59 saltos.core.human_size

```
test('saltos.core.human_size', ()
```

This function performs the test of the human_size function

2.3.60 saltos.core.is_number

```
test('saltos.core.is_number', ()
```

This function performs the test of the is_number function

2.3.61 saltos.core.is_function

```
test('saltos.core.is_function', ()
```

This function performs the test of the is_function function

2.3.62 Core Module Tests

```
describe('Core Module Tests', ()
```

This test suite validates the core functionalities of the SaltOS framework, ensuring that essential features operate correctly under different scenarios.

2.3.63 Test service worker registration

```
/*
```

This test checks if the service worker is registered properly when the browser supports service workers and the application is running over HTTPS.

2.3.64 Test proxy function messaging

```
test('Proxy function sends message to service worker', ()
```

This test ensures that the proxy function sends the correct message to the service worker's controller using the 'postMessage' method.

2.3.65 Test proxy synchronization on online events

```
test('Triggers proxy sync on online event', ()
```

This test verifies that the proxy synchronization is triggered correctly when the browser's online event is fired.

2.3.66 Test network protocol detection

```
test('Check network detects protocols correctly', async ()
```

This test checks that the 'check_network' function accurately detects HTTP and HTTPS protocols by simulating network conditions.

2.4 Customers unit tests

```
test_customers.js
```

This file contains the customers unit tests

2.4.1 Puppeteer setup

```
const pti = require('puppeteer-to-istanbul');
```

This lines contain the needed setup for run puppeteer and take screenshots

2.4.2 Global variables

```
let puppeteer;
```

This variables contains the browser and page links

2.4.3 Before All

```
beforeAll(async ()
```

This function contains all code executed before all tests, in this case the features provided by this function includes the launch of the browser, set the screen size and start the javascript coverage

2.4.4 After All

```
afterAll(async ()
```

This function contains all code executed after all tests, in this case the features provided by this function include the stop of the javascript coverage recording, the save feature to the desired storage path and the browser close

2.4.5 App Customers

```
describe('App Customers', ()
```

This test is intended to validate the correctness of the customers application by execute the list, more, reset, create, cancel, view, close, edit, back, insert, update and delete features and validate with the expected screenshot

2.4.6 Action List

```
test('Action List', async ()
```

This part of the test tries to load the list screen

2.4.7 Action List

```
test('Action More', async ()
```

This part of the test tries to validate the correctness of the more feature

2.4.8 Action Reset

```
test('Action Reset', async ()
```

This part of the test tries to validate the correctness of the reset feature

2.4.9 Action Create

```
test('Action Create', async ()
```

This part of the test tries to load the create screen

2.4.10 Action Cancel

```
test('Action Cancel', async ()
```

This part of the test tries to validate the correctness of the cancel feature

2.4.11 Action View

```
test('Action View', async ()
```

This part of the test tries to load the view screen

2.4.12 Action Close

```
test('Action Close', async ()
```

This part of the test tries to validate the correctness of the close feature

2.4.13 Action Edit

```
test('Action Edit', async ()
```

This part of the test tries to load the edit screen

2.4.14 Action Go Back

```
test('Action Go Back', async ()
```

This part of the test tries to validate the correctness of the go back feature

2.4.15 Action Insert

```
test('Action Insert (first part)', async ()
```

This part of the test tries to validate the correctness of the insert feature

2.4.16 Action Insert

```
test('Action Insert (second part)', async ()
```

This part of the test tries to validate the correctness of the insert feature

2.4.17 Action Update

```
test('Action Update (first part)', async ()
```

This part of the test tries to validate the correctness of the update feature

2.4.18 Action Update

```
test('Action Update (second part)', async ()
```

This part of the test tries to validate the correctness of the update feature

2.4.19 Action Delete

```
test('Action Delete (first part)', async ()
```

This part of the test tries to validate the correctness of the delete feature

2.4.20 Action Delete

```
test('Action Delete (second part)', async ()
```

This part of the test tries to validate the correctness of the delete feature

2.5 Emails unit tests

```
test_emails.js
```

This file contains the emails unit tests

2.5.1 Puppeteer setup

```
const pti = require('puppeteer-to-istanbul');
```

This lines contain the needed setup for run puppeteer and take screenshots

2.5.2 Global variables

```
let puppeteer;
```

This variables contains the browser and page links

2.5.3 Before All

```
beforeAll(async ()
```

This function contains all code executed before all tests, in this case the features provided by this function includes the launch of the browser, set the screen size and start the javascript coverage

2.5.4 After All

```
afterAll(async ()
```

This function contains all code executed after all tests, in this case the features provided by this function include the stop of the javascript coverage recording, the save feature to the desired storage path and the browser close

2.5.5 App Emails

```
describe('App Emails', ()
```

This test is intended to validate the correctness of the emails application by execute the list, control+f, profile, help, filter, create and view features and validate with the expected screenshot

2.5.6 Action List

```
test('Action List', async ()
```

This action tries to sets the emails as new and not new of all emails that appear in the screen

2.5.7 Action Control F

```
test('Action Control F (first part)', async ()
```

This part of the test tries to validate the control+f focus

2.5.8 Action Control F

```
test('Action Control F (second part)', async ()
```

This part of the test tries to validate the control+f focus

2.5.9 Action Profile

```
test('Action Profile', async ()
```

This part of the test tries to load the profile screen

2.5.10 Action Help

```
test('Action Help', async ()
```

This part of the test tries to load the help screen

2.5.11 Action About

```
test('Action About', async ()
```

This part of the test tries to load the about screen

2.5.12 Action Filter

```
test('Action Filter', async ()
```

This part of the test tries to load the filter screen

2.5.13 Action Create

```
test('Action Create', async ()
```

This part of the test tries to load the create screen

2.5.14 Action View

```
test('Action View', async ()
```

This part of the test tries to load the view screen

2.6 Filter unit tests

```
test_filter.js
```

This file contains unit tests for the filter management system including initialization, loading, saving, and UI interactions

2.6.1 Load all needed files of the project

```
const files = `app,backup,bootstrap,core,driver,filter,form,gettext,hash,storage,token`.split(',');
```

2.6.2 Reset mocks before each test

```
beforeEach(()
```

Ensures all Jest mocks are reset before each test case runs

2.6.3 Restore mocks after each test

```
afterEach(()
```

Ensures all Jest mocks are restored to their original implementations after each test case completes

2.6.4 Test suite for filter initialization

```
describe('saltos.filter.init()', ()
```

Contains tests for initializing the filter cache from server data

2.6.5 Setup before each test in this suite

```
beforeEach(()
```

Mocks window location and sets up AJAX response for filter data

2.6.6 Test filter cache initialization

```
test('should initialize filter cache', async ()
```

Verifies that the init function makes an AJAX call to load filters and properly populates the cache

2.6.7 Test cache reuse

```
test('should not make ajax call if cache is already populated', async ()
```

Verifies that subsequent init calls don't make AJAX requests when cache is already populated

2.6.8 Test suite for filter loading

```
describe('saltos.filter.load()', ()
```

Contains tests for loading filter data into forms and triggering searches

2.6.9 Setup before each test in this suite

```
beforeEach(()
```

Mocks form data and driver search functions

2.6.10 Test loading existing filter

```
test('should load filter data and trigger search', ()
```

Verifies that loading a filter populates form data and triggers a search

2.6.11 Test loading non-existent filter

```
test('should only trigger search if filter not found', ()
```

Verifies that loading an unknown filter only triggers search without modifying form data

2.6.12 Test suite for filter updates

```
describe('saltos.filter.update()', ()
```

Contains tests for updating the local filter cache

2.6.13 Test updating filter cache

```
test('should update filter cache', ()
```

Verifies that update modifies the filter cache correctly

2.6.14 Test suite for filter saving

```
describe('saltos.filter.save()', ()
```

Contains tests for saving filters to both cache and server

2.6.15 Test saving new filter

```
test('should save new filter to cache and server', ()
```

Verifies that new filters are added to cache and saved to server

2.6.16 Test updating existing filter

```
test('should update existing filter if data changed', ()
```

Verifies that modified filters are updated in cache and server

2.6.17 Test unchanged filter

```
test('should not make server call if data unchanged', ()
```

Verifies that unchanged filters don't trigger server updates

2.6.18 Test filter deletion

```
test('should delete filter when data is null', ()
```

Verifies that filters are removed from cache and server when set to null

2.6.19 Test deleting non-existent filter

```
test('should not delete non-existent filter', ()
```

Verifies that attempting to delete unknown filters doesn't trigger server calls

2.6.20 Test suite for filter UI buttons

```
describe('saltos.filter.button()', ()
```

Contains tests for all filter-related UI actions

2.6.21 Setup before each test in this suite

```
beforeEach(()
```

Sets up DOM elements and mocks filter functions

2.6.22 Test load action

```
test('should handle load action', ()
```

Verifies that load button loads selected filter and resets selection

2.6.23 Test update action

```
test('should handle update action', ()
```

Verifies that update button saves current form data to selected filter

2.6.24 Test delete action

```
test('should handle delete action', ()
```

Verifies that delete button removes selected filter and refreshes UI

2.6.25 Test create action

```
test('should handle create action', ()
```

Verifies that create button saves current form data as new filter

2.6.26 Test rename action

```
test('should handle rename action', ()
```

Verifies that rename button moves filter data to new name and removes old filter entry

2.6.27 Test invalid action

```
test('should do nothing for invalid actions', ()
```

Verifies that unknown actions don't modify filter cache

2.6.28 Test suite for filter selection UI

```
describe('saltos.filter.select()', ()
```

Contains tests for updating filter dropdown and tree view

2.6.29 Setup before each test in this suite

```
beforeEach(()
```

Populates filter cache with test data

2.6.30 Test UI update

```
test('should update select options and jstree', ()
```

Verifies that select updates dropdown options and tree view

2.6.31 Test missing tree element

```
test('should handle missing form elements gracefully', ()
```

Verifies graceful handling when tree element is missing

2.6.32 Test missing select element

```
test('should handle missing select elements gracefully', ()
```

Verifies graceful handling when select element is missing

2.6.33 Test missing form elements

```
test('should handle missing form elements gracefully', ()
```

Verifies graceful handling when all form elements are missing

2.7 Core unit tests

```
test_gettext.js
```

This file contains the core unit tests

2.7.1 Load all needed files of the project

```
const files = `bootstrap,core,gettext,storage`.split(',');
```

2.7.2 beforeEach used in this test

```
beforeEach ( ()
```

2.7.3 afterEach used in this test

```
afterEach ( ()
```

2.7.4 saltos.gettext.bootstrap.set/get/get_short/unset

```
test ('saltos.gettext.set/get/get_short/unset', ()
```

This function performs the tests of the set/get/get_short and unset functions

2.7.5 saltos.gettext.bootstrap.field

```
test ('saltos.gettext.bootstrap.field', ()
```

This function performs the tests of the field function

2.7.6 saltos.gettext.bootstrap.modal

```
test ('saltos.gettext.bootstrap.modal', ()
```

This function performs the tests of the modal function

2.7.7 saltos.gettext.bootstrap.toast

```
test ('saltos.gettext.bootstrap.toast', ()
```

This function performs the tests of the toast function

2.7.8 saltos.gettext.bootstrap.menu

```
test ('saltos.gettext.bootstrap.menu', ()
```

This function performs the tests of the menu function

2.7.9 saltos.gettext.bootstrap.offcanvas

```
test ('saltos.gettext.bootstrap.offcanvas', ()
```

This function performs the tests of the offcanvas function

2.8 Hash unit tests

```
test_hash.js
```

This file contains unit tests for hash management functionality including hash parsing, manipulation, and event triggering

2.8.1 Load all needed files of the project

```
const files = `hash`.split(',');
```

2.8.2 Reset mocks before each test

```
beforeEach(()
```

Initializes mock implementations for history API functions and resets all mocks between test cases

2.8.3 Restore mocks after each test

```
afterEach(()
```

Restores original implementations of mocked functions after each test case completes

2.8.4 Test suite for hash helper function

```
describe('saltos.hash.__helper', ()
```

Contains tests for the internal hash normalization function that cleans hash strings by removing special characters

2.8.5 Test hash with leading

```
test('should remove leading #', ()
```

Verifies the helper removes the # character from the beginning

2.8.6 Test hash with leading /

```
test('should remove leading /', ()
```

Verifies the helper removes the / character from the beginning

2.8.7 Test hash with leading #/

```
test('should remove both leading # and /', ()
```

Verifies the helper removes both # and / characters from the beginning

2.8.8 Test empty hash

```
test('should return empty string for empty input', ()
```

Verifies the helper returns empty string for empty input

2.8.9 Test clean hash

```
test('should not modify clean hash', ()
```

Verifies the helper returns unchanged input when no special characters

2.8.10 Test suite for hash getter function

```
describe('saltos.hash.get', ()
```

Contains tests for retrieving the current window hash with proper formatting

2.8.11 Test getting current hash

```
test('should return current hash without #', ()
```

Verifies the function returns hash without # prefix

2.8.12 Test getting empty hash

```
test('should return empty string when no hash', ()
```

Verifies the function returns empty string when no hash exists

2.8.13 Test getting hash with leading /

```
test('should remove leading /', ()
```

Verifies the function removes leading / from the hash

2.8.14 Test suite for hash setter function

```
describe('saltos.hash.set', ()
```

Contains tests for replacing the current hash using history.replaceState

2.8.15 Test setting new hash

```
test('should set new hash with proper format', ()
```

Verifies the function updates hash with proper format and uses replaceState

2.8.16 Test setting same hash

```
test('should not set same hash', ()
```

Verifies the function doesn't update history when hash doesn't change

2.8.17 Test setting hash with

```
test('should handle hash with #', ()
```

Verifies the function properly handles input containing #

2.8.18 Test setting hash with /

```
test('should handle hash with /', ()
```

Verifies the function properly handles input containing /

2.8.19 Test setting empty hash

```
test('should handle empty hash', ()
```

Verifies the function properly handles empty hash input

2.8.20 Test suite for hash adder function

```
describe('saltos.hash.add', ()
```

Contains tests for adding new hash entries using history.pushState

2.8.21 Test adding new hash

```
test('should add new hash with proper format', ()
```

Verifies the function updates hash with proper format and uses pushState

2.8.22 Test adding same hash

```
test('should not add same hash', ()
```

Verifies the function doesn't update history when hash doesn't change

2.8.23 Test adding hash with

```
test('should handle hash with #', ()
```

Verifies the function properly handles input containing #

2.8.24 Test adding hash with /

```
test('should handle hash with /', ()
```

Verifies the function properly handles input containing /

2.8.25 Test adding empty hash

```
test('should handle empty hash', ()
```

Verifies the function properly handles empty hash input

2.8.26 Test suite for URL hash extraction

```
describe('saltos.hash.url2hash', ()
```

Contains tests for extracting hash fragments from URLs

2.8.27 Test extracting hash from URL

```
test('should extract hash from URL', ()
```

Verifies the function extracts hash fragment correctly

2.8.28 Test extracting hash with /

```
test('should handle URL with / after #', ()
```

Verifies the function handles hashes containing /

2.8.29 Test URL without hash

```
test('should return empty string when no hash', ()
```

Verifies the function returns empty string when no hash exists

2.8.30 Test suite for hash change events

```
describe('saltos.hash.trigger', ()
```

Contains tests for triggering hashchange events

2.8.31 Test triggering hash change

```
test('should dispatch hashchange event', ()
```

Verifies the function dispatches a hashchange event

2.9 Invoices unit tests

```
test_invoices.js
```

This file contains the invoices unit tests

2.9.1 Puppeteer setup

```
const pti = require('puppeteer-to-istanbul');
```

This lines contain the needed setup for run puppeteer and take screenshots

2.9.2 Global variables

```
let puppeteer;
```

This variables contains the browser and page links

2.9.3 Before All

```
beforeAll(async ()
```

This function contains all code executed before all tests, in this case the features provided by this function includes the launch of the browser, set the screen size and start the javascript coverage

2.9.4 After All

```
afterAll(async ()
```

This function contains all code executed after all tests, in this case the features provided by this function include the stop of the javascript coverage recording, the save feature to the desired storage path and the browser close

2.9.5 App Invoices

```
describe('App Invoices', ()
```

This test is intended to validate the correctness of the invoices application by execute the list, checkbox, create, view and edit features and validate with the expected screenshot

2.9.6 Action List

```
test('Action List', async ()
```

This part of the test tries to load the list screen

2.9.7 Action List

```
test('Action Checkbox (first part)', async ()
```

This part of the test tries to validate the correctness of the checkbox feature

2.9.8 Action List

```
test('Action Checkbox (second part)', async ()
```

This part of the test tries to validate the correctness of the checkbox feature

2.9.9 Action Create

```
test('Action Create', async ()
```

This part of the test tries to load the create screen

2.9.10 Action View

```
test('Action View', async ()
```

This part of the test tries to load the view screen

2.9.11 Action Edit

```
test('Action Edit', async ()
```

This part of the test tries to load the edit screen

2.10 Proxy unit tests

```
test_proxy.js
```

This file contains the proxy unit tests

2.10.1 beforeEach used in this test

```
beforeEach(()
```

2.10.2 afterEach used in this test

```
afterEach(()
```

2.10.3 Load the needed environment of the proxy part

```
Object.assign(global, myrequire(
```

2.10.4 md5

```
test('md5', ()
```

This function performs the test of the md5 function

2.10.5 human_size

```
test('human_size', ()
```

This function performs the test of the human_size function

2.10.6 service-worker-mock@2.0.5's Headers stub deviates from the spec in two ways

```
const headersPath = require.resolve('service-worker-mock/models/Headers');
```

- Headers[Symbol.iterator] returns .values() instead of .entries(), so spreading a Headers instance (e.g. [...response.headers]) yields plain values instead of [key](#), pairs.
- its constructor can't parse an array of [key](#), pairs (only plain objects or another Headers instance), which is the format request_serialize()/request_unserialize() round-trip through IndexedDB. Patch the shared Headers class in the require cache before requiring service-worker-mock, so its own Request/Response classes (which capture their own internal reference via require('./Headers')) pick up the fix too.

2.11 Push unit tests

```
test_push.js
```

This file contains unit tests for the push notification functionality and favicon status updates in the SaltOS framework.

2.11.1 Load all needed files of the project

```
const files = `app,bootstrap,bootstrap/toast,core,gettext,push,storage,token`.split(',');
```

2.11.2 Reset mocks before each test

```
beforeEach(()
```

Ensures all Jest mocks are reset before each test case runs

2.11.3 Restore mocks after each test

```
afterEach(()
```

Ensures all Jest mocks are restored to their original implementations after each test case completes

2.11.4 Test suite for saltos.push.fn functionality

```
describe('saltos.push.fn', ()
```

Contains tests for the push notification system's main function, including various execution conditions and response handling

2.11.5 Setup before each test in this suite

```
beforeEach(()
```

Initializes mock implementations and resets push notification state

2.11.6 Test push function when already executing

```
test('should return early if executing is true', ()
```

Verifies that the push function exits early when a push operation is already in progress

2.11.7 Test push function without token

```
test('should return early if token is not available', ()
```

Verifies that the push function exits early when no authentication token is available

2.11.8 Test push function when offline

```
test('should return early if navigator is offline', ()
```

Verifies that the push function exits early when the browser is offline

2.11.9 Test push function with positive count

```
test('should return early if count is greater than or equal to 0', ()
```

Verifies that the push function exits early when the countdown counter hasn't reached zero

2.11.10 Test push function with successful response

```
test('should call ajax and handle success response', ()
```

Verifies that the push function makes an AJAX call and properly handles a successful response

2.11.11 Test push function with error response

```
test('should handle error response', ()
```

Verifies that the push function properly handles an error response from the server

2.11.12 Test suite for saltos.favicon.fn functionality

```
describe('saltos.favicon.fn', ()
```

Contains tests for the favicon status update functionality, including visibility state handling

2.11.13 Test favicon function activation

```
test('should start interval if bool is true and executing is false', ()
```

Verifies that the favicon update interval starts when the function is activated

2.11.14 Test favicon function deactivation

```
test('should clear interval if bool is false and executing is true', ()
```

Verifies that the favicon update interval stops when the function is deactivated

2.12 Screenshots unit tests

```
test_screenshots.js
```

This file contains the screenshots unit tests

2.12.1 Puppeteer setup

```
const pti = require('puppeteer-to-istanbul');
```

This lines contain the needed setup for run puppeteer and take screenshots

2.12.2 Global variables

```
let puppeteer;
```

This variables contains the browser and page links

2.12.3 Before All

```
beforeAll(async ()
```

This function contains all code executed before all tests, in this case the features provided by this function includes the launch of the browser, set the screen size and start the javascript coverage

2.12.4 After All

```
afterAll(async ()
```

This function contains all code executed after all tests, in this case the features provided by this function include the stop of the javascript coverage recording, the save feature to the desired storage path and the browser close

2.12.5 App Customers

```
describe('Screenshots', ()
```

This test is intended to validate the correctness of the customers application by execute the list, more, reset, create, cancel, view, close, edit, back, insert, update and delete features and validate with the expected screenshot

2.12.6 Action List

```
test('users login', async ()
```

This part of the test tries to load the list screen

2.13 Storage unit tests

```
test_storage.js
```

This file contains the storage unit tests

2.13.1 Load all needed files of the project

```
const files = `core,storage`.split(',');
```

2.13.2 beforeEach used in this test

```
beforeEach(()
```

2.13.3 afterEach used in this test

```
afterEach(()
```

2.13.4 saltos.storage

```
test('saltos.storage', ()
```

This function performs the test of the storage functions

2.14 Tester unit tests

```
test_tester.js
```

This file contains the tester unit tests

2.14.1 Puppeteer setup

```
const pti = require('puppeteer-to-istanbul');
```

This lines contain the needed setup for run puppeteer and take screenshots

2.14.2 Global variables

```
let puppeteer;
```

This variables contains the browser and page links

2.14.3 Before All

```
beforeAll(async ()
```

This function contains all code executed before all tests, in this case the features provided by this function includes the launch of the browser, set the screen size and start the javascript coverage

2.14.4 After All

```
afterAll(async ()
```

This function contains all code executed after all tests, in this case the features provided by this function include the stop of the javascript coverage recording, the save feature to the desired storage path and the browser close

2.14.5 App Tester

```
describe('App Tester', ()
```

This test is intended to validate the correctness of the tester application by execute the init, disabled, enabled, all bs_themes and all css_themes and validate with the expected screenshot

2.14.6 Action Init

```
test('Action Init', async ()
```

This part of the test tries to initialize the tester screen by provide a valid credentials and loads the tester application

2.14.7 Action Disabled

```
test('Action Disabled', async ()
```

This part of the test tries to disable all widgets

2.14.8 Action Enabled

```
test('Action Enabled', async ()
```

This part of the test tries to enable all widgets

2.14.9 Prepare the test.each iterator

```
const themes = ['default',
```

2.14.10 Visual Theme Combinations

```
test.each(cases)('$label', async ({mode, theme, label})
```

This test iterates all css themes combined with both light and dark bootstrap modes. For each permutation the bootstrap theme and the css theme are applied and the resulting screen is validated against the expected visual snapshot.

This ensures visual consistency across all supported theme combinations without duplicating structural tests like enabled/disabled state.

2.15 Token unit tests

```
test_token.js
```

This file contains the token unit tests

2.15.1 Load all needed files of the project

```
const files = `core,storage,token`.split(',');
```

2.15.2 beforeEach used in this test

```
beforeEach(()
```

2.15.3 afterEach used in this test

```
afterEach(()
```

2.15.4 saltos.token

```
test('saltos.token', ()
```

This function performs the test of the token functions

2.16 Window unit tests

```
test_window.js
```

This file contains unit tests for window management functionality including window opening/closing and cross-tab communication

2.16.1 Load all needed files of the project

```
const files = `core,storage>window`.split(',');
```

2.16.2 Reset mocks before each test

```
beforeEach(()
```

Ensures all Jest mocks are reset before each test case runs

2.16.3 Restore mocks after each test

```
afterEach(()
```

Ensures all Jest mocks are restored to their original implementations after each test case completes

2.16.4 Test suite for window open/close functionality

```
describe('saltos.window.open/close', ()
```

Contains tests for opening new windows with different URL types and closing the current window

2.16.5 Setup before each test in this suite

```
beforeEach(()
```

Mocks window.open and window.close functions

2.16.6 Test opening app URLs

```
test('should call window.open with the app prefix', ()
```

Verifies that app URLs are properly prefixed with .#/ when opening new windows

2.16.7 Test opening HTTP URLs

```
test('should call window.open with the http prefix', ()
```

Verifies that HTTP URLs are passed through unchanged when opening new windows

2.16.8 Test opening HTTPS URLs

```
test('should call window.open with the https prefix', ()
```

Verifies that HTTPS URLs are passed through unchanged when opening new windows

2.16.9 Test unsupported URL protocols

```
test('should throw an error when call window.open with non supported protocol', ()
```

Verifies that attempting to open URLs with unsupported protocols throws an error

2.16.10 Test window closing

```
test('should call window.close', ()
```

Verifies that the close function properly calls window.close

2.16.11 Test suite for window event listeners

```
describe('saltos.window.listeners', ()
```

Contains tests for cross-tab communication functionality including setting listeners and sending events between tabs

2.16.12 Test setting event listeners

```
test('set_listener should add a listener for a specific event', ()
```

Verifies that listeners can be registered for specific events

2.16.13 Test removing event listeners

```
test('unset_listener should remove a listener for a specific event', ()
```

Verifies that listeners can be removed for specific events

2.16.14 Test sending events to current tab

```
test('send should trigger the listener in the same tab when scope is "me"', ()
```

Verifies that events with "me" scope only trigger callbacks in the current tab

2.16.15 Test sending events to other tabs

```
test('send should trigger the listener in other tabs when scope is "other"', ()
```

Verifies that events with "other" scope trigger callbacks in other tabs through localStorage events

2.16.16 Test sending events to all tabs

```
test('send should trigger the listener in all tabs when scope is "all"', ()
```

Verifies that events with "all" scope trigger callbacks in all tabs including the current one

2.16.17 Test sessionStorage event filtering

```
test('storage event listener should not trigger if the event is not from localStorage', ()
```

Verifies that events from sessionStorage don't trigger the cross-tab communication callbacks

2.16.18 Test event key filtering

```
test('storage event listener should not trigger if the key does not match', ()
```

Verifies that events with incorrect keys don't trigger the cross-tab communication callbacks

2.16.19 Test unregistered event filtering

```
test('storage event listener should not trigger if the event name is not in listeners', ()
```

Verifies that events for unregistered event names don't trigger any callbacks