

# Minería de datos y Patrones

Version 2024-I

**Gabor**

[ Capítulo 2 ]

**Dr. José Ramón Iglesias**

DSP-ASIC BUILDER GROUP

Director Semillero TRIAC

Ingeniería Electrónica

Universidad Popular del Cesar

## Texture Features for Browsing and Retrieval of Image Data

B.S. Manjunath and W.Y. Ma

**Abstract**—Image content based retrieval is emerging as an important research area with application to digital libraries and multimedia databases. The focus of this paper is on the image processing aspects and in particular using texture information for browsing and retrieval of large image data. We propose the use of Gabor wavelet features for texture analysis and provide a comprehensive experimental evaluation. Comparisons with other multiresolution texture features using the Brodatz texture database indicate that the Gabor features provide the best pattern retrieval accuracy. An application to browsing large air photos is illustrated.

**Index Terms**—Digital libraries, image database, content-based image retrieval, texture analysis, Gabor wavelets.

# Funciones de Gabor

---

The Gabor functions are a complete (but a nonorthogonal) basis set given by:

$$f(x, y) = \frac{1}{2\pi\sigma_x\sigma_y} \exp\left(-\frac{1}{2}\left(\frac{x^2}{\sigma_x^2} + \frac{y^2}{\sigma_y^2}\right)\right) \exp(2\pi j u_0 x)$$

where  $\sigma_x$  and  $\sigma_y$  denote the Gaussian envelope along the  $x$  and  $y$ -axes, and  $u_0$  defines the radial frequency of the Gabor function.

# Funciones de Gabor

self-similar filter bank can be obtained by appropriate dilation and rotation of  $f(x, y)$  through the generating function

$$f_{pq}(x, y) = \alpha^{-p} f(x', y')$$



where

$$\begin{aligned} x' &= \alpha^{-p}(x \cos \theta_q + y \sin \theta_q) \\ &= \alpha^{-p}(-x \sin \theta_q + y \cos \theta_q), \\ \alpha &> 1; \quad p = 1, 2, \dots, S; \quad q = 1, 2, \dots, L. \end{aligned}$$

The integer subscripts  $p$  and  $q$  represent the index for scale (dilation) and orientation (rotation), respectively.  $S$  is the total number of scales and  $L$  is the total number of orientations in the self-similar Gabor filter bank. For each orientation  $q$ , the angle  $\theta_q$  is given by

$$\theta_q = \frac{\pi(q-1)}{L}, \quad q = 1, 2, \dots, L.$$

# Funciones de Gabor




# Funciones de Gabor

$$\alpha = \left( \frac{f_h}{f_l} \right)^{-(1/(S-1))}$$

$$\sigma_x = \frac{\sqrt{2 \ln 2}(\alpha + 1)}{2\pi f_h(\alpha - 1)}$$

$$\sigma_y = \left[ 2 \ln 2 - \left( \frac{2 \ln 2}{2\pi \sigma_x f_h} \right)^2 \right]^{1/2} \cdot \left[ 2\pi \tan\left(\frac{\pi}{2L}\right) \left( f_h - 2 \ln\left(\frac{1}{4\pi^2 \sigma_x^2 f_h}\right) \right) \right]^{-1}$$

Se asegura así que la respuesta en frecuencia de los filtros Gabor escogidos no se traslapen.



# Funciones de Gabor

$$I_{pq}(x, y) = \left\{ [f_{pq}(x, y)_e * I(x, y)]^2 + [f_{pq}(x, y)_o * I(x, y)]^2 \right\}^{1/2} \quad (6)$$

where “\*” denotes 2-D convolution operation, and  $f_{pq}(x, y)_e$  and  $f_{pq}(x, y)_o$  represent the even and odd parts of the Gabor filter separated from (3).


for  $p=1 \dots s$  for  $q=1 \dots r$  (‘s’ scales and ‘r’ orientations)

$$g(p, q) = I_{pq}$$

$$J = (g_{\max} - g_{\min}) / g_{\min}$$

**Typically,  $r = s = 8$**

Input



**I**



# Kernels Gabor

$G_{11}$



$G_{12}$




:




$G_{88}$





Input




**I**





















Ejemplo

**Base de Datos: Brodatz**  
**111 texturas**  
**9 imágenes por textura**







**Cómo diseñar un clasificador que reconozca 111 Texturas?**

# Solución (1 / 2)

## 1. Extracción de Características

BD: 111 clases,  
9 imágenes por clase

→ Gabor →

Matriz X: 999 x 67 elementos  
Vector y: 999 elementos

## 2. Separación de Training/Testing

Training: características de las primeras 8 imágenes por clase

Xtrain: matriz de 888 x 67      ytrain: vector de 888 elementos

Testing: características de la última imagen de la clase

Xtest: matriz de 111 x 67      ytest: vector de 111 elementos

## Solución (2/2)

### 3. Diseño del Clasificador



### 4. Predicción en el set de testing



### 5. Evaluación de Desempeño



## Resultados (KNN con $k=1$ )

