



R-CENTRAL

```
R-central#
```

Neighbor ID	Pri	State	Dead Time	Address	Interface
5.5.5.5	1	FULL/DR	00:00:34	10.0.4.2	GigabitEthernete
4.4.4.4	1	FULL/DR	00:00:31	10.0.3.2	GigabitEthernete
3.3.3.3	1	FULL/DR	00:00:33	10.0.2.2	GigabitEthernete
2.2.2.2	1	FULL/DR	00:00:36	10.0.1.2	GigabitEthernete

R-SUCURSAL 1

```
R-sucursal-1#
R-sucursal-1#show ospf neighbor
R-sucursal-1#show ip ospf neighbor
```

Neighbor ID	Pri	State	Dead Time	Address	Interface
1.1.1.1	1	FULL/BDR	00:00:32	10.0.1.1	GigabitEthernete

R-SUCURSAL 2

```
R-sucursal-2#
R-sucursal-2#show ip ospf neighbor
```

Neighbor ID	Pri	State	Dead Time	Address	Interface
1.1.1.1	1	FULL/BDR	00:00:33	10.0.2.1	GigabitEthernete

R-SUCURSAL 3

```
R-sucursal-3#
R-sucursal-3#
R-sucursal-3#show ip ospf neighbor
```

Neighbor ID	Pri	State	Dead Time	Address	Interface
1.1.1.1	1	FULL/BDR	00:00:32	10.0.3.1	GigabitEthernete



R- HQ

```
HQ#show ip osp neighbor
```

Neighbor ID	Pri	State	Dead Time	Address	Interface
1.1.1.1	1	FULL/BDR	00:00:36	10.0.4.1	GigabitEthernet0/0

```
HQ#
```

PROTOCOLO OSPF:

```
Gateway of last resort is not set
```

```

10.0.0.0/8 is variably subnetted, 5 subnets, 2 masks
0       10.0.1.0/30 [110/2] via 10.0.4.1, 01:50:52, GigabitEthernet0/0
0       10.0.2.0/30 [110/2] via 10.0.4.1, 01:50:52, GigabitEthernet0/0
0       10.0.3.0/30 [110/2] via 10.0.4.1, 01:50:52, GigabitEthernet0/0
0 IA    192.168.31.0/24 [110/3] via 10.0.4.1, 01:50:52, GigabitEthernet0/0
0 IA    192.168.32.0/24 [110/3] via 10.0.4.1, 01:50:52, GigabitEthernet0/0
0 IA    192.168.110.0/24 [110/3] via 10.0.4.1, 01:50:52, GigabitEthernet0/0
0 IA    192.168.120.0/24 [110/3] via 10.0.4.1, 01:50:52, GigabitEthernet0/0
0 IA    192.168.210.0/24 [110/3] via 10.0.4.1, 01:50:52, GigabitEthernet0/0
0 IA    192.168.220.0/24 [110/3] via 10.0.4.1, 01:50:52, GigabitEthernet0/0
HQ#
```

CONFIGURACIÓN DE SWITCHES

SWITCH HQ

```

layer2switch3 - PuTTY
SW-HQ(config)#vlan 10
SW-HQ(config-vlan)#name Admin_HQ
SW-HQ(config-vlan)#exit
SW-HQ(config)#
SW-HQ(config)#vlan 20
SW-HQ(config-vlan)#
SW-HQ(config-vlan)#name Ventas_HQ
SW-HQ(config-vlan)#exit
SW-HQ(config-vlan)#vlan 30
SW-HQ(config-vlan)#name TI_Monitoreo
SW-HQ(config-vlan)#exit
SW-HQ(config-vlan)#vlan 50
SW-HQ(config-vlan)#name VPM_Clientes
SW-HQ(config-vlan)#exit
SW-HQ(config-vlan)#vlan 60
SW-HQ(config-vlan)#name Servidores
SW-HQ(config-vlan)#exit
SW-HQ(config)#
SW-HQ(config)#
SW-HQ(config)#interface g0/0
SW-HQ(config-if)#switchport trunk encapsulation dot1q
SW-HQ(config-if)#switchport mode trunk
SW-HQ(config-if)#exit
SW-HQ(config)#
SW-HQ(config)#interface g0/1
SW-HQ(config-if)#switchport mode access
SW-HQ(config-if)#switchport access vlan 10
SW-HQ(config-if)#no shutdown
SW-HQ(config-if)#exit
SW-HQ(config)#
SW-HQ(config)#interface g0/2
SW-HQ(config-if)#switchport mode access
SW-HQ(config-if)#switchport access vlan 20
SW-HQ(config-if)#no shutdown
% Invalid input detected at '^' marker.
SW-HQ(config-if)#no shutdown
SW-HQ(config-if)#exit
SW-HQ(config)#
SW-HQ(config)#do write
Building configuration...
Compressed configuration from 3076 bytes to 1472 bytes[OK]
SW-HQ(config)#
*May 18 02:40:51.214: %GRUB-5-CONFIG_WRITING: GRUB configuration is being update
d on disk. Please wait...
*May 18 02:40:51.872: %GRUB-5-CONFIG_WRITTEN: GRUB configuration was written to
disk successfully

```



SWITCH - SUCURSAL 2

```
layer2switch-5 - PuTTY
* Cisco in writing.
*****
Switch>
Switch>enable
Switch#
*May 18 02:16:32.980: %PLATFORM-5-SIGNATURE_VERIFIED: Image 'flash0:/vios_l2-adv
enterprise9-m' passed code signing verification
Switch#
Switch#configure terminal
^
% Invalid input detected at '^' marker.

Switch#
Switch#config terminal
Enter configuration commands, one per line. End with CNTL/Z.
Switch(config)#
Switch(config)#hostname SW-S2
SW-S2(config)#vlan 10
SW-S2(config-vlan)#name Administracion
SW-S2(config-vlan)#exit
SW-S2(config)#vlan 20
SW-S2(config-vlan)#name Ventas
SW-S2(config-vlan)#
SW-S2(config-vlan)#exit
SW-S2(config)#interface g0/0
SW-S2(config-if)#switchport trunk encapsulation dot1q
SW-S2(config-if)#
SW-S2(config-if)#switchport mode trunk
SW-S2(config-if)#exit
SW-S2(config)#
SW-S2(config)#interface g0/1
SW-S2(config-if)#switchport mode access
SW-S2(config-if)#switchport access vlan 10
SW-S2(config-if)#no shutdown
SW-S2(config-if)#exit
SW-S2(config)#
SW-S2(config)#interface g0/2
SW-S2(config-if)#switchport mode access
SW-S2(config-if)#switchport access vlan 20
SW-S2(config-if)#no shutdown
SW-S2(config-if)#exit
SW-S2(config)#do write
Building configuration...
Compressed configuration from 2812 bytes to 1363 bytes[OK]
SW-S2(config)#
*May 18 02:19:54.397: %GRUB-5-CONFIG_WRITING: GRUB configuration is being update
d on disk. Please wait...
*May 18 02:19:55.043: %GRUB-5-CONFIG_WRITTEN: GRUB configuration was written to
disk successfully.
```

SWITCH SUCURSAL 3

```
layer2switch-6 - PuTTY
Switch>enable
Switch#config terminal
^
% Invalid input detected at '^' marker.

Switch#config terminal
Enter configuration commands, one per line. End with CNTL/Z.
Switch(config)#hostname SW-S3
SW-S3(config)#vlan 10
SW-S3(config-vlan)#name Administracion
SW-S3(config-vlan)#exit
SW-S3(config)#vlan 20
SW-S3(config-vlan)#name Ventas
SW-S3(config-vlan)#exit
SW-S3(config)#interface g0/0
SW-S3(config-if)#switchport trunk encapsulation dot1q
SW-S3(config-if)#switchport mode trunk
SW-S3(config-if)#exit
SW-S3(config)#
SW-S3(config)#interface g0/1
SW-S3(config-if)#switchport mode access
SW-S3(config-if)#switchport access vlan 10
SW-S3(config-if)#no shutdown
SW-S3(config-if)#exit
SW-S3(config)#
SW-S3(config)#interface g0/2
SW-S3(config-if)#switchport mode access
^
% Invalid input detected at '^' marker.

SW-S3(config-if)#switchport
SW-S3(config-if)#exit
SW-S3(config)#interface g0/2
SW-S3(config-if)#switchport mode access
SW-S3(config-if)#switchport access vlan 20
SW-S3(config-if)#no shutdown
SW-S3(config-if)#exit
SW-S3(config)#
SW-S3(config)#do write
Building configuration...
Compressed configuration from 2812 bytes to 1362 bytes[OK]
SW-S3(config)#
*May 18 02:26:43.718: %GRUB-5-CONFIG_WRITING: GRUB configuration is being update
d on disk. Please wait...
*May 18 02:26:44.363: %GRUB-5-CONFIG_WRITTEN: GRUB configuration was written to
disk successfully.
SW-S3(config)#
SW-S3(config)#
```

