

ARRANGER

BUILD | CONTROL | MANAGE

User Manual for DigitalInxIP 5000 Series System

Table of Contents

Status	5
Device Stats.....	5
Groups.....	8
Streams and Subscriptions.....	9
Encoder.....	9
Decoder.....	10
Device Settings Access.....	11
On-Screen Decoder Identify.....	11
Export Device Info.....	12
Export All Device Info.....	12
Health Check.....	13
Device Settings	14
Edit Settings.....	14
Device Name.....	15
Device Groups.....	16
Network.....	17
HDMI Input (Encoder).....	18
HDMI Output (Decoder).....	20
Audio Output (Encoder).....	22
Audio Output (Decoder).....	23
RS232 Serial.....	24
Display Control (Decoder Only).....	26
Idle Image (Decoder Only).....	28
Export Settings.....	29
Import Settings.....	30
Matrix	31
Video / Audio.....	31
Serial.....	32
Infrared.....	33
USB.....	33
Video Wall	34
Tools	36
Send Serial.....	36
Control Commands.....	37
Reboot Device.....	38
Reset Device.....	39
Update Device Firmware.....	40
Preview.....	41

Global Cache Assistant	43
Sending Serial Signals	43
Sending IR Signals	50
Controlling Contact Closures	56
Controlling Relays	61
Configuring Sensor and Contact Closure Triggers	68
Global Settings	74
Users	74
Add User	75
Edit User	76
Delete User	77
Active Users	78
Groups	79
Add Group	80
Edit Group	81
Delete Group	82
Multicast	83
Permissions	84
Security Keys	86
HTTP API Security Key	86
TCP Security Key	88
Analytics	91
Source Availability	92
Display Availability	93
Source Resolution	94
Source Count	95
Display Count	96
Display Source Change	97
Network Downtime	98
UI Creator	99
Notifications	100
Email Settings	101
Presets	102
Make a New Preset	103
Edit a Preset	104
Delete a Preset	105
Apply a Preset	106
Export a Preset	107
Export ALL Presets	108
Import a Preset	109
Import ALL Presets	110
QR Code Preset	111
Scheduler	114

Table of Contents continued.....

<i>Events.....</i>	<i>115</i>
<i>UI Creator.....</i>	<i>117</i>
<i>Create a New User Interface.....</i>	<i>117</i>
<i>Edit a User Interface</i>	<i>118</i>
<i>UI Modes</i>	<i>120</i>
<i>Standard Mode</i>	<i>121</i>
<i>QR Code Result Mode</i>	<i>122</i>
<i>Adding Labels</i>	<i>123</i>
<i>Adding Buttons.....</i>	<i>125</i>
<i>Button Logic.....</i>	<i>130</i>
<i>Button Logic - Momentary</i>	<i>131</i>
<i>Button Logic - Toggle.....</i>	<i>132</i>
<i>Button Logic - Radio Toggle.....</i>	<i>133</i>
<i>Button Logic - Split</i>	<i>134</i>
<i>Button Logic - Repeat.....</i>	<i>137</i>
<i>Button Logic - QR Code</i>	<i>138</i>
<i>Adding an Image</i>	<i>139</i>
<i>Copying and Pasting Elements</i>	<i>142</i>
<i>Adding a Background</i>	<i>144</i>
<i>Duplicate a User Interface</i>	<i>146</i>
<i>Delete a User Interface</i>	<i>147</i>
<i>Generating a Local UI QR Code and URL</i>	<i>148</i>
<i>Generating a Remote UI QR Code and URL</i>	<i>149</i>
<i>Exporting / Importing User Interface.....</i>	<i>150</i>
System / Controller Settings.....	152
<i>Network Settings.....</i>	<i>153</i>
Single Network Mode.....	153
Dual Network Mode	154
<i>Advanced Settings.....</i>	<i>155</i>
<i>Export Settings</i>	<i>157</i>
<i>Import Settings.....</i>	<i>158</i>
<i>System Clock</i>	<i>159</i>
<i>System Reboot</i>	<i>160</i>
<i>System Logs.....</i>	<i>161</i>
<i>License</i>	<i>162</i>
<i>Software Version.....</i>	<i>163</i>
<i>Check for Updates.....</i>	<i>164</i>
<i>Import Updates.....</i>	<i>165</i>
Security Features.....	166
How to HTTP Request	167
Example 1 - POST - ajax.....	167
Example 2 - POST - xhr	168
Preset Logic	169
Using Google Assistant.....	171
Using Command Assistant	175

Status

The *Status* tab contains information about how an encoder or decoder is currently functioning. By default this is the first screen you will see when logging onto the Arranger server application.

Device Stats

Arranger will detect all Digi IP devices on the AV LAN and will display all the current and up-to-date stats for each encoder and decoder by default. To expand individual information on a device, click on the *EXPAND* button on the desired encoder or decoder.

The screenshot displays the 'Status' tab in the Arranger application. The interface includes a top navigation bar with tabs: Status, Device Settings, Matrix, Video Wall, Tools, and Global Settings. Below the navigation bar, there is a 'Select' dropdown menu set to 'ALL DEVICES', an 'Export Status Report' button, and a 'Group Health' button. The main content area is divided into two sections: 'ENCODER' and 'DECODER'. Each section contains a list of device statistics, including Name, Group, Alias, IP Address, MAC, and Status. The 'ENCODER' section shows three devices: InRoomPC, MEDIA, and PC2. The 'DECODER' section shows two devices: DELL and VIZIO. Each device entry has an 'Expand' button next to it. The 'Expand' button for the PC2 device is highlighted with a red box.


Device Type	Name	Group	Alias	IP Address	MAC	Status
ENCODER	InRoomPC	ROOM1	InRoomPC	10.8.11.25	341B22808F3	STREAMING
	MEDIA		MEDIA	10.8.11.96	341B2280CF12	STREAMING
	PC2	ROOM1	PC2	10.8.11.7	341B2280631D	STREAMING
DECODER	DELL		DELL	10.8.11.65	341B22806156	STREAMING
	VIZIO	ROOM1	VIZIO	10.8.11.74	341B228061C2	STREAMING

Device Stats continued.....

The expanded menu provides up-to-date information on the device such as alias / device name, group name, IP address, MAC address, streaming status, firmware version, resolution/format type, and video quality and will also show a preview of the video feed being ingested (encoder) or routed (decoder).

Expanded menu also provides quick access to device streams / subscriptions, access to deeper device settings, export details for device via JSON formatted string and identify decoder locations on screen to a connected display.

Below is an expanded menu for an encoder; the legend below explains the **status** icons shown in the menu.



Note: Device video previews are turned OFF by default.

See *Device Settings > HDMI Input* of this manual for more info on turning on preview.

○ **Status** icons are used to visually indicate the status of a device as follows:



Encoder with video source connected



Decoder with monitor / display connected



Encoder / decoder is connected to the network; no source or display connected



Encoder / decoder is disconnected from the network




Encoder / decoder has a network issue and has timed out



Device has an error

Device Stats continued.....

To display all details for ALL devices, click the up/down arrow button as shown below




Groups

Encoders and decoders can be filtered by groups to limit the number of devices being displayed.

To filter by group, select the group from the drop-down menu below. When a group is selected only the devices in that group will be edited by the various menus.


Note: By default all encoders and decoders are grouped in the *UNGROUPED* category, when devices are sectioned into user-defined groups this file will eventually be empty and cannot be deleted as it is default file for new devices found on a network. The *ALL DEVICES* selection will select all devices regardless of what group they may be associated with.



To learn how to set up devices in a group, see *Global Settings > Groups*

Streams and Subscriptions

Details option under the encoder / decoder contains information regarding the streams and subscriptions to those streams.



Encoder

The *Streams* tab of an encoder will show the status of all streams along with their multicast address. From here you can stop or start all streams.




Streams and Subscriptions continued.....

Decoder

The *Subscriptions* tab of a decoder will show what multicast address is being used to receive data. It will also indicate from what encoder it is receiving the streams.


From here you can leave any of the streams.



Device Settings Access


Clicking the *Settings* button on a device will send you directly to the device settings tab so device settings can be changed quickly.

To learn more about settings, see *Device Settings*




On-Screen Decoder Identify

Identify button in device details on a decoder allows you to display the decoder's name on the connected display or monitor. Device name will be displayed on screen for 30 seconds.




Export Device Info

A JSON formatted file will export the complete status of the selected device. This is to be used for system diagnostics. A *.ini file with the device name will be saved to your downloads folder on your PC.




Export All Device Info

Export Status Report will save a csv formatted file with all the status details from this section.



Health Check

Group Health will report the up-to-date status of all the encoders and decoders in the selected group. If a group has a default preset associated with it, this can also be selected and applied to make sure there are no issues before the system is put into use.



The screenshot shows the 'Status' tab of the Arranger Digi IP 5000 web interface. The 'Group Health' button is highlighted with a red box. The interface displays a list of encoders and decoders with their respective status icons and details.

ENCODER	DECODER		
 NAME InRoomPC GROUP ROOM1 ALIAS InRoomPC IP ADDRESS 10.8.11.25 MAC 341B22808F3 STATUS STREAMING Expand ▼	 NAME MEDIA GROUP ALIAS MEDIA IP ADDRESS 10.8.11.96 MAC 341B2280CF12 STATUS STREAMING Expand ▼	 NAME DELL GROUP ALIAS DELL IP ADDRESS 10.8.11.65 MAC 341B22806156 STATUS STREAMING Expand ▼	 NAME VIZIO GROUP ROOM1 ALIAS VIZIO IP ADDRESS 10.8.11.74 MAC 341B228061C2 STATUS STREAMING Expand ▼
 NAME PC2 GROUP ROOM1 ALIAS PC2 IP ADDRESS 10.8.11.7 MAC 341B2280631D STATUS STREAMING Expand ▼			

Device Settings


This is where all the encoder and decoder device settings are configured in the system. encoders and decoders can be individually configured or configured in batches to save time for setting up standardized equipment.

For settings that can be applied to all encoders or decoders, the option is given to update ALL or you can select which devices to apply the global setting to. If there is no *apply to all* or *group apply* option given then that is a specific setting for that device; for instance you cannot name all decoders the same name so that is not an option to apply to all or multiple selected devices.

Device settings can also be exported to the csv formatted data and manipulating it as required before importing it back into the system. All changes made in the DeviceExport.csv configuration file will be applied to the encoders and decoders.

Edit Settings

Here you can change the device settings for encoders and decoders on the system.



1. Select allows you to filter out devices by groups or you can select ALL devices.
2. Select *Edit* from *Device Settings*
3. Select *Device Type* to filter between encoder and decoder type.
4. Select a *Device*.

Device Name

The name of a device is used for control purposes. This is the device name used in API commands. Device and alias names have a maximum of 19 characters and no spaces are allowed.

1. Enter *Name*.
2. Enter *Alias*.
3. Tick *Update Alias* to update the alias name of the device.
4. Click *Save* or *Default* to return to factory default name of device.

NOTE: The following device names cannot be used:

- 'all'
- 'all_rx'
- 'all_tx'
- 'ungrouped'
- 'all_devices'
- Any Group name
- Any Preset name

Device Groups

Encoders and decoders can be assigned to groups. These groups are created from the *Global Settings* tab. Once an encoder or decoder has been placed in a group, an alias name and an icon can be assigned to it. This alias name and icon will then be used on the *Matrix* tab / page once a group is selected.

Group names have a maximum of 19 characters and no spaces are allowed.

1. Assign device to *Group* by ticking the desired box; in this example we have built two groups; Group 1 and Group 2.

To learn how to build *Groups* see *Global Settings > Groups*.

2. Select an appropriate icon.
3. Click *Clear* to clear selection or click *Save*.

Network

Click on *Network* to change network settings for device(s).

1. Select *IP mode*; AUTO, MANUAL or DEFAULT

- AUTO - DHCP, this mode will allow the IP address to be set automatically by a third-party router or DHCP server.
- MANUAL - Static address mode, enter in user-specified IP address, subnet and gateway.
- DEFAULT - resets to factory default, device will be set to 169.254.0.0/16 Network ID range.

2. Click *Save* to save individual device settings.

OR

Click *Save to Devices* to apply this setting to multiple devices.

Note: Only *MANUAL* and *DEFAULT* mode will save multiple devices.

HDMI Input (Encoder)

Click *HDMI Input* to adjust settings to the video input of an encoder. Here you can enable / disable the devices preview stream, decide video quality and set EDID table to HDMI input.

Status

Device Settings

Matrix

Video Wall

Tools

Global Settings

Select

ALL DEVICES

Device Settings

Edit

Select Device Type

Encoder

Select Device

PC2

Name

Group

Network

HDMI Input

1

Preview

Enabled

?

2

Video Quality

AUTO

3

EDID

1080P 2CH

4

External File

5

Save

Save To Devices

EDID

00 FF FF FF FF FF FF 00 06 74 00 00 82 00 00 00
20 19 01 03 80 59 32 78 0A EE 91 A3 54 4C 99 26
0F 50 54 21 08 00 81 C0 81 00 81 80 90 40 95 00
B3 00 01 00 01 01 02 3A 80 18 71 38 20 40 58 2C
45 00 20 C2 31 00 00 1E 01 10 80 18 71 38 20 40
58 2C 25 00 20 C2 31 00 00 9E 00 00 00 F0 00 18
3C 1E 5A 1E 00 0A 20 20 20 20 20 20 00 00 FC
00 48 44 4D 49 0A 20 20 20 20 20 20 20 01 21
02 03 29 F1 4E 90 1F 22 21 20 05 14 04 13 12 16
03 07 01 23 09 07 07 83 01 00 00 6A 03 0C 00 10
00 88 1E 21 00 00 E2 00 0F 01 10 00 72 51 00 1E
20 6E 28 55 00 60 59 21 00 00 1E 66 21 56 AA 51
00 1E 30 46 8F 33 00 50 10 74 00 00 1E 00 00 00
00 00 00 00 00 00 00 00 00 00 00 00 00 00 00
00 00 00 00 00 00 00 00 00 00 00 00 00 00 00
00 00 00 00 00 00 00 00 00 00 00 00 00 00 F0

EDID Version: 1.3
EDID Valid: Yes
CEA Extension Valid: Yes

Manufacturer ID: AST
Product ID: 0000
Serial Number: 130
Manufacturer Date: Week 32, Year 2015
Screen Size: 89 x 50 cm (35.0 x 19.7 in)
Preferred Format: HD60
Preferred Width: 1920
Preferred Height: 1080
Preferred FPS: 60
Monitor Name: HDMI

Preferred Timing 1:
Pixel Clock 148.50MHz
Active Pixels 1920x1080
Vertical Clock 60.00Hz
Format HD60

6

Save EDID to File

Copy to Clipboard

Audio Output

RS232 Serial Parameters

HDMI Input (Encoder) In continued.....

1. Select enable / disable option in *Preview* drop-down menu, by default all previews are set to *DISABLED*.
2. Select *Video Quality* setting by selecting quality rating 0 - 5, 0 with 5 being the best quality.
Note: This option applies more compression to further decrease the variable bit rate.
3. Select a desired EDID table to the HDMI input, by default EDID is set to 4K 2 channel audio with HDR. Below is a list of all EDID options in the EDID drop-down menu.
 - 4K 2ch, 6ch, 8ch audio with and without HDR10
 - 1080p 2ch, 6ch, 8ch audio
 - 1920 x 1200 2 ch audio
 - Copy and apply EDID from a display or another device connected to a decoder.
4. Click on *External File* to load an external EDID file (must be .edid format).
5. Click *Save* to save individual device settings.

OR

Click *Save to Devices* to apply this setting to multiple devices.

6. Click *Save EDID to file* as an external .edid formatted file; click *Copy to Clipboard* to copy the current displayed EDID file characters.

HDMI Output (Decoder)

Click *HDMI Output* to adjust settings to the video output of a decoder.

Select: ALL DEVICES

Device Settings: Edit

Select Device Type: Decoder

Select Device: Decoder1

Name

Group

Network

HDMI Output

Preview

1

2 Resolution: Original

3 HDCP: HDCP 1.x

4 Video Mute: Disabled

5 Detect Video Loss: Disable

5a Timeout (seconds): 10

5b Turn Video Off: Disable

6 Rotation: None

Aspect Ratio: Fit To Display

7 Save Save To Devices

EDID: No Display Connected

Audio Output

RS232 Serial Parameters

Display Control

Idle Image

6

HDMI Output (Decoder) continued.....

1. Display Preview.
2. Select output *Resolution*.
3. Select *HDCP*.
4. Enable / Disable *Video Mute*.
5. Enable / Disable *Video Loss*.
 - 5a. Select *Video Timeout*.
 - 5b. Select *Enable/Disable* to black the display.
6. Select display *Rotation*.
 - 6a. Select *Aspect Ratio*.
6. Click *Save* to save individual device settings.

OR

Click *Save to Devices* to apply this setting to multiple decoders.

Audio Output (Encoder)

Click on the *Audio Output* menu to configure the 3.5mm analog audio output jack of an encoder. By default the audio output is set to HDMI embedded audio, 2 channel only.

Select: ALL DEVICES

Device Settings: Edit

Select Device Type: Encoder

Select Device: PC2

Name

Group

Network

HDMI Input

Audio Output

1 → Audio Source: HDMI

2 → Analog Audio Output Volume: 0

3 → Save Save To Devices

RS232 Serial Parameters

1. Select *Audio Source*; AUTO, HDMI or ANALOG.

- AUTO - Will automatically switch between the analog audio input on the encoder and the HDMI 2 channel embedded audio.
- HDMI - Sets audio output to HDMI 2 channel embedded audio.
- ANALOG - Sets 3.5mm audio input on encoder as the default output.

2. Set the *Analog Audio Output Volume*.


3. Click *Save* to save individual device settings.

OR

Click *Save to Devices* to apply this setting to multiple encoders.

Audio Output (Decoder)

The 3.5mm analog audio output jack of a decoder is an output of embedded HDMI audio. The analog output level can be adjusted here.



1. Set desired level for the *Analog Audio Output Volume*.
2. Click *Save* to save individual device settings.

OR

Click *Save to Devices* to apply this setting to multiple decoders.

RS232 Serial

Here you configure the parameters for the serial RS232 port of a device so third-party devices using RS232 can be controlled with Arranger.

Select: ALL DEVICES

Device Settings: Edit

Select Device Type: Encoder

Select Device: PC2

Name

Group

Network

HDMI Input

Audio Output

RS232 Serial Parameters

1 → Baud Rate: 9600

2 → Data Bits: 8

3 → Stop Bits: 1

4 → Parity: NONE

5 → Mode: MATRIX

6 → Feedback Timeout (seconds): 1

7 → Save Save To Devices

RS232 Serial continued...

Note: If you are setting up the RS232 serial port to control a third-party device, be sure the RS232 settings match that of the controllable device.

1. Select *Baud Rate*.
2. Select *Data Bits*.
3. Select *Stop Bits*.
4. Select *Parity*.
5. Select *Mode*; MATRIX or CONTROL.
 - MATRIX - Device will appear in the serial *Matrix* menu and can be routed.
 - CONTROL - Device will not appear in the *Matrix* menu and can be used to send and receive from external serial peripherals.
6. Select Feedback Timeout.

Feedback Timeout is an encoder-only setting in *MATRIX* mode. The *Timeout* sets the time an encoder will only respond to the decoder sending data and not broadcast to all connected decoders. After the timeout an encoder's data is sent to all connected decoders.

7. Click *Save* to save individual device settings.

OR

Click *Save to Devices* to apply this setting to multiple encoders or decoders.

Display Control (Decoder Only)

Here you can turn the display's power ON or OFF with CEC or RS232.

With CEC selected and a compatible display the power can be switched with no other commands.

The screenshot shows the 'Device Settings' tab in the Arranger Digi IP 5000 web interface. The 'Select' dropdown is set to 'ALL DEVICES', 'Device Settings' is 'Edit', 'Select Device Type' is 'Decoder', and 'Select Device' is 'VIZIO'. Below these are fields for Name, Group, Network, HDMI Output, Audio Output, RS232 Serial Parameters, and Display Control. The 'Display Control' section has a 'Method' dropdown set to 'CEC'. Below the dropdown are two rows of buttons: the first row has 'Save' and 'Save To Devices' buttons, and the second row has 'ON' and 'OFF' buttons. Red numbers '1' and '2' with arrows point to the 'Save' and 'ON' buttons respectively. A blue question mark icon is visible on the right side of the 'Display Control' section.

1. Click *Save* to save individual device settings.

OR

Click *Save to Devices* to apply this setting to multiple decoders.

2. Press ON to power display ON; press OFF to power display OFF.

Display Control (Decoder Only) continued...

With RS232 selected and a compatible display the power can be switched with ASCII or HEX commands depending on the serial port setting applied.

Enter a command for *ON Command* and *OFF Command*, then save. Now the power buttons are functional.

The screenshot shows the 'ARRANGER' web interface for the 'Digi IP 5000 SERIES'. The 'Device Settings' tab is active. Under 'Display Control', the 'Method' is set to 'RS232'. There are input fields for 'On Command' and 'Off Command'. Below these are checkboxes for 'Append CR' and 'Append LF'. At the bottom of the 'Display Control' section are four buttons: 'Save', 'Save To Devices', 'ON', and 'OFF'. Red numbers 1 and 2 with arrows point to the 'Save' and 'ON/OFF' buttons respectively.

1. Click *Save* to save individual device settings.

OR


Click *Save to Devices* to apply this setting to multiple decoders.

2. Press *ON* to power display ON, press *OFF* to power display OFF.

Idle Image (Decoder Only)

Here is where you can change the default splash screen shown when no video is displayed.

The format of the image must be jpg with a resolution of 1280x720 and a maximum size of 1.5MB.



1. *Select File* from local folder on your PC to upload to decoder.

2. Click *Upload* to upload file into individual device.


OR

Click *Upload to All* to apply this setting to multiple decoders.

Export Settings

The current settings of all the encoders and decoders can be exported to a csv formatted file to be used as a configuration backup or be used to reconfigure the encoders and decoders by changing the required data and importing it back into the Arranger controller.


A file named “DeviceExport.csv” will be exported to your downloads folder.



1. Select *Export* option in *Device Settings* drop-down menu.
2. Click *Export Settings*.

Import Settings

The exported device settings file can be imported back into the system from here. Any device configuration changes made to the DeviceExport.csv will be applied once the file has been imported. This may take some time depending on the amount of configuration changes that need to be performed.



1. Select *Import* option in *Device Settings* drop-down menu.
2. Click *Import Settings*.

Matrix

The *Matrix* tab contains up to 5 individual matrix tabs for each of the signal types; video, audio, serial, infrared and USB. Here you can create or stop joins between encoders and decoders.


Click a white square to make a join.

Click a blue square to remove a join.

Click *ALL* square to make a join from an encoder to ALL decoders.

Video / Audio


Here the video and audio are combined so they are both joined to the destination device.



The scaled video resolution of a decoder's HDMI output can also be changed by clicking the individual decoder settings buttons.


Video / Audio continued.....

When independent routing of the video and audio is required select the *Separate Audio Routing* checkbox. Now the video and audio will appear in separate independent matrix tabs.`




Serial

The matrix *Serial* tab is intended for making serial joins between encoders and decoders for devices set to serial *MATRIX* mode. Devices set to *CONTROL* mode will not be seen in the matrix. To change serial modes see *Devices Settings > RS232 Serial*.



Infrared


The matrix Infrared tab is intended for making infrared joins between encoders and decoders.



USB

The matrix USB tab is intended for making USB joins between encoders and decoders.


The matrix has a KVM (keyboard video mouse) checkbox that will control USB along with video/audio routing.



Video Wall

In the *Video Wall* tab, multiple decoders can be grouped together to form a video wall. Each display requires a decoder and at least one encoder source is required. In a view wall configuration, the decoder's frame buffer is now locked with multiple frame buffers of other decoders. All the decoders working in tandem are receiving the same video stream. Each decoder crops the feed according to relative position within the video wall array and then scaled to a specified resolution.

Here decoders can be assigned to a video layout and an encoder can be routed to the joined video wall. You can also adjust parameters such as resolution and bezel control.



1. Select the group of encoders and decoders to be used in configuration.
2. Select mode (only *Standard* is available for now).
3. Select the video wall layout up to 8 x 5.
4. Select the source encoder for the video to be displayed in the layout.
5. Select the resolution of the displays. The cropped video area from the original source content will be scaled to a display resolution. So if the cropped area is only 960x540, in this case it will be scaled to 1920x1080 for the display.
6. Select *Bezel Compensation* to automatically compensate for the bezel widths.

Video Wall continued...

7. Enter total display width in millimeters (mm).
8. Enter display's viewable screen width in millimeters (mm).
9. Enter total display height in millimeters (mm).
10. Enter display's viewable screen height in millimeters (mm).
11. Drag and drop displays into desired video wall quadrants.
12. Drag and drop encoder to video wall to display video source.
13. Click *Apply* to apply current video wall configuration, click *Save Preset* to save as a recallable preset or click *Load Preset* to load an existing video wall preset. When clicking on *Load Preset* a pop-up window will open with a list of your current video wall presets.

Tools

The *Tools* tab contains many utilities to assist in the installation and updating process.

Send Serial

The *Send Serial* tab is used to test serial strings being sent from an encoder or decoder to third-party peripheral devices such as projectors. The Receive mode will indicate the feedback format of the selected device(s).

1. Select device(s) from the group drop-down menu and select the appropriate device(s).
2. Select either *ASCII* or *HEX* as the input format of the string.
3. Enter the desired data string.
4. Select <CR> and/or <LF> terminator if required.
5. Click *Send*.

Control Commands

The *Control Command* is used to send any of the API commands available to the system for testing purposes.

The screenshot displays the 'Control Commands' interface. At the top, there's a navigation bar with tabs: Status, Device Settings, Matrix, Video Wall, Tools (highlighted), and Global Settings. Below this is a sub-navigation bar with buttons: Send Serial, Control Commands (highlighted), Reboot Device, Reset Device, Update Device Firmware, Preview, and Global Cache Assistant. The main content area contains three numbered steps: 1. Select Control Command (points to a dropdown menu), 2. Assistant (points to a button), and 3. Send (points to a button). There is also a Data String input field, a Receive output area, a Clear button, and a View Command Manual link.

1. Select a command from the *Select Control Command* drop-down menu.

Note: Click on the *View Command Manual* link next to the ? for system command definitions.


2. *Assistant* is a command wizard that will allow you to easily input the information required for the command in order to render the finished code correctly.

Use *Assistant* to configure the command or change the parameters manually in the *Data String* field surrounded with "<" & ">"

3. Click *Send*.

Reboot Device


The *Reboot Device* tab is used to reboot the selected device(s).



1. Select device(s) from the group drop-down menu and select the appropriate devices(s).
2. Click *Reboot*.

Reset Device

The *Reset Device* tab is used to reset the selected device(s) back to factory defaults.




1. Select device(s) from the group drop-down menu and select the appropriate device(s).
2. Click *Reset*.

Update Device Firmware

The *Update Device Firmware* tab is used to update the encoders and decoders.


Note: An Internet connection is required to obtain the latest firmware update available.



1. Select device(s) from the group drop-down menu and select the appropriate device(s) to be updated from the firmware options available.
2. Click *Update Firmware*.

Preview

The preview tab is used to view the preview stream of all encoders. The Preview Available checkbox can be selected to only display encoders with a video source / preview stream available.



Global Cache Assistant

The *Global Cache Assistant* tab is used to configure and communicate with Global Cache endpoints to communicate with third-party devices over a network via serial, infrared (IR), contact closures, and relays using the API control command ***send gc.***

Sending Serial Signals

The following wired and wireless Global Cache devices can be used to send serial signals to 3rd party devices from Arranger.



iTach Flex PoE
PN: FLEXIP-IP



iTach Flex WiFi
PN: FLEXIP-IP

The following Global Cache accessories can be used on all devices listed above for serial endpoint communication.



FLC-SL-232



FLC-SL-485



FLC-SL-MJ

Sending Serial Signals continued.....

The following wired Global Cache devices can be used to send serial signals to 3rd party devices from Arranger and does not require proprietary cabling for serial / RS232 connections.



iTach Ethernet to Serial
PN: IP2SL



iTach Ethernet to Serial
PN: IP2SL-P (PoE)



iTach Ethernet to Serial
PN: WF2SL (WiFi)



GC-100 Products

- GC-100-06
- GC-100-12
- GC-100-18
- GC-100-18R

Sending Serial Signals continued.....

In this example we will configure the iTach IP2SL TCP/IP to serial endpoint which will allow us to send a serial command string to a third-party device connected to the IP2SL via DB9 / RS232 connection.

In order to communicate with a 3rd party device, gather device details for the serial connection of the device, i.e. baud rate, parity, stop bits and ASCII control commands that you wan to use. This unit will not generate those commands or settings for you automatically.

NOTE: The Global Cache Assistant is also used in the *PRESETS* menu so you can save the generated strings for future use

The screenshot shows the 'Global Cache Assistant' window in the 'ARRANGER UI CREATOR' application. The 'Select Mode' section has 'Wizard' selected. The 'Security Key (optional)' field is populated with a long alphanumeric string. The 'IP Address' is '0.0.0.0' and the 'Port' is '4998'. The 'Disconnect (optional)' checkbox is unchecked. The 'Global Caché Command' field is empty. The 'Data String' field contains the command 'send gc [key:<security_key>] <ip> <port> <gc_api>'. A 'Send' button is visible. The 'Receive' section has a 'Clear' button. A red number '1' is overlaid on the 'Device Discovery' button.

1. To identify Global Cache devices on your network, click *Device Discovery*; this will search for the Global Cache devices and will return a list like below.

Sending Serial Signals continued.....

- After initial discovery of Global Cache devices click on the iTachIP2SL in the menu below. Click on the desired Global Cache device to configure.

The screenshot displays the 'Global Cache Assistant' window in the ARRANGER UI CREATOR. On the left, the 'Device Discovery' panel is highlighted with a red border. It lists three discovered devices: '000C1E054F80@10.8.11.85 (iTachIP2SL)', '000C1E054917@10.8.11.100 (iTachIP2IR)', and '000C1E055003@10.8.11.40 (iTachIP2CC)'. A red number '2' is positioned next to the first device. The right panel contains configuration options: 'Select Mode' (Wizard selected), 'Security Key (optional)' (31303534373030333662346663303039), 'IP Address' (0.0.0.0), 'Port' (4998), 'Disconnect (optional)' (unchecked), 'Global Cache Command' (empty), 'Data String' (send gc [key:<security_key>] <ip> <port> <gc_api>), and a 'Receive' section with a 'Clear' button.

Sending Serial Signals continued.....

The following menus appear after the iTach device is selected. This menu is referred to as *Wizard mode*; to enter information in manually select *Normal* as the *Select Mode* option.

The screenshot displays the 'Global Caché Assistant' configuration window. On the left, a 'Serial' dropdown menu is visible, with 'Device Discovery', 'Wizard', and 'Config Page' as options. The 'Wizard' option is highlighted with a red '1', and the 'Config Page' option is highlighted with a red '2'. The 'Wizard' option is also highlighted with a red '3'. The main configuration area includes a 'Select Mode' section with 'Wizard' selected. Below it is a 'Security Key (optional)' field with a value. A 'Serial@10.8.11.85 (iTachIP2SL)' label is present. The 'Alias Name (optional)' and 'Description (optional)' fields are empty. The 'IP Address' field contains '10.8.11.85' and the 'Port' field contains '4999'. The 'Disconnect (optional)' checkbox is unchecked. The 'Global Caché Command' field is empty. The 'Data String' field contains 'send gc [key:<security_key>] <ip> <port> <gc_api>'. The 'Receive' area is empty. The 'Save' button is highlighted with a red '3'. The 'Finish' button is highlighted with a red '3'. The 'Send' button is highlighted with a red '3'. The 'Clear' button is highlighted with a red '3'.

1. The *Wizard* menu provides access to configure the device to send serial strings.
2. The *Config Page* will direct you to the Global Caches internal web server; this will pop-up in another browser menu.
3. Apply an alias name and description of the device and click *Save* so the device can be accessed more quickly in the future, otherwise you will need to discover the device again. These named devices will appear via drop-down above the *Device Discovery* menu.

Sending Serial Signals continued.....

The following appears after the *Wizard* menu is selected in the previous step. Here we will configure the serial command to send.

1. *Network* option allows you to update the Global Caches devices network settings; by default the IP2SL is set to DHCP and falls back on APIPA 169.254.0.0/16 Network ID in absence of a DHCP server / router.

2. *Serial* option allows you to update the serial communication parameters of the device i.e. baud rate.

3. Apply an *alias name* and *description* of the device and click *Save* so the device can be accessed more quickly in the future otherwise you will need to discover the device again. These named devices will appear via drop-down above the *Device Discovery* menu.

Sending Serial Signals continued.....

4. Enter in the serial string you would like to transmit (see 3rd party device documentation for commands)
5. Add terminator <CR> and/or <LF> if required.
6. Enter desired *Feedback* (optional).
7. Once all the above parameters are entered click *Set*; this will format the entered command in the *Global Cache Command* field automatically for use.
8. Select port and disconnect if required (optional).
9. Once the information above has been entered in click *Finish*.
10. Click *Send* to test the code.

You can now use this generated command in a preset to be used with UI control, scheduling and automation OR send this command from a 3rd party control system to the Arranger controller to activate the current configuration. Arranger controller listens on TCP port 6980.

Sending IR Signals

The following wired and wireless Global Cache devices can be used to send IR signals to 3rd party devices from Arranger.



iTach Flex PoE
PN: FLEXIP-IP



iTach Flex WiFi
PN: FLEXIP-IP

The following Global Cache accessories can be used on all devices listed above for IR endpoint communication.



FLC-1E



FLC-3E



FLC-SL-MJ



FLC-BL



FLC-T3

Sending IR Signals continued.....

The following wired Global Cache devices can be used to send IR signals to 3rd party devices from Arranger.



iTach WiFi to IR
PN: WF2IR



iTach Ethernet to IR
PN: IP2SL-P (PoE)



iTach Ethernet to IR
PN: IP2SL



GC-100 Products

- GC-100-06
- GC-100-12
- GC-100-18
- GC-100-18R

Sending IR Signals continued.....

In this example we will configure the iTach IP2IR TCP/IP to IR endpoint. The IP2IR can connect, monitor, and control infrared devices over a network.

After initial discovery of Global Cache devices click on the iTach IP2IR in the menu below.

The screenshot displays the 'Global Cache Assistant' interface within the Arranger Digi IP 5000 software. The interface is divided into two main sections. On the left, a 'Discovered Devices' list shows three devices: '000C1E054F80@10.8.11.85 (iTachIP2SL)', '000C1E054917@10.8.11.100 (iTachIP2IR)' (highlighted with a red box), and '000C1E055003@10.8.11.40 (iTachIP2CC)'. A 'Refresh' button is located below the list. On the right, the 'Wizard' mode is selected. The 'Security Key' is set to '31303534373030333662346663303039'. The 'IP Address' is '0.0.0.0' and the 'Port' is '4998'. The 'Disconnect' checkbox is unchecked. The 'Global Cache Command' field is empty. The 'Data String' field contains the template 'send gc [key:<security_key>] <ip> <port> <gc_api>'. A 'Send' button is visible below the data string field. A 'Receive' area is at the bottom right, with a 'Clear' button below it.

Sending IR Signals continued.....

The follow menus appear after the iTach device is selected. This menu is referred to as *Wizard mode*; to enter information in manually select *Normal* as the *Select Mode* option.

The screenshot displays the 'Global Caché Assistant' interface within the 'ARRANGER UI CREATOR' application. The interface is divided into a sidebar and a main content area. The sidebar contains three buttons: 'Device Discovery', 'Wizard', and 'Config Page'. The main content area is titled 'Global Caché Assistant' and contains the following fields and controls:

- Select Mode:** Radio buttons for 'Wizard' (selected) and 'Normal'.
- Security Key (optional):** A text field containing '31303534373030333662346663303039'.
- Relay_1_2@10.8.11.40 (iTachIP2CC):** A light blue button.
- Alias Name (optional):** A text field with a red number '3' overlaid on it.
- Description (optional):** A text field.
- Save:** A blue button.
- IP Address:** A text field containing '10.8.11.40'.
- Port:** A dropdown menu showing '4998'.
- Disconnect (optional):** A checkbox.
- Global Caché Command:** A text field.
- Finish:** A blue button.
- Data String:** A text field containing 'send gc [key:<security_key>] <ip> <port> <gc_api>'.
- Send:** A blue button.
- Receive:** A large text area.
- Clear:** A yellow button.

Red numbers 1, 2, and 3 are overlaid on the 'Wizard' button, 'Config Page' button, and 'Alias Name' field respectively.

1. The *Wizard* menu provides access to configure the device to send serial strings.
2. The *Config Page* will direct you to the Global Caches internal web server; this will pop-up in another browser menu.
3. Apply an alias name and description of the device and click *Save* so the device can be accessed more quickly in the future otherwise you will need to discover the device again. These named devices will appear via drop-down above the *Device Discovery* menu.

Sending IR Signals continued.....

The following appears after the *Wizard* menu is selected in the previous step. Here we will configure the serial command to send.

The screenshot displays the 'Wizard' configuration screen for the Arranger Digi IP 5000. At the top, 'Select Mode' is set to 'Wizard' (radio button selected). Below it, 'Security Key (optional)' is shown as '31303534373030333662346663303039'. A light blue bar indicates 'TV_IR@10.8.11.100 (iTachiIP2IR)'. On the left, a dropdown menu shows 'TV_IR' and three buttons: 'Device Discovery', 'Wizard' (highlighted with a red box), and 'Config Page'. The main area features a diagram of the device with numbered steps (1-9) pointing to various configuration fields:

- 1** points to the 'Network' tab.
- 2** points to the 'Select I/O' dropdown.
- 3** points to the 'Select Mode' dropdown (set to 'Infrared').
- 4** points to the 'Acquire Mode' dropdown (set to 'Manual').
- 5** points to the 'HEX Code' text area.
- 6** points to the 'Set' and 'Stop' buttons.
- 7** points to the 'IP Address' field (set to '10.8.11.100').
- 8** points to the 'Port' dropdown (set to '4998').
- 9** points to the 'Data String' field (containing 'send gc [key;<security_key>] <ip> <port> <gc_api>').

Other visible fields include 'Disconnect (optional)' (checkbox), 'Global Cache Command' (text area), and a 'Send' button. A 'Receive' section with a large text area and a 'Clear' button is at the bottom.

1. *Network* option allows you to update the Global Caches devices network settings; by default the IP2IR is set to DHCP and falls back on APIPA 169.254.0.0/16 Network ID in absence of a DHCP server / router.

2. *Select I/O* option allows you to select the IR port you wish to use.

Sending IR Signals continued.....

3. *Select Mode* drop-down menu gives you the following options:

Infrared

- *The selected connection will be used as an IR output.*

Sensor

- *The selected connection will be used as a sensor input such as an occupancy sensor.*

Sensor Notify

- *The selected connection will be used as sensor input for notification purposes.*

LED Lighting

- *The selected connection will be used as output to control LED lighting.*

4. *Acquire Mode* drop-down menu gives you the following options:

Manual

- *Enter IR HEX codes manually.*

Cloud Based

- *Use the Global Cache Device IR Cloud Database.*

NOTE: *This option requires the Arranger controller to have an Internet connection.*

Learn

- *Use the Global Cache IP2IR IR learner to learn codes from remotes*

5. Enter desired IR HEX code in this field if using the *Infrared Mode* from step 3.

6. Once all the above parameters are entered in click *Set/Stop*.

7. Select port and disconnect if required (optional).

8. Once the information above has been entered in click *Finish*.

9. Click *Send* to set or test.

You can now use this generated command in a preset to be used with UI control, scheduling and automation OR send this command from a 3rd party control system to the Arranger controller to activate the current configuration. Arranger controller listens on TCP port 6980.

Controlling Contact Closures

The following wired Global Cache devices can be used to open/close contact closures connected to 3rd party devices from Arranger.



iTach WiFi to IR
PN: WF2IR



iTach Ethernet to IR
PN: IP2SL-P (PoE)



iTach Ethernet to IR
PN: IP2SL



GC-100 Products

- GC-100-12
- GC-100-18
- GC-100-18R

Contact Closures continued.....

In this example we will configure the iTach IP2CC TCP/IP to contact closure endpoint.

After initial discovery of Global Cache devices click on the iTach IP2CC in the menu below.

The screenshot shows the 'Global Caché Assistant' window in the ARRANGER UI CREATOR. The interface is divided into two main sections: a left sidebar and a right configuration area.

Left Sidebar:

- At the top is a 'Select Device' dropdown menu.
- Below it is a 'Device Discovery' button.
- A 'Discovered Devices' section lists three devices:
 - 000C1E054F80@10.8.11.85 (iTachIP2SL)
 - 000C1E054917@10.8.11.100 (iTachIP2IR)
 - 000C1E055003@10.8.11.40 (iTachIP2CC) - This device is highlighted with a red border.
- At the bottom is a 'Refresh' button.

Right Configuration Area:

- Select Mode:** Radio buttons for 'Wizard' (selected) and 'Normal'.
- Security Key (optional):** A text field containing '31303534373030333662346663303039'.
- IP Address:** A text field containing '0.0.0.0'.
- Port:** A dropdown menu showing '4998'.
- Disconnect (optional):** A checkbox that is currently unchecked.
- Global Caché Command:** A text field with a 'Finish' button next to it.
- Data String:** A text field containing 'send gc [key:<security_key>] <ip> <port> <gc_api>'.
- Send:** A button with a paper plane icon.
- Receive:** A large text area for receiving data, with a 'Clear' button below it.

At the bottom of the window, there is a footer: 'Copyright © 2021 Liberty AV Solutions. Disclaimer'.

Contact Closures continued.....

The following menus appear after the iTach device is selected. This menu is referred to as *Wizard mode*; to enter information in manually select *Normal* as the *Select Mode* option.

The screenshot shows the 'Global Cache Assistant' interface in the 'ARRANGER UI CREATOR' application. The 'Select Mode' section has 'Wizard' selected. The 'Security Key' field contains '31333331306339326330373066613065'. A light blue bar displays '000C1E055003@10.8.11.40 (iTachIP2CC)'. On the left, a 'Select Device' dropdown is followed by buttons for 'Device Discovery', 'Wizard' (marked with a red '1'), and 'Config Page' (marked with a red '2'). The main form area has fields for 'Alias Name (optional)' (marked with a red '3'), 'Description (optional)', 'IP Address' (10.8.11.40), 'Port' (4998), 'Disconnect (optional)' (checkbox), and 'Global Cache Command'. Below these are 'Data String' (send gc [key:<security_key>] <ip> <port> <gc_api>) and a 'Receive' section. Buttons for 'Save', 'Finish', 'Send', and 'Clear' are present.

1. The *Wizard* menu provides access to configure the device to send serial strings.
2. The *Config Page* will direct you to the Global Caches internal web server, this will pop-up in another browser menu.
3. Apply an alias name and description of the device and click *Save* so the device can be accessed more quickly in the future, otherwise you will need to discover the device again. These named devices will appear via drop-down above the *Device Discovery* menu.

Contact Closures continued.....

The following appears after the *Wizard* menu is selected in the previous step. Here we will configure which contact closure to open or close.

The screenshot displays the 'Wizard' configuration mode for the Arranger Digi IP 5000. The interface includes a sidebar on the left with options: 'Select Device', 'Device Discovery', 'Wizard' (highlighted with a red box), and 'Config Page'. The main configuration area contains the following elements:

- Select Mode:** Radio buttons for 'Wizard' (selected) and 'Normal'.
- Security Key (optional):** A text field containing '31333331306339326330373066613065'.
- Device Address:** A light blue bar displaying '000C1E055003@10.8.11.40 (iTachIP2CC)'.
- Network Settings:** A section with a 'Network' button (callout 1), a 'Select Relay' dropdown (callout 2), and a 'Select State' dropdown (callout 3). Below these are 'Set' and 'Get' buttons (callout 4).
- IP Address:** A text field containing '10.8.11.40'.
- Port:** A dropdown menu showing '4998'.
- Disconnect (optional):** A checkbox that is currently unchecked.
- Global Caché Command:** A text field.
- Data String:** A text field containing 'send gc [key:<security_key>] <ip> <port> <gc_api>' (callout 5).
- Send:** A button (callout 6).
- Receive:** A large text area for receiving data.
- Clear:** A yellow button at the bottom right.

Callouts 1 through 6 are numbered red numbers with arrows pointing to the corresponding UI elements.

1. *Network* option allows you to update the Global Caches devices network settings; by default the IP2CC is set to DHCP and falls back on APIPA 169.254.0.0/16 Network ID in absence of a DHCP server / router.

2. *Select Relay* option allows you to select the port you wish to use.

3. *Select State* allows you to select open or closed status of selected port.

Contact Closures continued.....

4. Once all the above parameters are entered in click *Set/Get* (**Set** will configure the port as desired, **Get** will retrieve current status of selected port).
5. Once the information above has been entered in click *Finish*.
6. Click *Send*.

You can now use this generated command in a preset to be used with UI control, scheduling and automation OR send this command from a 3rd party control system to the Arranger controller to activate the current configuration. Arranger controller listens on TCP port 6980.

Controlling Relays

The following wired and wireless Global Cache devices, paired with the FLC-RS adapter, can control relay outputs connect to device from Arranger.



iTach Flex PoE
PN: FLEXIP-IP



iTach Flex WiFi
PN: FLEXIP-IP



FLC-RS


Controlling Relays continued.....

In this example we will configure the iTach Flex PoE TCP/IP endpoint coupled with the Global Cache FLC-RS cable that supports four configurable relay outputs.


Relay outputs are configurable into common relay types

- Single Pole Single Throw (SPST)
- Single Pole Double Throw (SPDT)
- Double Pole Double Throw (DPDT)

When using the FLC-RS relay cable, be sure to set the pins on the relays for the desired configuration



Wiring and jumper configuration examples...



Controlling Relays continued.....

After initial discovery of Global Cache devices click on the iTach Flex PoE in the menu below.

The screenshot shows the 'Global Cache Assistant' tab in the ARRANGER UI CREATOR. On the left, under 'Discovered Devices', a device with MAC address '000C1E0561EA@10.8.11.68 (iTachFlexEthernetPoe)' is highlighted with a red box. The right panel contains configuration fields: 'Select Mode' (Wizard selected), 'Security Key (optional)' (32363733353235323239303466323031), 'IP Address' (0.0.0.0), 'Port' (4998), 'Disconnect (optional)' (unchecked), 'Global Cache Command' (empty), 'Data String' (send gc [key:<security_key>] <ip> <port> <gc_api>), and a 'Receive' area. Buttons for 'Device Discovery', 'Finish', 'Send', and 'Clear' are visible.

LIBAV UI CREATOR ARRANGER

Global Settings UI Creator Global Cache Assistant

Select Device

Device Discovery

Discovered Devices

000C1E0561EA@10.8.11.68 (iTachFlexEthernetPoe)

Refresh

Select Mode

☒ Wizard

☐ Normal

Security Key (optional)

32363733353235323239303466323031

IP Address

0.0.0.0

Port

4998

Disconnect (optional)

☐

Global Cache Command

Finish

Data String

send gc [key:<security_key>] <ip> <port> <gc_api>

Send

Receive

Clear

Copyright © 2021 Liberty AV Solutions. Disclaimer

Controlling Relays continued.....

The follow menus appear after the iTach device is selected. This menu is referred to as *Wizard mode*; to enter information in manually select *Normal* as the *Select Mode* option.

The screenshot displays the 'Global Cache Assistant' interface within the 'ARRANGER UI CREATOR' application. The interface is divided into several sections:


- Global Settings:** Includes a 'Select Device' dropdown menu.
- UI Creator:** Contains buttons for 'Device Discovery', 'Wizard' (labeled with a red '1'), and 'Config Page' (labeled with a red '2').
- Global Cache Assistant:**
 - Select Mode:** Radio buttons for 'Wizard' (selected) and 'Normal'.
 - Security Key (optional):** A text field containing '32363733353235323239303466323031'.
 - Global Cache Command:** A text field containing '00C1E0561EA@10.8.11.68 (iTachFlexEthernetPoe)'.
 - Alias Name (optional):** A text field (labeled with a red '3').
 - Description (optional):** A text field.
 - Save:** A blue button.
 - IP Address:** A text field containing '10.8.11.68'.
 - Port:** A dropdown menu showing '4998'.
 - Disconnect (optional):** A checkbox.
 - Global Cache Command:** A text field.
 - Finish:** A blue button.
 - Data String:** A text field containing 'send gc [key:<security_key>] <ip> <port> <gc_api>'.
 - Send:** A blue button.
 - Receive:** A large text area.
 - Clear:** A yellow button.

Copyright © 2021 Liberty AV Solutions. [Disclaimer](#)

1. The *Wizard* menu provides access to configure the device to send serial strings.
2. The *Config Page* will direct you to the Global Caches internal web server; this will pop-up in another browser menu.
3. Apply an alias name and description of the device and click *Save* so the device can be accessed more quickly in the future otherwise you will need to discover the device again. These named devices will appear via drop-down above the *Device Discovery* menu.


Controlling Relays continued.....

The following appears after the *Wizard* menu is selected in the previous step. Here we will configure which relay to open or close.



1. *Network* option allows you to update the Global Caches devices network settings; by default the IP2CC is set to DHCP and falls back on APIPA 169.254.0.0/16 Network ID in absence of a DHCP server / router.
2. Select the *FLC-RS relay cable* in the accessories option.
3. Click on the *Control* settings

Controlling Relays continued.....



4. Select *Relay* that you wish to control.
5. Select desired *State*.
6. Once all the above parameters are entered in click *Set/Get* (**Set** will configure the port as desired, **Get** will retrieve current status of selected port).
7. Once the information above has been entered in click *Finish*.

Controlling Relays continued.....

The screenshot shows the 'Wizard' mode of the Arranger Digi IP 5000 configuration interface. The 'Select Mode' section has 'Wizard' selected. The 'Security Key (optional)' field contains '32363733353235323239303466323031'. Below this, a light blue bar displays the IP address '000C1E0561EA@10.8.11.68 (iTachFlexEthernetPoe)'.

On the left, there is a 'Select Device' dropdown menu and three buttons: 'Device Discovery', 'Wizard', and 'Config Page'. The main area displays a grid of device icons: FLC-SL, FLC-SL-MJ, FLC-SL-485, FLC-RS (highlighted with a red box), FLC-1E, FLC-BL, FLC-T3, FLC-3E, and FLC-2E1B. To the right of the grid are buttons for 'Network', 'Control', and 'Sensor'.

Below the device grid, the 'IP Address' field is set to '10.8.11.68' and the 'Port' is set to '4998'. The 'Disconnect (optional)' checkbox is unchecked. The 'Global Caché Command' field contains 'setstate,1;1,1'. A red number '7' is next to the 'Finish' button. The 'Data String' field contains 'send gc [key:<security_key>] <ip> <port> <gc_api>'. A red number '8' is next to the 'Send' button. Below the 'Data String' field is a 'Receive' section with a large text area and a 'Clear' button.

8. Click *Send*.

You can now use this generated command in a preset to be used with UI control, scheduling and automation OR send this command from a 3rd party control system to the Arranger controller to activate the current configuration. Arranger controller listens on TCP port 6980.

Configuring Sensor and Contact Closure Triggers

The following wired and wireless Global Cache devices, paired with the FLC-RS adapter allows configuration of sensor and contact closure input triggers in Arranger



iTach Flex PoE
PN: FLEXIP-IP



iTach Flex WiFi
PN: FLEXIP-IP



FLC-RS

The following wired Global Cache devices, paired with sensor accessories, can be used to configure sensor and contact closure input triggers.



iTach WiFi to IR
PN: WF2IR



iTach Ethernet to IR
PN: IP2SL-P (PoE)



iTach Ethernet to IR
PN: IP2SL



IT-SP1 AC/DC Voltage Sensor




IT-SC1 Contact Closure Sensor

Contact Closure and Sensor Triggers continued.....


In this example we will configure the iTach Flex PoE TCP/IP endpoint coupled with the Global Cache FLC-RS cable to set up sensor and contact closure input triggers.

Once the wiring configuration is complete we will set up the Arranger API command [set listener] that will 'listen' for the sensor or contact closures to activate, this event can then trigger a *PRESET* in Arranger. See *Global Settings > Presets* for more information on creating Presets in Arranger.

When using the FLC-RS relay cable, be sure to set the pins on the closures are set for the desired configuration .



Wiring and jumper configuration examples for both a sensor and a contact closure.....



Contact Closure and Sensor Triggers continued.....


Navigate to *Global Settings*, then click on the *Presets* sub menu

The screenshot shows the 'ARRANGER' UI CREATOR interface. The top navigation bar includes 'LIBAV UI CREATOR' and 'ARRANGER' logos. Below it, a sub-navigation bar has 'Global Settings', 'UI Creator', and 'Global Cache Assistant'. The main content area has tabs for 'Users', 'Security Keys', 'Analytics', 'Notifications', 'Presets', 'Control Commands', and 'Scheduler'. The 'Presets' tab is selected. The form contains the following elements:

- Select Option:** A dropdown menu with 'New' selected. (Red number 1)
- Preset Name:** A text input field containing 'MyPreset1'. (Red number 2)
- Select Control Command:** A dropdown menu with 'set listener' selected. (Red number 3)
- Assistant:** A button with a person icon. (Red number 4)
- Add Control Command:** A section with a template: 'set listener [key:<security_key>] <ip> <notify_port> <protocol> <condition> <state> <device_port> <preset_name> [<delay>]'. Below it is an 'Add' button.
- Delay (ms):** A text input field containing '1000'.
- Preset Commands:** A large text area for additional commands.
- Buttons:** 'Save' and 'Apply' buttons at the bottom.
- Link:** A link with a question mark icon and text 'View Command Manual'.

1. Choose *New* preset.
2. Name the preset.
3. Choose the command [set listener] from the drop down list.
4. Click on *Assistant*.

Contact Closure and Sensor Triggers continued.....



5. Click *Device Discovery* to locate Global Cache devices on the network.
6. Click on the Flex device in the list once discovered.

Contact Closure and Sensor Triggers continued.....

Parameters

Select Mode ☒ Wizard
☐ Normal

Security Key (optional) 343733343031306435303737353335

Select Device Device Discovery

Alias Name (optional)

Description (optional)

Save

Select I/O **7** ☒ ☐ ☐ ☐

Notify Port 101 **8**

Notify Timer 0

Set **9**

IP Address 239.255.250.250

Notify Port 101

Protocol UDP

10 Condition ON

11 State ENABLED

12 Device Port 1

13 Preset Name TVon

Delay [minutes](optional) 0 60

Finish **15**

7. Select the input port you wish to use, in this example we chose the first input option which is set for a contact closure according to the physical pin-out configuration on the FLC-RS.
8. Configure the *Notify Port*, numbers start at 101.
9. Click *Set*.
10. Choose *ON* for the *Condition*.
11. Choose *ENABLED* for the *State*.
12. Change the *Device Port* (I/O port if you want to change the port number in the configuration)
13. Choose the appropriate *Preset Name* you want to execute when the contact closure closes.
14. Apply an alias name and description of the device and click *Save* so the device can be accessed more quickly in the future, otherwise you will need to discover the device again. These named devices will appear via drop-down above the *Device Discovery* menu.
15. Click *Finish*.

Contact Closure and Sensor Triggers continued.....

16. Click *ADD* to add the generated code to the preset.

17. Click *Apply* to test, then click *Save*.

The configuration for using sensors, like a PIR sensor, to execute a preset in Arranger is the SAME as above accept the input ports physical configuration will need to be set to *VOLTAGE SENSOR*.

You can now schedule this preset to always be ON and listening when the Arranger controller is on or has been rebooted. See *Global Settings > Scheduler* for more information on how to use the *System Start* scheduler option.

Global Settings


In the *Global Settings* tab you will find all the global settings of the software.

Users

The system can be configured for user access control. Two levels of access are available, administrator and user. An administrator will have complete access, while a user is limited to the following areas:

- Status
- Matrix
- Video Wall

The device groups for a user can also be limited so that only selected groups of encoders and decoders may be accessed.



Add User

Here you can add a user to the system by selecting **Administrator** or **User** access level, then enter a name and password for the new user. For user level access you can also select the accessible groups and functions.

The screenshot shows the 'Add User' form with the following elements:

- 1** → Select Option: Add
- 2** → Level: ☐ Administrator, ☒ User
- 3** → Password: [Text Field]
- Confirm Password: [Text Field]
- 4** → Group: ☒ All
- 5** → Functions: ☒ Status, ☒ Matrix, ☒ Video Wall
- 6** → Save: [Save Button]

1. Select *Add*.
2. Select *Level*.
3. Enter in *username*, *password* and then *confirm password*.
4. Select *Group*.
5. Select *Function*.
6. Click *Save*.

Edit User

Here you can edit an existing user's username, password, allocated groups, and functions.

The screenshot shows the 'Edit User' form in the Arranger Digi IP 5000 web interface. The form is titled 'Edit User' and is part of the 'Global Settings' section. It contains the following fields and options:


- Select Option:** A dropdown menu with 'Edit' selected.
- Edit:** A dropdown menu with 'User' selected.
- Username:** A text input field with 'User' entered.
- New Password:** A text input field.
- Confirm Password:** A text input field.
- Group:** A checkbox labeled 'All' which is checked.
- Functions:** Three checkboxes labeled 'Status', 'Video Wall', and 'Matrix'. 'Status' and 'Video Wall' are checked.
- Save:** A blue button with a white icon of a person and the text 'Save'.

Red numbers 1 through 6 are overlaid on the form with arrows pointing to the 'Select Option' dropdown, the 'Edit' dropdown, the 'New Password' field, the 'Confirm Password' field, the 'Group' checkbox, and the 'Save' button respectively.

1. Select *Edit*.
2. Select *User*.
3. Enter in *new password* and then *confirm password*.
4. Select *Group*.
5. Select *Function*.
6. Click *Save*.

Delete User


Here you can delete an existing user from the system.



1. Select *Delete*.
2. Select *Username*.
3. Click *Delete*.

Active Users


Here you can see all the active users logged into the system and the time of their last activity.



- 1. Select *Active Users*.

Groups

System encoders and decoders can be arranged into various groups. These groups can then be individually controlled via the API or displayed in the UI. Here we manage the groups by adding, editing or deleting them. Once a group has been added to the system, the group can then be assigned to any or all encoders and decoders from the *Device Settings* tab.



NOTE: The following group names cannot be used:

- 'all'
- 'all_rx'
- 'all_tx'
- 'ungrouped'
- 'all_devices'
- Any Device name
- Any Preset name

Add Group

Here you can add a new group to the system to easily manage encoders and decoders. Devices can then be added to the group.

Encoders or decoders can also be assigned to groups from *Device Settings > Group*.

1. Select *Add*.
2. Enter a group name.
3. Select *Devices*.
4. Click Save.

Edit Group

Here you can change the name of an existing group or devices associated with the group.

1 → Select Option Edit

2 → Group

3 → New Name

* deviceNameCharLimit

4 → Select Device

☐ All Devices ☐ All Decoders ☐ All Encoders ☒ Individual

☐ Dell ☐ InRoomPC

☐ Laptop_WP ☐ MediaPlayer


☐ Nec ☐ TCL

5 → Save

1. Select *Edit*.
2. Select *Group*.
3. Enter in new name.
4. Select *Devices*.
5. Click *Save*.

Delete Group

Here you can delete an existing user from the system.




1. Select *Delete*.
2. Select *Group*.
3. Click *Delete*.

Multicast

The Multicast section is used to configure the multicast range of the devices from between 224.x.x.x and 239.x.x.x with a default of 239.x.x.x.

All devices must be set to the same multicast prefix.



1. Select *Default* or enter a preferred *Multicast Prefix*.
2. Click *Save & Restart* to apply the changes.

Permissions

Permissions adds the ability to only allow selected encoders to be joined with selected decoders. Individual rules can be set per device or as a group as a whole. Rules are applied to the decoder.

Below, Decoder1 is only allowed to be joined with Encoder1, and Encoder2 can be joined with any other decoder except for Decoder2. Multiple conditions can be applied. Joining point-to-point the following rules will be considered before applying the join. Joining point-to-all the following rules will be applied after the join by sending a leave command to denied decoders.

The screenshot shows the 'Permissions' tab in the Arranger Digi IP 5000 interface. It features a table with three columns: 'Select Encoder', 'Select Decoder', and 'Permissions'. The first row has 'Encoder1' selected for the encoder and 'Decoder1' for the decoder, with 'Allow' as the permission. The second row has 'Encoder2' for the encoder and 'Decoder2' for the decoder, with 'Deny' as the permission. A third row is empty. A 'Save' button is at the bottom right. Red numbers 1 through 5 are overlaid on the interface to indicate steps: 1 points to the 'Select Encoder' dropdown, 2 points to the 'Select Decoder' dropdown, 3 points to the 'Permissions' dropdown, 4 points to the 'Save' button, and 5 points to the 'X' delete icons next to the first two rules. A help icon and text are at the bottom of the table area.

Select Encoder	Select Decoder	Permissions
Encoder1	Decoder1	Allow
Encoder2	Decoder2	Deny

1 **2** **3** **4** **5**

? A Group permission allows all Decoders to join with all Encoders in the group.

1. Select encoder.
2. Select decoder.
3. Select Permission as either *Allow* or *Deny*.
4. Click *Save*.
5. Select the cross icons to delete.

Permissions continued.....

Below, the decoders in Group1 can only be joined with the encoders in the group unless individual allow rules are also set for the decoders with other encoders outside of the group.


1. Select Group.
2. Click Save.
3. Select the cross icons to delete.

Security Keys

Security keys are required with all HTTP level requests and optional for TCP commands on port 6980. Only keys generated from the software can be used.

HTTP API Security Key

The Arranger Controller API can be accessed via HTTP GET and POST requests. To ensure security over the network a HTTP security key is required to be passed with all such requests. Here you can generate a new key or import a saved key that had been previously generated.




1. Select *Import Security Key* button.

OR


2. Select *Generate New* button.

Security Keys continued.....

Importing a HTTP API Security Key



1. Select *Import Security Key* button.




2. Enter Security Key.
3. Click *Save*.

Security Keys continued.....

TCP Security Key


The Arranger Controller API can be accessed via Telnet requests on TCP port 6980. To ensure security over the network a TCP security key can be passed with all such commands. Here you can generate a new key or import a saved key that had been previously generated. As the TCP security key is optional its use can be enabled or disabled from here.




1. Select *Generate New* button.
2. Click *Enable*.

Security Keys continued.....

Importing a TCP API Security Key




1. Select *Import Security Key* button.



2. Enter Security Key.
3. Click *Save*.

Security Keys continued.....

Importing a TCP API Security Key Continued....



4. Click *Enable*.

Analytics

Analytical data is constantly being stored on the system. By default data will be maintained for 1 month, but this can be changed up to 12 months.

Various types of information are stored and can be exported for use in a third-party analytical application such as Microsoft's Power Bi. Internal results for the following can be generated from the UI:

Source Availability

The *Source Availability* represents the percentage (%) of time an encoder has a video signal.

Display Availability

The *Display Availability* represents the percentage (%) of time a decoder has a monitor connected.

Source Resolution

The *Source Resolution* represents the combination of different resolutions used as a source.

Source Count

The *Source Count* represents the number of times an encoder detects a source available.

Display Count

The *Display Count* represents the number of times a decoder detects a display available.

Display Source Change

The *Display Source Change* represents the number of times a decoder has been switched to an encoder.

Network Downtime

The *Network Downtime* represents the time in hours a device is missing off the network.

UI Creator


UI Creator represents usage of various user interface function.

Note: *Analytics* is a licensed required feature. If you do not have access to this option contact your Liberty AV sales rep to upgrade.

Analytics continued.....

Source Availability

The *Source Availability* metric represents the time in hours an encoder has video signal.




1. Select *Source Availability* from the *Select Data* drop-down.
2. Select *Group*.
3. Select *Start Date*.
4. Select *End Date*.
5. Click *Export Report*.

Analytics continued.....

Display Availability

The *Display Availability* metric represents the time in hours a decoder has a monitor connected.




1. Select *Display Availability* from the *Select Data* drop-down.
2. Select *Group*.
3. Select *Start Date*.
4. Select *End Date*.
5. Click *Export Report*.

Analytics continued.....

Source Resolution

The *Source Resolution* metric represents the combination of different resolutions used as a source.




1. Select *Source Resolution* from the *Select Data* drop-down.
2. Select *Group*.
3. Select *Start Date*.
4. Select *End Date*.
5. Click *Export Report*.

Analytics continued.....

Source Count

The *Source Count* metric represents the number of times an encoder detects a source available.




1. Select *Source Count* from the *Select Data* drop-down.
2. Select *Group*.
3. Select *Start Date*.
4. Select *End Date*.
5. Click *Export Report*.

Analytics continued.....

Display Count

The *Display Count* metric represents the number of times a decoder detects a display available.




1. Select *Display Count* from the *Select Data* drop-down.
2. Select *Group*.
3. Select *Start Date*.
4. Select *End Date*.
5. Click *Export Report*.

Analytics continued.....

Display Source Change

The *Display Source Change* metric represents the number of times a decoder has been switched to an encoder.




1. Select *Display Source Change* from the *Select Data* drop-down.
2. Select *Group*.
3. Select *Start Date*.
4. Select *End Date*.
5. Click *Export Report*.

Analytics continued.....

Network Downtime

The *Network Downtime* metric represents the time in hours a device is disconnected from the network.




1. Select *Network Downtime* from the *Select Data* drop-down.
2. Select *Group*.
3. Select *Start Date*.
4. Select *End Date*.
5. Click *Export Report*.

Analytics continued.....

UI Creator


The *UI Creator* metric represents usage of various user interface functions.



1. Select *UI Creator* from the *Select Data* drop-down.
2. Select *User Interface*.
3. Select *Start Date*.
4. Select *End Date*.
5. Click *Export Report*.

Notifications

Notifications will send e-mail alerts whenever a selected event occurs on the system.



1. Select Event.
2. Select *Save*.

Email Settings

Here you configure the e-mail client to allow notification alerts to be sent from a specified e-mail account. The *Test* button sends a confirmation e-mail to confirm the settings are correct.

The screenshot displays the Arranger Digi IP 5000 Series web interface. The top navigation bar includes 'Status', 'Device Settings', 'Matrix', 'Users', 'Groups', 'Multicast', 'Permissions', and 'Security Key'. The 'E-Mail Settings' dialog box is open, showing the following fields:

- To: [Text Input]
- Cc: [Text Input]
- SMTP Server [smtp.xyz.com]: [Text Input]
- From Address [me@xyz.com]: [Text Input]
- Account Username: [Text Input]
- Account Password: [Text Input with toggle icon]
- Authentication: [Dropdown menu showing 'NONE']
- Port [25,465,587...]: [Text Input showing '25']

At the bottom of the dialog box are 'Save' and 'Test' buttons. The background interface shows a list of events with checkboxes for 'System Start', 'System Error', 'Preset Applied', 'User Login Failure', 'Invalid Security', 'Disconnection', 'Video Loss', and 'Display Loss'. A 'Save' button is also visible at the bottom of the event list.

Presets

The system can store a virtually unlimited number of presets. A preset can be applied with a single ***preset load*** command. The preset can contain a virtually unlimited number of commands.

Presets can contain anything from a single command to a video wall layout.

Presets can also contain basic *if else* logic to allow you to build some “smarts” into your system.
Refer to – Preset Logic for further details.

The following preset names cannot be used:

- ‘all’
- ‘all_rx’
- ‘all_tx’
- ‘ungrouped’
- ‘all_devices’
- Any Device name
- Any Group name

Make a New Preset

Here you can create a new preset to be stored on the system. Give the preset a name and then start adding control commands as required by either entering commands directly or using the *Assistant* wizard.

1. Select *New*.
2. Enter a name for the preset.
3. Select a command from the drop-down menu.

Note: Click on the *View Command Manual* link next to the ? for command definitions.

4. *Assistant* is a command wizard that will allow you to easily input the information required for the command in order to render the finished code correctly.

Click on *Assistant* to build the command or enter the command manually in the *Add Control Command* field.

5. Click *Add*.

Notice that the command is now entered into the field labeled *Preset Commands*. If you need to enter in more commands to the preset repeat steps 3-5.

Best practice! When using multiple commands in a preset, add the *preset delay* command to the preset. *Preset delay* will allow you to separate each command execution in a preset in milliseconds.

6. Click *Save* or *Apply* to test the preset.


Edit a Preset

Here you can edit any existing preset by adding, deleting or changing control commands as required.

1. Select *Edit*.
2. Select *Preset*.
3. Click *Load*.
Notice that the commands in the current preset have now populated in the *Preset Commands* field which can be edited manually.
4. Change *preset name*.
5. Select a system command from the *Select Control Command* drop-down menu.
Note: Click on the *View Command Manual* link next to the ? for command definitions.
6. *Assistant* is a command wizard that will allow you to easily input the information required for the command in order to render the finished code correctly.
Click on *Assistant* to build the command or enter the command in manually in the *Add Control Command* field.
7. Click *Add*.
8. Commands can be edited manually here.
9. Click *Save* or *Apply* to test the edited preset.

Delete a Preset


Here you can delete any existing preset from the system.



1. Select *Delete*.
2. Select *Preset*.
3. Click *Delete*.

Apply a Preset

Here you can apply any existing preset on the system.




1. Select *Apply*.
2. Select *Preset*.
3. Click *Apply*.

NOTE: To initiate a *Preset* using API commands use the command ***preset load [PRESET NAME]***.

Export a Preset


Here you can export an existing preset on the system which can then be used as a backup or edited. The preset will be saved to your Downloads folder on your PC as an ini file, example; *preset1.ini*. The export preset can be edited with an application like Notepad++; right click the file and select “Open with...”



1. Select *Apply*.
2. Select *Preset*.
3. Click *Export*.

Export ALL Presets


Here you can export all existing presets on the system which can then be used as a backup or edited. The presets will be saved to your Downloads folder as an exp file:presets.exp.



1. Click *Export All*.

Import a Preset

Here you can import a preset into the system.



1. Select *Import*.

2. Click *Import*.


A pop-up window on your PC will appear; find the appropriate .ini file to import from your PC.

3. Rename the preset if required.

4. Click *Save*.

Import ALL Presets

Here you can import all presets into the system from an all preset export.



1. Select *Import ALL*.

2. Click *Browse*.

A pop-up window on your PC will appear; find the appropriate .exp file to import from your PC.

3. Select *Skip files* or *Replace Files*.

4. Click *Import All*.

QR Code Preset

You can create a QR code to directly execute a preset. After the QR code has been scanned and opened in a browser the preset will be executed and the result displayed in the user's default web browser.

Here you can set how the result of a preset when scanned from a QR code will be displayed on the user's browser. This includes QR code buttons used in UI Creator.

The QR result can be *Text* for a standard API text response. Select *Static Image* to display a user uploaded image on success or failure of the preset. Or, select *User Interface* to be redirected to a *QR Results User Interface*. See *Global Settings > UI Creator > QR Code Result mode* for more information.

The below will provide a text response: *preset load preset1 success*.

1. Select *QR Code*.
2. Select *Preset*.
3. Select *Text* from the *QR Result* drop-down menu.
4. Click *Save* button.
5. Enter *Remote URL* if QR must be accessed over the Internet.
6. Enter *QR Graphics Size*.
7. Click either *Remote or Local QR Code* button.
8. Click *Download* button.

QR Code Preset continued....

The below will provide a static image response:

1. Select *QR Code*.
2. Select *Preset*.
3. Select *Static Image* from the *QR Result* drop-down menu.
4. Select *Success Image*.
5. Select *Error Image*.
6. Click *Save* button.
7. Enter *Remote URL* if QR must be accessed over the Internet.
8. Enter *QR Graphics Size*.
9. Click either *Remote* or *Local QR Code* button.
10. Click *Download* button.

QR Code Preset continued....

The below will provide a QR Results user interface response:

The screenshot shows the 'Presets' configuration page for a QR Code. The interface includes a top navigation bar with tabs like Status, Device Settings, Matrix, Video Wall, Tools, Global Settings, Users, Groups, Multicast, Permissions, Security Keys, Analytics, Notifications, Presets, Scheduler, Events, and UI Creator. The 'Presets' tab is active. The main content area has several dropdown menus and buttons. Red numbers 1 through 9 are overlaid on the interface, pointing to specific elements: 1 points to the 'Select Option' dropdown (set to 'QR Code'), 2 points to the 'Preset' dropdown (set to 'preset1'), 3 points to the 'QR Result' dropdown (set to 'User Interface'), 4 points to the 'Select User Interface' dropdown (set to 'TouchScreen1'), 5 points to the 'Save' button, 6 points to the 'Remote URL' text input field, 7 points to the 'Size' text input field (set to '150'), 8 points to the 'Remote QR Code' and 'Local QR Code' buttons, and 9 points to the 'Download' button. Below the buttons, a QR code is displayed, and below it, the URL 'http://10.8.11.50:80/api/v2/public/preset/qr/preset1/f8f8270dd3127431' is shown, followed by a 'Download' button.

1. Select *QR Code*.
2. Select *Preset*.
3. Select *User Interface* from the *QR Result* drop-down menu.
4. Select *User Interface*.
5. Click *Save* button.
6. Enter *Remote URL* if QR must be accessed over the Internet.
7. Enter *QR Graphics Size*.
8. Click either *Remote* or *Local QR Code* button.
9. Click *Download* button.

Scheduler

The scheduler is used to apply presets at a particular time of a given day or on system start.

1. Enter *Event Name*.
2. Select a time.
3. Select day(s).
4. Select *Preset*.
5. Click *Save*.
6. Once saved, the pen icon is used to edit the event.
7. Click the cross icon to delete the event

Events

Events is a button-less control system to operate a display device such as a TV or projector automatically depending on the source status of a selected encoder. The triggered presets can contain any number of functions to select source, volume and even raise and lower projector screens.

Here you configure presets to be applied controlling a display and other devices when an encoder source becomes available or removed.

Select a *Source Connected* trigger event from an encoder then select a preset to be applied when the encoder source becomes available. You can set the *Repeat Connected Preset* option to apply this preset each time a source is applied or only if the display is off. See example below.

Event Name	Select Encoder	Select Trigger	Select Preset	Disconnect to OFF Delay (min)	OFF to ON Delay (sec)
Display ON	Encoder1	Source Connected	systemOn	0	0

Save

? Enable Repeat Connected Preset to trigger the Source Connected preset each time a source is applied to the Encoder.

1. Enter *Event Name*.
2. Select an encoder.
3. Select *Source Connected* trigger.
4. Select an 'ON' preset.
5. Click *Save*.
6. Set *Repeat Connected Preset* option

Events Continued....

Select a *Source Disconnected* trigger event from an encoder then select a preset to be applied when the encoder source becomes unavailable. The preset will only be applied after the disconnect to OFF delay duration. This event is canceled each time an encoder source becomes available.

The OFF to ON delay will prevent the source connected event for the delay duration.

Global Settings

Events

Repeat Connected Preset: Enabled

Event Name	Select Encoder	Select Trigger	Select Preset	Disconnect to OFF Delay (min)	OFF to ON Delay (sec)	
System Off	Encoder1	Source Disconnected	systemOff	5	5	Save
System On	Encoder1	Source Connected	systemOn	0	0	Delete

? Enable Repeat Connected Preset to trigger the Source Connected preset each time a source is applied to the Encoder.

1. Enter *Event Name*.
2. Select an encoder.
3. Select *Source Disconnected* trigger.
4. Select an 'ON' preset.
5. Select a *Disconnect to OFF* duration.
6. Select an *OFF to ON* duration.
7. Click *Save*


UI Creator

UI Creator can be used instead of a third-party control system to fully control the functions of the system and much more. Here you can design your own user interface (UI) to recall functions that have been saved as presets.

UI Creator lets you create a virtually unlimited number of UI's which can be viewed on any device's supported web browser such as Google Chrome or Safari.

Create a New User Interface

Here you can add a new UI to the system ready to be edited as required. The UI name must be specified along with the UI resolution. A selection of standard-sized displays are available or user can enter their own size from 100x100 to 3820x2160.

The screenshot shows the 'UI Creator' section of a software interface. At the top, there is a navigation bar with tabs: Status, Device Settings, Matrix, Video Wall, Tools, Global Settings, Users, Groups, Multicast, Permissions, Security Keys, Analytics, Notifications, Presets, Scheduler, Events, and UI Creator. The 'UI Creator' tab is active. Below the navigation bar, there is a form to create a new preset. The form has four numbered steps: 1. 'Select Option' with a dropdown menu showing 'Add'. 2. 'Name' with a text input field containing 'MyPreset1'. 3. 'Size' with a dropdown menu showing 'iPad 1/2/3/4 (1024x768)'. 4. A 'Save' button with a user icon. Below the form, there is a question mark icon and the text 'All users will view the UI with the same button states.'.

1. Select *Add*.
2. Enter UI *Name*.
3. Select UI *Size*.
4. Click *Save*.

You can now *edit* this preset to build the UI.

Edit a User Interface

Here you can change the UI name or edit and preview an existing UI on the system. The UI service and login requirements can also be set from here.

1. Select *Edit*.
2. Select UI *Name*.

Edit a User continued.....

Initially only 3 pages are available, *Master*, *Home* and *Login*. The *Master* page is used for elements to be displayed on all other pages that do not have a background set. The *Home* page is the displayed page when the UI is loaded. The *Login* page is displayed when a pin code is required to access the UI. From here you can add and remove pages whenever required.

The screenshot shows the 'UI Creator' interface with the 'Edit' option selected. The left sidebar contains a 'Page' list with 'Master', 'Home', and 'Login' links. A red '1' points to an empty text input field below 'Login'. A red '2' points to the 'Add' button next to it. Below the input field are settings for 'Mode' (Standard), 'Initial Preset', 'Service' (Disabled), 'Maximum Clients' (Unlimited), and 'Login' (NONE). At the bottom are 'Save' and 'Preview' buttons. The main area is a large empty box. The right sidebar shows a 'Grid' dropdown set to 'None' and a 'Drag Elements To Location' section with icons for 'Label', 'Button', 'Image', 'Background Image', and 'Background Colour'. A footer note with a question mark icon states: 'All users will view the UI with the same button states.'

1. Enter new page name
2. Click *Add*

UI Modes


In the highlighted section below is how you will define your UI mode.

There are two modes:

1) Standard - *Standard* mode provides the default pages *Master Page*, *Home Page* and *Login Page*. The *Master Page* is used to display the elements on all other pages without a background applied. The *Home Page* is the initial page to be displayed. The *Login page* is shown when a login code is required. *Standard mode* provides options for limiting the maximum allowed clients and login with fixed or random number with a session timeout.


2) QR Code Result - *QR Code Result* mode provides the default pages *Master*, *Success* and *Error*. The *Master* page is used to display the elements on all other pages without a background applied. The *Success page* is shown after a scanned QR code preset is executed successfully. The *Error page* is shown after a scanned QR Code preset is executed with an error. The resulting user interface can be used to display a single page message or a multipage user interface with the same abilities as standard mode.

See *Global Settings > Presets > QR Code Preset* or more details.



Standard Mode

In the section below a standard configuration has been made.



1. Select *Standard* mode.

2. Select a *Preset* from the Initial Preset drop-down.

The *Initial Preset* is used to select a preset to be executed when the UI service is enabled. This preset can be used to set a default configuration to match the user interface initial button states. The control command **set ui** can be used to toggle the service state.

3. Select *Enable* from *Service* drop-down.

When *Service* is *disabled* the UI will not be able to be accessed by a client.

4. Select a maximum number of control clients that can access the UI simultaneously.

5. Select *Login* option; *NONE*, *Random*, *User defined Login*.

If a pin code to access the user interface is not required then leave the login as *NONE*. The login page will not be used or shown in the case.

6. If the *Random* login code option is selected in Step 5, a random number will be displayed here, this is the login code. If *User Defined option* was selected in Step 5 then you will be able to define the code in this field.

7. A *timeout* can also be applied here when using a login pin code that will prevent the client access after the selected time has elapsed.

8. Click *Save* to save UI or *Preview* to preview your UI in a web browser.

QR Code Result Mode

In the section below a *QR Code Result* configuration has been made.

See *Global Settings > Presets > QR Code Preset* for more information on linking QR Code presets to a QR Code Result UI.

The screenshot displays the 'UI Creator' interface within the 'Global Settings' section. The top navigation bar includes tabs for Status, Device Settings, Matrix, Video Wall, Tools, and Global Settings. The 'Global Settings' tab is active, and the 'UI Creator' sub-tab is selected. The interface is divided into three main areas: a left sidebar, a central canvas, and a right sidebar.

Left Sidebar:

- Select Option:** A dropdown menu set to 'Edit'.
- UI:** A dropdown menu set to 'MyPreset1'.
- Name:** A text input field containing 'MyPreset1'.
- Page:** A section with links for 'Master', 'Success', and 'Error'. Below these links is a text input field and an 'Add' button.
- 1 Mode:** A dropdown menu set to 'QR Code Result'.
- 2 Service:** A dropdown menu set to 'Enabled'.
- Buttons:** 'Save' and 'Preview' buttons.

Central Canvas: A large empty rectangular area for designing the UI.

Right Sidebar:

- Grid:** A dropdown menu set to 'None'.
- Drag Elements To Location:** A section with icons for 'Label', 'Button', and 'Image'.
- Background Image:** A section with a monitor icon and a landscape image.
- Background Colour:** A section with a monitor icon and a color selection area.


Footer: A blue question mark icon followed by the text: 'All users will view the UI with the same button states.'

1. Select *QR Code Result* mode.
2. Select *Enable* from *Service* drop-down.
When *Service* is *disabled* the UI will not be able to be accessed by a client.

Adding Labels

A *label* can be dragged to any location and used as a heading, label or wherever text is required on the UI. The label must be given a name to change the color, text and visibility via the control command ***set ui_label***.

Here we are adding a title for the UI on the *master page* by dragging and dropping the label icon into the UI layout.



Adding Labels continued....

Once a label has been added the *Label Settings* will load to the right of the screen, see highlighted section below.


From here you can edit the text font, size, style, alignment and position, given the label a name or remove it from the UI.

Note: You can always populate the *Label Settings* by clicking on any label in the UI.

The screenshot displays the 'UI Creator' interface within the 'Global Settings' tab. The central workspace shows a canvas with a single label element named 'Label'. To the left, a sidebar contains configuration options for the UI, including 'Select Option' (set to Edit), 'UI' (MyPreset1), 'Name' (MyPreset1), a 'Page' section with links to Master, Home, and Login, and various mode and service settings. To the right, the 'Label Settings' panel is highlighted with a red border. This panel includes fields for position (Left: 424, Top: 61), size (Width: 100, Height: 50), Layer (1), Visibility (True), and Name. It also features a 'Copy Element' section with font settings (Verdana, size 20) and styling options (Bold, Italic, Underline, Text Color, Background Color). The 'Vertical Alignment' is set to Middle, and the 'Text' field contains the label text. A 'Delete' button is located at the bottom of the settings panel. At the bottom of the interface, a note states: '? All users will view the UI with the same button states.'

Adding Buttons


A *button* can be dragged to any location and used as a press button, QR Code or an indicator.



Adding buttons continued....


Once a button has been placed in the UI the *Button Settings* will populate to right of the UI Creator. See highlighted section below.

Note: You can always populate the *Button Settings* by clicking on any button in the UI.



Note: There are two selectable menus in *Button Settings*.

1. Graphical - Will allow you to edit the button size, position, text font, size, style and alignment, or remove the button from the UI altogether.
2. Functional - Allows you to configure the *Preset* triggers once a button has been pressed.




Adding buttons continued....

There are three choices for a button image:

- 1) Use an external pre made button image (External File)
- 2) Use internal Arranger button image (Library)
- 3) Use a static or streamed preview image from the specified endpoint (Preview)


Select an image for the button by selecting either *External File* and browsing your own images or selecting *Library* to choose one from the button library. When selecting an image from the button library, both state 1 and state 2 images will be assigned when required. When using external file, an image must be assigned for each button state.



1. Select *Library*, *External File* or *Preview* from image drop-down.
2. If you select *Library* from Step 1, click *Library* to access the internal library of button graphics. If you select *External File* from Step 1, click *Browse* to access your files on your PC to use as the button graphic. If you choose *Preview* then you will need to select the *Device* and *Function* associated with the preview in the *Graphical* and *Functional Properties*.


Adding buttons continued....

In the examples below, common buttons from the internal graphical library have been used.



Adding buttons continued....


Note: To help align buttons on the UI layout, click on any open and unused space in the UI and select *Grid* type near the top right of UI Creator. The buttons will align with the grid selections you have made. In the example to the right, small grid size has been used.



Multiple elements can be aligned with respect to the first selected element.

Click on the first referenced element to select it, then hold Ctrl while selecting further elements to be aligned. An *Element Alignment & Distribution* panel will then be shown to Align Vertically, Align Horizontally, Distribute Horizontally or Distribute Vertically.

Clicking in white space will deselect selected elements.



Button Logic

A *button* can be configured to operate with 6 different functions as explained here:

1. **Momentary button** - A *Momentary* button will operate in a push-button single-state fashion where a preset is executed once for every press.
2. **Repeat button** - A *Repeat* button will operate in a momentary fashion where only a preset is assigned to state 1 but the preset will be repeated while the button is held down. The preset will be executed as soon as the button is pressed, then there is a configurable repeat delay before repeating begins and a configurable repeating interval which sets the delay time between preset execution.
3. **Toggle button** - A *Toggle* button will operate in a *push on, push off* fashion so a preset can be assigned to both state 1 and state 2. First press of the button executes state 1 preset and puts the button into state 2 showing a state 2 button image. Second press of the button then executes state 2 preset and returns the button back to state 1.
4. **Radio Toggle button (Exclusive Toggle button)** - A *Radio Toggle* group of buttons will operate in an exclusive toggle fashion and must be assigned to a *Button Group*. When you want a group of buttons to work together as radio toggle buttons where only one button of the group can be in state 2 (down), such as a radio station selector or source selection, then define the same button group name for each of those buttons.
5. **Split button** - A *Split* group of buttons will work in a matrix type way whereby buttons are configured as either an encoder button or decoder Button. Encoder buttons will operate as radio (exclusive) toggle buttons so only one can be selected, while the decoder buttons will operate as a toggle button so multiple can be selected.
6. **QR Code Button** - Adds touchless functionality to a touchscreen control panel. A QR code button will operate in a momentarily fashion where only a preset is assigned to state 1 and a QR code replaces the button image. When the QR code is scanned a virtual press of the button is performed.

Button logic options can be accessed and set in the *Functional* menu of *Button Settings* under *Button Type* for the selected button in the UI layout.

The screenshot shows the 'Button Settings' dialog box with the 'Functional' tab selected. The 'Button Type' dropdown menu is open, displaying the following options: Momentary, Toggle, Radio Toggle, Split, Repeat, and QR Code. The 'Momentary' option is currently selected. Other visible fields include 'Name', 'Analytics' (set to Momentary), 'Initial Button State' (set to No Change), 'Preset' (set to None), 'Change Page' (set to None), 'Change Button State', and 'Change Button Image'.

Button Logic - Momentary

A *Momentary* button will operate in a push-button single-state fashion where a preset is executed once for every press.

Select a button in the UI layout to populate the *Button Settings*, then navigate to the *Functional* menu.

Button Settings

Graphical Functional

Name 1

Button Type Momentary 2

Analytics None 3

Initial Button State No Change 4

State 1

Preset None 5

Change Page None 6

Change Button State + 7

Change Button Image + 8

1. Enter a *Name* for the button. A button name is required as a reference for *Analytics* or when manipulating the button from another buttons functionality or via the API. See *Global Settings > Analytics > UI Creator* for reference.
2. Select *Momentary*.
3. Select a button function from the *Analytics* list that best matches the operation of the button.
4. Select *Initial Button State*: This is the initial state of the button when the UI is loaded.
5. Select the *Preset* to be executed on button press.
6. Change Page: This allows you to change to another page.
7. Change Button State: This allows you to change the state of a button.
8. Change Button Image: This allows you to change the image of a button.

Button Logic - Toggle

A *Toggle* button will operate in a push on, push off fashion so a preset can be assigned to both state 1 and state 2. First press of the button executes state 1 preset and puts the button into state 2 showing a state 2 button image. Second press of the button then executes state 2 preset and returns the button back to state 1.

Button Settings

Graphical **Functional**

Name 1

Button Type Toggle 2

Analytics None 3

Initial Button State No Change 4

State 1 **State 2**

Preset None 5

Change Page None 6

Change Button State + 7

Change Button Image + 8

1. Enter a *Name* for the button. A button name is required as a reference for analytics or when manipulating the button from another buttons functionality or via the API. See *Global Settings > Analytics > UI Creator for reference*.
2. Select *Toggle*.
3. Select a button function from the *Analytics* list that best matches the operation of the button.
4. Select *Initial Button State*: This is the initial state of the button when the UI is loaded.
5. State 1 / State 2: These buttons allow you to select the following for each button state:

Preset: Select the preset to be executed on button press.


Change Page: This allows you to change to another page.

Change Button State: This allows you to change the state of a button.

Change Button Image: This allows you to change the image of a button.

Button Logic - Radio Toggle

A *Radio Toggle* group of buttons will operate in an exclusive toggle fashion and must be assigned to a *Button Group*. When you want a group of buttons to work together as radio toggle buttons where only one button of the group can be in state 2 (down), such as a radio station selector or source selection, then define the same button group name for each of those buttons.



Button Settings

Graphical Functional

Name 1

Button Type Radio Toggle 2

Analytics None 3

Button Group 4

* Radio Toggle button needs a Button Group

Initial Button State No Change 5

State 1

Preset None 6

Change Page None 7

Change Button State + 8

Change Button Image + 9

1. Enter a *Name* for the button. A button name is required as a reference for analytics or when manipulating the button from another buttons functionality or via the API. See *Global Settings > Analytics > UI Creator* for reference.
2. Select *Radio Toggle*.
3. Select a button function from the *Analytics* list that best matches the operation of the button.
4. *Button Group*: A group name must be provided to combine individual buttons to function together.
5. Select *Initial Button State*: This is the initial state of the button when the UI is loaded.
6. Select the *Preset* to be executed on button press.
7. *Change Page*: This allows you to change to another page.
8. *Change Button State*: This allows you to change the state of a button.
9. *Change Button Image*: This allows you to change the image of a button.

Button Logic - Split

A *Split* group of buttons will work in a matrix type way whereby buttons are configured as either an *Encoder* button or *Decoder* button. *Encoder* buttons will operate as *Radio* (Exclusive) toggle buttons so only one can be selected, while the *Decoder* buttons will operate as a *Toggle* button so multiple can be selected.

Once a button is configured as an encoder button next the actual encoder to be used is selected. Buttons configured as a decoder button will also have the required decoder selected along with a preset that is executed when the decoder button is pressed.

Special presets have to be created for this decoder button. In the *Preset* assistant you will notice in the device lists “<<Encoder>>” and “<<Decoder>>”. These are the device selections required to create presets for split button functionality. “<<Encoder>>” will be replaced by the selected encoder button and “<<Decoder>>” will be replaced by the selected decoder button.

Preset example:

```
join av <<Encoder>> <<Decoder>>  
set volume <<Decoder>> 0
```

If you need to interact with buttons then a unique name for the button must be specified. The state of the button can then be changed with the functionality settings or via the control command **set ui_button**. The **set ui_button** command can also be used to change the buttons toggle state, enabled state, text or be virtually pressed.

Here you can see the functionality of an encoder split button.

Button Settings

Graphical **Functional**

Name 1

Button Type 2

Analytics 3

Button Group 4

* Split button needs a Button Group

Initial Button State 5

Function 6

Group 7

Select Device 8

State 1

Change Button State 9

Change Button Image 10

1. Enter a *Name* for the button. A button name is required as a reference for analytics or when manipulating the button from another button's functionality or via the API. *See Global Settings > Analytics > UI Creator for reference.*
2. Select *Split*.
3. Select a button function from the *Analytics* list that best matches the operation of the button.
4. Enter *Button Group* name: A group name must be provided to combine individual buttons to function together.
5. Select *Initial Button State*: This is the initial state of the button when the UI is loaded.
6. Function: Select the button to operate the encoder.
7. Group: Allows you to filter the encoders by group.
8. Select Device: Select the required encoder.
9. Change Page: This allows you to change to another page.
10. Change Button State: This allows you to change the state of a button.

Button Logic - Split continued....

Here you can see the functionality of a decoder split button.

Button Settings

Graphical **Functional**

Name **1**

Button Type **2**

Analytics **3**

Button Group **4**

* Split button needs a Button Group

Initial Button State **5**

Function **6**

Group **7**

Select Device **8**

State 1 **State 2**

Preset

Change Button State **9**

Change Button Image **10**

1. Enter a *Name* for the button. A button name is required as a reference for analytics or when manipulating the button from another button's functionality or via the API. *See Global Settings > Analytics > UI Creator for reference.*
2. Select *Split*.
3. Select a button function from the analytics list that best matches the operation of the button.
4. Enter *Button Group* name: A group name must be provided to combine individual buttons to function together.
5. Select *Initial Button State*: This is the initial state of the button when the UI is loaded.
6. Function: Select the button to operate the decoder.
7. Group: Allows you to filter the decoders by group.
8. Select Device: Select the required decoder.
9. State 1 / State 2: These buttons allow you to select the following for each button state:

Preset: Select the preset to be executed on button press.

Change Button State: This allows you to change the state of a button.

Change Button Image: This allows you to change the image of a button.

Button Logic - Repeat

A *Repeat* button will operate in a momentary fashion where only a preset is assigned to state 1 but the preset will be repeated while the button is held down. The preset will be executed as soon as the button is pressed, then there is a configurable repeat delay before repeating begins and a configurable repeating interval which sets the delay time between preset execution.

Button Settings

Graphical Functional

Name

Button Type Repeat

Analytics None

Initial Button State No Change

☐ Continue On Error

Repeating Interval 100 1000

Repeat Delay 500 1000 2000

State 1

Preset None

Change Page None

Change Button State

Change Button Image

1. Enter a *Name* for the button. A button name is required as a reference for analytics or when manipulating the button from another button's functionality or via the API. See *Global Settings > Analytics > UI Creator* for reference.
2. Select *Repeat*.
3. Select a button function from the *Analytics* list that best matches the operation of the button.
4. Select *Initial Button State*: This is the initial state of the button when the UI is loaded.
5. Continue On Error: This is an option to continue executing the preset if it returns failed.
6. Repeating Interval: This is the time delay in milliseconds the button preset repeats while being held down.
7. Repeat Delay: This is the time in milliseconds the button must remain held down before the preset starts repeating.
8. Preset: Select the preset to be executed on button press.
9. Change Page: This allows you to change to another page.
10. Change Button State: This allows you to change the state of a button.
11. Change Button Image: This allows you to change the image of a button.

Button Logic - QR Code

Adds touchless functionality to a touchscreen control panel. A *QR Code* button will operate in a momentary fashion where only a preset is assigned to state 1 and a QR code replaces the button image. When the QR code is scanned a virtual press of the button is performed.

Button Settings

Graphical Functional

Name **1**

Button Type QR Code **2**

Analytics None **3**

External URL **4**

State 1 **5**

Preset

None **6**

Change Page

None **7**

Change Button State **7**


Change Button Image **8**

1. Enter a *Name* for the button. A button name is required as a reference for analytics or when manipulating the button from another button's functionality or via the API. *See Global Settings > Analytics > UI Creator for reference.*
2. Select *Repeat*.
3. Select a button function from the *Analytics* list that best matches the operation of the button.
4. External URL: Enter the controller's external URL if working outside of the local network.
5. Preset: Select the preset to be executed on button press.
6. Change Page: This allows you to change to another page.
7. Change Button State: This allows you to change the state of a button.
8. Change Button Image: This allows you to change the image of a button.

Adding an Image

An *Image* can be dragged to any location then resized by dragging the image placeholder or changing the image settings directly. The selected image will be resized to fit the size of the image placeholder. It is recommended to use only the same sized images as the size being displayed.


The image must be given a name to change the visibility via the control command **set ui_image**.



Adding an Image continued....

Once an image has been placed in the UI the *Image Settings* will populate to right of the UI Creator. Image settings gives you the ability to size and name the image as required. See highlighted section below.


Note: You can always populate the *Image Settings* by clicking on any image in the UI.



To select an image from your PC, select the *Image > Browse* button to browse local folders on your PC.


Adding an Image continued....

Here a logo image has now been assigned.



Copying and Pasting Elements


Any button label or image can be copied and pasted onto the UI. You copy the style, size or the element exactly.



1. Click on any button, label or image element in the UI.
2. Click *Copy Element*, then choose what copy type and click *Copy*.

Copying and Pasting continued.....


Once an element has been copied, you will now see in the upper right-hand corner of the UI Creator an icon that says *Paste Element*. Click this icon to paste the copy type selection into the UI.



Adding a Background

Either an image or solid color can be selected for the page background. Applying a background on the *Master Page* will be seen on all other pages without a background. Applying a background to any other page than the *Master Page* will hide the *Master Page* altogether.


Click the *Background Image* icon to the right of UI creator to browse your local folders on your PC for a background image to use as a background.




If a solid color for the background is required then select the *Background Color* icon and select a color from the pop-up color picker.

Adding a Background continued.....

Here a background image has been applied to the *Master Page*.



Here a background color has been applied to the *Master Page*.



Duplicate a User Interface

Here you can duplicate an existing user interface to be used as a backup or duplicated from a template file that can then be edited.

The screenshot shows the 'UI Creator' tab in the top navigation bar. Below it, a secondary navigation bar contains tabs for 'Users', 'Groups', 'Multicast', 'Permissions', 'Security Keys', 'Analytics', 'Notifications', 'Presets', 'Scheduler', 'Events', and 'UI Creator'. The main content area has a 'Select Option' dropdown menu with 'Duplicate' selected, a 'UI' dropdown menu with 'MyPreset1' selected, and a 'Name' text input field. A blue 'Save' button is at the bottom left. Red numbers 1, 2, 3, and 4 are placed next to the 'Select Option', 'UI', 'Name', and 'Save' elements respectively. A blue question mark icon and a note are also visible.

1. Select *Duplicate*.

2. Select *UI*.


3. Enter name of duplicate UI.

4. Click *Save*.

1. Select *Duplicate*.
2. Select *UI*.
3. Enter name of duplicate UI.
4. Click *Save*.

Delete a User Interface

To delete an existing UI select option *Delete*, select the user interface and then click the delete button.



1. Select *Delete*.
2. Select *UI*.
3. Click *Save*.

Generating a Local UI QR Code and URL

QR codes and URL links can be generated and downloaded to easily create the URL required to browse to the *User Interface* webpage. The size of the QR code can be set between 100 – 2000px.

The screenshot shows the 'UI Creator' tab in the top navigation bar. On the left, there are four numbered steps: 1. 'Select Option' with a dropdown menu set to 'Generate QR Code'; 2. 'UI' with a dropdown menu set to 'MyPreset1'; 3. 'Remote URL' with an empty text input field; and 4. 'Size' with a text input field set to '150'. Below these are two buttons: 'Remote QR Code' and 'Local QR Code'. On the right, a QR code is displayed with the URL 'http://10.8.11.50:80/controlui/#/MyPreset1' underneath it. A 'Download' button is located below the URL. A red number '5' is placed next to the 'Download' button. At the bottom, there is a blue question mark icon and the text 'All users will view the UI with the same button states.'

1. Select *Generate QR Code*.
2. Select *UI*.
3. Enter QR code *Size*.
4. Click *Local QR Code*.
5. Click *Download*.

The URL for the UI is displayed under the QR code.

Generating a Remote UI QR Code and URL

To browse to the UI via an external URL enter the details in the external URL box and select remote QR code. The size of the QR code image can be changed then downloaded to be used in manuals or printed as required.

The screenshot shows the 'UI Creator' tab in the top navigation bar. The main content area has a left sidebar with form fields and a right section for the QR code and URL. Red numbers 1 through 6 are overlaid on the interface to indicate the sequence of steps:

- 1**: Select 'Generate QR Code' from the 'Select Option' dropdown.
- 2**: Select 'MyPreset1' from the 'UI' dropdown.
- 3**: Enter 'remote.url' in the 'Remote URL' text box.
- 4**: Enter '150' in the 'Size' text box.
- 5**: Click the 'Remote QR Code' button.
- 6**: Click the 'Download' button.

The right section displays a QR code, the URL `http://remote.url/controlui/#/MyPreset1`, and a 'Download' button. A note at the bottom states: '? All users will view the UI with the same button states.'


1. Select *Generate QR Code*.
2. Select *UI*.
3. Enter *Remote URL*.
4. Enter QR code *Size*.
5. Click *Remote QR Code*.
6. **Click** *Download*.

The URL for the UI is displayed under the QR code.

Exporting / Importing User Interface

To keep a backup of your UI work select *Export / Import* then click the *Export* button.

A *.exp file will be saved to your downloads folder.




1. Select *Export / Import*.
2. Select *UI*.
3. Click *Export* to export .exp file to your Downloads folder.

OR

Click *Import* to import an .exp file from your local PC.

System / Controller Settings

All the controller's system level settings can be accessed by admin level users via drop-down menu by clicking the gear icon on the top right of the Arranger software banner.




Network Settings

Single Network Mode

NOTE: By default the Arranger controller operates in *Single Network Mode*. Connect the RJ45 connection of the Arranger controller directly to the AV LAN for this operation. See next page for *Dual Network Mode*.

Here you can change the network configuration of the Arranger controller. This address must be set in the same range as the encoders and decoders. By default the Arranger controller will be found at 169.254.1.1. To locate the IP address of the Arranger controller at any time, connect the HDMI output of the controller into any display; the IP address will show on the on-screen display upper left-hand corner.



1. Select *Network Settings*.
2. DHCP - check this box if you want the IP address for the controller to be set automatically by a third-party router or DHCP server.
3. If using a static IP address simply enter the static address, subnet, gateway and name of hostname if required.
4. Click *Save and Restart*.
5. Click *Load Default* to reset device to the factory default IP address of 169.254.1.1.

Network Settings continued.....

Dual Network Mode

When using *Dual Network Mode* you can use the Arranger controller to bridge a Client or primary LAN to access or control the AV LAN without converging the two networks. This allows for a physical dedicated network for the AV components so multicast doesn't have to be managed on the Client or primary LAN.

A USB to Gigabit Ethernet NIC Network Adapter can be attached to the controller providing a second dedicated AV Endpoint network. Approved adapters include Insignia NS-PU98505, Tripp-Lite U236-000-GBW and Cable Matters 202013.


The controllers NIC (RJ45) can be dedicated to Client LAN Communication while the secondary NIC (USB) is dedicated to Digi IP endpoint communication / subnet. Peripheral TCP devices can be controlled from either.

By default the Arranger Controller will be found on the primary NIC (RJ45) at 192.168.1.1 while maintaining 169.254.1.1 IP for the Digi IP LAN via USB / Ethernet adapter.

NOTE: Only a static IP address can be applied to the secondary NIC, the primary NIC also supports DHCP.


All Digi IP Endpoints must be connected to secondary NIC and set in the same IP range.

1. Power on the Arranger Controller and wait for at least 1 minute before continuing.
2. Plug the USB to Gigabit Ethernet NIC Network Adapter into a USB port of the controller.
3. Perform a Factory Reset: Insert a USB key into the Arranger controller with ONLY a text file titled *factoryreset.txt* for 10 seconds, then remove the USB key.
4. Browse to the controllers default IP address at 192.168.1.1 and configure the controllers network by navigating to 1) the settings icon on Arranger 2) choose Network Settings from drop down menu



Advanced Settings

The *Advanced Settings* section contains the timing, leave subscriptions and Telnet port restriction settings of the controller.




Advanced Settings continued.....

1. Select *Advanced Settings*
2. **Device Data Refresh** - *Device Data Refresh* is the time in milliseconds the Arranger Controller requests information about the encoders and decoders. This keeps the UI up-to-date with any changes that have occurred that do not cause an event which would automatically update data. The default is 60000 = 60 seconds with a range of 10000 – 120000.
3. **Leave Subscriptions on System Start** - *Leave Subscriptions* on system start is an optional condition of the system whereby all decoders will leave their assigned encoder subscription when the system starts. The default is disabled.
4. **Telnet Port 6980 Connection limitation** - Here you can set the number of simultaneous connections to the Telnet TCP control port 6980 to unlimited or from 1 to 10 connections.
5. **Serial Timeout** - *Serial Timeout* is the maximum time in milliseconds the Arranger Controller will wait for a response from a RS232 serial controlled device. The default is 3000 = 3 seconds with a range of 1000 – 30000.
6. **TCP Timeout** - *TCP Timeout* is the maximum time in milliseconds the Arranger controller will wait for a response from a TCP-controlled device. The default is 3000 = 3 seconds with a range of 1000 – 30000.
7. **Global Cache Timeout** - *Global Cache Timeout* is the maximum time in milliseconds the Arranger controller will wait for a response from a Global Cache device. The default is 5000 = 5 seconds with a range of 1000 – 30000.
8. **Static Preview Image Override** - *Static Preview Image Override* enables the use of static JPG preview images rather than a MJPEG stream provided by the endpoints. A stream requires a direct connection to the endpoint which is not always possible when the client side is working over a remote URL or different subnet. Using static images instead overcomes this issue by caching the images on the server and pushing them out to clients.
9. **Static Preview Image Interval** - *Static Preview Image Interval* used with *Static Preview Image Override* is the interval in seconds the preview images are updated client side. The default is 10, with selectable 5, 10, 20, 30, 60 second intervals.
10. Click **Save**.

Export Settings


Export Settings will save a file named UIsettings.exp to your downloads folder. This file contains all the settings of the Arranger controller. Use this exported file as a configuration backup that can be imported back into the system to restore the current configuration.



1. Select *Export Settings*.
2. Click *Export Settings*.

Import Settings


Use Import Settings to load an exported Uisettings.exp file which will restore the Arranger controller's settings.



1. Select *Import Settings*.
2. Click *Import Settings*.


System Clock

The Arranger controller contains a RTC (Real Time Clock) to maintain the correct time and date. Set your local time and date here and click the Save button to apply the changes. The system clock is used for the scheduler and also time stamping the log entries.




System Reboot

Here you can reboot the Arranger controller. It takes 90 seconds for the controller to reboot.




System Logs

The system keeps a log of all system activities. The level of logged information can be set from the Log Level selection. Click the *Export* button to export the log. A file named softwareLog.exp will be saved to your downloads folder. This file has zip compression.




License

The Arranger controller will not operate without a valid license. When the Arranger controller is used for the first time you will be prompted to enter a license key. If a license key has already been issued it can be entered into the system from here. Contact your Liberty AV sales rep or distributor for all licensing requirements.




Software Version

Here you can find the current software version.



Check for Updates


Check for Updates will contact an ftp server over the Internet to obtain the latest releases.



Import Updates

When no Internet access is available or a specific update is required, the files will be provided to manually update the system.

Select the type of update being performed by either selecting Software, Encoder or Decoder. Then click the browse button to select the required file from the file dialog pop-up.



Security Features

The Arranger software has many security features built in which will be described in detail below. Some of these features are optional and can be enabled or disabled depending on your system security requirements.

1. Required security key with all HTTP requests

The API of the system is accessible via HTTP PUT & GET requests which are protected with the addition of a security key that must be passed with each request.

The security key is accessible from the Global Settings – Security Keys tab.

2. Optional security key with all TCP commands

The API of the system is accessible via TCP port 6980 which can be optionally protected with a security key that must be passed with each command.

The security key is accessible from the Global Settings – Security Keys tab.

3. Leave Subscriptions on new Decoder detection

Without this feature there is a possibility that connecting a decoder to the network could receive video and audio if already subscribed (joined) to a used encoder's multicast address.

To eliminate this possibility any newly discovered decoder will be issued a leave-all command which will cause the decoder to leave all video and audio subscriptions (remove joins). This feature is active only after system start and connected encoders and decoders are detected.

4. Leave Subscriptions on System Start

This is an optional feature which can be enabled or disabled from the Settings – Advanced Settings tab.

Without this feature all decoders will still be subscribed (joined) to the same encoders as before the system was powered off.

Some systems will be required to power on in the same state with the same joins as when powered off, while other situations this could be a security risk.

To eliminate this possibility when the feature is enabled a leave-all command will be sent to all decoders automatically on system start.

5. Permissions

Permissions has the ability to only allow certain encoders to be joined with certain decoders.

Example: Encoder1 is only allowed to be joined with Decoder1, and Encoder2 can be joined with any decoder except for Decoder2. Multiple conditions can be applied.

6. User Login Failure

This is an optional feature that is part of the system *Notifications* functions available from the Global Settings – *Notifications* tab.

An email can be sent after three (3) failed login attempts to the system.

7. Limiting simultaneous TCP connections to control port 6980

By default there is no limitation to the number of simultaneous TCP connections to control port 6980.

The number of simultaneous TCP connections can be limited between 1 and 10 from the UI Settings *Advanced* tab *Connections Limit*.

How to HTTP Request

- GET = `http://<controllerURL>/api/command/<ARRANGER_API_COMMAND>/<KEY>`
- POST = `http://<controllerURL>/api/command/{'cmd': '<ARRANGER_API_COMMAND>', 'key': '<KEY>'}`

Example 1 - POST - ajax

```
<script language='JavaScript' type='text/javascript'>

var controllerIP = '169.254.1.1'; *change this to the same IP address as the
controller var BaseURL = 'http://' + controllerIP + '/api/command/';
var MAXIMUM_WAITING_TIME = 5000; *timeout in milliseconds
var CheckStatusTimer; var key = '123xyz'; *replace this with the generated
security key var command = '123xyz'; *replace with any Arranger API command

$.ajax({
  type: 'POST',
  crossDomain: true,
  contentType: 'application/json; charset=utf-8',
  dataType: 'text',
  url: BaseURL, data: "{ 'cmd': ' + command + ', 'key': ' + key + ' }",
  timeout: MAXIMUM_WAITING_TIME,
  success: function(data, textStatus, XMLHttpRequest){
    console.log(data);
  },

  error: function (XMLHttpRequest, textStatus, errorThrown) {
    console.log('ERROR = ' + errorThrown;
  }
});

</script>
```

Example 2 - POST - xhr

```
<script language='JavaScript' type='text/javascript'>

var controllerIP = '169.254.1.1'; *change this to the same IP address as the
controller
var BaseURL = 'http:// ' + controllerIP + '/api/command/';
var key = '123xyz'; *replace this with the generated security key
var command = '123xyz'; *replace with any Arranger API command
var xmlRequest = new XMLHttpRequest(); xmlRequest.open('POST', BaseURL,
true);
var params = "{ 'cmd':' +command+ ', 'key':' + key + ' }";
var MAXIMUM_WAITING_TIME = 5000;
xmlRequest.onreadystatechange = function () {

    if (this.readyState == 4) {
        clearTimeout(xmlTimer);
        if(this.status == 200){
            console.log(this.responseText);

        }else{
            console.log('ERROR = ' + this.status + ' ' + this.statusText);
        }
    }else{
        if(this.status != 200){
            console.log('ERROR = ' + this.status + ' ' + this.statusText);
        }
    };
xmlRequest.send(params);
var xmlTimer = setTimeout(function() {
    xmlRequest.abort();
    console.log('ERROR = timeout');
}, MAXIMUM_WAITING_TIME);

</script>
```

Preset Logic

Basic **if else** logic can be applied within a preset to allow you to build some smarts into your system. All get commands can be used as an expression.

The following syntax applies:

```
if (something) {
    do_something
    ...
} else {
    do_this_instead
    ...
}
```

The following get commands will return a string value that can be used with:

- == (equal to)
- != (not equal to)

```
o get audio_source
o get devices
o get edid
o get scaler <encoder_device_name> all
o get status
o get var
o get ver
o get video <encoder_device_name> all
o get encoder
```

Example 1:

```
if (get encoder Decoder1 == Encoder1) {
    join all Encoder2 Decoder1
} else {
    join all Encoder1 Decoder2
}
```

Example 2:

```
if (get audio_source Decoder1 != hdmi) {
    set audio_source Decoder1 hdmi
}
```

The following **get** commands will return an integer value that can be used with:

- `==` (equal to)
- `!=` (not equal to)
- `<` (less than)
- `>` (greater than)

```
o get frame_converter
o get preferred
o get rotation
o get scaler <encoder_device_name> width
o get scaler <encoder_device_name> height
o get scaler <encoder_device_name> fps
o get video <encoder_device_name> width
o get video <encoder_device_name> height
o get video <encoder_device_name> fps
o get video <encoder_device_name> sm
o get video quality
o get volume
```

Example:

```
if (get rotation Encoder1 != 0) {
    set rotation Encoder1 0
} else {
    join all Encoder1 Decoder1
}
```

The following **get** commands will return a boolean value that can be used with:

- `!` (not)

```
o get display_status
o get var
o get video_mute
o get video_status
o get ui_button
```

Example 1:

```
if (get video_status Encoder1) {
    join all Encoder1 Decoder1
} else {
    if (get video_status Encoder2) {
        join all Encoder2 Decoder1
    }
}
```

Example 2:

```
if !(get video_status Encoder1) {
    join all Encoder2 Decoder1
}
```

Using Google Assistant

The Arranger controller can be controlled with voice commands via Google Assistant. In this example we will run through the requirements to do so. An IFTTT account will also be required. Visit www.ifttt.com for more information.

To find out how to link your Google account with IFTTT visit this Google help page.


<https://support.google.com/googlenest/answer/7194656>

First step is to set up the Arranger controller so it is accessible from the Internet. Port 80 of the Arranger controller will need to be port-forwarded to an external IP port. For this example we are going to use an external IP address of 123.456.789.100 and a controller IP address of 169.254.1.1. From your router, port forward from internal 169.254.1.1 port 80 to external, say port 9999 (you can use any unused port number here). Every router is configured differently, so consult your router's owner's manual if required.


Now externally you should be able to access the Arranger controller's webpage by entering '123.456.789.100:9999' into a browser.

Now we can set up IFTTT to activate any command on the Arranger controller but we strongly advise that Arranger *Presets* only are specified for this activity.

Open your IFTTT account
and *Create* a new applet




Click *if This Add*




Using Google Assistant continued....


Search and select *Google Assistant* when asked to choose a service in the IFTTT applet wizard




You will be prompted for your Google account login, click *Connect* to proceed



Choose the *Say a Simple Phrase* when asked for a trigger




Choose what you will say, the Google response and click *Create Trigger*




Using Google Assistant continued....


Click *Then That* Add




You will be prompted to connect to *Webhooks* click *Connect* to proceed



Search and choose *Webhooks* when asked for a service



Click *Make a web request*



Using Google Assistant continued....

- Now enter the URL which is the external IP address and port established in the router. In our previous example; '123.456.789.100:9999'
- Select Method: 'POST'
- Select Content Type: 'application/json'
- Enter Body with desired command (see below)
- Click 'Create action'

```
{"cmd":"<command>","key":"<security_key>"}
```

```
=
```

```
{"cmd":"preset load <preset>","key":"<security_key>"}
```

where:

*<preset> = Name given to the preset to be applied

^<security_key> = HTTP Security key

Example:

```
{"cmd":"preset load MyPreset","key":"ts2Xe1sn1Nk1rm1>l1$P1Tk18q14e"}
```

*For more information on building and using Presets, see
Global Settings > Presets

^For more information on generating and using HTTP Security keys, see
Global Settings > Security Keys > HTTP Security Key

Using Command Assistant

When dealing with direct API control commands or creating presets, the *Command Assistant* wizard is available for all commands to help make the construction of command strings as simple as possible.

Most commands have a *Normal* and *Wizard* mode of creation. In *Normal* mode most parameters are set by entering the details into the various text boxes manually, while in *Wizard* mode parameters are mostly set with drop-down selections to ensure the syntax of the command is correct.

Below are explanations for all commands using *Normal* and *Wizard* mode.

Command: join all - Normal Mode

Parameters

1. Enter optional Security Key
 2. Enter Encoder Device Name
 3. Enter Decoder or Group name
 4. Select Exclusive (optional)
 5. Select Video Mode (optional)
 6. Click Finish button

Select Mode
☐ Wizard
☒ Normal

Security Key (optional) 1

Encoder Device Name 2

Decoder / Group 3

Exclusive (optional) 4 ☐

Video Mode 5

6

Command: join all - Wizard Mode

Parameters

1. Select Encoder Device Name
 2.a Select Device(s)
 2.b Select Decoder or Group name
 3. Select Exclusive (optional)
 4. Select Video Mode (optional)
 5. Click Finish button

Select Mode
☒ Wizard
☐ Normal

Security Key (optional)

Encoder Device Name 1

Select
 2a ☒ Decoder Device Name
☐ Group Name
☐ All
 2b

Exclusive (optional) 3 ☐

Video Mode 4

5

Command: join av - Normal Mode

Parameters

1. Enter optional Security Key
2. Enter Encoder Device Name
3. Enter Decoder or Group name
4. Select Exclusive (optional)
5. Select Video Mode (optional)
6. Click Finish button

Select Mode
☐ Wizard
☒ Normal

Security Key (optional) 1

Encoder Device Name 2

Decoder / Group 3

Exclusive (optional) 4
☐

Video Mode 5
No Change

6

Command: join av - Wizard Mode

Parameters

1. Select Encoder Device Name
2.a Select Device(s)
2.b Select Decoder or Group name
3. Select Exclusive (optional)
4. Select Video Mode (optional)
5. Click Finish button

Select Mode
☒ Wizard
☐ Normal

Security Key (optional)
31333331306339326330373066613065

Encoder Device Name 1

Select
2a
☒ Decoder Device Name
☐ Group Name
☐ All

2b

Exclusive (optional) 3
☐

Video Mode 4
No Change

5

Command: join video - Normal Mode

Parameters

1. Enter optional Security Key
2. Enter Encoder Device Name
3. Enter Decoder or Group name
4. Select Exclusive (optional)
5. Select Video Mode (optional)
6. Click Finish button

Select Mode
☐ Wizard
☒ Normal

Security Key (optional) 1

Encoder Device Name 2

Decoder / Group 3

Exclusive (optional) 4 ☐

Video Mode 5 No Change

6

Command: join video - Wizard Mode

Parameters

1. Select Encoder Device Name
2.a Select Device(s)
2.b Select Decoder or Group name
3. Select Exclusive (optional)
4. Select Video Mode (optional)
5. Click Finish button

Select Mode
☒ Wizard
☐ Normal

Security Key (optional) 31333331306339326330373066613065

Encoder Device Name 1

Select
2a ☒ Decoder Device Name
☐ Group Name
☐ All

2b

Exclusive (optional) 3 ☐

Video Mode 4 No Change

5

Command: join audio - Normal Mode

Parameters

1. Enter optional Security Key
2. Enter Encoder Device Name
3. Enter Decoder or Group name
4. Select Exclusive (optional)
5. Click Finish button

Select Mode
☐ Wizard
☒ Normal

Security Key (optional) 1

Encoder Device Name 2

Decoder / Group 3

Exclusive (optional) 4
☐

5

Command: join audio - Wizard Mode

Parameters

1. Select Encoder Device Name
2.a Select Device(s)
2.b Select Decoder or Group name
3. Select Exclusive (optional)
4. Click Finish button

Select Mode
☒ Wizard
☐ Normal

Security Key (optional) 31333331306339326330373066613065

Encoder Device Name 1

Select
2a
☒ Decoder Device Name
☐ Group Name
☐ All

2b

Exclusive (optional) 3
☐

4

Command: join serial - Normal Mode

Parameters ✕

1. Enter optional Security Key
 2. Enter Encoder Device Name
 3. Enter Decoder or Group name
 4. Select Exclusive (optional)
 5. Click Finish button

Select Mode ☐ Wizard
☒ Normal

Security Key (optional) **1**

Encoder Device Name **2**

Decoder / Group **3**

Exclusive (optional) **4** ☐

5

Command: join serial - Wizard Mode

Parameters ✕

1. Select Encoder Device Name
 2.a Select Device(s)
 2.a Select Decoder or Group name
 3. Select Exclusive (optional)
 4. Click Finish button

Select Mode ☒ Wizard
☐ Normal

Security Key (optional)

Encoder Device Name **1**

Select **2a** ☒ Decoder Device Name
☐ Group Name
☐ All

2b

Exclusive (optional) **3** ☐

4

Note: Only devices in serial *Matrix* mode will be seen in the device lists. To change serial modes see *Devices Settings > RS232 Serial*.

Command: join ir - Normal Mode

Parameters

1. Enter optional Security Key
2. Enter Encoder Device Name
3. Enter Decoder or Group name
4. Select Exclusive (optional)
5. Click Finish button

Select Mode
☐ Wizard
☒ Normal

Security Key (optional) 1

Encoder Device Name 2

Decoder / Group 3

Exclusive (optional) 4
☐

5

Command: join ir - Wizard Mode

Parameters

1. Select Encoder Device Name
2.a Select Device(s)
2.b Select Decoder or Group name
3. Select Exclusive (optional)
4. Click Finish button

Select Mode
☒ Wizard
☐ Normal

Security Key (optional) 31333331306339326330373066613065

Encoder Device Name 1

Select
2a
☒ Decoder Device Name
☐ Group Name
☐ All

2b

Exclusive (optional) 3
☐

4

Command: join usb - Normal Mode

Parameters ×

1. Enter optional Security Key
2. Enter Encoder Device Name
3. Enter Decoder or Group name
4. Select Exclusive (optional)
5. Click Finish button

Select Mode ☐ Wizard
☒ Normal

Security Key (optional) **1**

Encoder Device Name **2**

Decoder / Group **3**

Exclusive (optional) **4** ☐

5

Command: join usb - Wizard Mode

Parameters ×

1. Select Encoder Device Name
2.a Select Device(s)
2.a Select Decoder or Group name
3. Select Exclusive (optional)
4. Click Finish button

Select Mode ☒ Wizard
☐ Normal

Security Key (optional)

Encoder Device Name **1**

Select **2a** ☒ Decoder Device Name
☐ Group Name
☐ All

2b

Exclusive (optional) **3** ☐

4

Command: join kvm - Normal Mode

Parameters

1. Enter optional Security Key
2. Enter Encoder Device Name
3. Enter Decoder or Group name
4. Select Exclusive (optional)
5. Select Video Mode (optional)
6. Click Finish button

Select Mode
☐ Wizard
☒ Normal

Security Key (optional) 1

Encoder Device Name 2

Decoder / Group 3

Exclusive (optional) 4
☐

Video Mode 5 No Change

6

Command: join kvm - Wizard Mode

Parameters

1. Select Encoder Device Name
2.a Select Device(s)
2.b Select Decoder or Group name
3. Select Exclusive (optional)
4. Select Video Mode (optional)
5. Click Finish button

Select Mode
☒ Wizard
☐ Normal

Security Key (optional) 1

Encoder Device Name

Select
2a ☒ Decoder Device Name
☐ Group Name
☐ All

2b

Exclusive (optional) 3
☐

Video Mode 4 No Change

5

Command: join wall - Normal Mode

Parameters

1. Enter optional Security Key
2. Enter Encoder Device Name
3. Enter Decoder Device Name
4. Select Wall Type
eg 2x2
5. Select Display Position
6. Optionally change display resolution and framerate
6.a Enter Resolution Width
6.b Enter Resolution Height
6.c Enter Framerate
7. Optionally apply bezel compensation
7.a Enter Display Width
7.b Enter Viewable Height
7.c Enter Display Height
7.d Enter Viewable Height
8. Click Finish button

Select Mode
☐ Wizard
☒ Normal

Security Key (optional) 1

Encoder Device Name 2

Decoder Device Name 3

Wall Type 4

Display Position 5

Width (optional) 6a

Height (optional) 6b

Frame Rate (optional) 6c

Display Width (mm) (optional) 7a

Viewable Width (mm) (optional) 7b

Display Height (mm) (optional) 7c

Viewable Height (mm) (optional) 7d

8

Command: join wall - Wizard Mode

Parameters

1. Select Encoder Device Name
2. Select Decoder Device Name
3. Select Wall Type
eg 2x2
4. Select Display Position
5. Select Video Mode
6. Optionally apply bezel compensation
6.a Enter Display Width
6.b Enter Viewable Height
6.c Enter Display Height
6.d Enter Viewable Height
7. Click Finish button

Select Mode
☒ Wizard
☐ Normal

Security Key (optional) 31333331306339326330373066613065

Encoder Device Name 1

Decoder Device Name 2

Wall Type 3

Display Position 4

Video Mode (optional) 5

Display Width (mm) (optional) 6a

Viewable Width (mm) (optional) 6b

Display Height (mm) (optional) 6c

Viewable Height (mm) (optional) 6d

7

Command: leave all - Normal Mode

1. Enter optional Security Key
2. Enter Decoder or Group name
3. Click Finish button

Select Mode
☐ Wizard
☒ Normal

Security Key (optional) **1**

Decoder / Group **2**

3

Command: leave all - Wizard Mode

1.a Select Device(s)
1.b Select Decoder or Group name
2. Click Finish button

Select Mode
☒ Wizard
☐ Normal

Security Key (optional)

Select
☒ Decoder Device Name
☐ Group Name
☐ All

1a

1b

2

Command: leave av - Normal Mode

1. Enter optional Security Key
2. Enter Decoder or Group name
3. Click Finish button

Select Mode
☐ Wizard
☒ Normal

Security Key (optional) **1**

Decoder / Group **2**

3

Command: leave av - Wizard Mode

1.a Select Device(s)
1.b Select Decoder or Group name
2. Click Finish button

Select Mode
☒ Wizard
☐ Normal

Security Key (optional)

Select
☒ Decoder Device Name
☐ Group Name
☐ All

1a

1b

2

Command: leave video - Normal Mode

Parameters ×

1. Enter optional Security Key

2. Enter Decoder or Group name

3. Click Finish button

Select Mode

☐ Wizard

☒ Normal

Security Key (optional) **1**

Decoder / Group **2**

3

Command: leave video - Wizard Mode

Parameters ×

1.a Select Device(s)

1.b Select Decoder or Group name

2. Click Finish button

Select Mode

☒ Wizard

☐ Normal

Security Key (optional)

31333331306339326330373066613065

Select

1a ☒ Decoder Device Name

1b ☐ Group Name

☐ All

2

Command: leave audio - Normal Mode

Parameters ×

1. Enter optional Security Key

2. Enter Decoder or Group name

3. Click Finish button

Select Mode

☐ Wizard

☒ Normal

Security Key (optional) **1**

Decoder / Group **2**

3

Command: leave audio - Wizard Mode

Parameters ×

1.a Select Device(s)

1.b Select Decoder or Group name

2. Click Finish button

Select Mode

☒ Wizard

☐ Normal

Security Key (optional)

31333331306339326330373066613065

Select

1a ☒ Decoder Device Name

1b ☐ Group Name

☐ All

2

Command: leave serial - Normal Mode

Parameters

1. Enter optional Security Key
2. Enter Decoder or Group name
3. Click Finish button

Select Mode
☐ Wizard
☒ Normal

Security Key (optional) 1

Decoder / Group 2

3

Finish

Command: leave serial - Wizard Mode

Parameters

1.a Select Device(s)
1.b Select Decoder or Group name
2. Click Finish button

Select Mode
☒ Wizard
☐ Normal

Security Key (optional)

31333331306339326330373066613065

Select
1a
1b
2

☒ Decoder Device Name
☐ Group Name
☐ All

Finish

Command: leave ir - Normal Mode

Parameters

1. Enter optional Security Key
2. Enter Decoder or Group name
3. Click Finish button

Select Mode
☐ Wizard
☒ Normal

Security Key (optional) 1

Decoder / Group 2

3

Finish

Command: leave ir - Wizard Mode

Parameters

1.a Select Device(s)
1.b Select Decoder or Group name
2. Click Finish button

Select Mode
☒ Wizard
☐ Normal

Security Key (optional)

31333331306339326330373066613065

Select
1a
1b
2

☒ Decoder Device Name
☐ Group Name
☐ All

Finish

Command: leave usb - Normal Mode

Parameters ×

1. Enter optional Security Key
2. Enter Decoder or Group name
3. Click Finish button

Select Mode ☐ Wizard
☒ Normal

Security Key (optional) **1**

Decoder / Group **2**

3

Command: leave usb - Wizard Mode

Parameters ×

1.a Select Device(s)
1.b Select Decoder or Group name
2. Click Finish button

Select Mode ☒ Wizard
☐ Normal

Security Key (optional)

Select **1a** ☒ Decoder Device Name
1b ☐ Group Name
☐ All

2

Command: leave kvm - Normal Mode

Parameters ×

1. Enter optional Security Key
2. Enter Decoder or Group name
3. Click Finish button

Select Mode ☐ Wizard
☒ Normal

Security Key (optional) **1**

Decoder / Group **2**

3

Command: leave kvm - Wizard Mode

Parameters ×

1.a Select Device(s)
1.b Select Decoder or Group name
2. Click Finish button

Select Mode ☒ Wizard
☐ Normal

Security Key (optional)

Select **1a** ☒ Decoder Device Name
1b ☐ Group Name
☐ All

2

Command: stop - Normal Mode

Parameters

1. Enter optional Security Key
2. Enter Encoder
3. Click Finish button

Select Mode
☐ Wizard
☒ Normal

Security Key (optional) 1

Encoder Device Name 2

3

Command: stop - Wizard Mode

Parameters

1. Select Encoder
2. Click Finish button

Select Mode
☒ Wizard
☐ Normal

Security Key (optional) 31333331306339326330373066613065

Encoder Device Name 1

2

Command: start - Normal Mode

Parameters

1. Enter optional Security Key
2. Enter Encoder
3. Click Finish button

Select Mode
☐ Wizard
☒ Normal

Security Key (optional) 1

Encoder Device Name 2

3

Command: start - Wizard Mode

Parameters

1. Select Encoder
2. Click Finish button

Select Mode
☒ Wizard
☐ Normal

Security Key (optional) 31333331306339326330373066613065

Encoder Device Name 1

2

Command: reboot - Normal Mode

Parameters

1. Enter optional Security Key
2. Enter Device or Group name
3. Click Finish button

Select Mode
☐ Wizard
☒ Normal

Security Key (optional) 1

Device / Group 2

3

Command: reboot - Wizard Mode

Parameters

1.a Select Device(s)
1.b Select Decoder or Group name
2. Click Finish button

Select Mode
☒ Wizard
☐ Normal

Security Key (optional) 31333331306339326330373066613065

Select 1a
☒ Device Name
☐ Group Name
☐ All
☐ All Decoders
☐ All Encoders

1b

2

Command: set audio_source - Normal Mode

Parameters

1. Enter optional Security Key
2. Enter Encoder Device Name
3. Select Audio Source:
HDMI / ANALOG
4. Click Finish button

Select Mode
☐ Wizard
☒ Normal

Security Key (optional) 1

Encoder Device Name 2

Audio Source 3

4

Command: set audio_source - Wizard Mode

Parameters

1. Select Encoder Device Name
2. Select Audio Source:
HDMI / ANALOG
3. Click Finish button

Select Mode
☒ Wizard
☐ Normal

Security Key (optional) 31333331306339326330373066613065

Encoder Device Name 1

Audio Source 2

3

Command: set edid - Normal Mode

The screenshot shows the 'Parameters' dialog box for the 'set edid - Normal Mode' command. The dialog has a title bar with a close button. Inside, there are four numbered steps in red text: 1. Enter optional Security Key, 2. Enter Encoder or Group name, 3. Enter EDID string, and 4. Click Finish button. The 'Select Mode' section has two radio buttons: 'Wizard' (unselected) and 'Normal' (selected). Below this, there are three input fields: 'Security Key (optional)' with a red '1' next to it, 'Encoder / Group' with a red '2' next to it, and 'EDID' with a red '3' next to it. At the bottom right, there is a blue 'Finish' button with a checkmark and a red '4' next to it.

Command: set edid - Wizard Mode

The screenshot shows the 'Parameters' dialog box for the 'set edid - Wizard Mode' command. The dialog has a title bar with a close button. Inside, there are three numbered steps in red text: 1. Select Encoder or Group name, 2. Select EDID type, and 3. Click Finish button. The 'Select Mode' section has two radio buttons: 'Wizard' (selected) and 'Normal' (unselected). Below this, there is a 'Security Key (optional)' field with the value '31333331306339326330373066613065'. The 'Select' section has three radio buttons: 'Encoder Device Name' (selected), 'Group Name' (unselected), and 'All Encoders' (unselected). Below this, there are two dropdown menus: 'EDID' with a red '2a' next to it, and 'EDID' with a red '2b' next to it. The 'EDID' dropdown has three options: 'Default EDID', 'Decoder EDID', and 'User Defined'. The 'EDID' dropdown has a red '2c' next to it. At the bottom right, there is a blue 'Finish' button with a checkmark and a red '3' next to it.

Command: set frame_converter` - Normal Mode

Parameters

1. Enter optional Security Key

2. Enter Encoder Device Name

3. Enter Frame rate

4. Click Finish button

Select Mode

☐ Wizard

☒ Normal

Security Key (optional)

1

Encoder Device Name

2

Frame Rate

3

4

✓ Finish

Command: set frame_converter - Wizard Mode

Parameters

1. Enter Encoder Device Name

3. Select Frame Rate

3. Click Finish button

Select Mode

☒ Wizard

☐ Normal

Security Key (optional)

31333331306339326330373066613065

Encoder Device Name

1

Frame Rate

2

3

✓ Finish

Parameters

1. Select Encoder Device Name

2. Select Frame Rate User Defined

3. Select Frame Rate

4. Click Finish button

Select Mode

☒ Wizard

☐ Normal

Security Key (optional)

31333331306339326330373066613065

Encoder Device Name

1

Frame Rate

2

User Defined

3

1

59

4

✓ Finish

Command: set listener - Normal Mode

Listener is OFF (disabled)

Parameters

1. Enter optional Security Key

2. Enter Multicast or Device IP

3. Enter Notify IP Port

4. Select Protocol UDP or TCP

5. Select Condition ON, OFF or ALL

6. Select State of listener

7. Select the device physically connected port

8. Click Finish button

Select Mode

☐ Wizard

☒ Normal

Security Key (optional)

1

IP Address

2

0.0.0.0

Notify Port

3

Protocol

4

Condition

5

State

6

DISABLED

Device Port

7

8

✓ Finish

Listener is ON (enabled)

Parameters

1. Enter optional Security Key

2. Enter Multicast or Device IP

3. Enter Notify IP Port

4. Select Protocol UDP or TCP

5. Select Condition ON, OFF or ALL

6. Select State of listener

7. Select the device physically connected port

8. Select Preset

9. Set delay time (optional)

10. Click Finish button

Select Mode

☐ Wizard

☒ Normal

Security Key (optional)

1

IP Address

2

0.0.0.0

Notify Port

3

Protocol

4

Condition

5

State

6

ENABLED

Device Port

7

Preset Name

8

Delay [minutes](optional)

9

0

60

10

✓ Finish

Command: set listener - Wizard Mode

Parameters ×

1. Select Device Discovery

Select Mode ☒ Wizard ☐ Normal

Security Key (optional) 31333331306339326330373066613065

🔍 Device Discovery

1

IP Address 0.0.0.0

Notify Port

Protocol

Condition

State DISABLED

Device Port

✓ Finish

Parameters ↻ ×

2. Select Device

Select Mode ☒ Wizard ☐ Normal

Security Key (optional) 31333331306339326330373066613065

🔍 Device Discovery

2

Discovered Devices

000C1E054917@10.8.11.100 (iTachIP2IR)

Refresh

IP Address 0.0.0.0

Notify Port

Protocol

Condition

State DISABLED

Device Port

✓ Finish

Command: set listener - Wizard Mode continued...

Listener is ON (enabled)

Parameters

Select Mode

☒ Wizard
 ☐ Normal

Security Key (optional)

31333331306339326330373066613065

Device Discovery

000C1E054917@10.8.11.100 (iTachIP2IR)



Select I/O

3

☒
☐
☐
☐

Sensor

Select Mode

4

Sensor Notify

Notify Port

5

9133

Notify Timer

6

11

7

Set

IP Address

239.255.250.250

Notify Port

Protocol

UDP

Condition

8

ON

State

9

ENABLED

Device Port

1

Preset Name

10

preset1

Delay [minutes](optional)

0

60

11

12

Finish

Command: set listener - Wizard Mode continued...

Listener is OFF (disabled)

Parameters

Select Mode

☒ Wizard
 ☐ Normal

Security Key (optional)

31333331306339326330373066613065

Device Discovery

000C1E054917@10.8.11.100 (iTachiP2IR)



3

Sensor

Select I/O

Select Mode

Sensor Notify

Notify Port

9133

Notify Timer

11

7

Set

IP Address

239.255.250.250

Notify Port

9133

Protocol

UDP

Condition

4 ON

State

5 DISABLED

Device Port

1

6

Finish

3. Select the device port being used

4. Select Condition ON, OFF or ALL

5. Select State of listener

5. Select the device physically connected port

6. Click Finish button

Command: set rotation - Normal Mode

1. Enter optional Security Key
2. Enter Decoder Device Name
3. Enter Rotation Method
4. Click Finish button

Select Mode

☐ Wizard
☒ Normal

Security Key (optional) 1

Decoder Device Name 2

Rotation 3
None

4
Finish

Command: set rotation - Wizard Mode

1. Select Decoder Device Name
2. Select Rotation Method
3. Click Finish button

Select Mode

☒ Wizard
☐ Normal

Security Key (optional)
31333331306339326330373066613065

Decoder Device Name 1

Rotation 2

3
Finish

Command: set scaler - Normal Mode

1. Enter optional Security Key
2. Enter Decoder Device Name
3. Enter Video Mode
4. Click Finish button

Select Mode

☐ Wizard
☒ Normal

Security Key (optional) 1

Decoder Device Name 2

Mode 3

4
Finish

Command: set scaler - Wizard Mode

1. Select Decoder Device Name
2. Select Video Mode
3. Click Finish button

Select Mode

☒ Wizard
☐ Normal

Security Key (optional)
31333331306339326330373066613065

Decoder Device Name 1

Mode 2

3
Finish

Command: set var - Normal Mode

Parameters [X]

1. Enter optional Security Key
2. Enter Variable Name
* MAX 256 characters
3. Enter value
* MAX 256 characters
4. Click Finish button

Select Mode ☐ Wizard ☒ Normal

Security Key (optional) 1

Variable Name 2

Value 3

4

Command: set var - Wizard Mode

Parameters [X]

1. Select / Enter Variable Name
* MAX 256 characters
2. Select Value or select Delete
* MAX 256 characters
3. Click Finish button

Select Mode ☒ Wizard ☐ Normal

Security Key (optional)

Variable Name 1

Delete ☐

Value 2

3

Command: set video_mute - Normal Mode

Parameters [X]

1. Enter optional Security Key
2. Enter Decoder Device Name
3. Select Option:
Enabled / Disabled
4. Click Finish button

Select Mode ☐ Wizard ☒ Normal

Security Key (optional) 1

Decoder Device Name 2

Option 3

4

Command: set video_mute - Wizard Mode

Parameters [X]

1. Select Decoder Device Name
2. Select Option:
Enabled / Disabled
3. Click Finish button

Select Mode ☒ Wizard ☐ Normal

Security Key (optional)

Decoder Device Name 1

Option 2

3

Command: set video_quality - Normal Mode

1. Enter optional Security Key
2. Enter Encoder Device Name
3. Select Option: AUTO / 0..5
4. Click Finish button

Select Mode
☐ Wizard
☒ Normal

Security Key (optional) 1

Encoder Device Name 2

Option 3

4

Command: set video_quality - Wizard Mode

1. Select Encoder Device Name
2. Select Option AUTO / 0..5
3. Click Finish button

Select Mode
☒ Wizard
☐ Normal

Security Key (optional)

Encoder Device Name 1

Option 2

3

Command: set volume - Normal Mode

1. Enter optional Security Key
2. Enter Device Name
3. Select Volume level
4. Click Finish button

Select Mode
☐ Wizard
☒ Normal

Security Key (optional) 1

Device Name 2

Analog Audio Output Volume 3
0 100

4

Command: set volume - Wizard Mode

1. Select Device Name
2. Select Volume level
3. Click Finish button

Select Mode
☒ Wizard
☐ Normal

Security Key (optional)

Select 1

Analog Audio Output Volume 2
0 100

3

Command: get audio_source - Normal Mode

The screenshot shows a 'Parameters' dialog box with a close button (X) in the top right corner. On the left, there are three numbered instructions in red: '1. Enter optional Security Key', '2. Enter Encoder Device Name', and '3. Click Finish button'. The main area contains a 'Select Mode' section with 'Wizard' selected (indicated by a blue dot) and 'Normal' unselected (indicated by a grey dot). Below this is a 'Security Key (optional)' text input field containing the value '31333331306339326330373066613065', with a red '1' next to it. Underneath is an 'Encoder Device Name' dropdown menu, with a red '2' next to it. At the bottom right is a blue 'Finish' button with a white checkmark, with a red '3' next to it.

Command: get audio_source - Wizard Mode

The screenshot shows a 'Parameters' dialog box with a close button (X) in the top right corner. On the left, there are two numbered instructions in red: '1. Select Encoder Device Name' and '2. Click Finish button'. The main area contains a 'Select Mode' section with 'Wizard' selected (indicated by a blue dot) and 'Normal' unselected (indicated by a grey dot). Below this is a 'Security Key (optional)' text input field containing the value '31333331306339326330373066613065'. Underneath is an 'Encoder Device Name' dropdown menu, with a red '1' next to it. At the bottom right is a blue 'Finish' button with a white checkmark, with a red '2' next to it.

Command: get devices - Normal Mode

The screenshot shows a 'Parameters' dialog box with a close button (X) in the top right corner. On the left, there are three numbered instructions in red: '1. Enter optional Security Key', '2. Select Device:', and '3. Click Finish button'. Under the second instruction, there are three red text options: 'ALL', 'ALL DECODERS', and 'ALL ENCODERS'. The main area contains a 'Select Mode' section with 'Wizard' unselected (indicated by a grey dot) and 'Normal' selected (indicated by a blue dot). Below this is a 'Security Key (optional)' text input field, with a red '1' next to it. Underneath is a 'Select Device' dropdown menu, with a red '2' next to it. At the bottom right is a blue 'Finish' button with a white checkmark, with a red '3' next to it.

Command: get devices- Wizard Mode

The screenshot shows a 'Parameters' dialog box with a close button (X) in the top right corner. On the left, there are two numbered instructions in red: '1. Select Device:' and '2. Click Finish button'. Under the first instruction, there are three red text options: 'ALL', 'ALL DECODERS', and 'ALL ENCODERS'. The main area contains a 'Select Mode' section with 'Wizard' selected (indicated by a blue dot) and 'Normal' unselected (indicated by a grey dot). Below this is a 'Security Key (optional)' text input field containing the value '31333331306339326330373066613065'. Underneath is a 'Select Device' dropdown menu, with a red '1' next to it. At the bottom right is a blue 'Finish' button with a white checkmark, with a red '2' next to it.

Command: get display_status - Normal Mode

Parameters

1. Enter optional Security Key
2. Select Decoder
3. Click Finish button

Select Mode
☐ Wizard
☒ Normal

Security Key (optional) 1

Decoder Device Name 2

3

Command: get display_status - Wizard Mode

Parameters

1. Select Decoder
2. Click Finish button

Select Mode
☒ Wizard
☐ Normal

Security Key (optional) 31333331306339326330373066613065

Decoder Device Name 1

2

Command: get edid - Normal Mode

Parameters

1. Enter optional Security Key
2. Enter Decoder Device Name
3. Click Finish button

Select Mode
☐ Wizard
☒ Normal

Security Key (optional) 1

Decoder Device Name 2

3

Command: get edid- Wizard Mode

Parameters

1. Select Decoder Device Name
2. Click Finish button

Select Mode
☒ Wizard
☐ Normal

Security Key (optional) 31333331306339326330373066613065

Decoder Device Name 1

2

Command: get encoder - Normal Mode

Parameters

1. Enter optional Security Key

2. Enter Decoder Device Name

3. Select Subscription:
VIDEO / AUDIO

4. Click Finish button

Select Mode

☐ Wizard

☒ Normal

Security Key (optional)

1

Decoder Device Name

2

Subscription

3

4

✓ Finish

Command: get encoder - Wizard Mode

Parameters

1. Select Decoder Device Name

2. Select Subscription:
VIDEO / AUDIO

3. Click Finish button

Select Mode

☒ Wizard

☐ Normal

Security Key (optional)

31333331306339326330373066613065

Decoder Device Name

1

Subscription

2

3

✓ Finish

Command: get frame_converter - Normal Mode

Parameters

1. Enter optional Security Key

2. Enter Encoder Device Name

3. Click Finish button

Select Mode

☐ Wizard

☒ Normal

Security Key (optional)

1

Encoder Device Name

2

3

✓ Finish

Command: get frame_converter- Wizard Mode

Parameters

1. Select Encoder Device Name

2. Click Finish button

Select Mode

☒ Wizard

☐ Normal

Security Key (optional)

31333331306339326330373066613065

Encoder Device Name

1

2

✓ Finish

Command: get preferred - Normal Mode

Parameters ×

1. Enter optional Security Key

2. Enter Decoder Device Name

3. Select Resolution:
WIDTH / HEIGHT / FRAME RATE

4. Click Finish button

Select Mode ☐ Wizard ☒ Normal

Security Key (optional) 1

Decoder Device Name 2

Resolution 3

4

Command: get preferred - Wizard Mode

Parameters ×

1. Select Decoder Device Name

2. Select Resolution:
WIDTH / HEIGHT / FRAME RATE

3. Click Finish button

Select Mode ☒ Wizard ☐ Normal

Security Key (optional)

Decoder Device Name 1

Resolution 2

3

Command: get rotation - Normal Mode

Parameters ×

1. Enter optional Security Key

2. Enter Decoder Device Name

3. Click Finish button

Select Mode ☐ Wizard ☒ Normal

Security Key (optional) 1

Decoder Device Name 2

3

Command: get rotation- Wizard Mode

Parameters ×

1. Select Decoder Device Name

2. Click Finish button

Select Mode ☒ Wizard ☐ Normal

Security Key (optional)

Decoder Device Name 1

2

Command: get scaler - Normal Mode

1. Enter optional Security Key
2. Enter Decoder Device Name
3. Select Option:
ALL / WIDTH /
HEIGHT / FRAME RATE
4. Click Finish button

Select Mode

☐ Wizard
☒ Normal

Security Key (optional) 1

Decoder Device Name 2

Option 3

4

Command: get scaler - Wizard Mode

1. Select Decoder Device Name
2. Select Option:
ALL / WIDTH /
HEIGHT / FRAME RATE
3. Click Finish button

Select Mode

☒ Wizard
☐ Normal

Security Key (optional) 31333331306339326330373066613065

Decoder Device Name 1

Option 2

3

Command: get status - Normal Mode

1. Enter optional Security Key
2. Enter Device Name
3. Select Streams:
VIDEO / AUDIO /
IR / SERIAL / USB
4. Click Finish button

Select Mode

☐ Wizard
☒ Normal

Security Key (optional) 1

Device Name 2

Streams (optional) 3

4

Command: get status- Wizard Mode

1. Select Device Name
2. Select Streams:
VIDEO / AUDIO /
IR / SERIAL / USB
3. Click Finish button

Select Mode

☒ Wizard
☐ Normal

Security Key (optional) 31333331306339326330373066613065

Device Name 1

Streams (optional) 2

3

Command: get var - Normal Mode

Parameters

1. Enter optional Security Key
2. Enter Variable Name
3. Click Finish button

Select Mode
☐ Wizard
☒ Normal

Security Key (optional) 1

Variable Name 2

3

Command: get var - Wizard Mode

Parameters

1. Enter / Select Variable Name
2. Click Finish button

Select Mode
☒ Wizard
☐ Normal

Security Key (optional) 31333331306339326330373066613065

Variable Name 1

2

Command: get ver - Normal Mode

Parameters

1. Enter optional Security Key
2. Select Device:
ALL
ALL DECODERS
ALL ENCODERS
3. Click Finish button

Select Mode
☐ Wizard
☒ Normal

Security Key (optional) 1

Device Name 2

3

Command: get ver- Wizard Mode

Parameters

1. Select Device:
ALL
ALL DECODERS
ALL ENCODERS
2. Click Finish button

Select Mode
☒ Wizard
☐ Normal

Security Key (optional) 31333331306339326330373066613065

Device Name 1

2

Command: get video - Normal Mode

Parameters

1. Enter optional Security Key

2. Enter Encoder Device Name

3. Select Option:
ALL / WIDTH / HEIGHT
FRAME RATE / SCAN MODE

4. Click Finish button

Select Mode

☐ Wizard

☒ Normal

Security Key (optional) 1

Encoder Device Name 2

Option 3

4

Command: get video - Wizard Mode

Parameters

1. Select Encoder Device Name

2. Select Option:
ALL / WIDTH / HEIGHT
FRAME RATE / SCAN MODE

3. Click Finish button

Select Mode

☒ Wizard

☐ Normal

Security Key (optional) 31333331306339326330373066613065

Encoder Device Name 1

Option 2

3

Command: get video_mute - Normal Mode

Parameters

1. Enter optional Security Key

2. Select Device:
ALL
ALL DECODERS
ALL ENCODERS

3. Click Finish button

Select Mode

☐ Wizard

☒ Normal

Security Key (optional) 1

Decoder Device Name 2

3

Command: get video_mute- Wizard Mode

Parameters

1. Select Device:
ALL
ALL DECODERS
ALL ENCODERS

2. Click Finish button

Select Mode

☒ Wizard

☐ Normal

Security Key (optional) 31333331306339326330373066613065

Decoder Device Name 1

2

Command: get video_quality - Normal Mode

Parameters ×

1. Enter optional Security Key

2. Enter Encoder Device Name

3. Click Finish button

Select Mode ☐ Wizard ☒ Normal

Security Key (optional) 1

Encoder Device Name 2

3

Command: get video_quality - Wizard Mode

Parameters ×

1. Select Encoder Device Name

2. Click Finish button

Select Mode ☒ Wizard ☐ Normal

Security Key (optional)

Encoder Device Name 1

2

Command: get video_status - Normal Mode

Parameters ×

1. Enter optional Security Key

2. Enter Encoder Device Name

3. Click Finish button

Select Mode ☐ Wizard ☒ Normal

Security Key (optional) 1

Encoder Device Name 2

3

Command: get video_status- Wizard Mode

Parameters ×

1. Select Encoder Device Name

2. Click Finish button


Select Mode ☒ Wizard ☐ Normal

Security Key (optional)

Encoder Device Name 1

2


Command: get volume - Normal Mode



The 'Parameters' dialog box for Normal Mode contains the following elements:

- Instructions:**
 - 1. Enter optional Security Key
 - 2. Select Device
 - 3. Click Finish button
- Select Mode:** Radio buttons for Wizard (unselected) and Normal (selected).
- Security Key (optional):** A text input field with a red '1' next to it.
- Device Name:** A text input field with a red '2' next to it.
- Finish Button:** A blue button with a checkmark and the text 'Finish', with a red '3' next to it.

Command: get volume - Wizard Mode



The 'Parameters' dialog box for Wizard Mode contains the following elements:

- Instructions:**
 - 1. Select Device
 - 2. Click Finish button
- Select Mode:** Radio buttons for Wizard (selected) and Normal (unselected).
- Security Key (optional):** A text input field containing the value '31333331306339326330373066613065'.
- Device Name:** A dropdown menu with a red '1' next to it.
- Finish Button:** A blue button with a checkmark and the text 'Finish', with a red '2' next to it.

Command: send cec - Normal Mode

1. Enter optional Security Key
2. Select Device
3. Enter CEC code
4. Click Finish button

Select Mode
☐ Wizard
☒ Normal

Security Key (optional) 1

Device / Group 2

CEC Code 3

4

Command: send cec - Wizard Mode

1. Select Device
2. Select / Enter CEC code
3. Click Finish button

Select Mode
☒ Wizard
☐ Normal

Security Key (optional)

Select 1
☒ Device Name
☐ All
☐ All Decoders
☐ All Encoders

CEC Code 2

3

Command: send gc - Normal Mode

1. Enter optional Security Key

2. Enter device IP address

3. Select device port

4. Enter command string

5. Click Finish button

Select Mode

☐ Wizard

☒ Normal

Security Key (optional)

1

IP Address

2

0.0.0.0

Port

3

4998

Global Caché Command

4

5

✓ Finish

Command: send gc - Wizard Mode

1. Select Device, Click Device Discovery or enter device IP address

2. Select device port

3. Disconnect (optional)

4. Enter command string or select Delete

5. Click Finish button

Select Mode

☒ Wizard

☐ Normal

Security Key (optional)

31333331306339326330373066613065

Select Device

▼

Device Discovery

1

IP Address

0.0.0.0

Port

2

4998

Disconnect (optional)

3

☐

Global Caché Command

4

5

✓ Finish

Command: send ir - Normal Mode

Parameters

1. Enter optional Security Key

2. Select Device

3. Enter IR code

4. Click Finish button

Select Mode

☐ Wizard

☒ Normal

Security Key (optional) 1

Device / Group 2

IR Code 3

4

Command: send ir - Wizard Mode

Parameters

1. Select Device

2. Enter IR code

3. Click Finish button

Select Mode

☒ Wizard

☐ Normal

Security Key (optional)

31333331306339326330373066613065

Select

1

☒ Device Name

☐ All

☐ All Decoders

☐ All Encoders

IR Code 2

3

Command: send serial - Normal Mode

Parameters ×

1. Enter optional Security Key

2. Enter Device

3. Enter Data String

4. Leave NONE selected (when no feedback required)

5. Click Finish button

Select Mode ☐ Wizard ☒ Normal

Security Key (optional) 1

Device / Group 2

Data String 3

Feedback (optional) 4 NONE ▼

5

Parameters ×

1. Enter optional Security Key

2. Enter Device

3. Enter Data String

4. Select Reply (when feedback required)

5. Click Finish button

Select Mode ☐ Wizard ☒ Normal

Security Key (optional) 1

Device / Group 2

Data String 3

Feedback (optional) 4 Reply ▼

5

Parameters ×

1. Enter optional Security Key

2. Enter Device

3. Enter Data String

4. Select Contains (when part feedback compared)

5. Enter compare string

6. Click Finish button

Select Mode ☐ Wizard ☒ Normal

Security Key (optional) 1

Device / Group 2

Data String 3

Feedback (optional) 4 Equals ▼

Feedback String 5

6

Parameters ×

1. Enter optional Security Key

2. Enter Device

3. Enter Data String

4. Select Equals (when full feedback compared)

5. Enter compare string

6. Click Finish button

Select Mode ☐ Wizard ☒ Normal

Security Key (optional) 1

Device / Group 2

Data String 3

Feedback (optional) 4 Contains ▼

Feedback String 5

6

Command: send serial - Wizard Mode

Parameters [X]

1. Select Device
2. Select string format:
ASCII / HEX
3. Enter Data String
4. Leave None selected
(when no feedback required)
5. Click Finish button

Select Mode ☒ Wizard
☐ Normal

Security Key (optional) 31333331306339326330373066613065

Select ☒ Device Name
☐ All
☐ All Decoders
☐ All Encoders

1 <<Decoder>>

Format 2 ASCII

Data String 3

Append CR (optional) ☐

Append LF (optional) ☐

Feedback (optional) 4 NONE

5 ✓ Finish

Parameters [X]

1. Select Device
2. Select string format:
ASCII / HEX
3. Enter Data String
4. Select Reply
(when feedback required)
5. Click Finish button

Select Mode ☒ Wizard
☐ Normal

Security Key (optional) 31333331306339326330373066613065

Select ☒ Device Name
☐ All
☐ All Decoders
☐ All Encoders

1 <<Decoder>>

Format 2 ASCII

Data String 3

Append CR (optional) ☐

Append LF (optional) ☐

Feedback (optional) 4 Reply

5 ✓ Finish

Command: send serial - Wizard Mode continued...

Parameters

1. Select Device

2. Select string format:
ASCII / HEX

3. Enter Data String

4. Select Contains
(when part feedback compared)

5. Enter compare string

6. Click Finish button

Select Mode: ☒ Wizard
☐ Normal

Security Key (optional): 31333331306339326330373066613065

Select: ☒ Device Name
☐ All
☐ All Decoders
☐ All Encoders

Format: ASCII

Data String:

Append CR (optional): ☐

Append LF (optional): ☐

Feedback (optional): Equals

Feedback String:

Append CR (optional): ☐

Append LF (optional): ☐

6

Parameters

1. Select Device

2. Select string format:
ASCII / HEX

3. Enter Data String

4. Select Equals
(when all feedback compared)

5. Enter compare string

6. Click Finish button

Select Mode: ☒ Wizard
☐ Normal

Security Key (optional): 31333331306339326330373066613065

Select: ☒ Device Name
☐ All
☐ All Decoders
☐ All Encoders

Format: ASCII

Data String:

Append CR (optional): ☐

Append LF (optional): ☐

Feedback (optional): Contains

Feedback String:

Append CR (optional): ☐

Append LF (optional): ☐

6

Command: send tcp - Normal Mode

Parameters

1. Enter optional Security Key
2. Enter device IP Address
3. Enter device Port
4. Enter command string
5. Leave NONE selected (when no feedback required)
6. Click Finish button

Select Mode
☐ Wizard
☒ Normal

Security Key (optional) 1
IP Address 2
Port 3
Command 4
Feedback (optional) 5 NONE
6 ✓ Finish

Parameters

1. Enter optional Security Key
2. Enter device IP Address
3. Enter device Port
4. Enter command string
5. Select Reply (when feedback required)
6. Click Finish button

Select Mode
☐ Wizard
☒ Normal

Security Key (optional) 1
IP Address 2
Port 3
Command 4
Feedback (optional) 5 Reply
6 ✓ Finish

Parameters

1. Enter optional Security Key
2. Enter device IP Address
3. Enter device Port
4. Enter command string
5. Select Contains (when part feedback compared)
6. Enter compare string
7. Click Finish button

Select Mode
☐ Wizard
☒ Normal

Security Key (optional) 1
IP Address 2
Port 3
Command 4
Feedback (optional) 5 Contains
Feedback String (optional) 6
7 ✓ Finish

Parameters

1. Enter optional Security Key
2. Enter device IP Address
3. Enter device Port
4. Enter command string
5. Select Equals (when all feedback compared)
6. Enter compare string
7. Click Finish button

Select Mode
☐ Wizard
☒ Normal

Security Key (optional) 1
IP Address 2
Port 3
Command 4
Feedback (optional) 5 Equals
Feedback String (optional) 6
7 ✓ Finish

Command: send tcp - Wizard Mode

Parameters ✕

1. Enter device IP Address
2. Enter device Port
3. Select Format:
ASCII / HEX
4. Enter command string
5. Leave NONE selected
(when no feedback required)
6. Click Finish button

Select Mode ☒ Wizard
☐ Normal

Security Key (optional) 31333331306339326330373066613065

IP Address **1**

Port **2**

Disconnect (optional) ☐

Format **3** ASCII ▼

Command **4**

Append CR (optional) ☐

Append LF (optional) ☐

Feedback (optional) **5** NONE ▼

6

Parameters ✕

1. Enter device IP Address
2. Enter device Port
3. Select Format:
ASCII / HEX
4. Enter command string
5. Select Reply
(when feedback required)
6. Click Finish button

Select Mode ☒ Wizard
☐ Normal

Security Key (optional) 31333331306339326330373066613065

IP Address **1**

Port **2**

Disconnect (optional) ☐

Format **3** ASCII ▼

Command **4**

Append CR (optional) ☐

Append LF (optional) ☐

Feedback (optional) **5** Reply ▼

6

Command: send tcp - Wizard Mode continued...

Parameters ×

1. Enter device IP Address

2. Enter device Port

3. Select Format
ASCII / HEX

4. Enter command string

5. Select Contains
(when part feedback compared)

6. Enter compare string

7. Click Finish button

Select Mode
☒ Wizard
☐ Normal

Security Key (optional)
31333331306339326330373066613065

IP Address **1**

Port **2**

Disconnect (optional)
☐

Format **3** ASCII

Command **4**

Append CR (optional)
☐

Append LF (optional)
☐

Feedback (optional) **5** Contains

Feedback String **6**

Append CR (optional)
☐

Append LF (optional)
☐

7

Parameters ×

1. Enter device IP Address

2. Enter device Port

3. Select Format
ASCII / HEX

4. Enter command string

5. Select Equals
(when all feedback compared)

6. Enter compare string

7. Click Finish button

Select Mode
☒ Wizard
☐ Normal

Security Key (optional)
31333331306339326330373066613065

IP Address **1**

Port **2**

Disconnect (optional)
☐

Format **3** ASCII

Command **4**

Append CR (optional)
☐

Append LF (optional)
☐

Feedback (optional) **5** Equals

Feedback String **6**

Append CR (optional)
☐

Append LF (optional)
☐

7

Command: preset add

Parameters

1. Enter Preset Name

2. Enter Preset Command

3. Click Finish button

Security Key (optional)

31333331306339326330373066613065

Preset Name

1

Preset Data

2

3

✓ Finish

Command: preset delete

Parameters

1. Select Preset Name

2. Click Finish button

Select Mode

• Wizard

○ Normal

Security Key (optional)

31333331306339326330373066613065

Preset Name

1

2

✓ Finish

Command: preset load

Parameters

1. Select Preset Name

2. Select optional delay time or select Cancel

3. Click Finish button

Select Mode

• Wizard

○ Normal

Security Key (optional)

31333331306339326330373066613065

Preset Name

1

Cancel

☐

Delay [minutes] (optional)

2

0

60

3

✓ Finish

Command: set ui_button - Normal Mode

Parameters

1. Enter optional Security Key
2. Enter UI Name
3. Enter Button Name
4. Select Function:
Position / State / Text / Press
5. Enter Value
6. Click Finish button

Select Mode
☐ Wizard
☒ Normal

Security Key (optional) 1

UI Name 2

Button Name 3

Function 4

Value 5

6

Command: set ui_button - Wizard Mode

Parameters

1. Select UI Name
2. Select Button Name
3. Select Function:
State / Text / Press
4. Click Finish button

Select Mode
☒ Wizard
☐ Normal

Security Key (optional) 31333331306339326330373066613065

UI Name 1

Button Name 2

Function 3

4

Command: set ui_label - Normal Mode

1. Enter optional Security Key

2. Enter UI Name

3. Enter Label Name

4. Select Function
Color / Visibility / Text

5. Enter Value

6. Click Finish button

Select Mode

☐ Wizard

☒ Normal

Security Key (optional) 1

UI Name 2

Label Name 3

Function 4

Value 5

6

Command: set ui_label - Wizard Mode

1. Select UI Name

2. Select Label Name

3. Select Function
Color / Visibility / Text

4. Click Finish button

Select Mode

☒ Wizard

☐ Normal

Security Key (optional)

UI Name 1

Label Name 2

Function 3

4

Command: set ui_image - Normal Mode

Parameters

1. Enter optional Security Key

2. Enter UI Name

3. Enter Image Name

4. Select Function
Visibility

5. Enter Value

6. Click Finish button

Select Mode

☐ Wizard

☒ Normal

Security Key (optional) 1

UI Name 2

Image Name 3

Function 4

Value 5

6 ✓ Finish

Command: set ui_image - Wizard Mode

Parameters

1. Select UI Name

2. Select Image Name

3. Select Function
Visibility

4. Click Finish button

Select Mode

☒ Wizard

☐ Normal

Security Key (optional) 31333331306339326330373066613065

UI Name 1

Image Name 2

Function 3

4 ✓ Finish

Command: set ui_page- Normal Mode

Parameters

1. Enter optional Security Key

2. Enter UI Name

3. Enter Page Name

4. Click Finish button

Select Mode

☐ Wizard

☒ Normal

Security Key (optional)

1

UI Name

2

Page Name

3

4

✓Finish

Command: set ui_page - Wizard Mode

Parameters

1. Select UI Name

2. Select Page Name

3. Click Finish button

Select Mode

☒ Wizard

☐ Normal

Security Key (optional)

31333331306339326330373066613065

UI Name

1

Page Name

2

3

✓Finish

Command: set ui - Normal Mode

Parameters

1. Enter optional Security Key

2. Enter UI Name

3. Select Service > Enabled

4. Enter optional UI Timeout (seconds)

5. Enter optional Client Limit (1 – 100)

6. Enter optional 4 digit code (0000 – 9999)

7. Click Finish button

Select Mode

☐ Wizard

☒ Normal

Security Key (optional)

1

UI Name

2

Service

3

Enabled

Session Timeout (optional)

4

Client Limit (optional)

5

Login (optional)

6

7

✓Finish

Parameters

1. Enter optional Security Key

2. Enter UI Name

3. Select Service > Disabled

4. Click Finish button

Select Mode

☐ Wizard

☒ Normal

Security Key (optional)

1

UI Name

2

Service

3

Disabled

4

✓Finish

Parameters

1. Enter optional Security Key

2. Enter UI Name

3. Select Service > Logout

4. Click Finish button

Select Mode

☐ Wizard

☒ Normal

Security Key (optional)

1

UI Name

2

Service

3

Logout

4

✓Finish

Command: set ui - Wizard Mode

Parameters

1. Select UI Name

2. Select Service > Enabled

3. Select optional UI Timeout (seconds)

4. Enter optional Client Limit (1 – 100)

5. Select optional Login: Random / Fixed

6. Click Finish button

Select Mode

☒ Wizard

☐ Normal

Security Key (optional)

31333331306339326330373066613065

UI Name

1

Service

2

Enabled

Session Timeout (optional)

3

Client Limit (optional)

4

☐

Login (optional)

5

NONE

6

✓Finish

Parameters

1. Select UI Name

2. Select Service > Disabled

3. Click Finish button

Select Mode

☒ Wizard

☐ Normal

Security Key (optional)

31333331306339326330373066613065

UI Name

1

Service

2

Disabled

3

✓Finish

Parameters

1. Select UI Name

2. Select Service > Logout

3. Click Finish button

Select Mode

☒ Wizard

☐ Normal

Security Key (optional)

31333331306339326330373066613065

UI Name

1

Service

2

Logout

3

✓Finish

Command: get ui - Normal Mode

Parameters

1. Enter optional Security Key
2. Enter UI Name
3. Click Finish button

Select Mode
☐ Wizard
☒ Normal

Security Key (optional) 1

UI Name 2

3

Command: get ui - Wizard Mode

Parameters

1. Select UI Name
2. Click Finish button

Select Mode
☒ Wizard
☐ Normal

Security Key (optional) 31333331306339326330373066613065

UI Name 1

2

Command: get ui_button - Normal Mode

Parameters

1. Enter optional Security Key
2. Enter UI Name
3. Enter Button Name
4. Enter Function > down
5. Click Finish button

Select Mode
☐ Wizard
☒ Normal

Security Key (optional) 1

UI Name 2

Button Name 3

Function 4

5

Command: get ui_button - Wizard Mode

Parameters

1. Select UI Name
2. Select Button Name
3. Select Function > Down
4. Click Finish button

Select Mode
☒ Wizard
☐ Normal

Security Key (optional) 31333331306339326330373066613065

UI Name 1

Button Name 2

Function 3

4



LIBERTY[®]
AV SOLUTIONS

A SUBSIDIARY OF WESCO DISTRIBUTION, INC.

Phone: 719-260-0061

Fax: 719-260-0075

Toll-Free: 800-530-8998

Email: supportlibav@libav.com