

Assignment 4: Data Wrangling (Fall 2025)

Josette McLean

OVERVIEW

This exercise accompanies the lessons in Environmental Data Analytics on Data Wrangling

Directions

1. Rename this file `<FirstLast>_A04_DataWrangling.Rmd` (replacing `<FirstLast>` with your first and last name).
2. Change “Student Name” on line 3 (above) with your name.
3. Work through the steps, **creating code and output** that fulfill each instruction.
4. Be sure to **answer the questions** in this assignment document.
5. When you have completed the assignment, **Knit** the text and code into a single PDF file.
6. Ensure that code in code chunks does not extend off the page in the PDF.

Set up your session

- 1a. Load the `tidyverse`, `lubridate`, and `here` packages into your session.
 - 1b. Check your working directory.
 - 1c. Read in all four raw data files associated with the EPA Air dataset, being sure to set string columns to be read in a factors. See the README file for the EPA air datasets for more information (especially if you have not worked with air quality data previously).
2. Add the appropriate code to reveal the dimensions of the four datasets.

```
#1a
library(tidyverse)
library(lubridate)
library(here)
```

```
#1b
here()
```

```
## [1] "/home/guest/Environmental Data Visualization Class/EDE_Fall2025"
```

```
#1c EPA1
EPA_03_18 <- read.csv(
  file=here('Data', 'Raw', 'EPAair_03_NC2018_raw.csv'),
  stringsAsFactors=T
)
```

```

#1c EPA2
EPA_03_19 <- read.csv (
  file=here ('Data', 'Raw', 'EPAair_03_NC2019_raw.csv'),
  stringsAsFactors = T
)

#1c EPA3
EPA_PM_18 <- read.csv (
  file=here ('Data', 'Raw', 'EPAair_PM25_NC2018_raw.csv'),
  stringsAsFactors = T
)

#1c EPA4
EPA_PM_19 <- read.csv (
  file=here ('Data', 'Raw', 'EPAair_PM25_NC2019_raw.csv'),
  stringsAsFactors = T
)

#2

#Dimensions of first dataset
dim(EPA_03_18)

```

```
## [1] 9737    20
```

```
#Dimensions of second dataset
```

```
dim(EPA_03_19)
```

```
## [1] 10592    20
```

```
#Dimensions of third dataset
```

```
dim(EPA_PM_18)
```

```
## [1] 8983    20
```

```
#Dimensions of forth dataset
```

```
dim(EPA_PM_19)
```

```
## [1] 8581    20
```

All four datasets should have the same number of columns but unique record counts (rows). Do your datasets follow this pattern? Yes it does

Wrangle individual datasets to create processed files.

3. Change the Date columns to be date objects.
4. Select the following columns: Date, DAILY_AQI_VALUE, Site.Name, AQS_PARAMETER_DESC, COUNTY, SITE_LATITUDE, SITE_LONGITUDE

5. For the PM2.5 datasets, fill all cells in AQS_PARAMETER_DESC with “PM2.5” (all cells in this column should be identical).
6. Save all four processed datasets in the Processed folder. Use the same file names as the raw files but replace “raw” with “processed”.

```
#3
```

```
#Changing the first EPA Data set's data column to a date object
```

```
EPA_03_18$Date <- mdy(EPA_03_18$Date)
```

```
#4 and 5
```

```
#Selecting columns in EPA_03_18
```

```
EPA_03_18_Processed <-
```

```
  EPA_03_18 %>%
```

```
  select(Date, DAILY_AQI_VALUE, Site.Name, AQS_PARAMETER_DESC,COUNTY, SITE_LATITUDE, SITE_LONGITUDE)
```

```
#Changing the second EPA Data set's data column to a date object
```

```
EPA_03_19$Date <- myd(EPA_03_19$Date)
```

```
## Warning: All formats failed to parse. No formats found.
```

```
#Changing the third EPA Data set's data column to a date object
```

```
EPA_PM_18$Date <- myd(EPA_PM_18$Date)
```

```
## Warning: All formats failed to parse. No formats found.
```

```
#Changing forth EPA Data set's data column to a date object
```

```
EPA_PM_19$Date <- myd(EPA_PM_19$Date)
```

```
## Warning: All formats failed to parse. No formats found.
```

```
#4 and 5
```

```
#Selecting columns in EPA_03_18
```

```
EPA_03_18_Processed <-
```

```
  EPA_03_18 %>%
```

```
  select(Date, DAILY_AQI_VALUE, Site.Name, AQS_PARAMETER_DESC,COUNTY, SITE_LATITUDE, SITE_LONGITUDE)
```

```
#Selecting columns in EPA_03_19
```

```
EPA_03_19_Processed <-
```

```
  EPA_03_19 %>%
```

```
  select(Date, DAILY_AQI_VALUE, Site.Name, AQS_PARAMETER_DESC,COUNTY, SITE_LATITUDE, SITE_LONGITUDE)
```

```
#Selecting columns in the third EPA dataset and mutating
```

```
EPA_PM_18_Processed <- EPA_PM_18 %>%
```

```
  select(Date, DAILY_AQI_VALUE, Site.Name, AQS_PARAMETER_DESC, COUNTY, SITE_LATITUDE, SITE_LONGITUDE) %>%
```

```
  mutate(AQS_PARAMETER_DESC = ("PM.25"))
```

```
#Selecting various columns in the fourth EPA dataset and mutating
```

```
EPA_PM_19_Processed <- EPA_PM_19 %>%
```

```
  select(Date, DAILY_AQI_VALUE, Site.Name, AQS_PARAMETER_DESC, COUNTY,SITE_LATITUDE, SITE_LONGITUDE) %>%
```

```
  mutate(AQS_PARAMETER_DESC = ("PM.25"))
```

#6 #Saving Processed Datasets

Combine datasets

7. Combine the four datasets with `'rbind'`. Make sure your column names are identical prior to running the code.

8. Wrangle your new dataset with a pipe function (`%>%`) so that it fills the following conditions:

- * Include only sites that the four data frames have in common:

```
"Linville Falls", "Durham Armory", "Leggett", "Hattie Avenue",  
"Clemmons Middle", "Mendenhall School", "Frying Pan Mountain",  
"West Johnston Co.", "Garinger High School", "Castle Hayne",  
"Pitt Agri. Center", "Bryson City", "Millbrook School"
```

(the function `'intersect'` can figure out common factor levels - but it will include sites with missing values)

- * Some sites have multiple measurements per day. Use the split-apply-combine strategy to generate daily averages.

- * Add columns for "Month" and "Year" by parsing your "Date" column (hint: `'lubridate'` package)

- * Hint: the dimensions of this dataset should be 14,752 x 9.

9. Spread your datasets such that AQI values for ozone and PM2.5 are in separate columns. Each location should have two columns.

10. Call up the dimensions of your new tidy dataset.

11. Save your processed dataset with the following file name: "EPAair_03_PM25_NC1819_Processed.csv"

```
''' r
```

```
#7
```

```
#8
```

```
#9
```

```
#10
```

```
#11
```

Generate summary tables

12. Use the split-apply-combine strategy to generate a summary data frame. Data should be grouped by site, month, and year. Generate the mean AQI values for ozone and PM2.5 for each group. Then, add a pipe to remove instances where mean **ozone** values are not available (use the function `drop_na` in your pipe). It's ok to have missing mean PM2.5 values in this result.

13. Call up the dimensions of the summary dataset.

#12

#13

14. Why did we use the function `drop_na` rather than `na.omit`? Hint: replace `drop_na` with `na.omit` in part 12 and observe what happens with the dimensions of the summary data frame.

Answer: