

Lab 4: Complex Mixer

Integrating a 3rd party library into an RCC Worker

Objectives



- Learn how [RCC] workers can:
  - Import a 3rd party library (liquid dsp) functionality into a worker
- Reiterate:
  - C++ conventions
    - Accessing port data and Properties
  - Framework interactions
    - RCC_ADVANCE vs. RCC_OK

Application Worker Development Flow



1. Protocol (OPS): Create new or select pre-existing
2. Component (OCS): Create new or select pre-existing
3. Create new App Worker (Modify OWD, Makefile, and source RCC/HDL code)
4. Build the App Worker for target device(s)
5. Create Unit Test (<component>-test.xml, generate, verify and view scripts)
6. Build Unit Test
7. Run Unit Test

Overview



- The “Complex Mixer” component receives I/Q data and multiplies this signal by a tone that is generated using a Numerically Controlled Oscillator (NCO).
- This causes the input signal to be shifted in the Frequency Domain by the frequency of the NCO that is generated in the worker.
- The frequency of the NCO is controlled by the properties of this worker.

Step 1 – Protocol Selection



- Identify the OPS(s) declared by this component
  - Examine the “Component Ports” table in it's Component Datasheet
- Determine if OPS(s) exists
  - Current project's component library?
    /home/training/training_project/components/specs
  - Other project's components/specs/ directories within scope
    - Project Registry
    - ProjectDependencies in {my_project}/Project.mk

- If NO to all questions => Create new OPS

ANSWER: OPS XML file is available from framework (REUSE!)

Step 2 - Create Component



- Examine the Properties and Ports listed in the Component Datasheet
  - Use Properties/Ports information to answer the following questions
- Is the OCS XML file available in this project's component library?
  - HINT: Browse /home/training/training_project/components/specs/
- Is the OCS XML file available from the framework?
  - HINT: Browse IDE options
- If **NO** to all questions => custom OCS XML file must be created

- **ANSWER: Custom OCS XML file must be created.**

Step 2 - Create Component



- The component datasheet is located in
  - `/home/training/provided/doc/Complex_Mixer.pdf`
- Review the component's datasheet and familiarize yourself the properties and their functionality.
- Create a component called complex_mixer based on the datasheet's properties and ports
  - Note: `data_select` is a HDL only property, you can ignore this.
  - Note: `iqstream_protocol.xml` is located in Core Project

Step 3 - Create Worker



- Create new Asset Type: Worker
  - Worker Name: complex_mixer
  - Library: components
  - Component: complex_mixer-spec.xml
  - Model: **RCC**
  - Prog. Lang: C++

- In the OWD RCC Editor
  - Make sure to add initialize and release to the control operations

Step 3 - Create Worker (cont.)



- Add the following **four** lines the RCC worker Makefile *before* the line that reads: "`include $(OCPI_CDK_DIR)/include/worker.mk`"

```
RccIncludeDirs+=/opt/opencpi/prerequisites/liquid/include/liquid

RccCustomLibs=-lliquid

RccCustomLibs_centos7=/opt/opencpi/prerequisites/liquid/linux-c7-
x86_64/lib/libliquid.a

RccCustomLibs_xilinx13_3=/opt/opencpi/prerequisites/liquid/linux-x13_3-
arm/lib/libliquid.a
```

Step 3 - Write the Worker's Code



- Copy complex_mixer.cc
  - From: /home/training/provided/lab4/
  - To: /home/training/training_project/components/complex_mixer.rcc
- Update any “???” in the source with the correct code

Liquid DSP NCO API (for reference)



- From liquidsdr.org:
  - `nco_crcf_create(type)`
    - creates an `nco` object of type LIQUID_NCO or LIQUID_VCO .
  - `nco_crcf_destroy(q)`
    - destroys an `nco` object, freeing all internally-allocated memory.
  - `nco_crcf_set_frequency(q,f)`
    - sets the frequency f (equal to the phase step size $\Delta\theta$).
  - `nco_crcf_set_phase(q,theta)`
    - sets the internal `nco` phase to θ

Liquid DSP NCO API (for reference)



- From liquidsdr.org:
  - `nco_crcf_step(q)`
    - increments the internal `nco` phase by its internal frequency, $\theta \leftarrow \theta + \Delta\theta$
  - `nco_crcf_mix_down(q,x,*y)`
    - rotates an input sample x by $e^{-j\theta}$, storing the result in the output sample y
  - All samples are of type `liquid_float_complex`

```
liquid_float_complex sample;
sample.I = 0;
sample.Q = 0;
```

Step 4 - Building the App Worker for x86 and ARM



1. Use the IDE to "**Add**" the App Worker to the Project Operations Panel
2. **Highlight** "centos7" *and* "xilinx13_3" in RCC Platforms panel
3. **Click** "Build Assets"
4. Review the Console window messages
5. Fix any syntax errors and repeat

Step 5(a) – 7(a) CentOS7 - x86



- These slides cover employing the framework's Unit Test Suite to generate:
  - OAS (OpenCPI Application Specification) XML file(s)
    - Used by the framework for running the Worker on a given platform
  - Input test data file(s)

- **CRITICAL NOTE: The IDE does not currently support creation of a unit test directory.**

Step 5(a) - Create Unit Test



- `ocpidev create test complex_mixer`
- Copy generate.py, verify.py, and view.sh

```
cp -a ~/provided/lab4/complex_mixer.test/*  ~/training_project/components/complex_mixer.test/
```

- Update complex_mixer-test.xml

```
<tests useHDLFileIo='true'>
  <input port='in' script='generate.py 100 12.5 32767 16384' messagesize='8192'/>
  <output port='out' script='verify.py 100 16384' view='view.sh'/>
  <property name='phs_inc' values='-8192'/>
  <property name='enable' values='0,1'/>
</tests>
```

Step 6(a) - Build Unit Test (x86)



- Build the Unit Test Suite for the target software platform
  1. Use the IDE to "**Add**" the Unit Test to the Project Operations panel
  2. **Highlight** "centos7" in the RCC Platforms panel
  3. **Click** "Build Tests"
  4. Review the Console window messages and address any errors

- Observe new artifacts in complex_mixer.test/gen/
  - cases.txt – "Human-readable" file which lists various test configurations.
  - cases.xml – Used by framework to execute tests.
  - cases.xml.deps – List of dependent files
  - applications/ - OAS files and scripts used by framework to execute applications.

Step 7(a) - Run Unit Test (x86)



- Similar in IDE, but “Run Tests” button
- OR in a terminal window, browse to complex_mixer.test/ and execute

$ make run View=1

  - This uses the default centos7

- The test should run quickly. Upon completion you should see “**PASSED**” along with input and output plots (expected results in following slides)
- Fix any errors with your component to make sure the testbench passes

Expected input file plot



Expected output file plot case 0 (bypass)





Expected output file plot case 1 (enabled)





Step 5(b) – 7(b) Xilinx13_3 - ARM



- These slides cover employing the framework's Unit Test Suite to generate:
  - OAS (OpenCPI Application Specification) XML file(s)
    - Used by the framework for running the Worker on a given platform
  - Input test data file(s)
  - Various scripts to manage the execution of the applications onto the target platform(s)

- **CRITICAL NOTE: The IDE does not currently support creation of a unit test directory.**

Step 5(b) - Create Unit Test



- Located in “complex_mixer.test/” directory
  - Same as used for CentOS7
    - **REUSE!**

```
<tests useHDLFileIo='true'>
  <input port='in' script='generate.py 100 12.5 32767 16384' messagesize='8192'/>
  <output port='out' script='verify.py 100 16384' view='view.sh'/>
  <property name='phs_inc' values='-8192'/>
  <property name='enable' values='0,1'/>
</tests>
```

Step 6(b) - Build Unit Test (ARM)



- Build the Unit Test Suite for the target software platform
  1. Use the IDE to "**Add**" the Unit Test to the Project Operations panel
  2. **Highlight** "xilinx13_3" the RCC Platforms panel
  3. **Click** "Build Tests"
  4. Review the Console window messages and address any errors

- Observe possibly-updated artifacts in complex_mixer.test/gen/
  - cases.txt – "Human-readable" file which lists various test configurations.
  - cases.xml – Used by framework to execute tests.
  - cases.xml.deps – List of dependent files
  - applications/ - OAS files and scripts used by framework to execute applications.

Step 7(b) - Run Unit Test (ARM)



- Setup deployment platform
  1. Connect to serial port via USB on rear of Matchstiq-Z1 using host
     - `screen /dev/ttyUSB0 115200`
  2. Boot and login into Petalinux
     - User/Password = root:root
  3. Verify host and Matchstiq-Z1 have valid IP addresses
     - For training, they should both be on the same subnet
  4. Run setup script on Matchstiq-Z1
     - `source /mnt/card/opencpi/mynetsetup.sh <host ip address>`

More detail on this process can be found in the **Matchstiq-Z1 Getting Started Guide** document

Step 7(b) - Run Unit Test (ARM) (cont.)



- On the Development Host, set OCPI_REMOTE_TEST_SYSTEMS, as shown:

```
$ export OCPI_REMOTE_TEST_SYSTEMS={IP of Matchsitq-Z1}=root=root=/mnt/training_project
```

- If using the IDE, the above must be set **before launching**!

- On the Development Host, browse to the peak_detector.test/

```
$ make run OnlyPlatforms=xilinx13_3 View=1
```

  - This will run the unit test remotely (over ssh) on the Matchstiq-Z1's ARM

- Also try:
  - `$ make run` {run on all available platforms, no plotting}
  - `$ make verify` {verify previous results}
  - `$ make view` {plot previous results}

Expected input file plot



Expected output file plot case 0 (bypass)



Expected output file plot case 1 (enabled)