



UNIVERSITY OF
BIRMINGHAM

Software Workshop 2

Real Time Multi-User Quiz System

Benjamin Crispin,
Samuel Farmer,
Deedar Fatima,
Rowan Stringer,
Josh Wainwright

Group Osaka

Supervisor: Joe Gardiner

Date: March 2014

Contents

Contents	1
1 Protocol	2
2 Client	3
2.1 System Design	3
3 Server	4
3.1 System Design	4
4 Database	5
5 Graphical User Interface	5
6 Test Plan	8
7 Evaluation	10
7.1 Evaluation of project work	10
7.2 Evaluation of project process	10
7.3 Team Organisation	10
Class Diagram	11
Database Design	13

1 Protocol

The protocol for communicating between the different parts of the system is based around objects. There exists an object class that can be created for any of the several message types that could be needed to transfer information from the server to the client, or from the client to the server. Each of these objects implements the `Serializable` interface, allowing them to be converted to bytes and transferred across the socket connection using object streams.

AnswerResponse object

To respond to a question, the Student selects the desired option. This information is passed to the server using an `AnswerResponse` object which simply holds the response and the timestamp to indicate when they made the selection.

DisplayQuestion object

In order to signify that the allotted time for the current question has ended, and the next question should be displayed, the server sends a `DisplayQuestion` object to all of the clients and they should move on to the next question in the `Quiz` object and change the GUI accordingly.

LoginReply object

Once a `loginRequest` has been received by the server, a `LoginReply` will be sent back. This gives the client the information about the requested login, most importantly if the login was successful, as well as the type of user that made the login, Student or Admin. This information is used to display the correct user interface.

LoginRequest object

This is the first object that could be created. It is sent, by the client, to the server and contains the username of the Student that is attempting to login and the `java.lang.String` hash code of the inserted password. Though the security concerns of such a trivial system are non-existent, the password is never stored in plaintext.

Question object

There exist several question objects in each `Quiz` object. They store the information required to present a Student with a question and the possible answers. Again, there is very little functionality as the question only serves as a wrapper for the question text and the possible answers that the user could respond with.

Quiz object

This is the most important object. It has very little functionality, simply acting as a wrapper to hold and easily transfer several `Question` objects.

QuizRequest object

Score object

When the quiz has been completed, each of the clients will display the position of its user relative to the other Students. This object contains the score of all of the users so that each of the clients can work out where they are in the ranking.

StartQuiz object

Once the user has successfully logged into the system, the next major event is the start of the quiz. This is signaled by an Admin user who is connected to the server, this information

must then be relayed to each of the connected clients. A `StartQuiz` object is sent to each of the clients, who, on receiving it, will display the first question to the user.

2 Client

The client exists to accept messages sent by the server, and present them in an order and a format that the user interface can present to the user, as well as accept the information entered by the user into the user interface and pass it to the server.

2.1 System Design

1. Login

When a client is started, a `QuizClient` object is created and starts the main loop. The initial stages set up the connection with the server and waits for the user to login. When the user enters their information, a `LoginRequest` object is created and pass to the server containing the username and password, to be checked against the contents of the database. The client then waits for a reponse from the server to indicate if the login was successfull or not. This comes in the form of a `LoginReply` object. If this says that the login was unsuccessful, the user is asked to re-input their details, otherwise, the display is changed and the options screen is shown.

2. Student/Admin

There exists separate functionality withing the client depending on if the user is a Student user, i.e. going to be answering questions, or an Admin, i.e. the teacher who starts and moderates the quiz. Distinguishing between these two is done by the server by checking the details associated with that user in the database. The `LoginReply` object contains this information and the client can then display the correct interface depending on the type of user that logged in.

3. Client Listens from Server

From here, the user can select the “Start Quiz” option to start the quiz. This causes the display to change to display the waiting screen and the client waits for information from the server.

From this point on, the client waits for any object to be sent from the server and acts according to what that object was. The possible objects that the client now expects to be able to distinguish between are:

- `Quiz`
- `StartQuiz`
- `DisplayQuestion`
- `Score`

`Quiz`

This object contains the information about the quiz itself, the number of questions, their contents and the duration that each question should be displayed for. It should

only ever be recieved once by the client, at the start of the session, reducing the transfer of information over the connection.

StartQuiz

Once an Admin has logged in, they have control over the start of the quiz. When they decide to start the quiz, this object is sent to each of the listening clients and so the client will procede to show the first question from the **Quiz** object.

DisplayQuestion

The first question is displayed as soon as the **StartQuiz** object is recieved. After this point in the quiz, the questions are changed when this object is received. The value contained verifies which question is to be displayed.

Score

After each question has been answered, the client can display a leader board showing the score of all the clients that have so far answered the current question along with the current client's position in this list. This object tells the client the relevant information for displaying the scores of the other clients.

4. Sent by Client

There are also a number of objects that the client can create and send to the server at different stages of the quiz:

- **LoginRequest**
- **QuizRequest**
- **AnswerResponse**

QuizRequest

This is sent by the client when an Admin is logged in in order to request a particular quiz from the server. Since the server can hold many quizzes, each with their own set of questions and answers, the Admin has the option to choose which of these to play when they log in.

AnswerResponse

This is the object that tells the server what answer the Student gave. It contains their response, so that it can be logged in the database, and the time it took for the Student to make their selection.

3 Server

The server exists to create a link between the database and the quiz program, as well creating connections with, and processing requests from, clients.

3.1 System Design

1. Initialising the server

When the server starts, a **QuizServer** object is created. The object creates a connection with the database, which allows the server object to retrieve, and update, information

contained in the database. In addition to this, a **ServerSocket** object is created, which waits to receive connections from **QuizClient** objects. When a connection from a client is received, a new **ClientThread** object is created.

2. Database Connectivity

The server interacts with the database through static methods contained in the **QuizJDBC** class. The class allows the server to establish a connection with the database through a **getConnection** method, which returns a **Connection** object.

A second method, **isUser**, is called by the server when it receives a **LoginRequest** object from a client thread. The method returns a **LoginReply** object containing the results of the query, which is sent to the client.

The final method, **getQuiz**, is called when the server receives a **QuizRequest** object from a client, and returns a **Quiz** object.

3. ClientThread Objects

When the server establishes a connection with a client, a **ClientThread** object is created, spawning a thread which allows interactions to occur between the server and client. The server then waits to receive a **LoginRequest** from the client, and returns a **LoginReply** object upon receiving it. Once the client has logged in, the server distinguishes between student and Admin users.

4. Admin Clients

If a connection to an Admin has been made, the server waits for a **QuizRequest** object. Once received, the server updates a static boolean variable, which informs all connected clients that a **Quiz** object has been created, and the quiz is started.

5. Student Client

Once a quiz has been started, the server sends a **Quiz** object to all connected clients, and then waits to receive an **AnswerReponse** from each of the student client threads. The **AnswerReposnse** objects contain the clients response to a question, and the time that it took for them to answer it. The server then calculates the clients score, and the results are stored in an **ArrayList**, which contains the results of all connected student clients. This **ArrayList** of scores is then sent to the connected clients at the end of each question.

4 Database

5 Graphical User Interface

The Student and Admin users will interact with a graphical user interface to take and run the quiz. The model deals with the data so the GUI can just be a visual interaction and representation of the client model. Instead of having many pop ups for each of the GUI panels, we decided to have one frame per client in which its content panel changes depending on the current part of the quiz.

1. Model/View Seperation

Originally we decided that the GUI would follow a model/view separation format where the model will be separate from the client. This, however, caused some problems so we decided to not have a separate model and use the client as the model instead. One of the problems we encountered was that the GUI would interact with the model and create an object that needs to be sent to the server. We found it tricky to find a way to send objects from the model to the client and realized that there was a lot of redundancy as objects had to go through the model and the client when really there only needed to be one.

2. GUI Panels

Each GUI panel used in the quiz has its own class. When a client is created, each of the GUI panels is instantiated and added to an array. To accomplish this we used inheritance. Each of the GUI panels extends the abstract class `MasterFrame`, and in turn, `MasterFrame` extends `JPanel`. Each of the GUI panels is added to the `guiElements'` `MasterFrame[]`. `MasterFrame` is an abstract class with one abstract method `resetDisplay()`. This method is used to reset the contents of the current panel to an updated version of the model. Whenever the content panel of the frame is changed, the `resetDisplay()` method is called to ensure correct information is displayed.

The overall GUI will display different panels depending on which part of the system is currently being used. The GUI panels are:

`LoginFrame`

The first panel users will log-in to (both Admin and Student). `LoginFrame` contains a username field, a password field and login button. When the login button is activated, it send the contents of the two fields to the client model to create a `LoginRequest` object using the `requestLogin()` method.

`StudentHomeFrame`

The panel a Student will see once they have logged in / received successful login reply object. Here they can push the Start quiz button which adds them to a pool of Students ready to start the quiz. This leads them to the `WaitingFrame` panel using the `requestWaitingScreen()` method.

`AdminHomeFrame`

The panel the Admin will see once they have logged in / received successful login reply object. Here they can see which Students have connected and joined the waiting pool to start the quiz. `AdminHomeFrame` has a `JComboBox` which lists the possible quizzes to run. This uses the `setCurrentQuizID()` method. The Admin can then push the start quiz button which sends the selected quiz to all the waiting Students using the `adminStart()` method.

`WaitingFrame`

The panel a Student will see when they have pushed start and are waiting for the Admin to start the quiz. Contains a message to the Student letting them know they are waiting for the Admin to start the quiz as well as a `JProgressBar` in intermediate state.

`QuestionFrame`

The panel which displays the question to the Students. This panel is only displayed for a limited time as each question has a short time limit. The question is displayed in a `JTextPane`, and each of the four possible multiple choice answers is displayed as a `JButton` beneath. To the side there is a countdown timer which visually displays

the time to answer the question. As soon as the question is answered or the time has run out, the panel is changed to the **StudentResultsFrame** panel. When a button is pushed, the **setResponseNumber(i)** method is called. If a student doesn't answer, then the response number is set to -1.

StudentResultsFrame

Once a Student has completed a question, they are displayed with this panel. **StudentResultsFrame** displays the last question with highlighted text for the correct answer and Students answer. It also displays the score received for the last question and current leader board for the quiz where each client is ranked by their total score so far. This panel is shown for a set amount of time before leading back to the **QuestionFrame** for a new question.

AdminResultsFrame

The **AdminResultsFrame** is displayed once the Admin has started the quiz. It displays the current question Students are completing and a live leader board showing the current scores of the students. The leader board ranks the Students by their current total score from the completed questions so far.

FinalResultsFrame

This is similar to **StudentResultsFrame** but is the final panel the student sees in the quiz. It shows the correct answers to the previous question and the score for the previous question. It also shows the final leader board rankings. Unlike **StudentResultsFrame**, there is no time limit so the Student can see the final results as long as they wish. There is a back button to return the Student to the **StudentHomeFrame** which uses the **returnHome()** method.

Other GUI components that we have created and used within the GUI panels are:

CountDownTimer

CountDownTimer is GUI component that counts down seconds. It shows a **JProgressBar** decrease as the time decreases. Also has a label beneath showing the seconds left to count down. Used in **QuestionFrame**.

LeaderBoard

A table consisting of each student in the quiz, their position and score. This is updated whenever the **resetDisplay()** method is called in its parent panel (**MasterFrame**). Used in **StudentResultsFrame**, **AdminResultsFrame** and **FinalResultsFrame**.

6 Test Plan

S.No	Category	Description	Expected Result	Actual Result
1	Registration	User is able to register by providing first name, last name, username and password.		
2	Registration	System should display username and password guidelines to users.		
3	Registration	System validates the credentials; displays an error message if user provides invalid username and password and asks user to choose valid credentials.		
4	Registration	If user enters valid credentials, system checks if the entered credentials already exists in the the users table. If credentials exists, system asks the user to choose different credentials.		
5	Registration	System inserts the credentials in the users table if the user enters valid credentials. A unique ID is created for the user in users table.		
6	Login	System displays the login page where user can enter username and password and login to the system.		
7	Login	System checks the entered credentials in the users table; displays an error message if incorrect credentials are entered and asks user to re-enter credentials.		
8	Login	If correct credentials are entered, user is taken to the Home page.		
9	HomePage-Student	Student homepage should display the buttons – Start, View Result, Update Profile and Quiz rules.		
10	HomePage-Student	Quiz should start when student clicks on “Start” button.		
11	HomePage-Student	Quiz result should be displayed when student clicks on “View Result” button. What is shown in View Result page?		
12	HomePage-Student	Profile page should be displayed when student clicks on “Update Profile” button. User should be able to edit profile; save changes or cancel changes.		
13	HomePage-Student	Quiz rules should be displayed when stuent clicks on “Quiz Rules” button. A new window or a popup screen?		
14	HomePage-Admin	Admin homepage should display the buttons – Start, View Result, Question settings (Add, remove or update questions), Update Profile. (Check the options displayed).		
15	HomePage-Admin	Admin should be able to select a quiz and click on Start to start the quiz.		
16	HomePage-Admin	Quiz result should be displayed when admin clicks on “View Result” button. What is shown in View Result page?		

17	HomePage-Admin	Admin should be able to add, remove or update questions/answers in questions table in the Question settings page.
18	HomePage-Admin	Profile page should be displayed when admin clicks on “Update Profile” button. Admin should be able to edit profile; save changes or cancel changes.
19	Play Quiz-Student	The quiz name should be displayed in quiz page.
20	Play Quiz-Student	Each quiz consists of 10 questions.
21	Play Quiz-Student	Each question has a set of possible answers (maximum 4).
23	Play Quiz-Student	Timer is displayed when question appears on screen.
24	Play Quiz-Student	Student is able to choose an answer by clicking on the answer.
25	Play Quiz-Student	When a student chooses the correct answer before time runs out, timer stops. The other students should not be able to select an option once the timer stops.
26	Play Quiz-Student	After quiz finishes, the result is inserted into user_result table.
27	Play Quiz-Student	Student should be able to see feedback after quiz finishes.
28	Play Quiz-Student	Student should be able to view result after quiz finishes (and after answering a question?).
29	Play Quiz-Student	Student should be able to view the historical result data from user_result table after quiz finishes.
30	Play Quiz-Student	Student should be able to click on the close button to exit the quiz.
31	Play Quiz-Admin	Admin should be able to click on start button to start the quiz once all students have logged in.
32	Play Quiz-Admin	Admin should be able to see the result after each question is answered.
33	Play Quiz-Admin	Admin should be able to see the result summary after quiz finishes.
34	Play Quiz-Admin	Student should be able to click on the close button to exit the quiz.
35	Server-Client	System ensures that all clients and server are synchronised.
36	JDBC	Database connection is established from JDBC.

7 Evaluation

7.1 Evaluation of project work

1. Correctness and reliability
2. Performance
3. Usability
4. Substantialness

7.2 Evaluation of project process

1. Management of team work
2. Time keeping and scheduling
3. Subdivision of work
4. Integration
5. Summary

7.3 Team Organisation

The group consists of 5 students. Since there were a number of distinct sections to the project, the different components were distributed among the members of the team with one person in a position of responsibility for that component and another to provide assistance. The allocations were as follows.

Component	Responsible	Assisting
GUI	Benjamin Crispin	Deedar Fatima
Client	Josh Wainwright	Rowan Stringer
Server	Rowan Stringer	Benjamin Crispin
Database	Deedar Fatima	Sam Farmer
Protocol	Sam Farmer	Josh Wainwright

These roles were followed closely during the initial stages of development and through the first round of testing. As the program became more complete and bug fixes were required, the roles were shared more evenly through the team. This has the advantage that all members have a full understanding of all aspects of the project having worked on all parts at some time.

References

- [1] Elliottte Harold. *Java Network Programming*. O'Reilly Media Inc., 2013.
- [2] Harvey Deitel and Paul Deitel. *Java: How to Program*. Pearson, 2002.

- [3] Scott Oaks and Henry Wong. *Java Threads*. O'Reilly Media Inc., 1999.
- [4] Xingchen Chu Rajkumar Buyya, S Thamarai Selvi. *Object-Oriented Programming with Java*. Tata McGraw Hill, 2009.
- [5] Kenneth L. Calvert and Michael J. Donahoo. *TCP/IP Sockets in Java*. Morgan Kauffman, 2001.

"Client → Server" Protocol

LoginRequest	AnswerResponse
-username: String -passwordHash: int +setUserName(userName:String) +getUserName(response:int): String +getPasswordHash(responseTime:int): int	-response: int -responseTime: long +getResponse(): int +setResponse(response:int) +getResponseTime(): long +setResponseTime(responseTime:int)

QuizRequest
-quizID: long +getQuizID(): long

Client
QuizClient
-PORT: int -connected: boolean -loginReply: LoginReply -quiz: Quiz -currentQuizID: long -currentQuestion: Question -loginSuccessful: boolean -responseNumber: int = -1 -allScores: ArrayList<Score> -username: String -passwordHash: String -questionReceivedTime: long -isStudentUser: boolean -loginSuccessful: boolean +main() +run() +getLoginReply(i:int): LoginReply +loginSuccessful(): boolean +isStudent(): boolean +sendObject(object:Object): boolean +changeContentPane(int:i) +getResponseNumber(): int +setResponseNumber(int:n) +getAnswer(int:i): String +getQuizIDs(): long [] +setUsername(String:username) +getUsername(): String +getPassword(String:password) +setCurrentQuizID(currentQuizID:long) +getAllScores(): ArrayList<Score> +getCurrentQuestion(): Question +isConnected(): boolean +getQuiz(): Quiz +requestLogin() +adminStart() +waitForUserResponse(): AnswerResponse +studentSession(object:Object) +adminSession(object:Object) +sendObject(object:Object): boolean

"Server → Client" Protocol


LoginReply	Question
-loginSuccessful: boolean -isStudent: boolean -name: String +quizzes: Quiz [] +isSuccessful(): boolean +isStudent(): boolean +getQuizzes(): Quiz [] +setQuizzes(quizzes:Quiz [])	-question: String -answers: String [] -correctAnswerPos: int -questionID: int -timeLimit: int +setQuestion(question:String) +setAnswer(i:int,answer:String) +getQuestion(): Question +getAnswer(i:int): String +getAnswers(): String [] +toString(): String +equals(o:Object): boolean +getCorrectAnswerPos(): int +getTimeLimit(): int +setTimeLimit(int:timeLimit)

Score
-mark: int -username: String +getMark(): int +setMark(int:mark) +getUsername(): String +setUsername(username:String)

StartQuiz
-quizID: long +getQuizStartTime(): long

Quiz
-quizID: long -questions: Question [] -name: String +setQuestions(questions:Question) +getQuestions(): Question [] +getQuestion(i:int): Question +getName(): String

DisplayQuestion
-number: int +getNumber(): int




Osaka Database Design Specification

Osaka - Database Design Specification

Server: The server used for the project Osaka was dbteach2.

Database: The database created for this project is called **osakaggp**. The owner of the database is dxf321 (Deedar). The other team members will be given access to the database shortly.

Entity-Relationship Diagram:



Osaka - Database Design Specification

Tables:

The tables created in osakagp DB are as follows.

USERS

Table name	users			
Description	The user login details are stored in the users table. The user details are inserted into this table when a new user or administrator registers. The login credentials entered by the users are validated and the users are allowed to login only if the entered credentials exist in the users table.			
Attribute	Description	Type	Nullability	Example of values
user_id	Unique ID of an admin/student	BIG INT	NOT NULL	Between 1 and 9223372036854775807
first_name	First name of admin/student	VARCHAR (20)	NULL	Mary
last_name	Last name of admin/student	VARCHAR (20)	NULL	Ande
role	Role of user	VARCHAR (20)	NULL	admin or student
password	Password entered by admin/student to access the tool	VARCHAR (10)	NULL	
inserted_date	Timestamp of the transaction	TIMESTAMP	NOT NULL	DEFAULT is the current timestamp.
Primary Key	user_id			
Foreign Key				
SQL code	SELECT * FROM users;			

QUIZ

Table name	quiz
-------------------	------

Osaka - Database Design Specification

Description	The quiz topics are stored in this table. The quiz could be on the following topics - Politics, Sports, History, Geography, Java, Database, etc. The admin chooses the quiz topic from quiz table and fetches the topic-related questions from the questions table.			
Attribute	Description	Type	Nullability	Example of values
quiz_id	Unique ID of quiz	BIG INT	NOT NULL	Between 1 and 9223372036854775807
quiz_name	Topic of quiz	VARCHAR (40)	NULL	Politics, Sports
inserted_date	Timestamp of the transaction	TIMESTAMP	NOT NULL	DEFAULT is the current timestamp.
Primary Key	quiz_id			
Foreign Key				
SQL code	SELECT * FROM quiz;			

QUESTIONS

Table name	questions			
Description	The questions table contains the questions which are answered in quiz. Question and possible answers are stored as rows in the questions table. The table also contains a separate column for quiz ID. The admin uses the quiz ID to get the questions for the chosen quiz topic.			
Attribute	Description	Type	Nullability	Example of values
question_id	Unique ID of question	BIG INT	NOT NULL	Between 1 and 9223372036854775807
question	The question to be answered by students	VARCHAR (100)	NULL	In which country is the Albert canal?
ans1_id	ID of first possible answer	INT	NOT NULL	DEFAULT is 1
ans1	First possible answer	VARCHAR (40)	NULL	Spain
ans2_id	ID of second possible answer	INT	NOT NULL	DEFAULT is 2
ans2	Second possible answer	VARCHAR (40)	NULL	Belgium
ans3_id	ID of third	INT	NOT NULL	DEFAULT is 3

Osaka - Database Design Specification

	possible answer			
ans3	Third possible answer	VARCHAR (40)	NULL	Canada
ans4_id	ID of fourth possible answer	INT	NOT NULL	DEFAULT is 4
ans4	Fourth possible answer	VARCHAR (40)	NULL	Portugal
correct_ans_id	The ID of correct answer	INT	NOT NULL	2
quiz_id	The ID of quiz	BIG INT	NOT NULL	4
inserted_date	Timestamp of the transaction	TIMESTAMP	NOT NULL	DEFAULT is the current timestamp.
Primary Key	question_id			
Foreign Key	quiz_id			
SQL code	SELECT * FROM questions;			

USER_RESULT

Table name	user_result			
Description	This table contains the quiz results for all the students. It is loaded with quiz result once the quiz is completed. The user can see the result by quiz date, quiz topic, score and quiz status.			
Attribute	Description	Type	Nullability	Example of values
user_result_id	Unique ID for the row	BIG INT	NOT NULL	Between 1 and 9223372036854775807
user_id	ID of user	BIG INT	NOT NULL	Between 1 and 9223372036854775807
quiz_date	Date on which quiz is played	TIMESTAMP	NOT NULL	DEFAULT is Current Timestamp
quiz_id	ID of quiz played by the student	BIG INT	NOT NULL	Between 1 and 9223372036854775807
total_question	Number of questions displayed in a quiz	INT	NULL	10

Osaka - Database Design Specification

ans_correct	Number of questions answered correctly before any other student	INT	NULL	Between 0 and 10
ans_incorrect	Number of questions answered incorrectly	INT	NULL	Between 0 and 10
total_score	Number of questions answered correctly before any other student	INT	NULL	Between 0 and 10
status	If a student won or lost the quiz	VARCHAR(10)	NULL	WON or LOST
inserted_date	Timestamp of the transaction	TIMESTAMP	NOT NULL	DEFAULT is the current timestamp.
Primary Key	user_result_id			
Foreign Key	user_id, quiz_id			
SQL code	SELECT * FROM user_result;			

SQL statements for database and tables creation:

```
CREATE DATABASE osakadb OWNER dxf321;
```

```
CREATE TABLE users
(
  user_id BIGSERIAL PRIMARY KEY,
  first_name VARCHAR (20),
  last_name VARCHAR (20),
  role VARCHAR (20),
  password VARCHAR (10),
  inserted_date timestamp default current_timestamp
);
```

```
CREATE TABLE quiz
(
  quiz_id BIGSERIAL PRIMARY KEY,
  quiz_name VARCHAR (40),
  inserted_date timestamp default current_timestamp
);
```

Osaka - Database Design Specification

```
CREATE TABLE questions
(
question_id BIGSERIAL PRIMARY KEY,
question VARCHAR (100),
ans1_id INT default 1,
ans1 VARCHAR (40),
ans2_id INT default 2,
ans2 VARCHAR (40),
ans3_id INT default 3,
ans3 VARCHAR (40),
ans4_id INT default 4,
ans4 VARCHAR (40),
correct_ans_id INT NOT NULL,
quiz_id BIGINT REFERENCES quiz (quiz_id),
inserted_date timestamp default current_timestamp
);
```

```
CREATE TABLE user_result (
user_result_id BIGSERIAL PRIMARY KEY,
user_id BIGINT REFERENCES users (user_id),
quiz_date timestamp default current_timestamp,
quiz_id BIGINT REFERENCES quiz(quiz_id),
total_question INT,
ans_correct INT,
ans_incorrect INT,
total_score INT,
status VARCHAR (10),
inserted_date timestamp default current_timestamp
);
```

Tables Load:

```
INSERT INTO users (first_name, last_name, role) VALUES ('Mary', 'Ande', 'student');
INSERT INTO users (first_name, last_name, role) VALUES ('Andrew', 'Baker',
'student');
INSERT INTO users (first_name, last_name, role) VALUES ('Katie', 'Bowyer',
'student');
INSERT INTO users (first_name, last_name, role) VALUES ('Katherine', 'Brittain',
'student');
INSERT INTO users (first_name, last_name, role) VALUES ('Thomas', 'Chapman',
'student');
INSERT INTO users (first_name, last_name, role) VALUES ('Andrew', 'Green',
'student');
INSERT INTO users (first_name, last_name, role) VALUES ('Matthew', 'Harris',
'student');
INSERT INTO users (first_name, last_name, role) VALUES ('Ella', 'Hibbert', 'student');
```

Osaka - Database Design Specification

```
INSERT INTO users (first_name, last_name, role) VALUES ('Daniel', 'Hirst', 'student');
INSERT INTO users (first_name, last_name, role) VALUES ('Antony', 'Judd', 'student');
INSERT INTO users (first_name, last_name, role) VALUES ('George', 'Kiff', 'admin');
INSERT INTO users (first_name, last_name, role) VALUES ('Joseph', 'May', 'admin');
```

```
INSERT INTO quiz (quiz_name) VALUES ('History');
INSERT INTO quiz (quiz_name) VALUES ('Politics');
INSERT INTO quiz (quiz_name) VALUES ('Sports');
INSERT INTO quiz (quiz_name) VALUES ('Java');
INSERT INTO quiz (quiz_name) VALUES ('Database');
INSERT INTO quiz (quiz_name) VALUES ('Geography');
```

```
INSERT INTO questions (question, ans1, ans2, ans3, ans4, correct_ans_id, quiz_id)
VALUES ('In which country is the Albert canal?', 'Spain', 'Belgium', 'Canada',
'Portugal', 2, 4);
```

```
INSERT INTO questions (question, ans1, ans2, ans3, ans4, correct_ans_id, quiz_id)
VALUES ('Which is the only US state named after an English county?', 'Kentucky',
'North Dakota', 'Vermont', 'New Hampshire', 4, 6);
```

```
INSERT INTO questions (question, ans1, ans2, ans3, ans4, correct_ans_id, quiz_id)
VALUES ('Which British cyclist won the 100th edition of the Tour de France?', 'Chris
Froome', 'Lizzie Armitstead', 'Matt Crampton', 'Kyle Evans', 1, 3);
```

```
INSERT INTO questions (question, ans1, ans2, ans3, ans4, correct_ans_id, quiz_id)
VALUES ('How many players are there in a basketball team?', '11', '14', '5', 6, 3, 3);
```

```
INSERT INTO user_result (user_id, quiz_id, total_question, ans_correct, ans_incorrect,
total_score, status) VALUES ( 1, 2, 10, 8, 2, 8, 'WON');
INSERT INTO user_result (user_id, quiz_id, total_question, ans_correct, ans_incorrect,
total_score, status) VALUES ( 1, 4, 10, 10, 0, 10, 'WON');
INSERT INTO user_result (user_id, quiz_id, total_question, ans_correct, ans_incorrect,
total_score, status) VALUES ( 6, 2, 10, 10, 0, 10, 'WON');
INSERT INTO user_result (user_id, quiz_id, total_question, ans_correct, ans_incorrect,
total_score, status) VALUES ( 6, 6, 10, 9, 1, 9, 'WON');
INSERT INTO user_result (user_id, quiz_id, total_question, ans_correct, ans_incorrect,
total_score, status) VALUES ( 7, 3, 10, 5, 5, 5, 'LOST');
```

Minutes of the
Team Osaka Project Meeting
UG04, Computer Science
March 04, 2014; 11:00-12:00
Minutes Taker: Rowan Stringer

Attendance

1. Rowan Stringer
2. Benjamin Crispin
3. Sam Farmer
4. Josh Wainwright
5. Deedar Fatima

Minutes

1. We need to hand in a more detailed written specification.
2. Get a paragraph on each section and splice together – add paragraph to Subversion as .txt file, Sam will splice together.
3. We need an object diagram.
4. We need a class diagram.
5. Deedar is responsible for JDBC (database connection) and Prepared Statements.
6. JDBC will be carried out in a separate server thread.
7. 4 responses possible for questions – so arrays will be used instead of ArrayLists.
8. Share ERD + document on databases on Subversion.
9. Short meeting for Thursday will be held at 14:30-15:00, like last week.
10. Sam will help out with JDBC
11. Deedar will form the SQL for the Prepared Statements.
12. Rowan is responsible for passing the quiz object to the client (clarifications):
 - Server notified with a question object
 - Client carries out timing
 - Server listens for results object (including username, answer, time)
 - Tell client to end connection their end, close connection, close thread.

Action Summary			
Action Specifics	Responsible	Deadline	Status
Hand in a more detailed written specification	Sam		Open
Get a paragraph on each section and splice together	All		Open
Create object diagram	-		Open
Create class diagram	-		Open
Give system JDBC functionality	Deedar, Sam		Open
Create PreparedStatements	Deedar		Open
Share ERD + document on databases on Subversion.	Deedar		Open

*** End of Minutes ***

Tutorial Notes

Team Osaka Project Meeting

245, Computer Science

March 06, 2014; 16:00-16:30

Notes Taker: Rowan Stringer

Attendance

1. Rowan Stringer
2. Benjamin Crispin
3. Sam Farmer
4. Josh Wainwright
5. Deedar Fatima
6. Joe Gardiner (Tutor)

Notes

- Protocols must be documented
 - Testing must be planned
 - Using JUnit
 - Manual tests where JUnit is inappropriate
 - Testing must be logged
 - Recording whether test cases were successful / failed
 - Recording what bugs were fixed
 - Working system by next Wednesday.
 - 2 weeks until report submission.
 - Need 1 week for testing / bug fixing.
-

Work Status

- Deedar:
 - Completed Actions:
 - Database is working
 - Upcoming Actions
 - JUnit test cases
 - JDBC / Prepared Statements
- Sam:
 - Completed Actions:
 - Server connections
 - Server searching through database
 - Upcoming Actions
 - Server obtaining quiz object
 - Aside note: On query, pass connection and close / leave open based on result of condition
 - JUnit testing should be done by only one person

- Josh:
 - Completed Actions:
 - Client talks to server
 - Client passes and receives objects
 - Upcoming Actions
 - Document protocol
 - Communication with GUI (ensuring right information is available)
 - Ben:
 - Completed Actions:
 - Some GUI screens are sorted
 - Upcoming Actions
 - All GUI screens will be done by Saturday (08/03/2014)
 - Communication with connected Client
 - Rowan:
 - Completed Actions:
 - Client side server code written to pass quiz data obtained from the server-database connection.
 - Upcoming Actions
 - Enforcing synchronisation between connected clients during quiz mode.
 - Passing on client result information to the server-database connection to be stored in the database.
-

- SVN repository currently in use was setup on Josh's account as project SVN repository was unavailable at the start of the project:
 - Ideally the project should be migrated to the new project repository
 - Logs should be exported as .txt files
 - Actual files should be copied not the SVN bit
- Command line will be supported (vs Eclipse plugins)
- Joe will provide support regarding connections to the database through Eclipse (check project setup)
- For connecting to the database from outside the school, use university VPN connection.
- Extra testing (MSc only):
 - Detailed test plan (document) is required, that is formal and comprehensive.
 - Tests must be carried out and results logged.
- Format of presentation:
 - 10 minute presentation / 20 minute demonstration / 10 minutes deciding mark
- See Joe Tuesday to check in with an update of project
- Add own work to Subversion, and provide log messages when committing (can do this by writing note in TortoiseSVN/ writing note in line above in cmd line while committing/ can use -n flag to write note in cmd line)

Action Summary			
Action Specifics	Responsible	Deadline	Status
Protocols must be documented.	-	13/03/2014	Open
Test plan must be documented	-	?	Open
Testing according to the plan must be logged	-	?	Open
System must be working	All	12/03/2014	Open
Report must be submitted	All	(Two weeks)	Open
Migrate project SVN directory to one provided	-	?	Open
Presentation must be prepared	All	?	Open
See Joe Tuesday to check in with update of project	-	11/03/2014	Open

*** End of Notes ***

Tutorial Notes

Team Osaka Project Meeting

245, Computer Science

March 13, 2014; 16:00-16:30

Notes Taker: Rowan Stringer

Attendance

1. Rowan Stringer
2. Benjamin Crispin
3. Sam Farmer
4. Josh Wainwright
5. Deedar Fatima
6. Joe Gardiner (Tutor)

Notes

- Wait / Notify vs while loop
- Could do a read while in the while loop condition to make it wait
- Answers should update on the server
- GUI needs some work – “pretty”
- Colour change on admin when students answer
 - Countdown screen (big)
 - Control screen + who has answered
- Students see updating leaderboard
- Report due by Monday + prepare presentation
- Reallocate work
 - If database done, give that person new work
 - If connections done, get that person to work on the GUI
- Comment code
- Stability is important
 - Shows good testing has been implemented
 - A crash during the presentation can impact heavily on marks
- Documentation
 - Design:
 - Write what you did
 - Technologies you used
 - How it works
 - Testing:
 - JUnit
 - Manual
- Joe is absent Tuesday until Friday next week
- Short meeting with Joe Monday next week

*** End of Notes ***

**Minutes of the
Team Osaka Project Meeting
UG04, Computer Science**

February 21, 2014; 10:00-11:00 (approved on February 22)

Minutes Taker: Rowan Stringer

Attendance

1. Rowan Stringer
2. Benjamin Crispin
3. Sam Farmer
4. Josh Wainwright

Agenda

1. Extra team member
2. Project documentation
3. Scoping out project and idea
4. Research
5. Allocations
6. Selection of Software Engineering Paradigm
7. Project Outline
8. Next Meeting
9. Any Other Business
10. Time of Meeting End

Minutes

- 1. Extra team member:**
 - Notify Deedar about meeting.
 - Send Deedar the minutes.
 - Add Deedar to WhatsApp group.
- 2. Project documentation:**
 - Write down project proposal down as soon as possible to avoid losing a week. Deadline of Monday.
 - Use latex for final deliverables (to give ability to use version control like subversion), if possible.
 - Team will use UML where appropriate.
- 3. Eliciting project requirements:**
 - Creating a *use case diagram* as a team to determine broad system requirements.
 - Brief system description: the system is a live educational quiz in which students compete in real time to answer questions correctly. It will implement a client-server model with connected computers. There will be two user classes, henceforth referred to as Admin and Student. The system will implement sockets and threads (which avoid races/deadlocks) where appropriate and will have a graphical user interface (GUI).

4. Research:

- The team should research other existing systems in order that the project solution can improve on and differ from currently existing systems.
- It is important to keep log of bibliography references during the project as this will be a useful resource at the end of the project.

5. Allocations:

- Rowan (rjs305@bham.ac.uk) will act as the team email liaison with the tutor.

6. Selection of Software Engineering Paradigm:

- Due to the project multiple streams running concurrently, and unclear initial requirements, an iterative model (such as an Iterative Waterfall Model) will be adopted to reduce the amount of planning required and allow changing requirements to be met in a natural progression.

7. Project Outline (in bullet point form):

- A real-time educational team quiz system
- The system allows Students to logs into a user account
- The system allows logged in Students to compete in a many on many in a multiple choice / simple answer quiz
- The system gives a set number of questions per quiz (as per the admin)
- The system ensures synchronicity between all clients and the server
- The system allows users to log on with past question results
- The system displays a leader board and some feedback about the question to the Student
- The system displays a basic statistical information during the quiz to the Admin
- The system displays a summary report of statistical information at the end of the quiz to the Admin
- The system will allow the Admin to add or remove questions
- The system will log information about the Student's quiz session

8. Next Meeting:

- Next meeting will be arranged via WhatsApp group in response to the Joe's feedback.

9. Any Other Business: – NIL.**10. Time of Meeting End:**

- The meeting was adjourned at 11:00.

Action Summary				
ID	Action Specifics	Responsible	Deadline	Status
1	Send a project outline (bullet points) to Joe	Josh	24/02/2014	Open
2	Notify Deedar about meeting, send her the minutes, add her to WhatsApp group	Rowan	21/02/2014	Open
3	Arrange next meeting via WhatsApp group in response to the Joe's feedback	Rowan	27/02/2014	Open
4	For the next meeting, have a bibliography reference about sockets and/or threads	All	Next Meeting	Open

*** End of Minutes ***

Minutes of the
Team Osaka Project Meeting
Student Common Room, Computer Science
February 24, 2014; 14:30-14:55 (approved on February 24)
Minutes Taker: Rowan Stringer

Attendance

1. Rowan Stringer
2. Benjamin Crispin
3. Sam Farmer
4. Josh Wainwright
5. Deedar Fatima
6. Joe Gardiner (Tutor)

Agenda

1. Present an informal project outline to tutor
2. Any Other Business
3. Time of Meeting End

Minutes

- 1. Present an informal project outline to tutor (outcomes)**
 - An outline time schedule must be created for the project
 - Animations in GUI should be considered in design, such as:
 - i. a digital countdown to each question start
 - ii. a leader board that that updates in real time
 - Either threads or a push-data model can be considered in order to provide 'real-time' feedback functionality
 - Students should receive more points for faster answers
 - The server should be designed to be robust in the circumstances of client connections dropping out, i.e. session should continue
 - Division of labour:
 - i. JDBC and socket programming should done by all group members to some extent
 - ii. No more than 2 people per task.
 -
- 2. Any Other Business:**
 - Next Meeting to be arranged for tomorrow.
- 3. Time of Meeting End:**
 - The meeting was adjourned at 14:55.

Action Summary				
ID	Action Specifics	Responsible	Deadline	Status
5	Time Plan (which includes testing) must be created	All	27/02/2014	Open
6	Some sketches for GUI must be created (this task could be split over modules of project with couple sketches each)	All	27/02/2014	Open
7	Arrange next meeting for 25/02/2014	Rowan	25/02/2014	Open

*** End of Minutes ***

**Minutes of the
Team Osaka Project Meeting
UG04, Computer Science**

February 27, 2014; 14:30-15:00 (approved on February 24)

Minutes Taker: Rowan Stringer

Attendance

1. Rowan Stringer
2. Benjamin Crispin
3. Sam Farmer
4. Josh Wainwright
5. Deedar Fatima

Agenda

1. Discuss GUI Sketches (that have been made)
2. Any Other Business
3. Time of Meeting End

Minutes

1. Discuss GUI Sketches

- Creating a list of GUI screens required for sketching:
 - i. Login Screen – same for student and admin – Ben
 - ii. Create quiz for admin – Ben
 - iii. Home Screen for Admin - Deedar
 - iv. Home Screen for Student - Deedar -> Keep frames to a minimum unless simple functions. Need a lobby for connected clients to wait in before quiz starts. Begin with harder user coding – need to know question IDs to delete them
 - v. Question Screen – 4 multiple choice options, with countdown timer, with an example question – Rowan -> just word question and answer to begin with. Randomise answers.
 - vi. Immediate results (Student) - Sam
 - vii. Immediate results (Admin) – Sam
 - viii. Final results (Student/Admin) – Sam

2. Any Other Business:

- Tutorial meeting in rm 245(?)
- How everyone is getting on with subversion.
- Next Meeting to be arranged via doodle poll for Friday.

3. Time of Meeting End:

- The meeting was adjourned at 14:53.

*** End of Minutes ***

Tutorial Notes

Team Osaka Project Meeting

245, Computer Science

February 27, 2014; 16:30-17:00

Notes Taker: Rowan Stringer

Attendance

1. Rowan Stringer
2. Benjamin Crispin
3. Sam Farmer
4. Josh Wainwright
5. Deedar Fatima
6. Joe Gardiner (Tutor)

Notes

Division of Labour should be (for creating and testing):

- Server – Control, most complex, need two people
- Database / JDBC
- Client – local state, connect with GUI
- GUI

Project is given a mark, and then a division of work document explains how team worked together.

A report of install instructions, troubleshooting document is required.

Want low latency in system.

Need to rework time plan if GUI will be created from the start, with a week to test.

When client logs in, something (like a string) will be required to facilitate the connection.

Server acknowledges, and can send back information.

Need a protocol which says what functionality component must provide – what situations will occur, and how component should act.

Need to plan test cases – not necessarily JUnit testing. Some will be set up a system, and check system behaviour. (E.g. might not want closing one window to close all Java windows). What happens if the client dies, server dies.

Run tests a few times to check for undefined behaviour.

Demonstrations will be on lab machines.

Project will be handed in with 3 paper copies of the report and subversion link – might be easier for us to give Uday and Joe access to our subversion rather than movement across to another subversion account.

No office hour on Monday – and Joe is out of contact all day Friday (this week).

Action Summary				
ID	Action Specifics	Responsible	Deadline	Status
19	Written specification needs to be written for next week.	-	06/02/2014	Open

*** End of Notes ***