

# EECS402 Lecture 13

Andrew M. Morgan

Savitch Ch. 8  
Operator Overloading  
Returning By Constant Value

1



## Consider This Program

EECS  
402

```
class ChangePocketClass
{
public:
    ChangePocketClass():quarters(0),dimes(0)
    ChangePocketClass(int q, int d):
        quarters(q), dimes(d)
    void setQuarters(int val)
    {
        quarters = val;
    }
    void setDimes(int val)
    {
        dimes = val;
    }
    int getQuarters()
    {
        return quarters;
    }
    int getDimes()
    {
        return dimes;
    }
private:
    int quarters;
    int dimes;
};
```

### From main:

```
ChangePocketClass c1;
ChangePocketClass c2;
ChangePocketClass c3;
c1.setQuarters(5);
c1.setDimes(7);
c2.setQuarters(3);
c2.setDimes(8);

c3 = c1 + c2;
```

EECS  
402

Andrew M Morgan

2



2



## Program Discussion

EECS  
402

- What does the line `"c3 = c1 + c2;"` do?
  - Logically, you would expect it to add the number of quarters in the `c1` object to the number of quarters in the `c2` object, and add the dimes as well
- Would you expect that adding two objects of any class works this way? (A member-by-member addition?)
  - No
  - For example, adding two `"PersonClass"` objects together doesn't make sense
- Due to this, addition is not provided by default for user-defined classes
  - Therefore, the compiler will not allow the addition (yet)

EECS  
402

Andrew M Morgan

3



3



## Using Operators

EECS  
402

- While the operator `"+"` makes perfect sense for types such as `int` and `float`, what does it mean for user-defined data types?
  - The programmer must define it, and implement it when appropriate
  - Often, it doesn't make any sense to perform mathematical operations on user-defined class types
- Rather than use the `"+"` operator, programmer could write a member function named `"add"`:
  - `ChangePocketClass ChangePocketClass::add(const ChangePocketClass &rhs) const;`
- Users aren't used to writing `"c3 = c1.add(c2);"` to add two items
  - `"c3 = c1 + c2;"` would make a lot more sense, and wouldn't require a user to look up a function prototype to determine how to add two objects together

EECS  
402

Andrew M Morgan

4



4

- C++ allows a programmer to customize common operators work for different classes
- When C++ comes across an operator for user-defined data types, a function is called to perform the operation
  - The "+" operator results in a call to a function named "operator+"
  - The "=" operator results in a call to a function named "operator="
  - etc
- The following list of operators can be overloaded:

+	-	*	/	%	^	&		~
!	=	<	>	+=	-=	*=	?=	%=
^=	&=	=	<<	>>	>>=	<<=	==	!=
<=	>=	&&		++	--	->*	,	->
[]	()	new	delete	new[]	delete[]			

- Note: Just because you can overload an operator doesn't necessarily mean it is a good idea

```
class ChangePocketClass
{
public:
    ChangePocketClass():
        quarters(0), dimes(0)
    {}
    ChangePocketClass(int q, int d):
        quarters(q), dimes(d)
    {}
    ...no change to readers/writers

    ChangePocketClass operator+(const ChangePocketClass in)
    {
        ChangePocketClass result;
        result.quarters = quarters + in.quarters;
        result.dimes = dimes + in.dimes;
        return result;
    }

private:
    int quarters;
    int dimes;
};
```

```

int main()
{
    ChangePocketClass c1;
    ChangePocketClass c2;
    ChangePocketClass c3;
    c1.setQuarters(5);
    c1.setDimes(7);
    c2.setQuarters(3);
    c2.setDimes(8);

    c3 = c1 + c2;

    cout << "c1 q: " << c1.getQuarters() << " d: " << c1.getDimes() << endl;
    cout << "c2 q: " << c2.getQuarters() << " d: " << c2.getDimes() << endl;
    cout << "c3 q: " << c3.getQuarters() << " d: " << c3.getDimes() << endl;

    return 0;
}

```

```

c1 q: 5 d: 7
c2 q: 3 d: 8
c3 q: 8 d: 15

```

- You always get an operator=( ) function by default.
  - If you do not overload it, it will do a member-by-member copy, just like the default copy ctor
  - Any problems that occur due to the copy ctor will also be problems for operator= (will discuss further during dynamic allocation discussion)
- The following is a general syntax for operator=( ):
 

```
ClassName& ClassName::operator=(const ClassName &rhs)
```

  - Note: Returns "ClassName&" to allow "nested assignment", such as:
    - val1 = val2 = val3; //val1 assigned to the evaluation of the "val2 = val3" expression
  - Can also just return "void" but then nested assignment won't work
- rhs is an abbreviation for "right hand side" since the parameter is the object on the rhs of the equal sign

**M**

## Adding Assignment Operator and Copy Ctor

EECS  
402

```

class ChangePocketClass
{
public:
    //rest of member functions as shown before

    //Copy constructor-called when a copy of an object is needed
    ChangePocketClass(const ChangePocketClass &copy)
    {
        quarters = copy.quarters;
        dimes = copy.dimes;
    }

    //Assignment operator-called when one object is assigned to another
    void operator=(const ChangePocketClass &rhs)
    {
        quarters = rhs.quarters;
        dimes = rhs.dimes;
    }

private:
    int quarters;
    int dimes;
};

```

I do not need to write this right?

why no & here?

EECS  
402

Andrew M Morgan

9 **M**

9

**M**

## Using The ChangePocketClass

EECS  
402

- Print statements added to many member functions

```

int main()
{
    ChangePocketClass c1;
    ChangePocketClass c2(4, 6);
    ChangePocketClass c3;

    cout << "Done with decls" << endl;

    c1.setQuarters(5);
    c1.setDimes(7);

    c3 = c1 + c2;

    cout << "c1 q: " << c1.getQuarters() <<
        " d: " << c1.getDimes() << endl;
    cout << "c2 q: " << c2.getQuarters() <<
        " d: " << c2.getDimes() << endl;
    cout << "c3 q: " << c3.getQuarters() <<
        " d: " << c3.getDimes() << endl;

    cout << "End of program" << endl;

    return 0;
}

```

←

Default ctor

Value ctor

Default ctor

Done with decls

Copy ctor

operator+ func

Default ctor

Copy ctor

operator= func

c1 q: 5 d: 7

c2 q: 4 d: 6

c3 q: 9 d: 13

End of program

EECS  
402

Andrew M Morgan

10 **M**

10

- Following is a portion of the output from the previous slide

From main:

```
c3 = c1 + c2;
```

From ChangePocketClass:

```
ChangePocketClass operator+(const ChangePocketClass in)
{
    cout << "operator+ func" << endl;
    ChangePocketClass result;
    result.quarters = quarters + in.quarters;
    result.dimes = dimes + in.dimes;
    return result;
}

void operator=(const ChangePocketClass rhs)
{
    cout << "operator= func" << endl;
    quarters = rhs.quarters;
    dimes = rhs.dimes;
}
```

Copy ctor  
operator+ func  
Default ctor  
Copy ctor  
operator= func

- Recall that function calls are relatively slow
- Can prevent copy ctors by passing objects by constant reference
  - This also prevents copies from being made, further improving efficiency
- Changing operator+ and operator= prototypes to:

```
ChangePocketClass operator+(const ChangePocketClass &in);
void operator=(const ChangePocketClass &rhs);
```

- Will lower the number of copy ctors being called
  - Objects passed by constant reference can not change, but do not incur the efficiency penalty of objects passed by value
- General Rule**
  - Always pass objects by reference or constant reference!**

- There are actually two versions of the increment and decrement operators
  - Postfix version: The “++” comes after the variable
    - In this case, the variable is still incremented, but the expression evaluates to the value **before** the increment occurred
  - Prefix version: The “++” comes before the variable
    - In this case, the variable is incremented, and the expression evaluates to the incremented value
- Example:

```
int int1, int2;

int1 = 10;
int2 = int1++;
cout << "POST: int1 was 10 - after int1: " << int1 << " int2: " << int2 << endl;

int1 = 10;
int2 = ++int1;
cout << "PRE: int1 was 10 - after int1: " << int1 << " int2: " << int2 << endl;
```

- Output:

```
POST: int1 was 10 - after int1: 11 int2: 10
PRE: int1 was 10 - after int1: 11 int2: 11
```

The difference is in what the increment expression evaluates to

int1 is always incremented as expected, regardless of postfix or prefix

- Not all operators have two operands (like + and \*)
  - Operators that operate on a single operand are called “**unary operators**”
  - Examples: -myVar (negate operator), val++ (postfix increment operator), ++val (prefix increment operator), etc
- Unary operators normally don't require any parameters, since they only operate on one object (i.e. one operand)
- For increment and decrement operators, postfix and prefix versions typically act differently
  - Both increment operators are named “operator++”
  - To differentiate between versions, by convention, **the postfix operator takes in a dummy int parameter that has no meaning**
  - The int parameter is used only to cue the language that the operator is postfix, rather than prefix



## An IntClass With Many Operators

EECS  
402

```
class IntClass
{
private:
    int val; //The value of the integer
public:
    //Print out attrs of the object
    void print() const
    {
        cout << "Val: " << val << endl;
    }

    //Assign to an integer var
    void operator=(int iVal)
    {
        val = iVal;
    }

    //Negate operator. Note: this operator
    //has no "side-effects". In other
    //words, it doesn't change the object
    //is operating on.
    const IntClass operator-() const
    {
        IntClass retVal;
        retVal.val = -val;
        return retVal;
    }

    //Prefix version (i.e. ++myObj)
    //increments the value first, and
    //the expression evaluates to the
    //incremented value
    const IntClass operator++()
    {
        IntClass retVal;
        val++;
        retVal.val = val;
        return retVal;
    }

    //Postfix version (i.e. myObj++)
    //increments the value, but the
    //expression evaluates to the value
    //before the increment occurred
    const IntClass operator++(int dummy)
    {
        IntClass retVal;
        retVal.val = val;
        val++;
        return retVal;
    }
};
```

EECS  
402

Andrew M Morgan

15



15



## Using The IntClass

EECS  
402

```
int main()
{
    IntClass iObj1;
    IntClass iObj2;

    iObj1 = 14;
    iObj2 = iObj1;

    cout << "iObj1 during increment:" << endl;
    (iObj1++).print();
    cout << "iObj2 during increment:" << endl;
    (++iObj2).print();
    cout << "iObj1 after increment:" << endl;
    iObj1.print();
    cout << "iObj2 after increment:" << endl;
    iObj2.print();

    iObj1 = -iObj2;
    cout << "iObj1 after negate:" << endl;
    iObj1.print();
    cout << "iObj2 after negate:" << endl;
    iObj2.print();

    return 0;
}
```

```
iObj1 during increment:
Val: 14
iObj2 during increment:
Val: 15
iObj1 after increment:
Val: 15
iObj2 after increment:
Val: 15
iObj1 after negate:
Val: -15
iObj2 after negate:
Val: 15
```

EECS  
402

Andrew M Morgan

16



16





## Operators As Non-Members

EECS  
402

- All overloaded operators so far have been member functions
- Binary operators (such as  $x * y$ ) have two operands, but only one parameter is passed in
  - The left hand side operand is the object that the function was called on, and the right hand side operand is passed in
    - For example, consider "iObj1 \* 4"
  - What if the left hand side operand isn't an object?
    - For example, consider "4 \* iObj1"
  - Users are used to both versions being available, but they are actually two completely different functions
  - Since the left hand side of the second version is not an object, this function **can not** be a member function
  - Must be made a global function with two parameters

EECS  
402

Andrew M Morgan

17



17



## New Operators For IntClass

EECS  
402

```
class IntClass
{
    //Previously described members here...

    //Reader function for val
    int getVal() const
    {
        return val;
    }

    //This function allows for
    //myObj * 4 multiplication
    const IntClass operator*(int rhs) const
    {
        IntClass retVal;
        retVal.val = val * rhs;
        return retVal;
    }
};
```

From main():

```
iObj1 = 5;

cout << "iObj1 * 4:" << endl;
(iObj1 * 4).print();
cout << "4 * iObj1:" << endl;
(4 * iObj1).print();
```

```
iObj1 * 4:
Val: 20
4 * iObj1:
Val: 20
```

This is a global function!

```
//This function allows for "4 * myObj" multiplication
const IntClass operator*(int lhs, const IntClass &rhs)
{
    IntClass retVal;
    retVal = lhs * rhs.getVal();
    return retVal;
}
```

EECS  
402

Andrew M Morgan

18



18

- The << operator is called the insertion operator
  - It is used to "insert" values into an output stream
- Consider "cout << val << endl;"
  - "cout << val" is performed first
  - Then the insertion operator is used again, with "endl" on the right side
  - What is on the left side of the operator, though?
  - Answer: The left side is the return value of "cout << val"
- When the insertion operator is used, it modifies the stream object
  - Attributes regarding the number of characters in the stream, etc, must be changed when the insertion operator is used
  - Since the insertion operator can be used multiple times as shown above, **the insertion operator must return a reference**, so the returned value can be changed during subsequent calls to the insertion operator

- The cout object in iostream is of type "ostream"
- Consider "cout << iObj1;"
  - The **left side is of type ostream**, and the **right side is of a class type**
  - It must return a reference, as described earlier
- Prototype for overloading the insertion operator for the IntClass would, therefore, be as follows:

What does the & mean here?

```
ostream& operator<<(ostream &os, const IntClass &iObj);
```

return by reference!

- Note: This function can **not** be a member function
  - As described earlier, the left hand side operand is not an IntClass object
  - It **could** be a member function of the ostream class, but you don't have the ability to add members to the ostream class
  - Therefore, **it must be a global function in the program**

```
ostream& operator<<(ostream &os, const IntClass &iObj)
{
    os << iObj.getVal();
    return os;
}
```

From main():

```
iObj1 = 81;
cout << "iObj1: " << iObj1 << endl;
iObj2 = iObj1++;
cout << "iObj1: " << iObj1 << " iObj2: " << iObj2 << endl;
```

```
iObj1: 81
iObj1: 82 iObj2: 81
```

- Thanks to the **property of inheritance**, an ofstream can be passed into a function expecting an ostream
  - Details of inheritance won't be discussed here
- The insertion operator written on the last slide can be used to output to files in addition to the cout object

```
ofstream outFile;
outFile.open("testOut.txt");
iObj1 = 81;
outFile << "iObj1: " << iObj1 << endl;
iObj2 = iObj1++;
outFile << "iObj1: " << iObj1 << " iObj2: " << iObj2 << endl;
outFile.close();
```

when to .c\_str()?

Contents of testOut.txt after execution:

```
iObj1: 81
iObj1: 82 iObj2: 81
```

Note: No change was necessary to operator<< function to allow this functionality