

A Hardware-Minimal Unscented Kalman Filter Framework for Visual-Inertial Navigation of Small Unmanned Aircraft

Joshua Galen Eddy

Thesis submitted to the Faculty of the
Virginia Polytechnic Institute and State University
in partial fulfillment of the requirements for the degree of

Master of Science
in
Aerospace Engineering

Kevin Kochersberger, Chair
Mazen Farhood
Craig Woolsey

May 5, 2017
Blacksburg, Virginia

Abstract

This thesis presents the formulation and implementation of an Unscented Kalman Filter (UKF) framework for fusion of visual and inertial sensor data in unmanned aircraft navigation. Specifically, we fuse sensor readings from a 3-axis accelerometer, 3-axis gyroscope, and a Simultaneous Localization and Mapping (SLAM) algorithm to estimate the pose of an aircraft, such as a quadcopter, capable of hovering flight. We discuss the formulation of our UKF fusion algorithm, the development of a Robot Operating System (ROS) software package implementing the algorithm, and experiments in which this algorithm was used to track the motion of a physical vehicle simulating hovering flight in an indoor environment. We assess the filter's effectiveness by comparing its output to that of a Vicon motion capture system. We then discuss possible applications of this system and future work that may build upon the results developed herein.

Acknowledgments

This work would not have been possible were it not for my graduate adviser and committee chair, Dr. Kevin Kochersberger. He has been a constant source of support since October 2012 when he provided my friends and me with lab space in which to design our first competition robots. Over the ensuing five years, Dr. Kochersberger has played a pivotal role in my development as an engineer and researcher. He demonstrates his commitment to nurturing students every day by giving tirelessly of his time and energy.

It is also my pleasure to thank Dr. Danette Allen of the NASA Langley Autonomy Incubator, who provided me with two summer internships in her lab and taught me much of what I know today about Kalman filtering. Dr. Allen supplied me with both funding and equipment in order to perform this research, even going so far as to allow me to use her lab's motion capture facilities for my experiments.

I would also like to thank Dr. Loc Tran and Mr. James Neilan of NASA Langley and Ralph Williams of Analytical Mechanics Associates, who collectively provided me with hours of programming guidance during my time at the Autonomy Incubator.

Special thanks go to Samuel Rubenking, who stuck with me to the end. Thanks, Sam.

Contents

1	Introduction	1
1.1	Personal Motivation	2
1.2	Organization of this Document	4
2	Prior Work	6
2.1	Development of the Unscented Kalman Filter	6
2.2	Visual-Inertial Navigation	8
3	Algorithm Design and Implementation	13
3.1	UKF Formulation	13
3.1.1	Prediction Step	13
3.1.2	Correction Step	16
3.1.3	Process Model	17
3.1.4	Observation Model	18
3.1.5	Process Noise Covariance Matrix	21
3.1.6	Measurement Noise Covariance Matrix	21
3.2	Software Design Considerations	22
4	Experimental Design	24
4.1	Testing Considerations	24
4.1.1	PTAM Anomalies	25
4.2	Experimental Procedures	29
4.3	Materials	30
4.3.1	Computation and Sensing	30
4.3.2	Mobile Test Stand	30

5 Experimental Results	33
5.1 Long Walk Trials	33
5.2 Box Pattern Trials	33
6 Conclusions	44
7 Future Work	45
7.1 System Improvements	45
7.1.1 Integration of New Sensors	45
7.1.2 Improvements for Current Sensors	47
7.1.3 Refinements to the Underlying Algorithm	48
7.2 Future Experiments	49
7.3 System Applications	49
Bibliography	54

List of Figures

1.1	CARD Team Logo	2
1.2	Example April Tag	3
4.1	3D-printed Sensor Mount	25
4.2	Mobile Test Stand	26
4.3	Testing Environment	27
4.4	Sensor Mount Instrumented with Retroreflectors	28
4.5	Rviz Visualization of a Box Pattern Trajectory	29
4.6	Rviz Visualization of Translational (Lens) Distortion	31
4.7	Rviz Visualization of Rotational Distortion	32
5.1	Long Walk Trial 1	34
5.2	Long Walk Trial 2	35
5.3	Long Walk Trial 3	36
5.4	Long Walk Trial 4	37
5.5	Long Walk Trial 5	38
5.6	Box Pattern Trial 1 2D Trajectory	39
5.7	Box Pattern Trial 1 3D Trajectory	39
5.8	Box Pattern Trial 2 2D Trajectory	40
5.9	Box Pattern Trial 2 3D Trajectory	40
5.10	Box Pattern Trial 3 2D Trajectory	41
5.11	Box Pattern Trial 3 3D Trajectory	41
5.12	Box Pattern Trial 4 2D Trajectory	42
5.13	Box Pattern Trial 4 3D Trajectory	42
5.14	Box Pattern Trial 5 2D Trajectory	43
5.15	Box Pattern Trial 5 3D Trajectory	43

Acronyms

EKF Extended Kalman Filter

GPS Global Positioning System

IMU Inertial Measurement Unit

KF Kalman Filter

PTAM Parallel Tracking and Mapping

ROS Robot Operating System

SLAM Simultaneous Localization and Mapping

UAS Unmanned Aircraft System

UAV Unmanned Aerial Vehicle

UKF Unscented Kalman Filter

UT Unscented Transform

VIN Visual-Inertial Navigation

VO Visual Odometry

Chapter 1

Introduction

Until recently, the sensing and localization capabilities of small unmanned aerial vehicles (UAVs) have been computationally constrained due to restrictions on both the size and weight of sensors and onboard computer systems. Recent advances in miniaturized desktop computers, as well as low-power Graphics Processing Units (GPUs), have enabled a new class of computationally intensive algorithms to run onboard small aircraft without degrading flight time or other performance metrics. Specifically, small drones now present a viable platform for high-fidelity Simultaneous Localization and Mapping (SLAM), visual object recognition, and state estimation algorithms employing numerous heterogeneous sensors. In addition, the rising popularity of drones among hobbyists and researchers has fueled tremendous growth in the markets for brushless motors, electronic speed controllers, and airframes. With high-quality flight hardware and lightweight computers readily available, the arsenal of the robotics researcher has never been better stocked. The work detailed in this thesis is, in many ways, the product of these advantageous market conditions. With small aircraft capable of lifting heavier payloads and computers now lighter and smaller in footprint, demand is high for outfitting high-performance vehicles with top-notch sensing capabilities.

This work centers on an algorithm known as the Unscented Kalman Filter (UKF), a sensor fusion method for estimating the state of systems such as small aircraft. For years, this algorithm was inaccessible to roboticists and aerospace researchers alike due to its computational complexity. Computers capable of

running the algorithm were simply too large, too heavy, and too power-hungry to be viable onboard components of small UAVs. The advent of smaller computers has changed this state of affairs. In this thesis, we present a formulation of the Unscented Kalman Filter aimed at estimating the pose of a quadcopter. This UKF formulation fuses outputs from only two sensors: an inertial measurement unit (IMU) and a downward-facing monocular camera. These two data streams are fused to estimate the vehicle's pose in real time. We propose this UKF framework as a hardware-minimal starting point for advanced multi-sensor fusion in UAV navigation.

1.1 Personal Motivation

This section is largely comprised of background information regarding certain experiences leading up to, and motivating, the research developed in my thesis. This section does not contain any technical material, and is included only to provide context to the larger work.

I first took an interest in unmanned aircraft in the fall of 2012, my sophomore year of college. In search of an exciting engineering challenge, several of my friends and I founded the Cooperative Autonomous Robotics Design (CARD) team at Virginia Tech. Our core team consisted of a dozen students devoted to designing and competing with drones and other robotic vehicles. Our team, guided by my future graduate adviser, Dr. Kevin Kochersberger, entered two design competitions and brought home two awards for the university. We were also one of four university robotics teams selected by the Smithsonian Institution to participate in the opening ceremony for Robotics Week 2015. These early experiences with the team brought me into contact with new skills such as microcontroller programming, Proportional-Integral-Derivative (PID) controller design, basic mechatronics, and computer-aided design (CAD) modeling.

After two years of involvement with the CARD team, I applied for an internship at the National Institute of Aerospace¹ (NIA) in Hampton, Virginia. In the



Figure 1.1: The CARD team logo.

¹<http://www.nianet.org>

summer of 2014, I was part of a team of NIA researchers working on the Flying Donkey Challenge², an international engineering competition centered around the idea of “flying donkeys,” full-sized autonomous airplanes capable of quickly carrying cargo between small airports in rural Africa. This competition, unfortunately now defunct, was divided into a number of sub-challenges focusing on different technical objectives such as precision landing and collision avoidance. Our team’s goal was to design an inexpensive navigation system that could reliably guide unmanned aircraft during a Global Positioning System (GPS) blackout. This project introduced me to many of the technologies and techniques that would later become my major research interests, particularly the Robot Operating System³ (ROS), Kalman Filtering, and sensor fusion.




Figure 1.2: An example of an April tag.

Through my internship at the NIA, I met Dr. Danette Allen, head of the NASA Langley Autonomy Incubator. During my 2014–15 academic year, Dr. Allen sponsored the CARD team to design and build two autonomous multirotor delivery drones. These aircraft were capable of delivering 5-lb packages to distances of up to 2.5 miles (or 5 miles, round trip). In addition, these vehicles were able to land precisely on 1 m² April tags such as that found in Figure 1.2⁴. Following the completion of this project, I worked as a summer intern at the Autonomy Incubator, thereby further advancing my interest in Kalman filtering, sensor

fusion, and visual localization.

During the summer of 2015, I began the research that evolved into my thesis project, studying Visual-Inertial Navigation (VIN) and the Unscented Kalman Filter (UKF). As I read more and more on these subjects, I became interested in the design of the algorithm underlying the UKF. Unlike many other formulations of the Kalman Filter, the UKF has a notably limited dependence on information about the system under scrutiny (this *system agnosticism* is discussed in more

²<http://www.flyingdonkey.org>

³<http://wiki.ros.org>

⁴http://wiki.ros.org/apriltags_ros

detail in Chapter 3). The more I learned about the UKF the more I became excited about the idea of taking advantage of this limited dependence trait to build a minimalistic software interface by which a wide variety of disparate systems could be tracked and studied in a ROS framework. I envisioned a “one-stop shopping” experience for massively reusable and customizable filtering profiles that could fulfill the needs of researchers and roboticists who may have little knowledge of state estimation techniques. This vision eventually drove my development of the `kalman_sense` ROS package, cementing my interest in unmanned aerial vehicle (UAV) state estimation processes and controls.

1.2 Organization of this Document

Prior Work

In Prior Work, we explore recent contributions to loosely coupled filter-based navigation and state estimation processes. We focus primarily on a number of impactful publications coming from the Autonomous Systems Lab⁵ (ASL) at ETH Zurich⁶ and the University of Pennsylvania’s GRASP Lab⁷. We define the current state of the art in filter-based navigation and establish the research context in which this thesis exists.

Algorithm Design and Implementation

Because of the algorithmic nature of state estimation processes, we explore in detail the design and implementation of the `kalman_sense` ROS package. We discuss plant model abstraction as well as code organization and data flow and then summarize the process by which one could extend `kalman_sense`’s functionality and the advantages of system-agnostic algorithm design.

Experimental Design

In this section, we first establish the goals of the testing regimen and then discuss the real-world execution of these goals. We discuss important statistical methods

⁵www.asl.ethz.ch

⁶*Eidgenössische Technische Hochschule Zürich*, the Swiss Federal Institute of Technology in Zurich.

⁷www.grasp.upenn.edu

for characterizing the system's effectiveness as well as data collection procedures and post-processing. The system's physical testing infrastructure is explored in detail.

Experimental Results

In Experimental Results, we evaluate the system's performance during testing and seek out any limiting factors that influence estimation accuracy. We probe for possible improvements to the algorithm and provide a notional understanding of the system's theoretical effectiveness in real-world scenarios.

Conclusions

We summarize the contributions made in this thesis, the effectiveness of the `kalman_sense` ROS package, and the insights acquired during programming and testing.

Future Work

In Future Work, we expand upon the possible improvements proposed in Experimental Results and also offer a number of applications for the algorithms and processes developed herein. Specific examples of heterogeneous fleet management and Unmanned Traffic Management (UTM) are explored.

Chapter 2

Prior Work

2.1 Development of the Unscented Kalman Filter

Since the late 1990s, the Unscented Kalman Filter (UKF) has been a frequent topic of interest in the field of guidance, navigation, and controls. This extension of the Kalman Filter (explored in detail in Chapter 3) appeals to roboticists and controls engineers because it allows the preservation of nonlinear behavior in both the state propagation and measurement prediction steps. Through its use of the unscented transform (discussed further below), the UKF retains not only the first and second moments of the state distribution—the mean and covariance—but also the third moment, the skew. It is this retention of higher order information, coupled with true nonlinear behavior, that makes the Unscented Kalman Filter such a desirable tool for motion tracking and localization.

In [1], Julier and Uhlmann presented a nonlinear estimation approach for the Kalman Filter, originally developed in Uhlmann's doctoral dissertation. Recognizing that most applications for autonomous navigation are fundamentally nonlinear in both their dynamics and their observation models, Julier and Uhlmann proposed the use of a set of discretely sampled “sigma points” to determine the mean and covariance of a probability distribution. By recasting the prediction and correction steps of the Kalman Filter in the form of unscented transforms (UTs), this new filter eliminates the need to calculate Jacobian matrices. Julier and Uhlmann argued that for this reason their formulation was easier to implement than the EKF and went on to suggest that its use could supplant the EKF in

virtually all applications, linear or nonlinear.

In [2], Julier acknowledges that the (linear) Kalman Filter has been used successfully in many nonlinear scenarios, but notes that the use of only the first two moments of the state estimate sigma points results in the neglect of all higher order information (that is, third-order moments, or “skew”), a potentially rich source of new and useful information relating to symmetry of the state estimate. By extending the sigma point selection scheme of the conventional unscented transform, Julier was able to present a tractable but computationally complex extension of the Kalman Filter that could predict not only the first two moments of a sigma point distribution but also the skew. Though formulated initially for unimodal distributions, Julier stated that the approach could, with additional mathematical considerations, be generalized for use with multimodal distributions. Julier’s contention was that the use of higher order information could promote better performance levels in autonomous vehicle navigation. The utility of maintaining and utilizing higher order information through the use of skewed filtering was assessed in a realistic tracking scenario. However, the results were somewhat disappointing as the change in performance was only marginal, presumably due to the linearity of the filter’s update rule. Accordingly, research in this area continues, including examination of the use of nonlinear update rules in the filtering process.

Julier describes a novel approach in [3] to modifying the UT state estimation method. In the new approach, Julier takes the additional step of introducing a framework for scaling sigma points as part of the state estimation process. The general framework of the new methodology allows preservation of the first two moments of any set of sigma points, thus providing a construct for limiting values to either the conventional unscented transform or the modified (scaled) transform. Providing detailed mathematical validations, Julier demonstrates that the new scaling algorithm is computationally manageable in that it is, in essence, little more than the conventional unscented transformation algorithm with the addition of a simple post-processing step, the only difference being the inclusion of an extra correction term. Thus, the new algorithm’s computational and storage costs are similar to that of the non-scaled transformation. The performance level of the scaled UT is thus demonstrably superior to the unscaled UT for propagating the two lower-order moments of a sigma point distribution.

In [4], Julier and Uhlmann discuss the application of the EKF as an estimation algorithm and the associated difficulties in doing so. Because the EKF is fundamentally a linearizing approach to estimation, its effectiveness is thus tied to the veracity of the local linearity assumption for the system under scrutiny. These limitations led to the development of the UT for nonlinear applications. In this paper, Julier and Uhlmann describe the UT and its benefits, including easier implementation and improved accuracy over the EKF. The UT offers greater accuracy and reliability by applying higher order information, using sigma point sampling, to the traditional mean and covariance information associated with linear applications. Julier and Uhlmann provide examples, which may be tailored to various process and observation models, that show how the UT overcomes the limitations of the EKF.

2.2 Visual-Inertial Navigation

Recent advancements in computing power have given rise to a plethora of once-inaccessible algorithms for visual localization and state estimation. Simultaneous Localization and Mapping (SLAM) algorithms have been one of the chief beneficiaries of this technological bounty. For example, the rise of Graphics Processing Units (GPUs) has allowed for tremendous increases in the speed of SLAM as well as Visual Odometry (VO) programs. Improved state estimation methods, such as the UKF, have grown in popularity at the same time. The convergence of these research avenues lies in Visual-Inertial Navigation (VIN), an approach to navigation using any number of methods to fuse either raw camera data or the outputs of vision-based algorithms with inertial sensor readings. In [5], Donavanik et al. provide a concise survey of the state of the art in VIN at the time of this writing. In this article, the researchers discuss many of the current challenges in robotic VIN, including those stemming from the use of particular SLAM algorithms and EKF-based frameworks, such as consistency of state estimates over time. As described in the article,

This problem [of consistency] concerns the EKF as it uses linearization of a non-linear model, which introduces errors that in turn will lead to inconsistency. [...] Over time, this error can accumulate. A possible mitigation is to use the Unscented Kalman Filter (UKF).

At this juncture, we will briefly explore recent advancements in VIN, paying particular attention to filter-based methods and their accompanying sensor frameworks.

In [6], Klein and Murray proposed a method for tracking a handheld camera in unknown environments for use in small augmented reality (AR) workspaces. In contrast to many previous SLAM-based approaches to camera tracking, Klein and Murray split the tracking and mapping functions into two separate computational tasks. They performed these tasks on a dual-core computer utilizing parallel threads, with one thread directly tracking erratic motion of the handheld camera and the other thread constructing a 3D map of the environment. Through the use of this Parallel Tracking and Mapping (PTAM) algorithm, Klein and Murray were able to take advantage of computationally expensive batch-optimization techniques for map reconstruction, techniques which were rarely used in real-time applications previously. This, in turn, allowed Klein and Murray to forego the common approach of creating a sparse map of high quality features in favor of a much denser map containing features that could vary widely in quality. The resulting system could produce detailed maps tracking thousands of features at frame-rate and could recover gracefully from a variety of intermittent tracking failures. That being said, the researchers made certain relaxing assumptions regarding the scenes to be tracked. PTAM, by nature of its orientation toward AR applications, operates best in small, static, planar environments (such as on the surface of a desk or the floor of an office). PTAM's value to the robotics community quickly became obvious due to its independence of *a priori* knowledge of the scene and its minimal initialization procedure (explored in Chapter 4).

Four years later, in [7], Weiss et al. presented a visual-inertial navigation system for autonomous UAV navigation which employed PTAM. The researchers presented the results of several experiments in which a UAV equipped with a single monocular camera and an IMU navigated through unknown environments without the aid of GPS satellites or other external sensing infrastructure. All calculations were performed in real time using an EKF framework, proving that this minimalist combination of sensors could be employed in real-world GPS-compromised flight scenarios to great effect. At approximately the same time, Shen et al. conducted experiments in [8] at the University of Pennsylvania GRASP Lab aimed at stable indoor flight and GPS-denied localization in constrained

write up
PTAM init
procedure
in Exp De-
sign

multi-floor environments with a similarly limited suite of purely onboard sensors. The research distinguishes itself by emphasizing the use of onboard sensors only, as well as fully autonomous, real-time internal computational capabilities, with no hands-on user interaction beyond basic high-level commands. The research extends to multi-floor UAV navigation with loop closure. It also addresses specially designed controllers to help compensate for sudden changes in wind velocity and air flow as the UAV traverses constrained low-clearance areas with potentially strong aerodynamic disturbances.

In [9], Weiss and Siegwart went on to tackle the problem of metric scale in monocular VIN systems. The researchers developed a general algorithm that provides metric scale to monocular visual odometry and monocular SLAM systems using inertial measurement unit (IMU) data. The authors accomplished the development of the metric scale by the addition of a 3-axis accelerometer and 3-axis gyroscope to track 3D motion and to correct visual scale drift. Weiss and Siegwart created a modular solution based on their existing EKF framework and provided both simulated and empirical results. They also provided in-depth analysis of their system's applications, versatility, and reliability for real-time visual odometry and SLAM.

In 2012, Weiss et al. built upon this metric scale algorithm to present a versatile sensor fusion framework for autonomous flight [10]. Due to latency, noise, and arbitrary scaling within the output of a UAV's sensors, it is both impractical and ill-advised to incorporate this sensor output for position control without calibration or post-processing. The researchers address these problems using an EKF-SLAM formulation which fuses pose measurements with inertial sensor data. In doing so, they not only estimate pose and velocity of the UAV, but also estimate the sensor biases, correct the scale of position measurements, and perform inter-sensor self-calibration in real time. Their research demonstrates that the proposed framework is capable of running entirely onboard a UAV and performing state prediction at a rate of 1 kHz. Their results illustrate that this approach is able to handle measurement delays (up to 500 ms), sensor noise (with positional standard deviation up to 20 cm), and slow update rates (as low as 1 Hz) while still allowing dynamic maneuvers. The researchers also present a detailed quantitative performance evaluation of the system under the influence of different disturbance parameters and different sensor setups to highlight the

versatility of their approach. That same year, Weiss et al. further developed the VIN system in [11], adding a speed-estimation module to turn the monocular camera into a metric body-speed sensor. They then demonstrated how this module could be used for self-calibration of the UAV's onboard sensor suite in real time.

Shortly thereafter, Huang et al. presented solutions in [12] to two UKF limitations that exist in current state-of-the-art SLAM systems. Specifically, the researchers addressed the problems of cubic complexity in the number of state pose estimates, and the inconsistencies in those estimates caused by a mismatch between the observability properties of statistically-linearized UKF systems and the observability properties of nonlinear systems. To address the problem of cubic complexity, they introduced a novel sampling strategy which produces a constant computational cost. This sampling method, while linear in the prediction phase, is quadratic in the update phase. Although this new sampling strategy was primarily proposed for resolving the cubic complexity SLAM problem, the researchers stressed that it has potential usefulness in other nonlinear estimation applications. To address the problem of inconsistency in state estimations, Huang et al. proposed a new UKF algorithm which, due to the imposition of observability constraints, ensures that the linear regression computations of the modified UKF system produce results similar to those of nonlinear SLAM systems and, in the process, provide improved accuracy and consistency in state estimations. Importantly, the researchers validated their results with both real-world and simulation experiments.

In 2013, Lynen et al. presented a generic framework in [13] based on the EKF-SLAM system developed in [10] which was shown to be more robust during sensor blackouts and to be self-correcting in scale. The researchers demonstrated that their Multi-Sensor-Fusion EKF (MSF-EKF) framework was capable of processing measurements from an unlimited number of sensors, as well as sensor types, while simultaneously performing automatic self-calibrations of the overall sensor suite. It was the design of this software framework, which the researchers released as open source software shortly after publication, that inspired many of the design decisions behind the `kalman_sense` ROS package.

In [14], Rogers et al. presented a methodology for overcoming some of the constraining conditions encountered in a GPS-guided autonomous robotic system,

such as occlusion (blocking of GPS signals) and multipath distortion (reception of indirect signals due to environmental reflections) and potentially to ameliorate the effects of jamming or spoofing resulting from adversarial activities. Specifically, the methodology incorporated GPS measurements into a feature-based mapping system, thus providing geo-referenced coordinates allowing for better execution of high-level missions and providing the ability to correct accumulated mapping errors over the course of long-term operations in both indoor and outdoor environments.

In [15], Faessler et al. reported on the development and demonstration of a low-cost, low-weight, vision-based quadrotor UAV with onboard sensing, computation, and control capabilities. These onboard capabilities eliminated reliance on external positioning systems such as GPS or motion capture systems. This development moved the UAV from its current line-of-sight control state to wireless communications with the ability to execute intricate processes autonomously and to transmit live feedback to a user. Reporting on both indoor and outdoor experiments, the researchers believe that such a vehicle potentially would be a great enhancement in search-and-rescue missions, disaster response, and remote inspection of terrain.

Chapter 3

Algorithm Design and Implementation

3.1 UKF Formulation

In this section, we develop a formulation of the Unscented Kalman Filter for estimating the state of a quadcopter. We begin with the two overarching phases of the algorithm, Prediction and Correction. Then we develop a kinematic process model which describes the vehicle's motion over time. After this, we develop an observation model which describes the relationship between the vehicle's state and the vehicle's sensor readings. Finally, we explore noise models which describe the Gaussian noise present in both the process and observation models.

3.1.1 Prediction Step

We begin by defining the following quantities:

$$\mathbf{p} = \{x, y, z\}^T \quad (3.1)$$

$$\mathbf{q} = \{q_x, q_y, q_z, q_w\}^T \quad (3.2)$$

$$\mathbf{v} = \{\dot{x}, \dot{y}, \dot{z}\}^T \quad (3.3)$$

$$\boldsymbol{\Omega} = \{\omega_x, \omega_y, \omega_z\}^T \quad (3.4)$$

$$\mathbf{a} = \{\ddot{x}, \ddot{y}, \ddot{z}\}^T \quad (3.5)$$

The vectors \mathbf{p} , \mathbf{v} , and \mathbf{a} represent the vehicle's position, velocity, and acceleration, respectively. The quaternion¹ \mathbf{q} represents the vehicle's orientation, and the vector $\boldsymbol{\Omega}$ represents the vehicle's angular rates. We now define the state vector \mathbf{x} as

$$\mathbf{x} = \left\{ \mathbf{p}^T, \mathbf{q}^T, \mathbf{v}^T, \boldsymbol{\Omega}^T, \mathbf{a}^T \right\}^T \quad (3.6)$$

and let $n = 16$ represent the number of state variables.

Let $\mathbf{P} \in \mathbb{R}^{n \times n}$ be the covariance matrix associated with the state \mathbf{x} . A set of $2n + 1$ sigma points is then derived from \mathbf{x} and \mathbf{P} as

$$\begin{aligned} \chi_{k-1|k-1}^0 &= \mathbf{x}_{k-1|k-1} \\ \chi_{k-1|k-1}^i &= \mathbf{x}_{k-1|k-1} + \left(\sqrt{(n + \lambda) \mathbf{P}_{k-1|k-1}} \right)_i, \quad i = 1, \dots, n \\ \chi_{k-1|k-1}^i &= \mathbf{x}_{k-1|k-1} - \left(\sqrt{(n + \lambda) \mathbf{P}_{k-1|k-1}} \right)_{i-n}, \quad i = n + 1, \dots, 2n, \end{aligned} \quad (3.7)$$

where χ^i is the i -th sigma point and $(\sqrt{(n + \lambda) \mathbf{P}_{k-1|k-1}})_i$ is the i -th column of the square root matrix $\sqrt{(n + \lambda) \mathbf{P}_{k-1|k-1}}$. The constants α , β , κ , and λ are defined as

$$\alpha = 0.75 \quad (3.8)$$

$$\beta = 2 \quad (3.9)$$

$$\kappa = 0 \quad (3.10)$$

$$\lambda = \alpha^2(n + \kappa) - n = -7 \quad (3.11)$$

These constants control the spread of the sigma points chosen within the filter. According to Wan et al. in [16], setting $\beta = 2$ is optimal for a Gaussian state distribution, and κ is commonly set to zero. The value of α is usually small and positive. Here, we chose α by trial and error after observing the rate at which the filter converged in a number of preliminary experiments. We found that choosing $0 < \alpha \leq 0.5$ made the filter slow to converge. The filter's estimates would lag behind the pose sensor's readings by an interval that was sometimes several seconds in length and, in steady state, would undershoot the pose sensor. Conversely, choosing $\alpha \geq 1$ caused the filter to diverge. At $\alpha \approx 0.75$, the filter had

¹All quaternion quantities are represented here according to the convention used in equation 3.2, where q_w is the scalar component and is always placed in the last position. This convention was chosen to maintain consistency with the Eigen library's internal representation of quaternions.

no distinguishable lag and was highly stable.

For the purpose of sigma point sampling, the square root matrix \mathbf{A} of a matrix \mathbf{B} is defined here as

$$\mathbf{AA}^T = \mathbf{B} \quad (3.12)$$

and is evaluated using Cholesky decomposition² for computational efficiency.

To predict the next state, the sigma points are propagated through the nonlinear process function f (defined in Section 3.1.3):

$$\boldsymbol{\chi}_{k|k-1}^i = f(\boldsymbol{\chi}_{k-1|k-1}^i), \quad i = 0, \dots, 2n. \quad (3.13)$$

These transformed sigma points are then used to determine the predicted state $\hat{\mathbf{x}}_{k|k-1}$ and its associated covariance $\mathbf{P}_{k|k-1}$ as

$$\hat{\mathbf{x}}_{k|k-1} = \sum_{i=0}^{2n} W_s^i \boldsymbol{\chi}_{k|k-1}^i \quad (3.14)$$

$$\mathbf{P}_{k|k-1} = \left(\sum_{i=0}^{2n} W_c^i (\boldsymbol{\chi}_{k|k-1}^i - \hat{\mathbf{x}}_{k|k-1}) (\boldsymbol{\chi}_{k|k-1}^i - \hat{\mathbf{x}}_{k|k-1})^T \right) + \mathbf{Q}, \quad (3.15)$$

where \mathbf{Q} is the process noise covariance matrix (defined in Section 3.1.5).

The state weights W_s and covariance weights W_c used in equations 3.14 and 3.15 (and later in equations 3.20, 3.21, and 3.22) are defined as

$$\begin{aligned} W_s^0 &= \frac{\lambda}{n+\lambda} \\ W_c^0 &= \frac{\lambda}{n+\lambda} + (1 - \alpha^2 + \beta) \\ W_s^i &= W_c^i = \frac{1}{2(n+\lambda)}, \quad i = 1, \dots, 2n \end{aligned} \quad (3.16)$$

²https://en.wikipedia.org/wiki/Cholesky_decomposition#The_Cholesky_algorithm

3.1.2 Correction Step

Given the belief defined by $\mathbf{x}_{k|k-1}$ and $\mathbf{P}_{k|k-1}$, we compute $2n+1$ sigma points again as

$$\begin{aligned}\boldsymbol{\chi}_{k|k-1}^0 &= \mathbf{x}_{k|k-1} \\ \boldsymbol{\chi}_{k|k-1}^i &= \mathbf{x}_{k|k-1} + \left(\sqrt{(n+\lambda) \mathbf{P}_{k|k-1}} \right)_i, \quad i = 1, \dots, n \\ \boldsymbol{\chi}_{k|k-1}^i &= \mathbf{x}_{k|k-1} - \left(\sqrt{(n+\lambda) \mathbf{P}_{k|k-1}} \right)_{i-n}, \quad i = n+1, \dots, 2n.\end{aligned}\tag{3.17}$$

Next, the sigma points are projected into the sensor space through the observation function h (defined in Section 3.1.4):

$$\boldsymbol{\gamma}_k^i = h(\boldsymbol{\chi}_{k|k-1}^i), \quad i = 0, \dots, 2n.\tag{3.18}$$

Let $m = 7$ represent the number of measurements taken from each PTAM message. Each of these messages is mathematically interpreted as an m -dimensional measurement vector \mathbf{z}_k of the form

$$\mathbf{z}_k = \{x, y, z, q_x, q_y, q_z, q_w\}_{meas.}^T.\tag{3.19}$$

The predicted measurement vector $\hat{\mathbf{z}}_k$ and measurement noise covariance \mathbf{P}_{zz} are then computed as

$$\hat{\mathbf{z}}_k = \sum_{i=0}^{2n} W_s^i \boldsymbol{\gamma}_k^i\tag{3.20}$$

$$\mathbf{P}_{zz} = \left(\sum_{i=0}^{2n} W_c^i (\boldsymbol{\gamma}_k^i - \hat{\mathbf{z}}_k) (\boldsymbol{\gamma}_k^i - \hat{\mathbf{z}}_k)^T \right) + \mathbf{R},\tag{3.21}$$

where \mathbf{R} is the measurement noise covariance matrix (defined in Section 3.1.6). The state-measurement cross-covariance \mathbf{P}_{xz} is then defined as

$$\mathbf{P}_{xz} = \sum_{i=0}^{2n} W_c^i (\boldsymbol{\chi}_{k|k-1}^i - \hat{\mathbf{x}}_{k|k-1}) (\boldsymbol{\gamma}_k^i - \hat{\mathbf{z}}_k)^T.\tag{3.22}$$

Next, we compute the Kalman gain \mathbf{K}_k per the definition

$$\mathbf{K}_k = \mathbf{P}_{xz} \mathbf{P}_{zz}^{-1}.\tag{3.23}$$

The corrected state $\hat{\mathbf{x}}_{k|k}$ is then the sum of the predicted state and the innovation, weighted by \mathbf{K}_k :

$$\hat{\mathbf{x}}_{k|k} = \hat{\mathbf{x}}_{k|k-1} + \mathbf{K}_k (\hat{\mathbf{z}}_k - \mathbf{z}_k). \quad (3.24)$$

The corrected covariance $\mathbf{P}_{k|k}$ is the difference between the predicted state covariance $\mathbf{P}_{k|k-1}$ and the predicted measurement covariance, weighted by the Kalman gain:

$$\mathbf{P}_{k|k} = \mathbf{P}_{k|k-1} - \mathbf{K}_k \mathbf{P}_{zz} \mathbf{K}_k^T. \quad (3.25)$$

3.1.3 Process Model

To propagate the vehicle's state forward in time, we perform a number of integration operations on the linear accelerations and angular rates measured by the IMU. To determine the orientation of the vehicle at some time k , we integrate the measured angular rate vector $\boldsymbol{\Omega}_{meas.}$ per the relationship given in [17],

$$\mathbf{q}_k = \mathbf{q}_{k-1} + \frac{1}{2} \Theta(\boldsymbol{\Omega}_k) \mathbf{q}_{k-1} \Delta t, \quad (3.26)$$

where $\Theta(\boldsymbol{\Omega}_k) \in \mathbb{R}^{4 \times 4}$ is the angular rate integration matrix defined by

$$\Theta(\boldsymbol{\Omega}_k) = \begin{bmatrix} 0 & \omega_z & -\omega_y & \omega_x \\ -\omega_z & 0 & \omega_x & \omega_y \\ \omega_y & -\omega_x & 0 & \omega_z \\ -\omega_x & -\omega_y & -\omega_z & 0 \end{bmatrix} \quad (3.27)$$

and the vehicle's current angular velocity vector is measured directly by the gyroscope:

$$\boldsymbol{\Omega}_k = \boldsymbol{\Omega}_{meas.}. \quad (3.28)$$

To calculate the vehicle's current acceleration, we first subtract gravity from the measured acceleration vector $\mathbf{a}_{meas.}$ and then rotate the difference into the inertial frame:

$$\mathbf{a}_k = R_b^g [\mathbf{q}_{k-1}] (\mathbf{a}_{meas.} - \mathbf{g}). \quad (3.29)$$

Here $R_b^g [\mathbf{q}_{k-1}]$ is the rotation matrix representation of the previous orientation quaternion \mathbf{q}_{k-1} and \mathbf{g} is the vector representation of gravity in the global frame.

Have Sam look over this. Are subscripts right?

For a given quaternion \mathbf{q} , the rotation matrix $R_b^g[\mathbf{q}]$ would be

$$R_b^g[\mathbf{q}] = \begin{bmatrix} 1 - 2q_y^2 - 2q_z^2 & 2q_xq_y - 2q_zq_w & 2q_xq_z + 2q_yq_w \\ 2q_xq_y + 2q_zq_w & 1 - 2q_x^2 - 2q_z^2 & 2q_yq_z - 2q_xq_w \\ 2q_xq_z - 2q_yq_w & 2q_yq_z + 2q_xq_w & 1 - 2q_x^2 - 2q_y^2 \end{bmatrix}. \quad (3.30)$$

With the vehicle's current acceleration known, we can compute the current velocity of the vehicle by integrating the vehicle's average acceleration between the current and previous time steps:

$$\mathbf{v}_k = \mathbf{v}_{k-1} + \frac{1}{2}(\mathbf{a}_k + \mathbf{a}_{k-1})\Delta t. \quad (3.31)$$

Similarly, we compute the vehicle's current position using the vehicle's average velocity:

$$\mathbf{p}_k = \mathbf{p}_{k-1} + \frac{1}{2}(\mathbf{v}_k + \mathbf{v}_{k-1})\Delta t. \quad (3.32)$$

Together, equations 3.26, 3.28, 3.29, 3.31, and 3.32 constitute the nonlinear process function f :

$$f(\mathbf{x}_k) = \begin{Bmatrix} \mathbf{p}_{k-1} + \frac{1}{2}(\mathbf{v}_k + \mathbf{v}_{k-1})\Delta t \\ \mathbf{q}_{k-1} + \frac{1}{2}\Theta(\boldsymbol{\Omega}_k)\mathbf{q}_{k-1}\Delta t \\ \mathbf{v}_{k-1} + \frac{1}{2}(\mathbf{a}_k + \mathbf{a}_{k-1})\Delta t \\ \boldsymbol{\Omega}_{meas.} \\ R_b^g[\mathbf{q}_{k-1}](\mathbf{a}_{meas.} - \mathbf{g}) \end{Bmatrix}. \quad (3.33)$$

3.1.4 Observation Model

Quaternion Continuity Correction

A defect was discovered in the ROS implementation of PTAM during preliminary testing. PTAM's quaternion estimates switch sign without warning after the

observation
model h

camera rotates approximately 270 degrees, clockwise or counterclockwise. This aberrant behavior was provoked predictably in dozens of early tests in multiple testing areas, precluding the possibility of a one-off mapping error caused by a particular environment.

Quaternions are defined mathematically such that any quaternion \mathbf{q} and its negative, $-\mathbf{q}$, encode precisely the same *orientation*, but opposite *rotations*. If \mathbf{q} encodes a clockwise rotation of 90 degrees about the z -axis, $-\mathbf{q}$ will encode a counterclockwise 270-degree rotation about the same axis. The final orientation is the same in either case, but the two quaternions imply rotations in opposite directions. This has major implications for motion tracking. For example, when estimating the orientation of a vehicle moving in the xy -plane, such a sign flip would be visualized as an instantaneous 360-degree rotation about the z -axis, implying a massive angular acceleration that never took place.

A simple way to detect this type of errant behavior is to check, upon receipt of each new quaternion \mathbf{q}_k , whether $-\mathbf{q}_k$ implies a smaller rotation from the previous quaternion \mathbf{q}_{k-1} . Given that PTAM produces pose estimates at a rate of about 20 Hz, we assume only small-angle rotations between pose estimates. Thus, the smaller of the two rotations should always come from the correct \mathbf{q}_k . We can compare the relative magnitude of each possible rotation by taking the norm of the “delta-quaternions” $\mathbf{q}_{k-1} - \mathbf{q}_k$ and $\mathbf{q}_{k-1} - (-\mathbf{q}_k)$. The smaller delta-quaternion is associated with the correct value of \mathbf{q}_k . We implement this logic using the following algorithm:

Check this
with Sam.

Algorithm 1 Check for continuity between quaternion estimates

```

1: function CHECKQUATERNIONCONTINUITY( $\mathbf{q}_{k-1}$ ,  $\mathbf{q}_k$ )
2:   sum  $\leftarrow \|\mathbf{q}_{k-1} + \mathbf{q}_k\|$ 
3:   diff  $\leftarrow \|\mathbf{q}_{k-1} - \mathbf{q}_k\|$ 
4:   if diff  $\leq$  sum then
5:      $\mathbf{q}_k \leftarrow -\mathbf{q}_k$ 
6:   return  $\mathbf{q}_k$ 
```

Pseudovelocity Correction

Of the various states being measured, only the acceleration vector \mathbf{a} and angular rate vector $\boldsymbol{\Omega}$ are measured directly by the IMU:

$$\mathbf{x} = \left\{ \mathbf{p}^T, \mathbf{q}^T, \mathbf{v}^T, \underbrace{\boldsymbol{\Omega}^T, \mathbf{a}^T}_{\text{IMU}} \right\}^T.$$

The vehicle's position \mathbf{p} and orientation \mathbf{q} are measured directly by PTAM:

$$\mathbf{x} = \left\{ \underbrace{\mathbf{p}^T, \mathbf{q}^T}_{\text{PTAM}}, \mathbf{v}^T, \boldsymbol{\Omega}^T, \mathbf{a}^T \right\}^T.$$

The vehicle's velocity \mathbf{v} , however, is not measured by either the IMU or PTAM. There is no sensor in place by which \mathbf{v} can be directly measured. Therefore, velocity must be determined through a derived measurement.

Because velocity is predicted by integrating the vehicle's acceleration (Section 3.1.3), Gaussian noise in the accelerometer can cause unbounded drift in the velocity. The resulting erroneous velocity then propagates through each successive prediction step, causing drift in the estimated position *regardless of corrective position measurements from PTAM*. In this situation, the filter produces position estimates which drift at a constantly increasing rate between PTAM messages. The Kalman Filter corrects the position each time that a PTAM message arrives, only to drift again a fraction of a second later when the next IMU message arrives. This kind of intermittent drift produces sharp “bounces” in the vehicle's estimated trajectory and makes the filter's output numerically unstable.

To prevent this potentially catastrophic drift, velocity is estimated by numerical differentiation of the vehicle's position during each correction step. When a PTAM message is received, the position reading from the last PTAM message is subtracted from the current position reading. This change in position is then divided by the time step between the two PTAM messages, Δt_P :

$$\mathbf{v}_k = \frac{\mathbf{p}_{k, \text{meas.}} - \mathbf{p}_{k-1, \text{meas.}}}{\Delta t_P}. \quad (3.34)$$

This pseudovelocity correction prevents unbounded velocity drift, which in turn makes the filter's output numerically stable.

3.1.5 Process Noise Covariance Matrix

The process noise covariance matrix $\mathbf{Q}_k \in \mathbb{R}^{n \times n}$ is symmetric, time-dependent, and positive definite. We assume that its nonzero coefficients are a function of multiple integrations between the linear accelerations and angular velocities measured by the vehicle's 3-axis accelerometer and 3-axis gyroscope.

diagonality?

We assume that all axes of the accelerometer and gyroscope exhibit white noise with known standard deviations σ_a and σ_ω , respectively³. We further assume that no cross-axis covariance exists between any two accelerometer axes or any two gyroscope axes.

For the sake of convenient estimation, we assume that the accelerometer and gyroscope variance terms grow linearly over each discrete time step Δt . Thus, in the case of the x -axis accelerometer and the x -axis gyroscope, the corresponding terms of \mathbf{Q}_k would be

$$Q_{a_x, a_x} = \sigma_a \Delta t \quad (3.35)$$

and

$$Q_{\omega_x, \omega_x} = \sigma_\omega \Delta t, \quad (3.36)$$

respectively. We can now estimate the other nonzero terms of \mathbf{Q}_k according to their integral relationships with the acceleration and angular velocity measurements.

integral
equations

We assume no coupling between the angular quantities (\mathbf{q} and $\boldsymbol{\Omega}$) and the linear quantities (\mathbf{p} , \mathbf{v} , and \mathbf{a}), making the process noise covariance matrix largely sparse. This assumption logically stems from the small angle assumption. Because the IMU runs at 250 Hz, we assume that the vehicle makes only small rotations between IMU measurements.

full Q ma-
trix

3.1.6 Measurement Noise Covariance Matrix

The matrix $\mathbf{R} \in \mathbb{R}^{m \times m}$ models the covariance between measurements made by the pose sensor, PTAM. Like the process noise covariance matrix \mathbf{Q}_k , the measurement noise covariance matrix \mathbf{R} is symmetric and positive definite. However,

diagonality?
Q-R ratio?

³This claim of equal standard deviations between axes is supported by the IMU data sheet.

for the purposes of this experiment, \mathbf{R} is assumed to be time-invariant due to nearly constant feature density in the experimental scene. Because the vehicle camera moves across the scene at an almost constant height (that is, at a nearly constant distance to the features it observes on the floor), the measurement noise covariance of the pose sensor is assumed to be approximately constant in time. The coefficients of \mathbf{R} were estimated by numerically computing the covariances between raw measurements from PTAM and the “ground truth” supplied by a Vicon motion capture system⁴.

The resulting \mathbf{R} matrix is as follows:

R Matrix

3.2 Software Design Considerations

Much of the impetus for creating the `kalman_sense` ROS package came from a desire to create a generic UKF framework for estimating the state of an arbitrary system using any number of relative and absolute sensors. To achieve this, the `kalman_sense` package is organized in an object-oriented manner around an overarching abstract class called `UnscentedKf`. This abstract class contains a number of member functions (“methods”) performing the different mathematical operations defined in Section 3.1. These methods have been written in a generic manner to enable easy extension of `UnscentedKf` by subclasses containing concrete implementations of various systems. Currently, the package contains only one subclass, known as `QuadUkf`. This subclass contains methods and data structures related directly to estimating the state of a quadcopter or other rotorcraft UAV.

The `UnscentedKf` class encapsulates the generic mathematics of the UKF without knowledge of particular system constraints. This class does little other than matrix mathematics and is designed to take as input the number of a system’s states n and its number of sensors m . With this information, `UnscentedKf` is able to populate a set of mean and covariance weights and then intelligently perform all of the requisite linear algebra for the UKF formulation. All other knowledge of particular states, sensors, vehicle geometry, and other metrics is hidden within subclasses such as `QuadUkf`.

`UnscentedKf` behaves in a manner similar to a Java interface in that it re-

⁴<https://www.vicon.com/>

quires the extending class to supply functions codifying a process model and an observation model for the system under scrutiny. These two functions, along with n and m , form the entirety of what `UnscentedKf` “knows” about the vehicle. All other details, including the fact that the class is being used in a ROS environment, are hidden from `UnscentedKf`. It is worth noting that `UnscentedKf`’s only dependency is on the Eigen C++ linear algebra library⁵.

The subclass (`QuadUkf` for the remainder of this thesis) handles all of the ROS communications for the given system. Specifically, this class has callback functions for receiving sensor data and is responsible for publishing state and covariance estimates.

⁵www.eigen.tuxfamily.org


Chapter 4

Experimental Design


4.1 Testing Considerations

Before venturing further, we now summarize the goals of the UKF framework described previously, paying particular attention to the needs of unmanned aircraft system (UAS) operations. This ROS package was designed with the intent of producing estimates of the position vector \mathbf{p} and orientation quaternion \mathbf{q} of a rotorcraft UAV in real time. Thus, the experiments testing the system's efficacy compare the filter's estimates of position and orientation to the ground truth as measured by Vicon. Vicon, like many commercially available motion capture systems, works by using a number of infrared cameras (usually 8–12) to track the positions of retroreflector balls in the cameras' field of view. Each camera illuminates the area with infrared light, which is in turn reflected by the retroreflector balls. Sets of these retroreflectors can be grouped together in software to represent rigid objects, thus allowing the system to track not only the position of an object, but its orientation as well.

This system depends upon two sensors: a global-shutter monocular camera and an IMU. The IMU used in this experiment contains a 3-axis accelerometer and 3-axis gyroscope. To simulate both sensors moving through the scene in a manner reminiscent of hovering rotorcraft flight, a rolling test stand was constructed to carry the sensors safely throughout a large motion capture environment. Mounting the sensor suite (Figure 4.1) on a large, steady, level platform (Figure 4.2) allows for a high degree of control over the accelerations and angular



(a) Top view of sensor mount.



(b) Bottom view of sensor mount.

Figure 4.1: The 3D-printed sensor mount. In (a), the Phidgets IMU is on the left and the mvBlueFOX camera is on the right. In (b), the linear braking handle and camera lens are visible.

velocities felt by the IMU, as well as the motion captured by the ventral camera. In order to validate the UKF framework’s effectiveness under ideal conditions, a modern laptop computer containing an Intel i7 processor with 16 GB of RAM was used for all computations. The floor of the motion capture environment was strewn with a mixture of April tags and modified Quick Response¹ (QR) codes in order to provide sufficient visual features for PTAM to track.

4.1.1 PTAM Anomalies

The experiments chosen to test the system’s effectiveness were influenced largely by the known capabilities and limitations of the ROS PTAM implementation². In previous exploratory experiments³, PTAM was frequently shown to lose tracking⁴ during large rotations. PTAM is particularly susceptible to losing tracking during pure rotations, in which the camera rotates in place without translational motion. Worse, whenever PTAM undergoes a rotation, it interprets this as an arc-like motion, regardless of whether any translation took place.

¹https://en.wikipedia.org/wiki/QR_code

²From here on, “PTAM” refers to the particular ROS implementation of PTAM used in the experiments, not to the algorithm in general.

³Performed both by the author and by various other parties at NASA Langley, where the experiments described here took place.

⁴“Tracking” here refers to current pose knowledge.




Figure 4.2: The mobile test stand, fully assembled. The aluminum rail holds the sensor mount 1 meter above the floor and is marked with an adhesive metric ruler for measuring camera displacement during PTAM initialization.



Figure 4.3: The mobile test stand in the testing environment. The area shown is part of a larger motion capture facility. The floor is covered with rubber tiles, many of which bear April tags and QR codes for visual geometry.



Figure 4.4: Close-up view of the sensor mount instrumented with Vicon infrared retroreflector balls.

4.2 Experimental Procedures

Two experiments were designed to characterize the UKF framework's effectiveness in various regimes of motion. In the second experiment, the mobile test stand was moved in a rectangular "box" pattern at approximately constant speed, without rotation.




Figure 4.5: An Rviz visualization of a box pattern trajectory. In this image, the orange segments are actually composed of arrows pointing along the vehicle's x -axis (parallel to the red axis at the origin). The experiment starts one meter above the origin and the cart is pushed in a rectangular pattern, coming to rest at the origin again.

Two data streams were collected for analysis using the `rosbag`⁵ data recording utility.

⁵<http://wiki.ros.org/rosbag>

describe
each ex-
periment

more ex-
planation
of post
processing

4.3 Materials

4.3.1 Computation and Sensing

1. One (1) MatrixVision mvBlueFOX-MLC Camera⁶
2. One (1) 1044_0 PhidgetSpatial Precision 3/3/3 High Resolution IMU⁷
3. One (1) Hewlett-Packard Spectre x360 Convertible Laptop 13-ac076nr⁸
4. Two (2) male Mini USB 2.0 to male USB Type A cables

4.3.2 Mobile Test Stand

1. One (1) Oklahoma Sound PRC200 Premium Presentation Cart⁹
2. One (1) 3D-printed Sensor Mount
3. Two (2) 4" C-Clamps
4. One (1) 1.2-meter 80/20® Inc. 1515 Rail¹⁰
5. One (1) 15 Series "L" Handle Linear Bearing Brake Kit¹¹
6. One (1) $\frac{5}{16}$ -18 × 0.687" Black FBHSCS (Screw)¹²
7. Two (2) Slide-In Economy T-Nuts¹³
8. Three (3) 1" Vicon Infrared Retroreflector Balls
9. Two (2) $\frac{1}{2}$ " Vicon Infrared Retroreflector Balls
10. One (1) 0.7-meter Length of $\frac{1}{8}$ "-thick Carbon Fiber Tube

⁶<https://www.matrix-vision.com/USB2.0-single-board-camera-mvbluefox-mlc.html>

⁷http://www.phidgets.com/products.php?product_id=1044

⁸<http://store.hp.com/us/en/pdp/hp-spectre-x360---13-ac076nr>

⁹<http://www.oklahomasound.com/products/product-category/single/?prod=9>

¹⁰<https://8020.net/1515.html>

¹¹<https://8020.net/6800.html>

¹²<https://8020.net/shop/3320.html>

¹³Also available at <https://8020.net/shop/3320.html>




Figure 4.6: An Rviz visualization of the “bowl-shaped” world seen by PTAM during a long translational motion. This image was created by translating the mobile test stand 3–4 meters in the $+x$ direction and then translating back 4–5 meters past the origin in the $-x$ direction.

write out explanation of figure




Figure 4.7: An Rviz visualization of aberrant rotational behavior. This image was created by moving the cart in a square ($3\text{ m} \times 3\text{ m}$) pattern, making clockwise 90-degree turns at each corner.

Chapter 5

Experimental Results

5.1 Long Walk Trials

Figures 5.1–5.5 plot the vehicle's x -, y -, and z -coordinates over time. These plots demonstrate that the UKF's pose estimates were able to track the vehicle's y -position accurately over the length of each experimental trial. The plots also show that the UKF pose estimates exhibit some amount of aberrant behavior causing the vehicle's z -position to rise the farther the vehicle moves from the origin. The shaded region in Figure 5.1 clearly highlights this behavior. The vehicle's altitude as estimated by the UKF rises steadily to a maximum of ~ 1.4 meters, although in truth the vehicle's altitude was constant throughout. The vehicle's maximum vertical error coincides with its maximal displacement from $(0, 0, 0)$.

5.2 Box Pattern Trials

Figures 5.6–5.15 plot the estimated and measured trajectories of the vehicle during all five box pattern trials.

[more](#)




Figure 5.1: Long Walk Trial 1 coordinate plots. The shaded region highlights aberrant behavior coinciding with maximal displacement from the origin.




Figure 5.2: Long Walk Trial 2 coordinate plots.




Figure 5.3: Long Walk Trial 3 coordinate plots.




Figure 5.4: Long Walk Trial 4 coordinate plots.




Figure 5.5: Long Walk Trial 5 coordinate plots.




Figure 5.6: Box Pattern Trial 1 2D Trajectory.




Figure 5.7: Box Pattern Trial 1 3D Trajectory.




Figure 5.8: Box Pattern Trial 2 2D Trajectory.




Figure 5.9: Box Pattern Trial 2 3D Trajectory.




Figure 5.10: Box Pattern Trial 3 2D Trajectory.




Figure 5.11: Box Pattern Trial 3 3D Trajectory.




Figure 5.12: Box Pattern Trial 4 2D Trajectory.




Figure 5.13: Box Pattern Trial 4 3D Trajectory.




Figure 5.14: Box Pattern Trial 5 2D Trajectory.




Figure 5.15: Box Pattern Trial 5 3D Trajectory.

Chapter 6

Conclusions



draw con-
clusions

Chapter 7

Future Work

7.1 System Improvements

Experimentation with the `kalman_sense` ROS package has revealed a number of areas for improvement. Speaking generally, the system needs enhancements to improve accuracy and to become more robust with respect to sensor malfunction. Further development of this work likely would center on three main areas:

1. Integration of new sensors,
2. Improvements for current sensors, and
3. Refinements to the underlying algorithm.

Modifications to any or all of these areas would produce a marked improvement to the system in terms of both accuracy and robustness. For maximal effectiveness in adverse conditions, the system's sensors would need to be both individually robust and collectively redundant, so that complementary sensors could compensate for the loss of another sensor's information.

7.1.1 Integration of New Sensors

The accuracy and robustness of the system could be augmented by the integration of additional sensors, including but not limited to, the following:

1. One or more GPS receivers (particularly Real Time Kinematic¹ GPS),

¹https://en.wikipedia.org/wiki/Real_Time_Kinematic

2. A pressure altimeter,
3. A 3-axis magnetometer,
4. One or more laser rangefinders,
5. One or more forward-facing cameras (preferably depth cameras, such as RGB-D),
6. One-dimensional, multi-dimensional, or scanning LIDAR².

We previously mentioned work from the GRASP Lab ([8]) that demonstrated the efficacy of similar UKF frameworks in indoor-outdoor transitions and in navigating confined spaces using an expanded suite of sensors. In the case where more than one sensor is used to observe a given vehicle state variable, those multiple sensors check one another and can even perform real-time, in-air calibration. The system developed in this thesis has the advantage of being hardware-minimal in that it depends on only two sensors (the IMU and the ventral camera), but this convenience comes at the cost of robustness because either sensor presents a single point of possible failure. Moreover, the sensors have no overlap. Neither can observe any of the states observed by the other. This eliminates the possibility of checking one sensor against the other. Introducing a ventral laser rangefinder or pressure altimeter would allow for much more precise measurement of the vehicle's altitude and would allow for in-flight re-initialization of any metric SLAM/VO algorithm.

With the exception of certain sensors such as scanning LIDAR, which can cost tens of thousands of dollars, and RTK-GPS, which often falls in the same price range, these proposed new sensors would be inexpensive additions to the vehicle. Given the sophistication of current miniaturized sensors, it is not unreasonable to expect sub-meter or centimeter-level position accuracy from vehicles weighing fewer than fifteen pounds (including a substantial sensor payload) and costing less than 20,000 USD. It has been the case for a number of years now that meter-level accuracy could be taken for granted with "toy" quadcopters using only MEMS³ IMUs and sub-\$100 GPS receivers. The trend of miniaturization has

²"Light Detection and Ranging," <https://en.wikipedia.org/wiki/Lidar>

³"Microelectromechanical systems,"
https://en.wikipedia.org/wiki/Microelectromechanical_systems

made more and more sensors of better and better quality increasingly available in the weight- and cost-constrained world of aerial robotics. A variety of inexpensive off-the-shelf autopilots, such as the Pixhawk 2.1⁴, already boast triple-redundant IMUs and support for multiple GPS modules. Many of the hardware integration challenges that once plagued hobbyists and researchers have been resolved by engineering developments stemming from popular demand for user-friendly drones.

The organization of the `kalman_sense` package's code base is such that the integration of new sensors would require only the addition of new callback functions and ROS subscribers, as opposed to a full redesign or major edits to the existing code. Further, a new SLAM or VO algorithm could also be used in lieu of PTAM, allowing an "apples-to-apples" comparison of different visual localization algorithms. For example, Donavanik et al. [5] have identified a new algorithm known as ORB-SLAM [18] as a promising candidate for robust SLAM, already implemented in ROS. Because of ROS's sophisticated ecosystem of interoperable packages and message formats, any pose sensor employing the same message type as PTAM could plug in to `kalman_sense` in a matter of seconds.

Much of the design thinking that went into the `kalman_sense` package was focused on this particular possibility. The aircraft of the future will be vehicles laden with a vast suite of heterogeneous sensors, the outputs of which would, at any given time, be used not only for inner-loop and outer-loop flight control, but also for self-calibration, real-time diagnostics, and operator telemetry. Future UAVs will be akin to floating laboratories, mobile arrays of cutting-edge measurement systems allowing remote sensing over areas of several square miles.

7.1.2 Improvements for Current Sensors

For improved pose measurements, a more robust implementation of PTAM could be written and the same experiments could be repeated for comparison. PTAM's rotation errors and inability to eliminate lens distortion constitute severe limitations to its effectiveness in small UAS navigation. Moreover, if a rewritten formulation were able to interface with a downward-facing rangefinder, the initialization process could be eliminated altogether. The drawback is that making these changes would require a major software rewrite, a project that could be fea-

⁴<http://www.proficnc.com/>

sibly undertaken only by an experienced team of computer vision researchers and software developers. The mere cost in terms of both time and labor would likely make this an unappealing proposition, especially if other ready-made SLAM/VO algorithms were available to serve as PTAM replacements.

Processing power will also be central to the system's effectiveness during deployment on a real aircraft. This research is in many ways the product of recent advances in computing power. The advent of miniature desktop computers, such as the Intel NUC⁵, as well as power-efficient Graphics Processing Units⁶ (GPUs) has made a new frontier of estimation and localization algorithms easily accessible for the first time in the UAV world. A simple and generally inexpensive approach to augmenting the `kalman_sense` system would thus be the inclusion of top-of-the-line lightweight computing hardware. With modern onboard computers, even the need for cross-platform code compilation (so-called "transpiling") is eliminated because these computers employ the same x86 architecture used by most software developers.

7.1.3 Refinements to the Underlying Algorithm

The UKF formulation itself presents another set of opportunities for improvement. In particular, better process and measurement noise modeling would allow for increased accuracy. As described previously, the noise covariance matrices used during the experiments were only rough, static models meant to overestimate the Gaussian noise in the system. In practice, it would be better to replace these with time-varying matrices with terms more closely matching the intrinsic parameters of the system. Due to the high degree of coupling between state variables and the fundamental nonlinearity of the process model, this type of work was considered to be outside the scope of my thesis. In the future, however, a better **Q** matrix could be determined, perhaps by application of autocovariance and system identification methods. Moreover, any new sensor integrated into the system would require its own **R** matrix detailing its particular idiosyncrasies. With this done, attention could then be turned to tuning the **Q/R** ratio of each sensor, thus making the system even more faithful to known sensor parameters. With more sensors, self-calibration techniques such as those employed in [10] could also be

⁵"Next Unit of Computing," https://en.wikipedia.org/wiki/Next_Unit_of_Computing

⁶https://en.wikipedia.org/wiki/Graphics_processing_unit

implemented in order to avoid reinitializing one or more sensors in mid-air.

7.2 Future Experiments

Using a SLAM/VO algorithm that addresses pure rotation and lens distortion would be the easiest and most cost effective way to improve the system. Testing different visual localization algorithms would thus be an appealing avenue of inquiry. It would behoove the researcher to characterize the system's behavior under the same conditions that caused the PTAM-based implementation to fail. In particular, experiments that include pure rotations and longer translations, as well as simulated flight movement over uneven but otherwise virtually unchanging terrain would mimic real-world flight missions more closely and provide a more holistic understanding of the system's effectiveness. Additionally, mounting the sensor suite on the underside of a UAV would allow for the collection of real-world flight data, which could shed light on the system's speed limits and behavior in the presence of in-flight vibrations.

After integrating new sensors, new experiments could be devised to characterize the system's effectiveness during sensor blackouts—for example, during an indoor-outdoor transition after integrating a GPS receiver. Experiments such as this could then inform the design of heuristic models for recognizing sensor degradation and perhaps even consensus-based estimation strategies.

7.3 System Applications

Applications for this system are wide-ranging, spanning virtually every conceivable use for a small drone. The following is a non-exhaustive list of possible applications:

1. Mapping and 3D reconstruction of structures and topography,
2. Emergency response,
3. Infrastructure inspection,
4. Autonomous package delivery, and
5. Military/defense solutions.

What all of these applications have in common is the need for robust localization. In each of the above scenarios, losing GPS could cause a crash. In such an event, the vehicle itself would pose a real threat to bystanders and property. Moreover, in the case of military aircraft, the vehicle could be captured by hostile forces.

Mapping and 3D Reconstruction

Growing demand for so-called “precision agriculture” has brought with it the need to map large areas of cropland at a high speed, with a low cost point. In the past, this need has been met by using satellite imagery and human-captured photography. With the arrival of low-cost drones, this work has been offloaded to aerial robots. Outfitted with specialized sensors such as hyperspectral cameras⁷, small UAS are now able to provide minute-by-minute coverage of large expanses of land. More interesting still, these robots can be outfitted with reservoirs of pesticide or fertilizer and deployed to spray individual plants autonomously. It is in roles such as this that high-accuracy robust localization becomes a necessity. The accuracy required for precision agriculture can be provided by utilizing the sensor fusion techniques discussed in this thesis.

The surfaces of buildings and other structures can be mapped in a similar fashion, given the appropriate sensors and the right framework by which to fuse them. 3D reconstruction has become popular among real estate agents, safety inspectors, and other parties with a vested interest in precise 3D renderings of large geometries. In this case, the aircraft must be able to localize itself precisely in order to take full advantage of onboard sense-and-avoid technologies. The ability of the aircraft to estimate its position is crucial to its ability to map hard-to-reach areas and maintain stable flight. Sensor fusion systems shine when GPS and other sensors are inevitably compromised by various environmental factors.

Emergency Response

UAS technologies have become a desirable tool for first responders in many parts of the world. The ability to deploy a UAV to survey forest fires or search for missing persons has been a game changer for law enforcement and emergency personnel. In the case of looking for survivors of a natural disaster, the requirements for an

⁷https://en.wikipedia.org/wiki/Hyperspectral_imaging

effective vehicle system are accurate localization and overall robustness. Vehicles sent into disaster areas will have to be able to navigate in sensor-compromised environments, sometimes at substantial speed. This use case highlights the need for redundant sensors and intelligent, failure-resistant sensor fusion.

Infrastructure Inspection

Infrastructure inspection is similar in several respects to 3D mapping. In both cases, small drones are preferable to manned aircraft because of their low cost, high maneuverability, and ease of use. In recent years, governments and private corporations have taken an interest in using small aircraft to automate the inspection of many types of infrastructure, including the following:

1. Power lines,
2. Oil rigs,
3. Gas pipelines,
4. Railroads, and
5. Buildings.

UAVs are an obvious ally to companies servicing most types of static infrastructure. Inspecting miles of wires or railroad track is a task well-suited to today's UAVs, which commonly ship with intuitive flight planning software. Operators—even those who have no experience flying remote-control aircraft—are now able to program missions and deploy drones with ease. The aircraft are able to survey miles of infrastructure regardless of conditions on the ground, such as flooding, ill-maintained roads, or wild animals. Operators with First-Person View (FPV) hardware can watch video streaming live from the aircraft as if they were onboard themselves. The need for robust localization here is obvious: the UAV cannot inspect anything to which it cannot navigate. Operating in the wilderness may require flying below the forest canopy or under natural overhangs that could block GPS reception. The same is true in urban environments, where tall buildings create so-called “urban canyons” which compromise GPS effectiveness. Large metal structures can also distort magnetometry readings and thus undermine the aircraft’s ability to maintain its heading. In any case, UAVs used for large-scale inspections will be dependent upon intelligently combined sensing modalities.

Autonomous Package Delivery

A number of organizations, most notably Amazon⁸, have made big bets on drones as the future of delivery services. The task of delivering goods to individual homes is no trifling matter. American homes come in all shapes and sizes and are surrounded by numerous structures and natural obstacles that could endanger a delivery aircraft and, by extension, the people and property nearby. Moreover, any drone delivery service would have to be predicated upon the ability of the UAV to land with sub-meter accuracy. Delivery drones will have to land precisely in cluttered environments amid dynamic obstacles. Visual sensing will be extremely important for identifying safe landing zones, avoiding power lines and fences, and surmounting other environmental challenges. GPS alone will not be enough to guide the vehicle safely in every conceivable circumstance.

Military/Defense Solutions

Perhaps the most obvious application of a UKF fusion framework is in military operations, where precision navigation and robustness to sensor degradation are paramount for protecting soldiers in the field. As of the time of this writing, UAVs have been used in combat for years. However, augmented navigation could still make revolutionary contributions in areas such as

1. Robust tracking of friendly and hostile elements,
2. Remote observation of roads and vehicle-related hazards,
3. Autonomous deliveries of materiel in-theater, and
4. Human-machine teaming.

Every combat zone will constitute a hostile environment for UAV operations, especially in the presence of GPS spoofing/jamming technologies. Combat UAVs will have to be able to tolerate multiple simultaneous sensor failures. Moreover, in-theater urban flight operations bring with them all of the same difficulties mentioned above, but with the added challenge of violent enemy interdiction. Robust sensor fusion could automate the task of operational overwatch and

⁸<https://www.amazon.com/Amazon-Prime-Air/b?node=8037720011>

provide mission-critical intelligence in a timely manner—but only if the vehicle can localize itself reliably in sensor-hostile environments.

Bibliography

- [1] S. J. Julier and J. K. Uhlmann, “A New Extension of the Kalman Filter to Nonlinear Systems,” in *Proc. SPIE*, vol. 3068, pp. 182–193, 1997.
- [2] S. J. Julier, “A Skewed Approach to Filtering,” in *Proc. SPIE*, vol. 3373, pp. 271–282, 1998.
- [3] S. J. Julier, “The Scaled Unscented Transformation,” in *Proceedings of the 2002 American Control Conference (IEEE Cat. No.CH37301)*, vol. 6, pp. 4555–4559, May 2002.
- [4] S. J. Julier and J. K. Uhlmann, “Unscented Filtering and Nonlinear Estimation,” in *Invited Paper Proceedings of the IEEE*, vol. 92, pp. 401–422, March 2004.
- [5] D. Donavanik, A. Hardt-Stremayr, G. Gremillion, S. Weiss, and W. Nothwang, “Multi-Sensor Fusion Techniques for State Estimation of Micro Air Vehicles,” 2016.
- [6] G. Klein and D. Murray, “Parallel Tracking and Mapping for Small AR Workspaces,” in *Proc. Sixth IEEE and ACM International Symposium on Mixed and Augmented Reality (ISMAR’07)*, (Nara, Japan), November 2007.
- [7] S. Weiss, D. Scaramuzza, and R. Siegwart, “Monocular-SLAM-Based Navigation for Autonomous Micro Helicopters in GPS-Denied Environments,” *Journal of Field Robotics*, vol. 28, pp. 854–874, Nov. 2011.
- [8] S. Shen, N. Michael, and V. Kumar, “Autonomous Multi-Floor Navigation with a Computationally Constrained MAV,” in *IEEE International Conference on Robotics and Automation*, pp. 20–25, 2011.

- [9] S. Weiss and R. Siegwart, “Real-Time Metric State Estimation for Modular Vision-Inertial Systems,” in *2011 IEEE International Conference on Robotics and Automation*, pp. 4531–4537, May 2011.
- [10] S. Weiss, M. W. Achtelik, M. Chli, and R. Siegwart, “Versatile Distributed Pose Estimation and Sensor Self-Calibration for an Autonomous MAV,” in *2012 IEEE International Conference on Robotics and Automation*, pp. 31–38, May 2012.
- [11] S. Weiss, M. W. Achtelik, S. Lynen, M. Chli, and R. Siegwart, “Real-Time Onboard Visual-Inertial State Estimation and Self-Calibration of MAVs in Unknown Environments,” in *2012 IEEE International Conference on Robotics and Automation*, pp. 957–964, May 2012.
- [12] G. P. Huang, A. I. Mourikis, and S. I. Roumeliotis, “A Quadratic-Complexity Observability-Constrained Unscented Kalman Filter for SLAM,” *IEEE Transactions on Robotics*, vol. 29, pp. 1226–1243, Oct 2013.
- [13] S. Lynen, M. W. Achtelik, S. Weiss, M. Chli, and R. Siegwart, “A Robust and Modular Multi-Sensor Fusion Approach Applied to MAV Navigation,” in *2013 IEEE/RSJ International Conference on Intelligent Robots and Systems*, pp. 3923–3929, Nov 2013.
- [14] J. G. Rogers, J. R. Fink, and E. A. Stump, “Mapping with a Ground Robot in GPS Denied and Degraded Environments,” in *2014 American Control Conference*, pp. 1880–1885, June 2014.
- [15] M. Faessler, F. Fontana, C. Forster, E. Mueggler, M. Pizzoli, and D. Scaramuzza, “Autonomous, Vision-Based Flight and Live Dense 3D Mapping with a Quadrotor Micro Aerial Vehicle,” *Journal of Field Robotics*, vol. 33, no. 4, pp. 431–450, 2016.
- [16] E. A. Wan and R. V. D. Merwe, “The Unscented Kalman Filter for Nonlinear Estimation,” in *Proceedings of the IEEE 2000 Adaptive Systems for Signal Processing, Communications, and Control Symposium (Cat. No.00EX373)*, pp. 153–158, 2000.
- [17] B. L. Stevens, F. L. Lewis, and E. N. Johnson, *Aircraft Control and Simulation: Dynamics, Controls Design, and Autonomous Systems*, pp. 1–62. Wiley, 2015.

- [18] R. Mur-Artal, J. M. M. Montiel, and J. D. Tardós, “ORB-SLAM: A Versatile and Accurate Monocular SLAM System,” *IEEE Transactions on Robotics*, vol. 31, pp. 1147–1163, Oct 2015.