

# Vue 3 at Keap

Making the world a better place by keeping up  
with modern frontend frameworks /s



# New to Vue 3

- Composition API
- Other new features
  - Teleport
  - Fragments (multiple root elements)
- Performance
- First-class Typescript support

# New features

- Teleport
  - Similar to `portal-vue`, can move elements/components through the DOM
- Fragments
  - Multiple root elements in component
- Composition API
- Many others

# Fragments example

BEFORE

```
<template>
  <div>
    <AppHeader />
    <AppMain />
    <AppFooter />
  </div>
</template>
```

AFTER

```
<template>
  <AppHeader />
  <AppMain />
  <AppFooter />
</template>
```

# Composition API

# Example Component

```
<template>
  <button @click="increment">+</button>
  <span>Count^2 {{ countSquared }}</span>
</template>
```

Multiple root nodes! 🎉

# Object API vs. Composition API

## OBJECT API

```
export default {  
  data() {  
    return { count: 0 }  
  },  
  computed: {  
    countSquared() {  
      return this.count ** 2  
    }  
  },  
  methods: {  
    increment() {  
      this.count += 1  
    }  
  }  
}
```

## COMPOSITION API

```
import { computed, ref } from 'vue'  
export default {  
  setup() {  
    const count = ref(0)  
    const increment = () => count.value += 1  
    const countSquared = computed(  
      () => count.value ** 2  
    )  
  
    return {  
      count,  
      countSquared,  
      increment  
    }  
  }  
}
```

Sure, that's great, it can do the  
same thing.

What makes it better?



# Separation of concerns

Imagine a component that has a header with a tooltip and also needs to render a list of things based on an API call.

## OPTIONS API

```
data() {  
  return {  
    isOpen: false,  
    loading: false,  
    items: []  
  }  
}
```

```
computed: {  
  sortedItems() { ... }  
  tooltipTitle() { ... }  
}
```

```
methods: {  
  async loadItems() { ... }  
  toggleTooltip() { ... }  
}
```

## COMPOSITION API

```
setup() {  
  // ITEMS  
  const loading = ref(false)  
  const items = ref([])  
  const sortedItems = computed(() => { ... })  
  const loadItems = () => { ... }  
  mounted(() => loadItems())  
  
  // TOOLTIP  
  const isOpen = ref(false)  
  const tooltipTitle = computed(() => { ... })  
  const toggleTooltip = () => { ... }  
  
  // Only return the items used in the template  
  // e.g. Don't return loadItems or items  
  return { ... }  
}
```

`<script setup>`

more info

```
<script setup>
import { ref, computed } from 'vue'

const count = ref(0)
const countDoubled = computed(() => count.value * 2)
const increment = () => count.value += 1
</script>
```

All of these constants become available in the template.

# Better Vue Tooling

- Enhanced Vue DevTools extension
- Better intelliense
- Vetur
- Volar

# Performance

- Smaller bundle size due to treeshakeability
- Mounts quicker
- Updates quicker
- Uses less memory
- Spreadsheet with details

# First-class Typescript support

# Why Typescript?

- More reliable/higher confidence in code
- Typing acts as documentation
- Better tooling/intellisense
- Easier to maintain with high amount of developers

Sure, but why Typescript in  
Vue?

# Better type safety for props

## VUE 2

```
props: {  
  broadcast: {  
    type: Object,  
    required: true,  
    // default: () => ({}),  
  },  
}
```

```
props: {  
  broadcast: {  
    type: Object,  
    required: true,  
    validator: (value) => {  
      ['id', 'scheduleDate'].forEach((key) => {  
        broadcast.hasOwnProperty(key)  
      })  
    },  
  },  
  // But what about the type of the values in broadcast?  
},  
}
```

## VUE 3 + TYPESCRIPT

```
import { PropType } from 'vue'  
  
type Broadcast = {  
  id: string | number;  
  scheduleDate: string;  
}
```

```
props: {  
  broadcast: {  
    type: Object as PropType<Broadcast>,  
    required: true,  
  },  
}
```

```
// Using <script setup> syntactic sugar  
type Broadcast = {  
  id: string | number;  
  scheduleDate: string;  
}
```

```
const { broadcast } = defineProps({  
  
  broadcast: Broadcast
```



Great, sign me up!

# Migration

1. Remove deprecated syntax for slots
2. Upgrade to compat version (Vue 3.1)
3. Resolve incompatible and partially compatible issues
4. Upgrade related dependencies (vuex, vue-router, vue-i18n)
5. Refactor app and components over time to remove features removed from Vue 3
6. Update eslint plugins to vue3 plugins

Full migration guide[Additional information for Keap's migration](#)